




12 VOLT JUMP STARTER QUICK START GUIDE

CHARGE BATTERY

IMPORTANT
YOU MUST CHARGE
COMPLETELY BEFORE
FIRST USE, AFTER
EVERY JUMP START,
AND EVERY 30 DAYS

1. Turn Jump Starter's
Clamp Power Switch OFF.
2. Plug Charging Cord into grounded
120VAC outlet. Plug other end
of Cord into Charging Port.
3. Charge until display reads FUL,
then unplug Jump Starter and
store out of children's reach.



JUMP START VEHICLE

WARNING


To prevent serious injury:

1. Do not touch positive and negative
battery clamps together.
2. Do not connect to the negative
terminal of the battery.
3. Read manual before
set up and/or use.

IMPORTANT
IF VEHICLE DOES
NOT START WITHIN
5 SECONDS, TURN CLAMP
POWER SWITCH OFF.

WAIT AT LEAST
3 MINUTES, THEN
TRY AGAIN.

1. Turn Jump Starter's
Clamp Power Switch OFF.
2. Turn Vehicle's Ignition OFF.
4. Turn Jump Starter's
Clamp Power Switch ON.
5. Turn Vehicle's Ignition ON.




3. Connect Red Positive Clamp,
then connect Black Negative
Clamp to a non-moving
metal part of the vehicle.



AFTER VEHICLE STARTS

1. Turn Jump Starter's
Clamp Power Switch OFF.
2. Remove Black Negative Clamp.
3. Remove Red Positive Clamp.
4. Recharge Jump Starter
immediately.

POWER 12VDC APPLIANCES (15A Max Draw)




1. Determine Appliance compatibility. Calculate total wattage needed to run Appliance. Formula: Amps x 12 = Watts. Use Chart at right as a guideline only.
2. Turn Jump Starter's Clamp Power Switch OFF.
3. Turn Appliance's Power Switch OFF.
4. Plug Appliance into 12VDC Outlet, then turn Power Switch ON.
5. When finished, turn Appliance OFF, then remove plug from Outlet.

Typical DC Appliances & Run Times		
Appliance	Est. Power (Watts)	Est. Lifetime (Hours)
• Fluorescent Light • Cell Phone	4	50
• Fan • Depth Finder	9	26
• Video Recorder • Spotlight	15	14
• Small Power Tool • Bilge Pump	24	8
• Electric Cooler	48	3
• Air Compressor	80	2

POWER / CHARGE USB DEVICES

1. Plug Device into USB Port.
2. Press LIGHT/USB Button, USB Indicator will light.
3. When finished, press LIGHT/USB Button again.
4. Remove Device from USB Port.



OPERATE WORK LIGHT

1. Press LIGHT/USB Button until Work Light comes on.
2. Continue to press Button to cycle through different light modes.
3. When finished, press LIGHT/USB Button until light goes out.