

Owner's Manual & Safety Instructions

Save This Manual Keep this manual for the safety warnings and precautions, assembly, operating, inspection, maintenance and cleaning procedures. Write the product's serial number in the back of the manual (or month and year of purchase if product has no number). Keep this manual and the receipt in a safe and dry place for future reference.

23j

Kenway™

REAR TRI-MARKER RUNNING LIGHT BAR



Visit our website at: <http://www.harborfreight.com>
Email our technical support at: productsupport@harborfreight.com

59657

When unpacking, make sure that the product is intact and undamaged. If any parts are missing or broken, please call 1-888-866-5797 as soon as possible.

Copyright© 2023 by Harbor Freight Tools®. All rights reserved.
No portion of this manual or any artwork contained herein may be reproduced in any shape or form without the express written consent of Harbor Freight Tools. Diagrams within this manual may not be drawn proportionally. Due to continuing improvements, actual product may differ slightly from the product described herein. Tools required for assembly and service may not be included.

⚠WARNING

Read this material before using this product.
Failure to do so can result in serious injury.
SAVE THIS MANUAL.

IMPORTANT SAFETY INFORMATION

Assembly Precautions

1. Install only according to these instructions. Improper installation can create hazards.
2. Wear ANSI-approved safety goggles and heavy-duty work gloves during assembly.
3. Keep installation area clean and well lit.
4. Keep bystanders out of the area during installation.
5. Do not install when tired or when under the influence of drugs or medication.

Use Precautions

1. This product is not a toy. Do not allow children to play with this item.
2. Use for intended purpose(s) only.
3. Inspect before use; do not use if parts are loose or damaged.
4. Application of this product must meet State requirements for vehicle lighting.
5. Turn vehicle off and disconnect the battery before installation.
6. Maintain product labels and nameplates. These carry important safety information. If unreadable or missing, contact Harbor Freight Tools for a replacement.

Specifications

Mount Dimensions	17-1/4" L x 1-1/10" W x 7/10" H
Mounting Holes	3/16" diameter and 16" apart at centers
Light Amperage Draw	0.06A
Electrical Requirements	12VDC

Installation



Read the **ENTIRE IMPORTANT SAFETY INFORMATION** section at the beginning of this document including all text under subheadings therein before set up or use of this product.

If you do not have experience doing this type of electrical work, the job should be done by an automotive service technician.

NOTICE: Placement of the light must comply with FMVSS/CMVSS 108 Federal Lighting regulations for Trailers.

WARNING! TO PREVENT SERIOUS INJURY: Turn off vehicle's engine, then disconnect the power supply (battery) before doing any maintenance or installation.

1. Place the Light Bar on the mounting location at the rear of the vehicle. Use the Light Bar as a template to mark the two mounting holes and center hole for the wires.

Note: The planned mounting area must provide a flush fit to the bottom of the Light Bar.

2. Ensure that the installation area has no hidden electrical or stereo lines before drilling.
3. Drill one 1/4" hole for the wires and two 1/8" holes for the mounting screws.
4. Place the Light Bar and feed the wires through the center hole.
5. Use a pin connector or in-line splice connector (both sold separately) to connect the light to your vehicle.

6. When using an in-line splice connector, it is not necessary to strip the wires.
 - a. Insert the wire from your vehicle into one channel of the in-line splice connector.
 - b. Insert the wire extending from the Light into the second channel of the in-line splice connector.
 - c. Fold down the tab on the in-line splice connector to make the connection.
7. Connect the white wire NEGATIVE (-) to ground and the brown wire POSITIVE (+) to running light circuit.
8. Once the wires are properly connected, reconnect the power supply (battery) and test the Light Bar before mounting it in place.
9. Turn off ignition/battery.
10. Use two #8 x 1" Fillet Head Self Drilling Screws (sold separately) to attach the Light Bar to the vehicle/trailer surface.
11. Make certain the Light Bar is well seated and the ground wire makes proper contact with a metal surface.

Limited 90 Day Warranty

Harbor Freight Tools Co. makes every effort to assure that its products meet high quality and durability standards, and warrants to the original purchaser that this product is free from defects in materials and workmanship for the period of 90 days from the date of purchase. This warranty does not apply to damage due directly or indirectly, to misuse, abuse, negligence or accidents, repairs or alterations outside our facilities, criminal activity, improper installation, normal wear and tear, or to lack of maintenance. We shall in no event be liable for death, injuries to persons or property, or for incidental, contingent, special or consequential damages arising from the use of our product. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation of exclusion may not apply to you. THIS WARRANTY IS EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS.

To take advantage of this warranty, the product or part must be returned to us with transportation charges prepaid. Proof of purchase date and an explanation of the complaint must accompany the merchandise. If our inspection verifies the defect, we will either repair or replace the product at our election or we may elect to refund the purchase price if we cannot readily and quickly provide you with a replacement. We will return repaired products at our expense, but if we determine there is no defect, or that the defect resulted from causes not within the scope of our warranty, then you must bear the cost of returning the product.

This warranty gives you specific legal rights and you may also have other rights which vary from state to state.

Record Serial Number Here:

Note: If product has no serial number, record month and year of purchase instead.

Note: Replacement parts are not available. Reference UPC 193175531490.

The logo for Kenway, featuring the brand name in a bold, italicized, black serif font. The letter 'K' is significantly larger and more stylized than the other letters, with a long horizontal stroke extending to the left. A small trademark symbol (TM) is located at the end of the word.

26677 Agoura Road • Calabasas, CA 91302 • 1-888-866-5797