

Owner's Manual & Safety Instructions

Save This Manual Keep this manual for the safety warnings and precautions, assembly, operating, inspection, maintenance and cleaning procedures. Write the product's serial number in the back of the manual near the assembly diagram (or month and year of purchase if product has no number). Keep this manual and the receipt in a safe and dry place for future reference.

CENTTECH[®]

ITEM 61652

6/12 VOLT CIRCUIT TESTER with 5ft LEAD



Visit our website at: <http://www.harborfreight.com>

Email our technical support at: productsupport@harborfreight.com

REV 14g

When unpacking, make sure that the product is intact and undamaged. If any parts are missing or broken, please call 1-888-866-5797 as soon as possible.

Copyright© 2013 by Harbor Freight Tools[®]. All rights reserved.

No portion of this manual or any artwork contained herein may be reproduced in any shape or form without the express written consent of Harbor Freight Tools. Diagrams within this manual may not be drawn proportionally. Due to continuing improvements, actual product may differ slightly from the product described herein.

Tools required for assembly and service may not be included.

⚠ WARNING

**Read this material before using this product.
Failure to do so can result in serious injury.
SAVE THIS MANUAL.**

Specifications

Electrical Requirements	Voltage Range: 6VDC and 12VDC Lead Wire Length: 60 IN. Bulb: 12VDC / 3 W Clamp Capacity: 20 AMP
Dimensions	Probe: 3-1/2 IN. L Handle: 8 IN. L x 1 IN. D

Important Safety Information

General Safety Warnings



WARNING Read all safety warnings and instructions. Failure to follow the warnings and instructions may result in electric shock, fire and/or serious injury.

Save all warnings and instructions for future reference.

1. Work area safety

- a. **Keep work area clean and well lit.**
Cluttered or dark areas invite accidents.
- b. **Do not operate tools in explosive atmospheres, such as in the presence of flammable liquids, gases or dust.** *The connection may create sparks which may ignite the dust or fumes.*
- c. **Keep children and bystanders away while operating the tool.**
Distractions can cause you to lose control.

2. Electrical safety

- a. **Avoid body contact with grounded surfaces such as pipes, radiators, ranges and refrigerators.** *There is an increased risk of electric shock if your body is grounded.*
- b. **Do not expose the tool to rain or wet conditions.** *Water entering a tool will increase the risk of electric shock.*
- c. **Do not abuse the cord. Never use the cord for carrying, pulling or disconnecting the tool. Keep cord away from heat, oil, sharp edges or moving parts.** *Damaged or entangled cords increase the risk of electric shock.*

3. Personal safety

- a. **Stay alert, watch what you are doing and use common sense when operating a tool. Do not use a tool while you are tired or under the influence of drugs, alcohol or medication.**
A moment of inattention while operating a tool may result in serious personal injury.

b. Use personal protective equipment.

Always wear eye protection. *Safety equipment such as dust mask, non-skid safety shoes, hard hat, or hearing protection used for appropriate conditions will reduce personal injuries.*

c. Do not overreach. Keep proper footing and balance at all times.

This enables better control of the power tool in unexpected situations.

d. Dress properly. Do not wear loose clothing or jewelry. Keep your hair, clothing and gloves away from electrical parts.

Loose clothes, jewelry or long hair can be caught in parts.

e. Only use safety equipment that has been approved by an appropriate standards agency.

Unapproved safety equipment may not provide adequate protection. Eye protection must be ANSI-approved and breathing protection must be NIOSH-approved for the specific hazards in the work area.

4. Power tool use and care

a. Store idle tools out of the reach of children and do not allow persons unfamiliar with the tool or these instructions to operate the tool.

Tools are dangerous in the hands of untrained users.

b. Maintain tools. Check for misalignment or binding of parts, breakage of parts and any other condition that may affect the tool's operation. If damaged, have the tool repaired before use.

Many accidents are caused by poorly maintained tools.

Circuit Tester Safety Warnings

1. Maintain labels and nameplates on the tool. These carry important safety information. If unreadable or missing, contact Harbor Freight Tools for a replacement.
2. Avoid unintentional starting. Prepare to begin work before connecting the tool.
3. Use as intended only.
4. Inspect before every use; do not use if parts are loose or damaged.
5. Do not leave the tool unattended when it is connected to an electrical source. Disconnect the tool from its electrical source before leaving.
6. This product is not a toy. Keep it out of reach of children.
7. People with pacemakers should consult their physician(s) before use. Electromagnetic fields in close proximity to heart pacemaker could cause pacemaker interference or pacemaker failure. In addition, people with pacemakers should:
 - Avoid operating alone.
 - Properly maintain and inspect to avoid electrical shock.
8. **WARNING:** The cord of this product contains lead, a chemical known to the State of California to cause cancer, and birth defects or other reproductive harm. Wash hands after handling. (California Health & Safety Code § 25249.5, *et seq.*)
9. The warnings, precautions, and instructions discussed in this instruction manual cannot cover all possible conditions and situations that may occur. It must be understood by the operator that common sense and caution are factors which cannot be built into this product, but must be supplied by the operator.



SAVE THESE INSTRUCTIONS.

Operating Instructions



Read the **ENTIRE IMPORTANT SAFETY INFORMATION** section at the beginning of this manual including all text under subheadings therein before set up or use of this product.

General Operating Instructions

1. Remove the protective tip from the Probe. Be careful, the tip is sharp.
2. To test 6 volt or 12 volt fuses, wiring, or other 6V/12V circuitry, connect the Cord Clamp to one side/end of the fuse, wire, vehicle battery post, etc. (either positive or negative pole).
3. Gently touch and hold the tip of the Probe against the other side/end of the object being tested.
4. If the Bulb inside the Handle illuminates, this indicates there is electricity flowing through the circuit. No illumination of the Bulb indicates no electricity flowing through the circuit and that repair or replacement of the object being tested is needed.
5. When finished using the Circuit Tester, replace the protective tip and store the tool in a clean, dry, safe location out of reach of children.

Record Product's Serial Number Here: _____

Note: If product has no serial number, record month and year of purchase instead.

Note: Replacement parts are not available for this item.

Maintenance and Servicing



Procedures not specifically explained in this manual must be performed only by a qualified technician.

!WARNING

TO PREVENT SERIOUS INJURY FROM ELECTRICAL CONNECTIONS:
Disconnect the Circuit Tester from all power sources before performing any inspection, maintenance, or cleaning procedures.

Do not use damaged equipment. If abnormal noise or vibration occurs, have the problem corrected before further use.

Cleaning, Maintenance, and Lubrication

1. **BEFORE EACH USE**, inspect the general condition of the tool. Check for loose hardware, misalignment or binding of parts, cracked or broken parts, damaged electrical wiring, and any other condition that may affect its safe operation.
Do not use damaged tools.
2. **AFTER USE**, wipe external surfaces of the tool with clean cloth.

Changing the Bulb

1. To change the Bulb, remove the Cord Clamp from all power sources.
2. Unscrew the Tail Base from the Handle, and remove the Spring.
3. Unscrew the Bulb from the Spring and replace with a new 12V/3W Bulb.
4. Replace the Spring and Bulb in the Handle and screw in the Tail Base.

Limited 90 Day Warranty

Harbor Freight Tools Co. makes every effort to assure that its products meet high quality and durability standards, and warrants to the original purchaser that this product is free from defects in materials and workmanship for the period of 90 days from the date of purchase. This warranty does not apply to damage due directly or indirectly, to misuse, abuse, negligence or accidents, repairs or alterations outside our facilities, criminal activity, improper installation, normal wear and tear, or to lack of maintenance. We shall in no event be liable for death, injuries to persons or property, or for incidental, contingent, special or consequential damages arising from the use of our product. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation of exclusion may not apply to you. THIS WARRANTY IS EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS.

To take advantage of this warranty, the product or part must be returned to us with transportation charges prepaid. Proof of purchase date and an explanation of the complaint must accompany the merchandise. If our inspection verifies the defect, we will either repair or replace the product at our election or we may elect to refund the purchase price if we cannot readily and quickly provide you with a replacement. We will return repaired products at our expense, but if we determine there is no defect, or that the defect resulted from causes not within the scope of our warranty, then you must bear the cost of returning the product.

This warranty gives you specific legal rights and you may also have other rights which vary from state to state.

CEN-TECH®

3491 Mission Oaks Blvd. • PO Box 6009 • Camarillo, CA 93011 • 1-888-866-5797