

Save This Document Keep these instructions for the safety warnings and precautions, assembly, operating, inspection, maintenance and cleaning procedures. Write the product's serial number on this document (or month and year of purchase if product has no number). Keep this document and the receipt in a safe and dry place for future reference.

Rev 23b

When unpacking, make sure that the product is intact and undamaged. If any parts are missing or broken, please call 1-888-866-5797 as soon as possible.

Copyright© 2023 by Harbor Freight Tools®. All rights reserved. No portion of this document or any artwork contained herein may be reproduced in any shape or form without the express written consent of Harbor Freight Tools. Diagrams within this document may not be drawn proportionally. Due to continuing improvements, actual product may differ slightly from the product described herein. Tools required for assembly and service may not be included.

IMPORTANT SAFETY INSTRUCTIONS

⚠️WARNING Read all safety warnings and instructions. Failure to follow the warnings and instructions may result in electric shock and/or serious injury. Save all warnings and instructions for future reference.

1. **DANGER! METAL CONDUCTS ELECTRICITY!** Do not let the ladder come in contact with live electrical wires.

2. Read all labels on the ladder before use.

3. Wear ANSI-approved safety goggles and heavy-duty work gloves during use.

4. Do not use ladder in high winds or storms.

5. Do not overreach, move ladder when needed.

6. To prevent injuries from pinching, keep hands and feet away from moving parts during set up.

7. Use only on a firm, level surface with all feet contacting the surface. Do not use on slippery surfaces.

8. Face ladder and maintain a firm hold when climbing up or down; keep body centered between side rails.
9. Do not place ladder in front of doors opening toward the ladder.

10. Destroy ladder if broken, worn or if exposed to fire or chemical corrosion.

11. Do not exceed listed weight capacity.

12. Dress properly. Do not wear loose clothing or jewelry. Keep hair, clothing and gloves away from moving parts. Loose clothes, jewelry or long hair can be caught in moving parts.

13. Wear slip resistant shoes. Do not wear shoes with leather soles.

14. Properly secure and support ladder while in transit.

15. Do not store materials on ladder.
16. Keep work area clean and well lit.

17. Keep bystanders out of the area during use.

18. Do not use when tired or when under the influence of alcohol, drugs or medication.

19. This product is not a toy. Do not allow children to play with or near this item.

20. Use as intended only.

21. Store in a safe, dry place out of the reach of children.

22. Inspect before every use; do not use if parts are loose or damaged.

23. Maintain product labels and nameplates. These carry important safety information. If unreadable or missing, contact Harbor Freight Tools for a replacement.

USE INSTRUCTIONS

⚠️ Read the **ENTIRE IMPORTANT SAFETY INFORMATION** section at the beginning of this document including all text under subheadings therein before set up or use of this product.

Before Each Use

1. Lubricate hinges with light machine oil or similar substance.

2. Inspect ladder:

a. Make sure all rivets, joints, nuts and bolts are tight; feet, steps and rungs are secure; all hinges function properly.

b. Check for dents, bends, damage from fire or corrosive substances. **Take damaged ladders out of service until repaired by a competent mechanic or destroyed.**
3. **CAUTION!** To avoid slipping injuries, clean all foreign materials from ladder and shoes.

UNLOCKED

Push Knob in until it clicks into unlocked position.

Hinge Lock

Pull Side Lock out, then rotate away from hole.

Side Lock

Hinges lock into place at 75° and 180°.

Hinge Lock

Pull Side Lock out, rotate to hole, then release into hole. Side lock must extend fully into hole.

Side Lock

CAUTION! To prevent injury, lay Ladder flat on the ground before making adjustments. Keep hands and feet away from moving parts during adjustments.

Step / A-Frame

1. Unlock Side Locks on top side.

2. Adjust top rail to desired length.

3. Lock Side Locks.

4. Turn Ladder over.

5. Unlock Side Locks on top side.

6. Adjust top rail to same length as other rail.

7. Lock Side Locks.

Side Locks (both sides)

Hinges (both sides)

8. Unlock Hinges.

9. Pull top side up until Hinges lock into place.

10. Stand Ladder upright.

11. **Verify all Hinges and Side Locks are in locked positions.**

12. Place long end on ground.

13. Place short end on step.

14. Stand Ladder against vertical surface.

15. Make sure top of Ladder is at least 3' above top of vertical surface.

16. Secure Ladder to top of vertical surface.

17. Make sure Ladder is at 75.5° angle to the ground.

18. Verify all Hinges and Side Locks are in locked position.

19. Stand Ladder against vertical surface.

20. Make sure top of Ladder is at least 3' above top of vertical surface.

21. Secure Ladder to top of vertical surface.

22. Verify all Hinges and Side Locks are in locked position.

23. Stand Ladder against vertical surface.

24. Make sure top of Ladder is at least 3' above top of vertical surface.

25. Secure Ladder to top of vertical surface.

26. Verify all Hinges and Side Locks are in locked position.

27. Stand Ladder against vertical surface.

28. Make sure top of Ladder is at least 3' above top of vertical surface.

29. Secure Ladder to top of vertical surface.

30. Verify all Hinges and Side Locks are in locked position.

31. Stand Ladder against vertical surface.

32. Make sure top of Ladder is at least 3' above top of vertical surface.

33. Secure Ladder to top of vertical surface.

34. Verify all Hinges and Side Locks are in locked position.

35. Stand Ladder against vertical surface.

36. Make sure top of Ladder is at least 3' above top of vertical surface.

37. Secure Ladder to top of vertical surface.

38. Verify all Hinges and Side Locks are in locked position.

39. Stand Ladder against vertical surface.

40. Make sure top of Ladder is at least 3' above top of vertical surface.

41. Secure Ladder to top of vertical surface.

42. Verify all Hinges and Side Locks are in locked position.

43. Stand Ladder against vertical surface.

44. Make sure top of Ladder is at least 3' above top of vertical surface.

45. Secure Ladder to top of vertical surface.

46. Verify all Hinges and Side Locks are in locked position.

47. Stand Ladder against vertical surface.

48. Make sure top of Ladder is at least 3' above top of vertical surface.

49. Secure Ladder to top of vertical surface.

50. Verify all Hinges and Side Locks are in locked position.

51. Stand Ladder against vertical surface.

52. Make sure top of Ladder is at least 3' above top of vertical surface.

53. Secure Ladder to top of vertical surface.

54. Verify all Hinges and Side Locks are in locked position.

55. Stand Ladder against vertical surface.

56. Make sure top of Ladder is at least 3' above top of vertical surface.

57. Secure Ladder to top of vertical surface.

58. Verify all Hinges and Side Locks are in locked position.

59. Stand Ladder against vertical surface.

60. Make sure top of Ladder is at least 3' above top of vertical surface.

61. Secure Ladder to top of vertical surface.

62. Verify all Hinges and Side Locks are in locked position.

63. Stand Ladder against vertical surface.

64. Make sure top of Ladder is at least 3' above top of vertical surface.

65. Secure Ladder to top of vertical surface.

66. Verify all Hinges and Side Locks are in locked position.

67. Stand Ladder against vertical surface.

68. Make sure top of Ladder is at least 3' above top of vertical surface.

69. Secure Ladder to top of vertical surface.

70. Verify all Hinges and Side Locks are in locked position.

71. Stand Ladder against vertical surface.

72. Make sure top of Ladder is at least 3' above top of vertical surface.

73. Secure Ladder to top of vertical surface.

74. Verify all Hinges and Side Locks are in locked position.

75. Stand Ladder against vertical surface.

76. Make sure top of Ladder is at least 3' above top of vertical surface.

77. Secure Ladder to top of vertical surface.

78. Verify all Hinges and Side Locks are in locked position.

79. Stand Ladder against vertical surface.

80. Make sure top of Ladder is at least 3' above top of vertical surface.

81. Secure Ladder to top of vertical surface.

82. Verify all Hinges and Side Locks are in locked position.

83. Stand Ladder against vertical surface.

84. Make sure top of Ladder is at least 3' above top of vertical surface.

85. Secure Ladder to top of vertical surface.

86. Verify all Hinges and Side Locks are in locked position.

87. Stand Ladder against vertical surface.

88. Make sure top of Ladder is at least 3' above top of vertical surface.

89. Secure Ladder to top of vertical surface.

90. Verify all Hinges and Side Locks are in locked position.

91. Stand Ladder against vertical surface.

92. Make sure top of Ladder is at least 3' above top of vertical surface.

93. Secure Ladder to top of vertical surface.

94. Verify all Hinges and Side Locks are in locked position.

95. Stand Ladder against vertical surface.

96. Make sure top of Ladder is at least 3' above top of vertical surface.

97. Secure Ladder to top of vertical surface.

98. Verify all Hinges and Side Locks are in locked position.

99. Stand Ladder against vertical surface.

100. Make sure top of Ladder is at least 3' above top of vertical surface.

101. Secure Ladder to top of vertical surface.

102. Verify all Hinges and Side Locks are in locked position.

103. Stand Ladder against vertical surface.

104. Make sure top of Ladder is at least 3' above top of vertical surface.

105. Secure Ladder to top of vertical surface.

106. Verify all Hinges and Side Locks are in locked position.

107. Stand Ladder against vertical surface.

108. Make sure top of Ladder is at least 3' above top of vertical surface.

109. Secure Ladder to top of vertical surface.

110. Verify all Hinges and Side Locks are in locked position.

111. Stand Ladder against vertical surface.

112. Make sure top of Ladder is at least 3' above top of vertical surface.

113. Secure Ladder to top of vertical surface.

114. Verify all Hinges and Side Locks are in locked position.

115. Stand Ladder against vertical surface.

116. Make sure top of Ladder is at least 3' above top of vertical surface.

117. Secure Ladder to top of vertical surface.

118. Verify all Hinges and Side Locks are in locked position.

119. Stand Ladder against vertical surface.

120. Make sure top of Ladder is at least 3' above top of vertical surface.

121. Secure Ladder to top of vertical surface.

122. Verify all Hinges and Side Locks are in locked position.

123. Stand Ladder against vertical surface.

124. Make sure top of Ladder is at least 3' above top of vertical surface.

125. Secure Ladder to top of vertical surface.

126. Verify all Hinges and Side Locks are in locked position.

127. Stand Ladder against vertical surface.

128. Make sure top of Ladder is at least 3' above top of vertical surface.

129. Secure Ladder to top of vertical surface.

130. Verify all Hinges and Side Locks are in locked position.

131. Stand Ladder against vertical surface.

132. Make sure top of Ladder is at least 3' above top of vertical surface.

133. Secure Ladder to top of vertical surface.

134. Verify all Hinges and Side Locks are in locked position.

135. Stand Ladder against vertical surface.

136. Make sure top of Ladder is at least 3' above top of vertical surface.

137. Secure Ladder to top of vertical surface.

138. Verify all Hinges and Side Locks are in locked position.

139. Stand Ladder against vertical surface.

140. Make sure top of Ladder is at least 3' above top of vertical surface.

141. Secure Ladder to top of vertical surface.

142. Verify all Hinges and Side Locks are in locked position.

143. Stand Ladder against vertical surface.

144. Make sure top of Ladder is at least 3' above top of vertical surface.

145. Secure Ladder to top of vertical surface.

146. Verify all Hinges and Side Locks are in locked position.

147. Stand Ladder against vertical surface.

148. Make sure top of Ladder is at least 3' above top of vertical surface.

149. Secure Ladder to top of vertical surface.

150. Verify all Hinges and Side Locks are in locked position.

151. Stand Ladder against vertical surface.

152. Make sure top of Ladder is at least 3' above top of vertical surface.

153. Secure Ladder to top of vertical surface.

154. Verify all Hinges and Side Locks are in locked position.

155. Stand Ladder against vertical surface.

156. Make sure top of Ladder is at least 3' above top of vertical surface.

157. Secure Ladder to top of vertical surface.

158. Verify all Hinges and Side Locks are in locked position.

159. Stand Ladder against vertical surface.

160. Make sure top of Ladder is at least 3' above top of vertical surface.

161. Secure Ladder to top of vertical surface.

162. Verify all Hinges and Side Locks are in locked position.

163. Stand Ladder against vertical surface.

164. Make sure top of Ladder is at least 3' above top of vertical surface.

165. Secure Ladder to top of vertical surface.

166. Verify all Hinges and Side Locks are in locked position.

167. Stand Ladder against vertical surface.

168. Make sure top of Ladder is at least 3' above top of vertical surface.

169. Secure Ladder to top of vertical surface.

170. Verify all Hinges and Side Locks are in locked position.

171. Stand Ladder against vertical surface.

172. Make sure top of Ladder is at least 3' above top of vertical surface.

173. Secure Ladder to top of vertical surface.

174. Verify all Hinges and Side Locks are in locked position.

175. Stand Ladder against vertical surface.

176. Make sure top of Ladder is at least 3' above top of vertical surface.

177. Secure Ladder to top of vertical surface.

178. Verify all Hinges and Side Locks are in locked position.

179. Stand Ladder against vertical surface.

180. Make sure top of Ladder is at least 3' above top of vertical surface.

181. Secure Ladder to top of vertical surface.

182. Verify all Hinges and Side Locks are in locked position.

183. Stand Ladder against vertical surface.

184. Make sure top of Ladder is at least 3' above top of vertical surface.

185. Secure Ladder to top of vertical surface.

186. Verify all Hinges and Side Locks are in locked position.

187. Stand Ladder against vertical surface.

188. Make sure top of Ladder is at least 3' above top of vertical surface.

189. Secure Ladder to top of vertical surface.

190. Verify all Hinges and Side Locks are in locked position.

191. Stand Ladder against vertical surface.

192. Make sure top of Ladder is at least 3' above top of vertical surface.

193. Secure Ladder to top of vertical surface.

194. Verify all Hinges and Side Locks are in locked position.

195. Stand Ladder against vertical surface.

196. Make sure top of Ladder is at least 3' above top of vertical surface.

197. Secure Ladder to top of vertical surface.

198. Verify all Hinges and Side Locks are in locked position.

199. Stand Ladder against vertical surface.