HARBOR FREIGHT TOOLS

1.1

12

1.3

14

15

1.6

1.7

1.8

1.9

2.1

4.1

4.2

4.3

4.4

4.5

4.6

Page 1 of 6 HFT-03185

SAFETY DATA SHEET Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 5/14/2015 1. PRODUCT & COMPANY IDENTIFICATION Product Name: 800 LB LOW LIFT TRANSMISSION JACK Chemical Name Hydraulic Oil Synonyms P/N 03185 Trade Names Pittsburgh Automotive Product Uses & Restrictions Hydraulic Oil Distributor's Name Harbor Freight Tools USA, Inc. Distributor's Address: 26541 Agoura Road, Calabasas, CA 91302 USA Emergency Phone: CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687) Business Phone / Fax: +1 (805) 388-1000 2. HAZARDS IDENTIFICATION Hazard Identification: This product is classified as a HAZARDOUS SUBSTANCE but not as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia). DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. Classification: Asp. Tox. 1 Hazard Statements (H): H304 - May be fatal if swallowed and enters airways. Precautionary Statements (P): P280 - Wear protective gloves/eye protection. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331 - Do NOT induce vomiting. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. P405 - Store locked up. P501 - Dispose of contents/ container to an approved waste disposal plant. 3. COMPOSITION & INGREDIENT INFORMATION EXPOSURE LIMITS IN AIR (mg/m³) ACGIH NOHSC OSHA ppm ppm ppm ES-ES-ESтιν STEL PEL STEL IDLH RTECS No. EINECS No. PEAK OTHER CHEMICAL NAME(S) CAS No. TWA STEL % 64741-51-4 NA NA 60-100 NA 5 5 NF NF 5 NA NA OIL MIST DISTILLATES (PETROLEUM), PARAFFINIC Asp. Tox.1; H304 4. FIRST AID MEASURES First Aid: Ingestion: DO NOT INDUCE VOMITING. Contact ChemTrec at +1 (703) 527-3887 or the nearest Poison Control Center or local emergency telephone number for assistance and instructions. Seek immediate medical attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration. If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 minutes, Eyes: holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately. Skin: Remove contaminated clothing and wash affected areas with soap and water. If irritation persists, seek prompt medical attention. Do not wear contaminated clothing until after it has been properly cleaned. Inhalation: Remove victim to fresh air at once. If breathing is difficult, administer supplemental oxygen and seek immediate medical attention. If breathing stops, perform artificial respiration. Effects of Exposure: If product is swallowed, may cause nausea, vomiting and/or diarrhea. Ingestion: Eves: May cause transient mild-eye irritation with short-term contact with liquid, spray or mist. Skin: This product can cause mild, transient skin irritation with short-term exposure. This product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. Inhalation: No significant adverse health effects are expected to occur upon short-term exposure to this product. Aspiration of liquid into the lungs can cause severe lung damage or death. Drowsiness, dizziness, headaches and nausea. Symptoms of Overexposure: Overexposure in eyes may cause redness, itching and watering. Eyes: Symptoms of skin overexposure may include redness, itching, and irritation of affected areas The product Skin: can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure Acute Health Effects: Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. Chronic Health Effects: Contains a petroleum-based mineral oil. Prolonged or repeated skin contact can cause mild irritation and inflammation characterized by drying, cracking, (dermatitis) or oil acne. Repeated or prolonged inhalation of petroleum-based mineral oil mists at concentrations above applicable workplace exposure levels can cause respiratory irritation or other pulmonary effects Target Organs: Eyes, Skin, Respiratory System, Central Nervous System (CNS).

HARBOR FREIGHT TOOLS Quality Tools at Ridiculously Low Prices

SAFETY DATA SHEET

Page 2 of 6 **HFT-03185**

Prepa	ared to OSHA, ACC, ANSI, N		C Stand	dards		SDS Rev	vision: 1.0		SDS Re	vision Da	te: 5/14/2015	
4. FIRST AID MEASURES – cont'd												
4.7	Medical Conditions Aggravated by Exposure:	Pre-existing dermatitis, other skin conditions, and disorders of the target organs (eyes, skin, and respiratory system). HEALTH 1 FLAMMABILITY 1 PHYSICAL HAZARDS 0 PROTECTIVE EQUIPMENT X EYES SKIN LUNGS										
	5. FIREFIGHTING MEASURES											
5.1												
	the flash point temperature that can ignite when exposed to a source of ignition. In enclosed spaces, heated vapor can ignite with explosive force. Mists or sprays may burn at temperatures below the flash point. Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and trace oxides of sulfur, phosphorus, zinc and nitrogen. Also, depending upon the conditions of use, low concentrations of hydrogen sulfide can be released.											
5.2 5.3	Extinguishing Methods: Firefighting Procedures:	Dry Chemical, Foam, Carbon Dio				water enr	ny ta agal f	ire evr	and a			
5.3	Fileighting Procedures.	and to protect personal. Avoid s boil over. Prevent runoff from f supply, or any natural waterway. positive pressure self-contained	Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Avoid spraying water directly into storage containers because of danger of boil over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.									
		6. ACCIDEN	TAL	RELE	EASE	MEASL	JRES					
6.1	Spills:	Before cleaning any spill or lead Equipment.	ak, indi	viduals	involved	in spill cle	eanup mus					
	For <u>small spills</u> (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water.											
			0.07									
7.1	Work & Hygiene Practices:	7. HANDLING Use normal hygiene practices. A this product and before eating, dr	Avoid b	reathing	vapors.			tact. \	Nash ha	ands the	proughly after using	
7.2	Storage & Handling:	Use and store in a cool, dry, we possible sources of ignition. Do r Recommended maximum shelf lift	ell-vent	ilated ar e in unm	rea. Keep				at, open	flames	, sparks, and other	
7.3	Special Precautions:	Empty containers may contain p empty containers without comme	roduct	residue.			cut, heat	or wel	d empty	contair	ners. Do not reuse	
		8. EXPOSURE CONT	ROI	S & I	PERSC)NAL F	ROTE	СТІС)N			
8.1	Exposure Limits:			GIH		NOHSC			OSHA	1	OTHER	
	ppm (mg/m ³)	CHEMICAL NAME(S) DISTILLATES (PETROLEUM),	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH		
		PARAFFINIC	NA	5	5	NF	NF	5	NA	NA	OIL MIST	
8.2	Ventilation & Engineering Controls: The use of mechanical dilution ventilation is recommended to maintain airborne concentrations below the recommended occupational exposure limits, whenever this material is used in a confined space, is heated above normal temperatures (up to 38 °C) or is agitated.										ormal temperatures	
8.3	Respiratory Protection: Vaporization or misting is not expected at ambient temperatures. Therefore, the need for respiratory protection is not anticipated under normal use conditions and with adequate ventilation. If elevated airborne concentrations above applicable workplace exposure levels are anticipated, a NIOSH-approved organic vapor respirator equipped with a dust/mist pre-filter should be used. Protection factors vary depending upon the type of respirator used. Respirators should be used in accordance with OSHA requirements (29 CFR 1910.134).											
8.4	Eye Protection: Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Wear goggles and/or face shield if splashing or spraying is anticipated. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants. Have suitable eye wash water available. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).											

SAFETY DATA SHEET

Page 3 of 6 HFT-03185

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 5/14/2015

	8. EXPOSURE CONTROLS & PERSONAL PROTECTION – cont'd								
8.5	Hand Protection:	Use gloves constructed of chemical-resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, or the EU member states.							
8.6	Body Protection:	Avoid prolonged and/or repeated skin contact. Use clean and impervious protective clothing (e.g., neoprene or Tyvek [®]) if splashing or spraying conditions are present. Protective clothing should include long-sleeves, apron, boots and additional facial protection. If necessary, refer to appropriate standards of Canada, the EU member states, or U.S. OSHA.							

	9. PHYSICAL & CHEMICAL PROPERTIES								
9.1	1 Appearance: Clear liquid								
9.2	Odor:	Characteristic mild petroleum odor							
9.3	Odor Threshold:	NA							
9.4	pH:	NA							
9.5	Melting Point/Freezing Point:	Pour Point: - 44.0 °C							
9.6	Initial Boiling Point/Boiling Range:	NA							
9.7	Flashpoint:	> 150 °C (> 302 °F)							
9.8	Upper/Lower Flammability Limits:	LEL: 0.9%; UEL: 7.0%							
9.9	Vapor Pressure:	NA							
9.10	Vapor Density:	NA							
9.11	Relative Density:	0.8337 g/cm ³ @ 15 °C (59 °F)							
9.12	Solubility:	Insoluble							
9.13	Partition Coefficient (log Pow):	NA							
9.14	Autoignition Temperature:	NA							
9.15	Decomposition Temperature:	NA							
9.16	Viscosity:	15.21 @ 40 °C SUS; 2.28 @ 100 °C							
9.17	Other Information:	NA							

10. STABILITY & REACTIVITY

10.1	Stability:	Stable at normal temperatures.							
10.2	Hazardous Decomposition Products:	Fumes, smoke, carbon monoxide, silicon oxides.							
10.3	Hazardous Polymerization:	Vill not occur.							
10.4	Conditions to Avoid:	Open flames, sparks, high heat, and close proximity to incompatible substances.							
10.5	10.5 Incompatible Substances: Strong oxidizing agents.								
		11. TOXICOLOGICAL INFORMATION							
11.1	Routes of Entry:	Inhalation: NO Absorption: YES Ingestion: YES							
11.2	Toxicity Data:	This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product and is presented below: Based on animal testing from similar materials & products, the acute toxicity of this product is expected to be: <u>Distillates</u> , <u>Petroleum</u> , <u>Paraffinic</u> – LD ₅₀ (oral, rat) > 5,000 mg/kg; LD ₅₀ (dermal, rabbit) > 2,000 mg/kg.							
11.3	Acute Toxicity:	Mineral oil mists derived from highly refined oils are reported to have low acute and sub-acute toxicities in animals. Effects from single and short-term repeated exposures to high concentrations of mineral oil mists well above applicable workplace exposure levels include lung inflammatory reaction, lipoid granuloma formation and lipoid pneumonia. In acute and sub-acute studies involving exposures to lower concentrations of mineral oil mists at or near current work place exposure levels produced no significant toxicological effects.							
11.4	Chronic Toxicity:	NA							
11.5	Suspected Carcinogen:	NA							
11.6	Reproductive Toxicity:	This product is not reported to produce reproductive toxicity in humans.							
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.							
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.							
	Teratogenicity:	This product is not reported to produce teratogenic effects in humans.							
	Reproductive Toxicity:	This product is not reported to produce reproductive effects in humans.							
11.7	Irritancy of Product:	See Section 4.3							
11.8	Biological Exposure Indices:	NE							
11.9	Physician Recommendations:	Treat symptomatically.							

HARBOR FREIGHT TOOLS

SAFETY DATA SHEET

Page 4 of 6 HFT-03185

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 5/14/2015

	12. ECOLOGICAL INFORMATION									
12.1	Environmental Stability:	There are no specific data available for this product.								
12.2										
12.3	2.3 Effects on Aquatic Life: There are no specific data available for this product.									
	13. DISPOSAL CONSIDERATIONS									
13.1	Waste Disposal:	Dispose of in accordance with federal, state, provincial and local regulations.								
13.2	Special Considerations:	NA								
		14. TRANSPORTATION INFORMATION								
		nber, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional e required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.								
14.1	49 CFR (GND):	NOT REGULATED								
14.2	IATA (AIR):	NOT REGULATED								
14.3	IMDG (OCN):	NOT REGULATED								
14.4	TDGR (Canadian GND):	NOT REGULATED								
14.5	ADR/RID (EU):	NOT REGULATED								
14.6	SCT (MEXICO):	NOT REGULATED								
14.7	ADGR (AUS):	NOT REGULATED								
		15. REGULATORY INFORMATION								
15.1	SARA Reporting Requirements:	This product does not contain any substances subject to SARA Title III, section 313 reporting requirements.								
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.								
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory or are otherwise exempt.								
15.4	CERCLA Reportable Quantity (RQ):	NA								
15.5	Other Federal Requirements:	None of the ingredients are listed as Hazardous Air Pollutants (HAPs). None of the ingredients are listed as Toxic Pollutants under the Clean Water Act (CWA). None of the ingredients are listed as Priority Pollutants under the Clean Water Act (CWA). This product does not contain any Class 1 or Class 2 ozone depletors.								
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS D2B (Other Toxic Effects)								
15.7	State Regulatory Information:	No ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).								
15.8	Other Requirements:	The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC: <u>Distillates (Petroleum), Paraffinic</u> : Harmful (Xn). <u>Risk Phrases</u> (R): 65 – Harmful: may cause lung damage if swallowed. <u>Safety Phrases</u> (S): 53-45 – Avoid exposure – obtain special instructions before use. In case of accident or if you feel unwell seek medical advice immediately (show the label where possible).								

SAFETY DATA SHEET

Page 5 of 6 HFT-03185

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 5/14/2015

	16. OTHER INFORMATION							
16.1	Other Information:	DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. Wash exposed skin areas thoroughly with soap and water after handling. Avoid eye contact. Wear protective gloves/eye protection/face protection. IF ON SKIN: Wash with soap and water. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If skin irritation or a rash occurs – Get medical advice/attention. Store in a well-ventilated place. Keep cool. Use only as directed. KEEP OUT OF REACH OF CHILDREN.						
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.						
16.3	Disclaimer:	government regulations must be reviewed for ap Tools USA, Inc.'s knowledge, the information accuracy, suitability or completeness is not guara provided. The information contained herein rela	his Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other overnment regulations must be reviewed for applicability to this product. To the best of ShipMate's & Harbor Freight ools USA, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, ccuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are rovided. The information contained herein relates only to the specific product(s). If this product(s) is combined with ther materials, all component properties must be considered. Data may be changed from time to time. Be sure to					
16.4	Prepared for:	Harbor Freight Tools USA, Inc. 26541 Agoura Road Calabasas, CA 91302 USA Tel: +1 (805) 388-1000 http://www.harborfreight.com/	HARBOR FREIGHT TOOLS Quality Tools at Ridiculously Low Prices					
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com						

SAFETY DATA SHEET

Page 6 of 6 HFT-03185

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 5/14/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No. Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:							
ACGIH	CGIH American Conference on Governmental Industrial Hygienists						
C Ceiling Limit							
ES	Exposure Standard (Australia)						
IDLH Immediately Dangerous to Life and Health							
OSHA	U.S. Occupational Safety and Health Administration						
PEL	Permissible Exposure Limit						
STEL	Short-Term Exposure Limit						
TLV Threshold Limit Value							
TWA Time Weighted Average							
FIRST AID MEASURES:							

CPR Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.

HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:								
0	Minimal Hazard	HEALTH						
1	1 Slight Hazard 2 Moderate Hazard 3 Severe Hazard		FLAMMABILITY					
2			PHYSICAL HAZARDS					
3			PERSONAL PROTECTION					
4	Extreme Hazard							

PERSONAL PROTECTION RATINGS:

ppm parts per million

FLAMMABILITY LIMITS IN AIR:

Autoianition

Temperature

LEL

UFI

SCBA Self-Contained Breathing Apparatus NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

source of ignition

Α					Ģ	6		E		8	
в					ŀ	1		E		品	
С			P.		I			E		8	
D	B		Par la		J	J		E)	Î	
Е					K	(9	E			
F 🕞 🕚 🕻					X	(Consult special I				r SOPs f s.
	0			9	F	Face Shield &					
Sa	fety Glass	es	Splash Goggles			Protective Eyewear			Gloves		
	Boots		Synthet	ic Apron		Protective Clothing & Full Suit			Dust Respirator		
			8	3		@			Ŵ		
Full I	ace Respi	rator		apor Half-	Full Face				Airline Hood/Mask or SCBA		
Mask Respirator Respirator OTHER STANDARD ABBREVIATIONS:									0 30	DA	
<u> </u>											
mg/m3 milligrams per cubic meter											
NA Not Available											
ND Not Determined											
NE Not Established											
	NF	Not Fo	ound								
NR No Results									_		

Minimum temperature required to initiate combustion in air with no other

Lower Explosive Limit - lowest percent of vapor in air, by volume, that will

Upper Explosive Limit - highest percent of vapor in air, by volume, that will

explode or ignite in the presence of an ignition source

explode or ignite in the presence of an ignition source

HAZARD RATINGS: FLAMMABILITY 0 Minimal Hazard Slight Hazard 1 REACTIVITY 2 Moderate Hazard 3 Severe Hazard 4 Extreme Hazard ACD Acidic ALK Alkaline COR Corrosive HEALTH ₩ Use No Water SPECIAL ox Oxidizer PRECAUTIONS TREFOIL Radioactive TOXICOLOGICAL INFORMATION: LD₅₀ Lethal Dose (solids & liquids) which kills 50% of the exposed animals LC₅₀ Lethal concentration (gases) which kills 50% of the exposed animal Concentration expressed in parts of material per million parts ppm TDIo Lowest dose to cause a symptom TCLo Lowest concentration to cause a symptom TD_{Io}, LD_{Io}, & LD_o or Lowest dose (or concentration) to cause lethal or toxic effects TC, TC_o, LC_{io}, & LC_o International Agency for Research on Cancer IARC NTP National Toxicology Program RTECS Registry of Toxic Effects of Chemical Substances BCF **Bioconcentration Factor** \mathbf{TL}_{m} Median threshold limit log K_{ow} or log K_{oc} Coefficient of Oil/Water Distribution **REGULATORY INFORMATION:** WHMIS Canadian Workplace Hazardous Material Information System DOT U.S. Department of Transportation тс Transport Canada EPA U.S. Environmental Protection Agency DSL Canadian Domestic Substance List NOHSC National Occupational Health and Safety Commission (Australia) NDSL Canadian Non-Domestic Substance List PSL Canadian Priority Substances List TSCA U.S. Toxic Substance Control Act EU European Union (European Union Directive 67/548/EEC) WGK Wassergefährdungsklassen (German Water Hazard Class) HMIS-III National Paint & Coatings Association Hazardous Materials Identification System WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM: 囊 Ř 0 4 ð Class A Class B Class C Class D1 Class D2 Class D3 Class E Class F Flammable Oxidizing Toxic Irritation Infectious Compressed Corrosive Reactive EC (67/548/EEC) INFORMATION: . .. -1 T × 4 С Е F Ν 0 т Xi Хn Corrosive Flammable Oxidizing Toxic Explosive Harmful Irritant Harmful CLP/GHS (1272/2008/EC) PICTOGRAMS: S. K 约 Θ Ł GHS01 GHS02 GHS03 GHS04 GHS05 GHS06 GHS07 GHS08 GHS09

Harmfu

Irritating

Flammable

Explosive

Oxidizer

Pressurize

Corrosive

Toxic

Health

Hazard

Environmer