SAFETY DATA SHEET

Page 1 of 6 HFT-40711

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 4/30/2015 SDS Revision: 1.0 1. PRODUCT & COMPANY IDENTIFICATION 1.1 Product Name LITHIUM GREASE 12 Chemical Name NA 1.3 Synonyms: P/N 40711 14 Trade Names **CRC** Industries 15 Product Uses & Restrictions Lubricating grease 1.6 Distributor's Name: Harbor Freight Tools USA, Inc. 1.7 Distributor's Address: 26541 Agoura Road, Calabasas, CA 91302 USA 1.8 Emergency Phone: CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687) 19 Business Phone / Fax: +1 (805) 388-1000 2. HAZARDS IDENTIFICATION This product is classified as a HAZARDOUS SUBSTANCE but not as DANGEROUS GOODS 2.1 Hazard Identification: according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia). In the event of an exposure or medical inquiry involving this product, please contact a physician or local poison control center, who may seek advice from the U.S. manufacturer, and show them this SDS. Aqueous solution. DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. Classification: Asp. Tox. 1; Hazard Statements (H): H304 - May be fatal if swallowed and enters airways. H350 - May cause cancer. Precautionary Statements (P): P280 - Wear protective gloves/eye protection. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331 - Do NOT induce vomiting. P405 - Store locked up. P501 - Dispose of contents/ container to an approved waste disposal plant 3. COMPOSITION & INGREDIENT INFORMATION EXPOSURE LIMITS IN AIR (mg/m³) ACGIH NOHSC OSHA ppm ppm ppm ES-ES-ES-CHEMICAL NAME(S) CAS No. RTECS No EINECS No. TLV STE TWA <u>STEI</u> PEAK PEI STEI IDLH OTHER 64742-52-5 265-155-0 85-95 NA NA OIL MIST SEVERELY HYDROTREATED NA (5) (10)(5) NA (5) NA 265-097-6 64741-96-4 NAPHTHENIC PETROLEUM OIL * contains less than 3% DMSO; Asp. Tox. 1; H304 NA 231-536-5 3-7 7620-77-1 15 NA NE NA NA NA 15 NA LITHIUM 12-HYDROXYSTEARATE 4. FIRST AID MEASURES 4.1 First Aid: DO NOT INDUCE VOMITING. Contact ChemTrec at +1 (703) 527-3887 or the nearest Poison Control Ingestion: Center or local emergency telephone number for assistance and instructions. Seek immediate medical attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration. Eyes: If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 minutes, holding evelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately. Remove contaminated clothing and wash affected areas with soap and water. If irritation persists, seek Skin: prompt medical attention. Do not wear contaminated clothing until after it has been properly cleaned. Inhalation: Remove victim to fresh air at once. If breathing is difficult, administer supplemental oxygen and seek immediate medical attention. If breathing stops, perform artificial respiration. 4.2 Effects of Exposure: If product is swallowed, may cause nausea, vomiting and/or diarrhea. Ingestion: May cause transient mild-eye irritation with short-term contact with liquid, spray or mist. Eyes: Skin: This product can cause mild, transient skin irritation with short-term exposure. This product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. Inhalation: No significant adverse health effects are expected to occur upon short-term exposure to this product. Aspiration of liquid into the lungs can cause severe lung damage or death. 43 Symptoms of Overexposure: Eyes: Overexposure in eyes may cause redness, itching and watering. Symptoms of skin overexposure may include redness, itching, and irritation of affected areas The product Skin: can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. 4.4 Acute Health Effects: Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea

SAFETY DATA SHEET

Page 2 of 6 **HFT-40711**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

		4. FIRST											
4.5	characterized by drying, cracking, (dermatitis) or oil acne. Repeated or prolonged inhalation of petroleum-based mineral oil mists at concentrations above applicable workplace exposure levels can cause respiratory irritation or other pulmonary effects.												
4.6	Target Organs:		Eyes, skin & respiratory system.										
4.7	Medical Conditions Aggravated by Exposure:	Pre-existing dermatitis, other s				rders of t	the HEAL	.TH				1	
	Aggravated by Exposure.	target organs (eyes, skin, and res	spirator	y systen	า).		FLAN	IMAB	ILITY			1	
							PHYS		HAZA	RDS		0	
											NIT		
										UIPME		В	
	EYES SKIN												
		5. FIRE	FIGH	ITING	MEAS	SURES	5						
5.1													
5.2	Extinguishing Methods:	Dry chemical, foam, carbon dioxi	de. and	water for	oa.							$\langle 0 \rangle$	
5.3	Firefighting Procedures:	Keep containers cool until well a and to protect personal. Avoid s boil over. Prevent runoff from f supply, or any natural waterway. positive pressure self-containe	Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Avoid spraying water directly into storage containers because of danger of boil over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.										
6.1	Spills:	6. ACCIDEN Before cleaning any spill or le											
		Equipment. For <u>small spills</u> (e.g., < 1 galled Maximize ventilation (open doo absorbent material and place int local, state and federal regulatio soap. Remove any contaminated For <u>large spills</u> (e.g., ≥ 1 gallor material (e.g., sand or earth). U recovery or disposal and solid dii promptly and wash affected skin sewers and open bodies of water	rs and o appro ons. W d clothir n (3.8 L se ONL se ONL king ma n areas	window opriate c ash all ng and w .)), deny .Y non-s iterial to	vs) and se closed con affected a vash thoro v entry to parking to separate	ecure all stainer(s) for reas and ughly befor all unprot pols for reconstainers	sources of or disposal. outside of ore reuse. ected indivi- covery and for proper	ignitio Dispo contair iduals. cleanu dispos	n. Rei ose of p ner with Dike p. Tran al. Ren	move sporoperly plenty and con sfer liqu	pilled mate in accorda of warm w ntain spill v uid to conta ntaminated	with inert ainers for clothing	
	•	7. HANDLING	& S	TORA	AGE IN	FORM	ATION						
7.1	Work & Hygiene Practices:	Use normal hygiene practices. It this product and before eating, dr				Avoid dire	ect skin con	tact. N	Wash ha	ands the	proughly af	ter using	
7.2	Storage & Handling:	Use and store in a cool, dry, w possible sources of ignition. Do n Recommended maximum shelf li	not stor	e in unm	rea. Keep narked cor	o away fro ntainers or	om excessiv storage dev	ve hea vices.	it, open	flames,	, sparks, a	nd other	
7.3	Special Precautions:	Empty containers may contain p empty containers without comme	roduct rcial cle	residue. eaning o	Do not j r reconditi	oressurize oning.	, cut, heat	or weld	d empty	contair	ners. Do n	ot reuse	
├				• • •				0T1-					
<u> </u>	T	8. EXPOSURE CON			PERSC		KOIE						
8.1	Exposure Limits:		AC	GIH		NOHSC	r		OSHA	1	OTHER		
	ppm (mg/m³)	CHEMICAL NAME(S) SEVERELY HYDROTREATED	TLV (5)	STEL (10)	ES-TWA (5)	ES-STEL NA	ES-PEAK NA	PEL (5)	STEL NA	IDLH NA	OIL MIST		
		NAPHTHENIC PETROLEUM OIL LITHIUM 12-HYDROXYSTEARATE	15	NA	NE	NA	NA	NA	15	NA			
8.2	Ventilation & Engineering												
0.2	Controls:	The use of mechanical dilution v occupational exposure limits, wh (up to 38 °C) or is agitated.											
8.3	Respiratory Protection:	(up to 38 °C) or is agitated. Vaporization or misting is not expected at ambient temperatures. Therefore, the need for respiratory protection is not anticipated under normal use conditions and with adequate ventilation. If elevated airborne concentrations above applicable workplace exposure levels are anticipated, a NIOSH-approved organic vapor respirator equipped with a dust/mist pre-filter should be used. Protection factors vary depending upon the type of respirator used. Respirators should be used in accordance with OSHA requirements (29 CFR 1910.134).											

SAFETY DATA SHEET

Page 3 of 6 **HFT-40711**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0 SDS

		8. EXPOSURE CONTROLS & PERSONAL PROTECTION – cont'd	
8.4	Eye Protection:	Safety glasses equipped with side shields should be adequate protection under most conditions of use. Wear goggles and/or face shield if splashing or spraying is anticipated. Wear goggles and face shield if material is heated above 125 °F (51 °C). Have suitable eye wash water available.	9
8.5	Hand Protection:	Use gloves constructed of chemical resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected.	
8.6	Body Protection:	Avoid prolonged and/or repeated skin contact. Use clean and impervious protective clothing (e.g., neoprene or Tyvek®) if splashing or spraying conditions are present. Protective clothing should include long-sleeves, apron, boots and additional facial protection. Remove oil contaminated clothing. Launder oil contaminated clothing before reusing. Contaminated leather goods should be removed promptly and discarded.	
		9. PHYSICAL & CHEMICAL PROPERTIES	
9.1	Appearance:	Amber colored semi-solid grease.	
9.2	Odor:	Mild petroleum odor.	
0.2	Odor Throshold:	N10	

9.2	Odor:	Mild petroleum odor.
9.3	Odor Threshold:	ΝΑ
9.4	pH:	NA
9.5	Melting Point/Freezing Point:	NA
9.6	Initial Boiling Point/Boiling Range:	NA
9.7	Flashpoint:	246.1 °C (475 °F) COC
9.8	Upper/Lower Flammability Limits:	NA
9.9	Vapor Pressure:	< 0.1 mmHg
9.10	Vapor Density:	> 5.0
9.11	Relative Density:	0.90 @ 60 °F
9.12	Solubility:	Insoluble
9.13	Partition Coefficient (log Pow):	NA
9.14	Autoignition Temperature:	NA
9.15	Decomposition Temperature:	NA
9.16	Viscosity:	NA
9.17	Other Information:	VOC: < 0.9 g/L; < 0.01 lbs/gal (< 0.1% w/w)
		10. STABILITY & REACTIVITY
10.1	Stability:	Stable at normal temperatures.
10.2	Hazardous Decomposition Products:	Fumes, smoke, carbon monoxide, silicon oxides.
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Open flames, sparks, high heat, and close proximity to incompatible substances.
10.5	Incompatible Substances:	Strong oxidizing agents.
		11. TOXICOLOGICAL INFORMATION
11.1	Routes of Entry:	Inhalation: NO Absorption: YES Ingestion: YES
11.2	Toxicity Data:	This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product, but is not presented in this document.
11.3	Acute Toxicity:	Mineral oil mists derived from highly refined oils are reported to have low acute and sub-acute toxicities in animals. Effects from single and short-term repeated exposures to high concentrations of mineral oil mists well above applicable workplace exposure levels include lung inflammatory reaction, lipoid granuloma formation and lipoid pneumonia. In acute and sub-acute studies involving exposures to lower concentrations of mineral oil mists at or near current work place exposure levels produced no significant toxicological effects.
11.4	Chronic Toxicity:	See section 4.5
11.5	Suspected Carcinogen:	No.
11.6	Reproductive Toxicity:	This product is not reported to produce reproductive toxicity in humans.
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.
	Teratogenicity:	This product is not reported to produce teratogenic effects in humans.
	Reproductive Toxicity:	This product is not reported to produce reproductive effects in humans.
11.7	Irritancy of Product:	See section 4.3
11.8	Biological Exposure Indices:	NE
11.9	Physician Recommendations:	The viscosity range of the product(s) represented by this SDS is between 100 and 400 SUS at 100 °F. Accordingly, upon ingestion there is a moderate risk of aspiration. Careful gastric lavage or emesis may be considered to evacuate large quantities of material. Subcutaneous or intramuscular injection requires prompt surgical debridement.

SAFETY DATA SHEET

Page 4 of 6 **HFT-40711**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

	12. ECOLOGICAL INFORMATION										
12.1	Environmental Stability:	There are no specific data available for this product.									
12.2	Effects on Plants & Animals:										
12.3	2.3 Effects on Aquatic Life: There are no specific data available for this product.										
	13. DISPOSAL CONSIDERATIONS										
13.1	Waste Disposal:	Dispose of in accordance with federal, state, provincial & local regulations.									
13.2	Special Considerations:	NA									
		14. TRANSPORTATION INFORMATION									
The	basic description (ID Nur	nber, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additiona	al								
		e required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.									
14.1	49 CFR (GND):	NOT REGULATED									
14.2	IATA (AIR):	NOT REGULATED									
14.3	IMDG (OCN):	NOT REGULATED									
14.4	TDGR (Canadian GND):	NOT REGULATED									
14.5	ADR/RID (EU):	NOT REGULATED									
14.6	SCT (MEXICO):	NOT REGULATED									
14.7	ADGR (AUS):	NOT REGULATED									
	1	15. REGULATORY INFORMATION									
15.1	SARA Reporting Requirements:	This product does not contain any substances subject to SARA Title III, section 313 reporting requirements.									
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.									
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory or are otherwise exempt.									
15.4	CERCLA Reportable Quantity (RQ):	NA									
15.5	Other Federal Requirements:	This material does not contain any hazardous air pollutants. None of the components in this product are listed as priori	ity								
		pollutants under the CWA. None of the components in this product are listed as toxic pollutants under the CWA.									
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List.									
		WHMIS D2B (Other Toxic Effects)									
15.7	State Regulatory Information:	Lithium 12-Hydroxystearate is found on the following state criteria list: NJ.									
	·····	No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state	te								
		criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substance	es								
		List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardou	us								
		Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvan	ia								
15.8	Other Requirements:	Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).									
15.6	Other Requirements.	The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC: Harmful (Xn). Risk Phrases (R): 65 – Harmful: may cause lung damage if swallowed. Safety									
		Phrases (S): 1/2-53-45-46 – Keep locked up and out of reach of children. Avoid exposure – obtain									
		special instructions before use. In case of accident or if you feel unwell seek medical advice									
		immediately (show the label where possible). If swallowed, seek medical advice immediately and									
		show this container label.									

SAFETY DATA SHEET

Page 5 of 6 HFT-40711

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

		16. OTHER INFO	DRMATION							
16.1	16.1 Other Information: DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. Wash exposed skin areas thoroughly with soap and water after handling. Avoid eye contact. Wear protective gloves/eye protection/face protection. IF ON SKIN: Wash with soap and water. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If skin irritation or a rash occurs – Get medical advice/attention. Store in a well-ventilated place. Keep cool. Use only as directed. KEEP OUT OF REACH OF CHILDREN.									
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.								
16.3	Disclaimer:	government regulations must be reviewed for an Tools USA, Inc.'s knowledge, the information accuracy, suitability or completeness is not guar provided. The information contained herein rela	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Harbor Freight Tools USA, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.							
16.4	Prepared for:	Harbor Freight Tools USA, Inc. 26541 Agoura Road Calabasas, CA 91302 USA Tel: +1 (805) 388-1000 http://www.harborfreight.com	HARBOR FREIGHT TOOLS Quality Tools at Ridiculously Low Prices							
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com								

SAFETY DATA SHEET

Page 6 of 6 HFT-40711

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 4/30/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No. Chemical Abstract Service Number

EXPOSURE	EXPOSURE LIMITS IN AIR:								
ACGIH	American Conference on Governmental Industrial Hygienists								
С	Ceiling Limit								
ES	Exposure Standard (Australia)								
IDLH	Immediately Dangerous to Life and Health								
OSHA	U.S. Occupational Safety and Health Administration								
PEL	Permissible Exposure Limit								
STEL	Short-Term Exposure Limit								
TLV	Threshold Limit Value								
TWA	Time Weighted Average								
FIRST AID MEASURES:									

CPR Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.

HMIS	HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:									
0	Minimal Hazard		HEALTH							
1	Slight Hazard		FLAMMABILITY							
2	Moderate Hazard		PHYSICAL HAZARDS							
3	Severe Hazard		PERSONAL PROTECTION							
4	Extreme Hazard									

PERSONAL PROTECTION RATINGS:

Α					G	0				
в					н	0		E.		
С	0		TT TT		I	0				
D	B		E T		J	0		Î		
Е			\bigcirc		κ			R		
F			E T		Х			pervisor o direction		
Sa	fety Glasse	es	Splash G	oggles		e Shield 8 tive Eyew		Gloves		
	Boots		Synthetic	Apron	Protective Clothing & Full Suit			Dust Respirator		
			8					Î		
Full I	Full Face Respirator Dust & Vapor Half- Mask Respirator					Full Face Airline Hoo Respirator or SCE				
отн	ER STAN			-					-	
ML Maximum Limit										
mg/m3 milligrams per cubic meter										
NA Not Available										
ND Not Determined										
	NE	Not Esta	ablished							
	NF	Not Fou	ind							
	NR	No Res	ults							

NE	Not Established					
NF	Not Found					
NR	No Results					
ppm	parts per million					
SCBA	Self-Contained Breathing Apparatus					
NATIONAL FI	RE PROTECTION ASSOCIATION: NFPA					
FLAMMABILI	TY LIMITS IN AIR:					
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition					
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					

UEL

Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD R	ATINGS:								
0	Minimal Hazard			FLAMMABILITY					
1	Slight Hazar	ď				A F	EACTIVITY		
2	Moderate H	azard			X	4	/		
3	Severe Haz	ard							
4	Extreme Ha	zard			1				
ACD	Acidic					<u> </u>			
ALK	Alkaline				\frown		/		
COR	Corrosive					₩ /			
W	Use No Wat	er		н	EALTH	X			
ох	Oxidizer						SPECIAL PRECAUTIONS		
TREFOIL	Radioactive						RECAUTIONS		
TOXICOLO	GICAL INFO	ORMAT	ION:						
	LD ₅₀	Lethal I	Dose (solids	& liquids) wh	ich kills 50%	of the exp	osed animals		
		s	``	, ,					
	LC ₅₀	Lethal of	concentration	(gases) which	ch kills 50% o	of the expo	sed animal		
	ppm	Concer	ntration expre	ssed in parts	of material p	er million	parts		
	TD _{lo}	Lowest	dose to caus	e a symptom	1				
	TCLo	Lowest concentration to cause a symptom							
	D _{io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects							
TC, TC₀,	LC _{io} , & LC _o								
	IARC		tional Agency		h on Cancer				
	NTP		al Toxicology						
	RTECS	Registry of Toxic Effects of Chemical Substances							
	BCF	Bioconcentration Factor							
	TLm		Median threshold limit						
	v or log K _{oc}			iter Distributi	on				
REGULATO	-	-							
WHMIS			Hazardous N		mation Syste	m			
DOT	-		ransportatior	1					
TC	Transport C								
EPA			Protection Ag						
DSL			Substance Lis						
NOHSC			al Health and		mission (Aus	tralia)			
NDSL			stic Substan						
PSL			bstances List						
TSCA			e Control Act						
EU			ropean Union						
WGK	J		dassen (Gerr						
HMIS-III			tings Associa						
WORKPLA	CE HAZAR		IATERIAL	S IDENTIF	CATION (WHMIS)	SYSTEM:		
\bigcirc	۵ (٩	$\textcircled{\begin{subarray}{c} \end{subarray}}$	()	۲		R		

\bigcirc	۲	٨	R	()	۲		Ŕ			
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F			
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive			
EC (67/548/EEC) INFORMATION:										

		Ny.	¥	8		×	×
С	E	F	N	0	т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\diamondsuit		
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment