



WHITE LITHIUM GREASE

SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade Name WHITE LITHIUM GREASE
Product Code 16-LG
Revision Date 12/02/2016

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) Lubricant

Company Identification

The Blaster Corporation
8500 Sweet Valley Drive
Valley View, Ohio 44125

Telephone

(216) 901-5800

Fax

(216) 901-5801

Website:

www.blastercorp.com

Emergency telephone number

ChemTel 800-255-3924 Contract #: MIS7234544

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)

Flam. Aerosol 2; Liquefied gas; Asp. Tox. 1

Label elements

This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

Hazard Symbol



DANGER

Signal word(s)

Hazard Statement(s)

Flammable aerosol.

Pressurised container: May burst if heated.

May be fatal if swallowed and enters airways.

Precautionary Statement(s)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Other hazards

Harmful to aquatic life. Harmful to aquatic life with long lasting effects.
Intentional inhalation of gas from the container may be fatal.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt.	CAS No.	Hazard classification
Petroleum Distillates, Hydrotreated	30 - 50	64742-47-8	Asp. Tox. 1; H304 Flam. Liq. 4; H227
Propane	5 - 15	74-98-6	Flam. Gas 2; H221



WHITE LITHIUM GREASE

n-Butane	5 - 15	106-97-8	Flam. Gas 2; H221
Zinc Oxide	<1	1314-13-2	Aquatic Acute 1; H400 Aquatic Chronic 1; H410

Additional Information - None

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation

Remove person to fresh air and keep comfortable for breathing. If breathing is labored, administer oxygen. If symptoms develop, obtain medical attention. Call a POISON CENTER/doctor if you feel unwell.

Skin Contact

Not normally required. If skin irritation occurs: Get medical advice/attention.

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Ingestion

Unlikely to be required but if necessary treat symptomatically. Do not give anything by mouth to an unconscious person. Seek medical treatment.

Most important symptoms and effects, both acute and delayed

IF SWALLOWED: Do not induce vomiting

Indication of any immediate medical attention and special treatment needed

Not normally required.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

- Suitable Extinguishing Media
- Unsuitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or water spray. Do not use water jet.

Special hazards arising from the substance or mixture

Flammable vapour.

Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid contact with skin and eyes. Avoid breathing gas/spray.

Environmental precautions

Prevent liquid entering sewers, basements and work pits.

Methods and material for containment and cleaning up

Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.

Reference to other sections

None

Additional Information

None



WHITE LITHIUM GREASE

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with skin and eyes. Use product in a well-ventilated area only. Do not use in confined spaces.

Conditions for safe storage, including any incompatibilities

-Storage temperature

Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F. Keep container tightly closed.

-Incompatible materials

This product should be stored away from sources of strong heat or oxidizing chemicals.

Specific end use(s)

Lubricant

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

SUBSTANCE.	CAS No.	(8hr TWA)		(STEL)		Note:
		PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	
C ₉ -C ₁₅ Alkanes & Cycloalkanes	Mixture	-----	1200 mg/m ³	-----	-----	-----
n-Butane	106-97-8	-----	250 ppm	-----	-----	-----
Propane	74-98-6	1000 ppm	Aspyx.#	-----	-----	#

*Assure minimum oxygen content of work atmosphere.

Recommended monitoring method

NIOSH 1500 (hydrocarbons, B.P. 36 - 126 °C); NIOSH 1550 (Naphthas)

Exposure controls

Appropriate engineering controls

Ensure adequate ventilation.

Personal protection equipment

Eye/face protection



Wear protective eyewear (goggles, face shield, or safety glasses).

Skin protection (Hand protection/ Other)



Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber or Butyl rubber).

Respiratory protection



Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment. Check with protective equipment manufacturer's data.

Thermal hazards

Not normally required. Use gloves with insulation for thermal protection, when needed.

Environmental Exposure Controls

None known

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance

Aerosol spray

Color.

Colourless



WHITE LITHIUM GREASE

Odor	Fuel oil-like.
Odor Threshold (ppm)	Not available
pH (Value)	Not available
Melting Point (°C) / Freezing Point (°C)	Not available.
Boiling point/boiling range (°C):	Not available.
Flash Point (°C)	-104 (-155 °F) - Propane
Evaporation Rate	Not available.
Flammability (solid, gas)	Flammable aerosol
Explosive Limit Ranges	2.1% - 9.5% v/v (Propane)
Vapor pressure (Pascal)	ca. 95 x 10 ⁴ (Propane)
Vapor Density (Air=1)	ca. 1.56 @ 0 °C (Propane)
Density (g/ml)	2.1% - 9.5% v/v (Propane)
Solubility (Water)	Not available.
Solubility (Other)	Not available
Partition Coefficient (n-Octanol/water)	Not available
Auto Ignition Point (°C)	Not available
Decomposition Temperature (°C)	Not available
Kinematic Viscosity (cSt)	<20 at 40°C
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Other information	Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Stable under normal conditions.
Chemical stability	Stable.
Possibility of hazardous reactions	None anticipated.
Conditions to avoid	Avoid contact with heat and ignition sources.
Incompatible materials	This product should be stored away from sources of strong heat or oxidizing chemicals.
Hazardous decomposition product(s)	Carbon monoxide, Carbon dioxide, Acid smoke

SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact

Information on toxicological effects

Acute toxicity (calculated / estimated)	Oral: LD50 >5 g/kg-bw Dermal: LD50 >2 g/kg-bw Inhalation: LC50 >20 mg/l (Vapor), 4-hr. rat - May cause drowsiness or dizziness.			
Irritation/Corrosivity	Repeated exposure may cause skin dryness or cracking.			
Sensitization	It is not a skin sensitizer.			
Repeated dose toxicity	No data			
Carcinogenicity	It is unlikely to present a carcinogenic hazard to man.			
NTP No.	IARC No.	ACGIH No.	OSHA No.	NIOSH No.
Mutagenicity	Not available.			
Reproductive toxicity	Not available			



WHITE LITHIUM GREASE

SECTION 12: ECOLOGICAL INFORMATION

Aquatic toxicity:

Zinc Oxide (CAS# 1314-13-2)

Short term

LOEC (96 hour): 180 µg/L (*Danio rerio*)
LC50 (96 hour): 1.793 mg/L (*Danio rerio*)
EC50 (48 hour): 1.7 mg/L (*Daphnia magna*, mortality)
NOEC (72 hour): 50 µg/L (*Pseudokirchnerella subcapitata*)

Long Term

NOEC (30 days) 26 µg/L (*Jordanella floridae*)
NOEC (21 days): 48 µg/L (*Daphnia magna*)
NOEL (72 hour) 50 µg/L (*Pseudokirchnerella subcapitata*)

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.

SECTION 14: TRANSPORT INFORMATION

	<u>U.S. DOT</u>	<u>Sea transport (IMDG)</u>	<u>Air transport (ICAO/IATA)</u>
UN number	1950	1950	1950
Proper Shipping Name	Aerosols, flammable	Aerosols, flammable	Aerosols, flammable
Transport hazard class(es)	2.1	2.1	2.1
Packing group	Not applicable	Not applicable	Not applicable
Environmental hazards	None assigned	None assigned	None assigned
Special precautions for user	None assigned	None assigned	None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
None	----	----	----

SARA 311/312 - Hazard Categories:

☒ Fire ☒ Sudden Release ☐ Reactivity ☐ Immediate (acute) ☐ Chronic (delayed)

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
None	----	----

SARA 302 - Extremely Hazardous Substances (40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None	----	----	----

California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
None	----	----



WHITE LITHIUM GREASE

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: 01/06/2016

Hazard Statement(s) and Risk Phrases Listed in: SECTION 2:/ SECTION 3:

Hazard Statement(s)

- H221: Flammable gas.
- H227: Combustible liquid.
- H304: May be fatal if swallowed and enters airways.
- H319: Causes serious eye irritation.
- H400: Very toxic to aquatic life.
- H410: Very toxic to aquatic life with long lasting effects.

Training advice: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.