



Safety Data Sheet

STP Products Manufacturing Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

1. Product And Company Identification

Product Name: STP® Premium Bar & Chain Oil

Responsible Party: STP Products Manufacturing Company
44 Old Ridgebury Road
Suite 300
Danbury, CT 06810

Information Phone Number: +1 203-205-2900

Emergency Phone Number:

For Medical Emergencies, call 1-866-949-6465 / +1 303-389-1332 (Outside US and Canada)
For Transportation Emergencies, call 1-800-424-9300 (Chemtrec) +1-703-527-3887 for
Outside US and Canada (call collect)

SDS Date of Preparation: 01/31/2018

Product Use: Automotive maintenance product – For consumer and professional use

2. Hazards Identification

Note: This product is a consumer product and is labeled in accordance with the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for the labeling of consumer products take precedence over OSHA labeling so the actual product label will differ from the OSHA label elements.

GHS Classification:

Physical:	Health:
Not Hazardous	Not Hazardous

GHS Label Elements: None

3. Composition/Information on Ingredients

Component	CAS No.	Amount
Distillates, petroleum, hydrotreated heavy Naphthenic	64742-52-5	>90%

The specific identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First Aid Measures

Inhalation: If symptoms of exposure develop, remove to fresh air. Get medical attention if symptoms appear and persist.

Skin Contact: Remove contaminated clothing and launder before reuse. Wash exposed skin with soap and water. If skin irritation or redness develops, get medical attention.

Eye Contact: Flush eyes with large amounts of water for several minutes. If irritation or other symptoms persist, get medical attention.

Ingestion: Do not induce vomiting unless directed to by a doctor or physician. Get medical assistance by calling a doctor or poison center.



Safety Data Sheet

STP Products Manufacturing Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

Most Important Symptoms: Direct eye contact may cause mild irritation. Inhalation of mists or vapors generated at elevated temperatures may cause respiratory irritation. Prolonged skin contact may cause dryness and defatting. Ingestion may cause gastrointestinal effects such as nausea, vomiting and diarrhea and central nervous system effects.

Indication of Immediate Medical Attention/Special Treatment: Immediate medical attention should not be required.

5. Firefighting Measures

Suitable (and Unsuitable) Extinguishing Media: Use water fog, foam, carbon dioxide or dry chemical. Cool fire exposed containers with water.

Specific Hazards Arising from the Chemical: Will burn under fire conditions. Closed containers may rupture if exposed to extreme heat. Burning may produce carbon monoxide and carbon dioxide, and hydrocarbons.

Special Protective Equipment and Precautions for Fire-fighters: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored.

6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures: Caution – slip hazard. Eliminate all ignition sources and ventilate the area. Wear appropriate protective equipment.

Environmental Precautions: Prevent entry in storm sewers and waterways. Report spill as required by local and national regulations. Notify the National Response Center if a spill of any amount enters navigable waters, the contiguous zone, or adjoining shorelines.

Methods for Containment and Clean-Up: Stop spill at the source if it is safe to do so. Absorb with an inert material. Collect into a suitable container for disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard.

7. Handling and Storage

Precautions for Safe Handling: Avoid contact with eyes. Avoid prolonged contact with skin and clothing. Avoid breathing vapors and mists. Wash exposed skin thoroughly with soap and water after use. Keep containers closed when not in use. Keep out of the reach of children.

Conditions for Safe Storage, Including any Incompatibilities: Store in a cool, dry, well-ventilated area. Store away from oxidizing agents and other incompatible materials.

8. Exposure Controls / Personal Protection

Exposure Guidelines:

CHEMICAL	EXPOSURE LIMIT
Distillates, petroleum, hydrotreated heavy Naphthenic	5 mg/m ³ TWA ACGIH TLV (Inhalable) 5 mg/m ³ TWA OSHA PEL (Oil Mist)

Engineering Controls: General ventilation should be adequate for all normal use. For operations where the TLV may be exceeded, forced ventilation such as local exhaust may be needed to maintain exposures below applicable



Safety Data Sheet

STP Products Manufacturing Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

limits.

Personal Protective Equipment

Respiratory Protection: None under normal use conditions. For operations where the TLV is exceeded, a NIOSH approved respirator with an organic vapor cartridge and a dust/mist prefilter or supplied air respirator is recommended. Equipment selection depends on contaminant type and concentration. Select in accordance with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.

Gloves: None normally required. Impervious gloves such as neoprene or nitrile are recommended if needed to avoid prolonged or repeated skin contact.

Eye Protection: None required for normal use. Avoid eye contact. Safety glasses or goggles are recommended if eye contact is possible.

Other Protective Equipment/Clothing: None required under normal use conditions.

9. Physical and Chemical Properties

Appearance And Odor: Amber liquid with a mild odor.

Physical State: Amber liquid	Odor Threshold: Not determined
pH: Not determined	Specific Gravity: 0.919
Initial Boiling Point/Range: Not determined	Vapor Pressure: Not determined
Melting/Freezing Point: Not determined	Vapor Density: (Air=1) >1
Solubility In Water: Insoluble	Percent Volatile: Nil
Viscosity: 10.3 cSt @ 100°C 146 cSt @ 40°C	Evaporation Rate: Not determined
Coefficient Of Water/Oil Distribution: Not determined	VOC Content: Not determined
Flash Point: 425°F (>218°C) COC	Autoignition Temp: Not determined
Decomposition Temperature: Not determined	Flammability Limits: LEL: Not determined UEL: Not determined
Flammability (solid, gas): Not applicable	

10. Stability and Reactivity

Reactivity: Not normally reactive

Chemical Stability: Stable.

Possibility of Hazardous Reactions: None known

Conditions to Avoid: Keep away from excessive heat and open flames.

Incompatible Materials: Strong oxidizing agents.

Hazardous Decomposition Products: Burning may produce carbon monoxide, carbon dioxide, and hydrocarbons.

11. Toxicological Information

POTENTIAL HEALTH EFFECTS:

Acute Hazards:

Inhalation: Inhalation of mists or vapors generated at elevated temperatures may cause upper respiratory tract



Safety Data Sheet

STP Products Manufacturing Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

irritation.

Skin Contact: Not a skin irritant. Prolonged or repeated contact may cause defatting and drying of the skin and dermatitis.

Eye Contact: Direct contact may cause slight eye irritation.

Ingestion: Ingestion may cause gastrointestinal effects such as nausea, vomiting and diarrhea and central nervous system effects.

Chronic Hazards: None currently known.

Carcinogenicity Listing: None of the components is listed as a carcinogen or potential carcinogen by IARC, NTP, ACGIH or OSHA.

Acute Toxicity Values:

Product ATE: LD50 Oral: >5,000 mg/kg
 LD50 Skin: >2,000 mg/kg
 LC50 Inhalation: >5 mg/L.

Distillates, petroleum, hydrotreated heavy Naphthenic:
Not classified as acutely toxic.

12. Ecological Information

Ecotoxicity:

All acute aquatic toxicity studies on samples of lubricant base oils show acute toxicity values greater than 100 mg/L for invertebrates, algae and fish. These tests were carried out on water accommodated fractions and the results are consistent with the predicted aquatic toxicity of these substances based on their hydrocarbon compositions.

Persistence and Degradability:

The hydrocarbons in this material are not readily biodegradable, but since they can be degraded by microorganisms, they are regarded as inherently biodegradable.

Bio accumulative Potential:

Has the potential for bioconcentration to occur.

Mobility in Soil:

This material is expected to have essentially no mobility in soil, and absorbs strongly to most soil types

Other Adverse Effects: No data available.

13. Disposal Considerations

Dispose of in accordance with all local, state/provincial and federal regulations. Offer empty containers for recycling.

14. Transport Information

DOT Hazardous Materials Description: Not Regulated

IMDG Dangerous Goods Description: Not Regulated



® Safety Data Sheet

STP Products Manufacturing Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

15. Regulatory Information

United States:

EPA TSCA INVENTORY: All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

CERCLA Section 103: This product has no RQ, however, oil spills must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA Hazard Category (311/312): Classified under OSHA Hazcom 2012 GHS as per Section 2 of this SDS.

SARA 313: This product contains the following chemicals subject to Annual Release Reporting Requirements under SARA Title III, Section 313 (40 CFR 372): None

16. Other Information

NFPA Rating (NFPA 704):	Health: 0	Fire: 1	Instability: 0
HMIS Rating:	Health: 0	Fire: 1	Physical Hazard: 0

REVISION DATE: 01/31/2018

REVISION SUMMARY: New SDS. Formula template

PREVIOUS REVISION DATE: N/A

DATA SUPPLIED IS FOR USE ONLY IN CONNECTION WITH OCCUPATIONAL SAFETY AND HEALTH