



SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 12/24/2015

1. PRODUCT & COMPANY IDENTIFICATION

1.1	Product Name:	IRON ARMOR® GLOSS BLACK CHASSIS AND GRILLE PAINT
1.2	Chemical Name:	Aerosol
1.3	Synonyms:	P/N 60780
1.4	Trade Names:	Iron Armor® Gloss Black Chassis And Grille Paint
1.5	Product Uses & Restrictions:	Aerosol Paint
1.6	Distributor's Name:	Harbor Freight Tools USA, Inc.
1.7	Distributor's Address:	26541 Agoura Road, Calabasas, CA 91302 USA
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687)
1.9	Business Phone / Fax:	+1 (805) 388-1000

2. HAZARDS IDENTIFICATION

2.1	Hazard Identification:	<p>This product is classified as a hazardous substance and as dangerous goods according to the classification criteria of [NOHSC: 1088 (2004)] and ADG Code (Australia).</p> <p>DANGER! EXTREMELY FLAMMABLE AEROSOL. PRESSURIZED CONTAINER MAY BURST IF HEATED. MAY BE HARMFUL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION.</p> <p><u>Classification:</u> Aerosol 1; Acute Tox. 4; Asp. Tox. 1; Skin Irrit. 2; Eye Irrit. 2.</p> <p><u>Hazard Statements (H):</u> H222 – Extremely flammable aerosol. H229 – Pressurized container may burst if heated. H304 – May be fatal if swallowed and enters airways. H315 – Causes skin irritation. H319 – Causes serious eye irritation.</p> <p><u>Precautionary Statements (P):</u> P210 – Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. P211 – Do not spray on an open flame or other ignition source. P251 – Do not pierce or burn, even after use. P410+P412 – Protect from sunlight. Do not expose to temperatures exceeding 50 °F (122 °F). P264 – Wash thoroughly with soap and water after handling. P270 – Do not eat, drink or smoke when using this product. P301+P312 – IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. P330 – Rinse mouth. P501 – Dispose of contents/container to licenses treatment, storage and disposal facility (TSDF). P280 – Wear protective gloves/protective clothing/eye protection/face protection. P302+P352 – IF ON SKIN: Wash with plenty of soap and water. P321 – Specific treatment – See Section 4 of this Safety Data Sheet. P332+P313 – If skin irritation occurs: Get medical advice/attention. P362+P364 – Take off contaminated clothing and wash it before reuse. P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 – If eye irritation persists: get medical advice/attention.</p>	 
-----	------------------------	---	--

3. COMPOSITION & INGREDIENT INFORMATION


CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m ³)								OTHER
					ACGIH		NOHSC			OSHA			
					TLV	STEL	ppm	ppm	ES-TWA	ES-STEL	ES-PEAK	PEL	
ACETONE	67-64-1	AL3150000	200-662-2	10-30	1800	NA	1185	2375	NF	2400	NA	2500	
PROPANE	74-98-6	TX2275000	200-827-9	10-30	1000	NA	1000	NF	NF	1000	NA	2100	
BUTANE	106-97-8	EJ4200000	203-448-7	10-30	1000	900	800	1900	NF	NA	NA	1900	
TOLUENE	108-88-3	XS52500000	203-625-9	5-10	50	300	100	150	574	200	300	500	SKIN
HEPTANE	142-82-5	MI7700000	205-563-8	5-10	400	500	400	1640	NF	500	NA	750	
VM & P NAPHTHA *	64742-89-8	NA	265-192-2	15-40	300	NA	NF	NF	NF	300	NA	NA	
ETHYL 3-ETHOXYPROPIONATE	763-69-9	UF3325000	212-112-9	1-5	50	100	NF	NF	NF	NA	NA	NA	
1,2,4-TRIMETHYLBENZENE	95-63-6	DC3325000	202-436-9	0.1-1	25	NA	25	NF	NF	NA	NA	NA	25 NIOSH
CARBON BLACK	1333-86-4	FF5800000	215-609-9	0.1-1	(3.5)	NA	(3.5)	NF	NF	(3.5)	NA	NA	

* contains < 0.1% BENZENE

4. FIRST AID MEASURES

4.1	First Aid:	<p>Ingestion: If ingested, do not induce vomiting. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.</p> <p>Eyes: Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes lifting upper and lower lids, occasionally.</p> <p>Skin: Wash thoroughly with soap and water. In case of contact, immediately flush skin with plenty of water for at least 15 minutes.</p> <p>Inhalation: Remove victim to fresh air at once. If breathing is difficult, administer oxygen. If breathing stops give artificial respiration. Keep person warm, quiet and get medical attention.</p>												
4.2	Effects of Exposure:	<p>Ingestion: If product is swallowed, may cause gastrointestinal disturbance.</p> <p>Eyes: Exposure to dust may cause eye irritation. Symptoms of overexposure may include redness, itching, irritation and watering.</p> <p>Skin: May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.</p> <p>Inhalation: Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. Drowsiness, dizziness, headaches and nausea.</p>												
4.3	Symptoms of Overexposure:	<p>Ingestion: If product is swallowed, may cause gastrointestinal disturbance.</p> <p>Eyes: Exposure to dust may cause eye irritation. Symptoms of overexposure may include redness, itching, irritation and watering.</p> <p>Skin: May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.</p> <p>Inhalation: Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.</p>												
4.4	Acute Health Effects:	Non-irritating when used as directed. Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of dust can cause coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract.												
4.5	Chronic Health Effects:	Non-irritating when used as directed. Possible allergic dermatitis in some sensitive individuals.												
4.6	Target Organs:	Eyes, Skin, Respiratory System, Central Nervous System (CNS), Liver, Reproductive System												
4.7	Medical Conditions Aggravated by Exposure:	Pre-existing dermatitis, other skin conditions, and disorders of the target organs (eyes, skin, respiratory system, CNS, liver, testes) or impaired kidney function may be more susceptible to the effects of this substance.												
		<table border="1"> <tr> <td>HEALTH</td> <td>2</td> </tr> <tr> <td>FLAMMABILITY</td> <td>4</td> </tr> <tr> <td>PHYSICAL HAZARDS</td> <td>0</td> </tr> <tr> <td>PROTECTIVE EQUIPMENT</td> <td>X</td> </tr> <tr> <td>EYES</td> <td>SKIN</td> </tr> <tr> <td>LUNGS</td> <td></td> </tr> </table>	HEALTH	2	FLAMMABILITY	4	PHYSICAL HAZARDS	0	PROTECTIVE EQUIPMENT	X	EYES	SKIN	LUNGS	
HEALTH	2													
FLAMMABILITY	4													
PHYSICAL HAZARDS	0													
PROTECTIVE EQUIPMENT	X													
EYES	SKIN													
LUNGS														

5. FIREFIGHTING MEASURES

5.1	Fire & Explosion Hazards:	Level 3 Aerosol (NFPA 30B). Aerosols may burst at temperatures above 120 °F. Cool uninvolved containers to prevent possible bursting. Aerosols may be projectile hazards when bursting. If aerosols are bursting, stay clear until bursting is complete. Do not use in presence of open flames or sparks. Do not place in hot water or near radiators, stoves or other sources of heat. Exposure to heat or sunlight may cause cans to burst and propel contents. Water from fog nozzles may be helpful in cooling un-ruptured containers to prevent build-up.	
5.2	Extinguishing Methods:	Water Fog, Foam, Dry Chemical, CO ₂	
5.3	Firefighting Procedures:	As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.	

6. ACCIDENTAL RELEASE MEASURES




6.1	Spills:	<p>Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.</p> <p>For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.</p> <p>For large spills (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water.</p>
-----	---------	---

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 12/24/2015

7. HANDLING & STORAGE INFORMATION

7.1	Work & Hygiene Practices:	Do not eat, drink or smoke when handling this product. Handle as to avoid puncturing container(s). Wash unintentional residues with soap and warm water. Keep tightly closed when not in use. Avoid contact with skin and clothing.
7.2	Storage & Handling:	Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Avoid temperatures above 120 °F. Keep away from incompatible substances. Protect containers from physical damage. Avoid breathing vapor.
7.3	Special Precautions:	Clean all spills promptly. Spilled material may present a slipping hazard.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Exposure Limits: ppm (mg/m ³)	CHEMICAL NAME(S)	ACGIH		NOHSC			OSHA			OTHER	
			TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH		
		ACETONE	1800	NA	1185	2375	NF	2400	NA	2500		
		PROPANE	1000	NA	1000	NF	NF	1000	NA	2100		
		BUTANE	1000	900	800	1900	NF	NA	NA	1900		
		TOLUENE	50	300	100	150	574	200	300	500	SKIN	
		HEPTANE	400	500	400	1640	NF	500	NA	750		
		VM & P NAPHTHA	300	NA	NF	NF	NF	300	NA	NA		
		ETHYL 3-ETHOXYPROPIONATE	50	100	NF	NF	NF	NA	NA	NA		
		1,2,4-TRIMETHYLBENZENE	25	NA	25	NF	NF	NA	NA	NA	25 NIOSH	
		CARBON BLACK	(3.5)	NA	(3.5)	NF	NF	(3.5)	NA	NA		
8.2	Ventilation & Engineering Controls:	Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).										
8.3	Respiratory Protection:	No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, EU member states, or Australia.										
8.4	Eye Protection:	Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Wear goggles and/or face shield if splashing or spraying is anticipated. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants. Have suitable eye wash water available. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).										
8.5	Hand Protection:	Use gloves constructed of chemical-resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, or the EU member states.										
8.6	Body Protection:	Avoid prolonged and/or repeated skin contact. Use clean and impervious protective clothing (e.g., neoprene or Tyvek®) if splashing or spraying conditions are present. Protective clothing should include long-sleeves, apron, boots and additional facial protection. If necessary, refer to appropriate standards of Canada, the EU member states, or U.S. OSHA.										

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Appearance:	Aerosol
9.2	Odor:	Solvent-like
9.3	Odor Threshold:	NA
9.4	pH:	7.0
9.5	Melting Point/Freezing Point:	NA
9.6	Initial Boiling Point/Boiling Range:	- 18 °C – 172 °C (0 °F - 342 °F)
9.7	Flashpoint:	< -18 °C (< 0 °F)
9.8	Upper/Lower Flammability Limits:	LEL: 0.9% / UEL: 12.8 %
9.9	Vapor Pressure:	NA
9.10	Vapor Density:	> 1.0 (air = 1.0)
9.11	Relative Density:	0.71
9.12	Solubility:	NA
9.13	Partition Coefficient (log P _{ow}):	NA
9.14	Autoignition Temperature:	NA
9.15	Decomposition Temperature:	NA
9.16	Viscosity:	NA
9.17	Other Information:	Evaporation Rate: Faster than Ether; VOC: 61.15 % w/w

SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 12/24/2015

10. STABILITY & REACTIVITY

10.1	Stability:	Stable under normal conditions; unstable with heat or contamination.
10.2	Hazardous Decomposition Products:	Oxides of Carbon (CO, CO ₂) and Nitrogen (NO _x)
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Open flames, sparks, high heat, incompatible substances and direct sunlight.
10.5	Incompatible Substances:	Avoid extreme heat and ignition sources. Store away from oxidizers.

11. TOXICOLOGICAL INFORMATION

11.1	Routes of Entry:	Inhalation: YES	Absorption: YES	Ingestion: YES
11.2	Toxicity Data:	This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product, but is not presented in this document.		
11.3	Acute Toxicity:	Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.		
11.4	Chronic Toxicity:	This material may aggravate any pre-existing skin condition (e.g., dermatitis).		
11.5	Suspected Carcinogen:	Toluene is listed as IARC Group 3 (Not classifiable as to its carcinogenicity to humans). VM & P Naphtha is listed as IARC Group 2B (Possibly carcinogenic to humans). Carbon Black is listed as IARC Group 2B (Possibly carcinogenic to humans); CA65 (cancer).		
11.6	Reproductive Toxicity:	This product contains Toluene, a substance reported to produce reproductive toxicity in humans.		
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.		
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.		
	Teratogenicity:	This product is not reported to produce teratogenic effects in humans.		
	Reproductive Toxicity:	This product contains Toluene, a substance reported to produce reproductive toxicity in humans.		
11.7	Irritancy of Product:	The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.		
11.8	Biological Exposure Indices:	NE		
11.9	Physician Recommendations:	Treat symptomatically.		

12. ECOLOGICAL INFORMATION

12.1	Environmental Stability:	There are no specific data available for this product.
12.2	Effects on Plants & Animals:	There are no specific data available for this product.
12.3	Effects on Aquatic Life:	There are no specific data available for this product.

13. DISPOSAL CONSIDERATIONS

13.1	Waste Disposal:	Dispose of in accordance with federal, state, provincial and local regulations.
13.2	Special Considerations:	NA

14. TRANSPORTATION INFORMATION



The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND):	CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) – until 12/31/20 UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	
14.2	IATA (AIR):	CONSUMER COMMODITY, 9, ID8000 (IP VOL ≤ 0.5 L) UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	or
14.3	IMDG (OCN):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	
14.4	TDGR (Canadian GND):	MARK PACKAGE ("LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (IP VOL ≤ 1.0 L) or UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	
14.5	ADR/RID (EU):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	
14.6	SCT (MEXICO):	UN1950, AEROSOLS, 2.1 (CANTIDAD LIMITADA, IP VOL ≤ 1.0 L)	
14.7	ADGR (AUS):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	

SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 12/24/2015

15. REGULATORY INFORMATION

15.1	SARA Reporting Requirements:	This product contains <u>Toluene</u> , and <u>1,2,4-Trimethylbenzene</u> , substances subject to SARA Title III, section 313 reporting requirements.
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory or are otherwise exempt.
15.4	CERCLA Reportable Quantity (RQ):	<u>Toluene</u> : 454 kg (1,000 lbs); <u>Acetone</u> : 2,270 kg (5,000 lbs)
15.5	Other Federal Requirements:	<u>Toluene</u> is listed as Hazardous Air Pollutants (HAPs). <u>Toluene</u> is listed as Toxic Pollutants under the Clean Water Act (CWA). <u>Toluene</u> is listed as a Priority Pollutant under the CWA. This product does not contain any Class 1 or Class 2 ozone depleters.
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDL. <u>Toluene</u> is listed on the Priorities Substances List. WHMIS Class B5, D2B (Flammable Aerosols, Other Toxic Effects). 
15.7	State Regulatory Information:	<u>Acetone</u> is found on the following state criteria lists: California OSHA Hazardous Substances List (CA), Delaware Air Quality Management List (DE), Massachusetts Hazardous Substances List (MA), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA) and Wisconsin Hazardous Substances List (WI). <u>VM & P Naphtha</u> is found on the following state criteria list: FLA, MA, MN, PA and WA. <u>Carbon Black</u> is listed in the following state criteria lists: California Proposition 65 (CA65), MA, MN, NJ, and PA. <u>Toluene</u> is found on the following state criteria list: CA65, DE, MA, NJ, NY, PA, WA, and WI. <u>Heptane</u> is found on the following state criteria list: FL, MA, MN, PA and WA. <u>1,2,4-Trimethylbenzene</u> is found on the following state criteria list: MA, NJ, and PA. No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). WARNING: This product contains a substance(s) known to the State of California to cause cancer, birth defects or other reproductive harm. California law requires this warning be given to customers in the State of California.
15.8	Other Requirements:	The primary components of this product are listed in Annex I of EU Directive 67/548/EEC: <u>Acetone</u> : Flammable, Harmful (F, Xn). <u>Risk Phrases</u> (R): 11-36-66-67 – Highly flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Vapors may cause dizziness or drowsiness. <u>Safety Phrases</u> (S): (2-)9-16-26-46 – Keep out of the reach of children. Keep container in a well-ventilated place. Keep away from sources of ignition – No smoking. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, seek medical advice immediately and show this container or label. <u>VM & P Naphtha</u> : Toxic (T). <u>Risk Phrases</u> (R): 45-46-65 - May cause cancer. May cause inheritable genetic damage. Harmful may cause lung damage if swallowed. <u>Safety Phrases</u> (S): 53-45 – Avoid exposure – obtain special instructions before use. In case of accident or if you feel unwell seek medical advice immediately (show the label where possible). Keep container in a well-ventilated place. Keep away from sources of ignition – No smoking. <u>Toluene</u> : Flammable, Harmful (F, Xn). <u>Risk Phrases</u> (R): 11-48/20-65-38 – Highly Flammable. Harmful: Danger of serious damage to health by prolonged exposure through inhalation. Harmful may cause lung damage if swallowed. Irritation to skin. <u>Safety Phrases</u> (S) 2-36/37-46-62 – Keep out of reach of children. Wear suitable protective clothing and gloves. If swallowed, seek medical advice immediately and show container or label. If swallowed do not induce vomiting; seek medical advice immediately and show this container or label. 


SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 12/24/2015

16. OTHER INFORMATION

16.1	Other Information:	<p>DANGER! EXTREMELY FLAMMABLE AEROSOL. PRESSURIZED CONTAINER MAY BURST IF HEATED. HARMFUL IF SWALLOWED. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION. Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °F (122 °F). Wash thoroughly with soap and water after handling. Do not eat, drink or smoke when using this product. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice/attention. KEEP OUT OF REACH OF CHILDREN.</p> <p>WARNING: This product contains a substance(s) known to the State of California to cause cancer, birth defects or other reproductive harm.</p>	
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Harbor Freight Tools USA, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.	
16.4	Prepared for:	Harbor Freight Tools USA, Inc. 26541 Agoura Road Calabasas, CA 91302 USA Tel: +1 (805) 388-1000 http://www.harborfreight.com	
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com	

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
----------------	----------------------------------

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
C	Ceiling Limit
ES	Exposure Standard (Australia)
IDLH	Immediately Dangerous to Life and Health
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
------------	--


HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard

HEALTH
FLAMMABILITY
PHYSICAL HAZARDS
PERSONAL PROTECTION

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD₀₁	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD₀₁, LD₀₁, & LD₀₁ or TC, TC₀₁, LC₀₁, & LC₀₁	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL_m	Median threshold limit
log K_{ow} or log K_{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NOHSC	National Occupational Health and Safety Commission (Australia)
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

C	E	F	N	O	T	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment

PERSONAL PROTECTION RATINGS:

A		G	
B		H	
C		I	
D		J	
E		K	
F		X	Consult your supervisor or SOPs for special handling directions.

Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves
Boots	Synthetic Apron	Protective Clothing & Full Suit	Dust Respirator
Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:

ML	Maximum Limit
mg/m³	milligrams per cubic meter
NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR	No Results
ppm	parts per million
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source