

SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards



SDS Revision: 1.1

SDS Revision Date: 12/24/2015

1. PRODUCT & COMPANY IDENTIFICATION

1.1	Product Name:	IRON ARMOR® GRAY SANDABLE PRIMER SPRAY PAINT
1.2	Chemical Name:	NA
1.3	Synonyms:	P/N 60789
1.4	Trade Names:	Iron Armor® Gray Sandable Primer Spray Paint
1.5	Product Uses & Restrictions:	Aerosol Undercoat
1.6	Distributor's Name:	Harbor Freight Tools USA, Inc.
1.7	Distributor's Address:	26541 Agoura Road, Calabasas, CA 91302 USA
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687)
1.9	Business Phone / Fax:	+1 (805) 388-1000

2. HAZARDS IDENTIFICATION

2.1	Hazard Identification:	<p>This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of [NOHSC: 1088 (2004)] and ADG Code (Australia).</p> <p>DANGER! EXTREMELY FLAMMABLE AEROSOL. PRESSURIZED CONTAINER MAY BURST IF HEATED. MAY BE HARMFUL IF SWALLOWED AND ENTERS AIRWAYS. HARMFUL IF SWALLOWED, IN CONTACT WITH SKIN, OR IF INHALED. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION.</p> <p>Classification: Aerosol 1; Acute Tox. 4; Asp. Tox. 1; Skin Irrit. 2; Eye Irrit. 2.</p> <p><u>Hazard Statements (H):</u> H222 – Extremely flammable aerosol. H229 – Pressurized container may burst if heated. H304 – May be fatal if swallowed and enters airways. H312 – Harmful in contact with skin. H315 – Causes skin irritation. H319 – Causes serious eye irritation. H332 – Harmful if inhaled.</p> <p><u>Precautionary Statements (P):</u> P210 – Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. P211 – Do not spray on an open flame or other ignition source. P251 – Do not pierce or burn, even after use. P410+P412 – Protect from sunlight. Do not expose to temperatures exceeding 50 °F (122 °F). P261 – Avoid breathing fume/mist/vapors/spray. P264 – Wash thoroughly with soap and water after handling. P270 – Do not eat, drink or smoke when using this product. P271 – Use only outdoors or in a well-ventilated area. P280 – Wear protective gloves/protective clothing/eye protection/face protection. P301+P312 – IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. P330 – Rinse mouth. P302+P352 – IF ON SKIN: Wash with plenty of soap and water. P304+P340 – IF INHALED: Remove person to fresh air and keep comfortable for breathing. P321 – Specific treatment – See Section 4 of this Safety Data Sheet. P332+P313 – If skin irritation occurs: Get medical advice/attention. P362+P364 – Take off contaminated clothing and wash it before reuse. P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 – If eye irritation persists: get medical advice/attention. P501 – Dispose of contents/container to licensed treatment, storage and disposal facility (TSDF).</p>	 
-----	------------------------	--	---

3. COMPOSITION & INGREDIENT INFORMATION

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m ³)									OTHER
					ACGIH		NOHSC			OSHA				
					ppm		ppm			ppm				
					TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH		
ACETONE	67-64-1	AL3150000	200-662-2	10-30	1800	NA	1185	2375	NF	2400	NA	2500		
	Flam. Liq. 2; Eye Irrit. 2; STOT SE 3, H225, H319, H336													
TALC	14807-96-6	WW2710000	238-877-9	10-30	2	NA	NF	2.5	NF	2	NA	1000		
PROPANE	74-98-6	TX2275000	200-827-9	10-30	1000	NA	1000	NF	NF	1000	NA	2100		
	Flam. Gas 1; Press. Gas; H220													
BUTANE	106-97-8	EJ4200000	203-448-7	7-13	1000	900	800	1900	NF	NA	NA	1900		
	Press. Gas; Flam. Gas 1; H220													
XYLENE	1330-20-7	ZE2100000	215-535-7	5-10	100	150	80	350	655	100	150	900		
	Flam. Liq 3; Acute Tox. 4; Skin Irrit. 2; H226, H312+H332, H315													
ISOBUTYL ACETATE	110-19-0	AI4025000	203-745-1	5-10	150	NA	(150)	713	NF	150	NA	1300		
	Flam. Liq. 2; H225													
TOLUENE	108-88-3	XS52500000	203-625-9	3-7	50	300	100	150	574	200	300	500	SKIN	
	Flam. Liq. 2; Repr. 2; Asp. Tox. 1; STOT RE 2 *; Skin Irrit. 2; STOT SE 3; H225, H361d ***, H304, H373 **, H315, H336													
ISOPROPANOL	67-63-0	NT8050000	200-661-7	1-5	400	500	400	500	NF	400	500	2000	400 TWA	
	Flam. Liq. 2; Skin Irrit. 3; Eye Irrit. 2A; STOT SE 3; H225, H316, H319													
ETHYLBENZENE	100-41-4	DA0700000	202-849-4	1-5	100	150	100	434	543	100	150	800		
	Flam. Liq. 2; Acute Tox. 4 *; H225, H332													
CALCIUM CARBONATE	471-34-1	FF9335000	207-439-9	0.5-1.5	10	5	NF	NF	NF	10	5	NA	RESP DUST	

SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards


SDS Revision: 1.1

SDS Revision Date: 12/24/2015

4. FIRST AID MEASURES

4.1	First Aid:	<p><u>Ingestion:</u> If ingested, do not induce vomiting. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.</p> <p><u>Eyes:</u> Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes lifting upper and lower lids, occasionally.</p> <p><u>Skin:</u> Wash thoroughly with soap and water. In case of contact, immediately flush skin with plenty of water for at least 15 minutes.</p> <p><u>Inhalation:</u> Remove victim to fresh air at once. If breathing is difficult, administer oxygen. If breathing stops give artificial respiration. Keep person warm, quiet and get medical attention.</p>																				
4.2	Effects of Exposure:	<p><u>Ingestion:</u> If product is swallowed, may cause gastrointestinal disturbance.</p> <p><u>Eyes:</u> Exposure to mists/fumes/vapors/spray may cause eye irritation. Symptoms of overexposure may include redness, itching, irritation and watering.</p> <p><u>Skin:</u> May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.</p> <p><u>Inhalation:</u> Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. Drowsiness, dizziness, headaches and nausea.</p>																				
4.3	Symptoms of Overexposure:	<p><u>Ingestion:</u> If product is swallowed, may cause gastrointestinal disturbance.</p> <p><u>Eyes:</u> Exposure to mists/fumes/vapors/spray may cause eye irritation. Symptoms of overexposure may include redness, itching, irritation and watering.</p> <p><u>Skin:</u> May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.</p> <p><u>Inhalation:</u> Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.</p>																				
4.4	Acute Health Effects:	Non-irritating when used as directed. Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of fumes/vapors can cause coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract.																				
4.5	Chronic Health Effects:	Non-irritating when used as directed. Possible allergic dermatitis in some sensitive individuals.																				
4.6	Target Organs:	Eyes, Skin, Respiratory System, Kidneys, Liver and Central Nervous System (CNS).																				
4.7	Medical Conditions Aggravated by Exposure:	<div><div>Pre-existing dermatitis, other skin conditions, and disorders of the target organs (eyes, skin) or impaired kidney function may be more susceptible to the effects of this substance.</div><table><tr><td colspan="3">HEALTH</td><td>2</td></tr><tr><td colspan="3">FLAMMABILITY</td><td>3</td></tr><tr><td colspan="3">PHYSICAL HAZARDS</td><td>0</td></tr><tr><td colspan="3">PROTECTIVE EQUIPMENT</td><td>X</td></tr><tr><td>EYES</td><td>SKIN</td><td>LUNGS</td><td></td></tr></table></div>	HEALTH			2	FLAMMABILITY			3	PHYSICAL HAZARDS			0	PROTECTIVE EQUIPMENT			X	EYES	SKIN	LUNGS	
HEALTH			2																			
FLAMMABILITY			3																			
PHYSICAL HAZARDS			0																			
PROTECTIVE EQUIPMENT			X																			
EYES	SKIN	LUNGS																				

5. FIREFIGHTING MEASURES

5.1	Fire & Explosion Hazards:	Level 3 Aerosol (NFPA 30B). Aerosols may burst at temperatures above 120 °F. Cool uninvolved containers to prevent possible bursting. Aerosols may be projectile hazards when bursting. If aerosols are bursting, stay clear until bursting is complete. Do not use in presence of open flames or sparks. Do not place in hot water or near radiators, stoves or other sources of heat. Exposure to heat or sunlight may cause cans to burst and propel contents. Water from fog nozzles may be helpful in cooling un-ruptured containers to prevent build-up.	
5.2	Extinguishing Methods:	Water Fog, Foam, Dry Chemical, CO ₂	
5.3	Firefighting Procedures:	As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.	





6. ACCIDENTAL RELEASE MEASURES

6.1	Spills:	<p>Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.</p> <p>For <u>small spills</u> (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.</p> <p>For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water.</p>
-----	---------	---

7. HANDLING & STORAGE INFORMATION

7.1	Work & Hygiene Practices:	Avoid breathing mist or vapor. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Avoid contact with skin and clothing. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area.
7.2	Storage & Handling:	Contents under pressure. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 49 °C/120 °F. Do not handle or store near an open flame, heat or other sources of ignition. Exposure to high temperature may cause can to burst. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).
7.3	Special Precautions:	Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Exposure Limits: ppm (mg/m ³)	CHEMICAL NAME(S)	ACGIH		NOHSC			OSHA			OTHER
			TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		ACETONE	1800	NA	1185	2375	NF	2400	NA	2500	
		TALC	2	NA	NF	2.5	NF	2	NA	1000	
		PROPANE	1000	NA	1000	NF	NF	1000	NA	2100	
		BUTANE	1000	900	800	1900	NF	NA	NA	1900	
		XYLENE	100	150	80	350	655	100	150	900	
		ISOBUTYL ACETATE	150	NA	(150)	713	NF	150	NA	1300	
		TOLUENE	50	300	100	150	574	200	300	500	SKIN
		ISOPROPANOL	400	500	NF	NF	NF	400	500	2000	400 TWA
		ETHYLBENZENE	100	150	100	434	543	100	150	800	
		CALCIUM CARBONATE	10	5	NF	NF	NF	10	5	NA	RESP DUST
8.2	Ventilation & Engineering Controls:	Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).									
8.3	Respiratory Protection:	No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, EU member states, or Australia.									
8.4	Eye Protection:	Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Wear goggles and/or face shield if splashing or spraying is anticipated. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants. Have suitable eye wash water available. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).									 
8.5	Hand Protection:	Use gloves constructed of chemical-resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, or the EU member states.									
8.6	Body Protection:	Avoid prolonged and/or repeated skin contact. Use clean and impervious protective clothing (e.g., neoprene or Tyvek®) if splashing or spraying conditions are present. Protective clothing should include long-sleeves, apron, boots and additional facial protection. If necessary, refer to appropriate standards of Canada, the EU member states, or U.S. OSHA.									

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 12/24/2015

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Appearance:	Aerosol
9.2	Odor:	Solvent like
9.3	Odor Threshold:	NA
9.4	pH:	NA
9.5	Melting Point/Freezing Point:	NA
9.6	Initial Boiling Point/Boiling Range:	- 18 °C – 144 °C (0 °F - 292 °F)
9.7	Flashpoint:	< -18 °C (< 0 °F)
9.8	Upper/Lower Flammability Limits:	LEL: 1.0% / UEL: 12.8 %
9.9	Vapor Pressure:	NA
9.10	Vapor Density:	> 1.0 (air = 1.0)
9.11	Relative Density:	0.83
9.12	Solubility:	NA
9.13	Partition Coefficient (log P _{ow}):	NA
9.14	Autoignition Temperature:	NA
9.15	Decomposition Temperature:	NA
9.16	Viscosity:	NA
9.17	Other Information:	Evaporation Rate: Faster than Ether; VOC: 53.06 % w/w

10. STABILITY & REACTIVITY

10.1	Stability:	Stable under normal conditions; unstable with heat or contamination.
10.2	Hazardous Decomposition Products:	Oxides of Carbon (CO, CO ₂) and Nitrogen (NO _x)
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Open flames, sparks, high heat, incompatible substances and direct sunlight.
10.5	Incompatible Substances:	Avoid extreme heat and ignition sources. Store away from oxidizers.

11. TOXICOLOGICAL INFORMATION

11.1	Routes of Entry:	Inhalation: YES	Absorption: YES	Ingestion: YES
11.2	Toxicity Data:	This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product, but is not presented in this document.		
11.3	Acute Toxicity:	Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.		
11.4	Chronic Toxicity:	This material may aggravate any pre-existing skin condition (e.g., dermatitis).		
11.5	Suspected Carcinogen:	<u>Xylene</u> is listed as IARC Group 3 (Not classifiable as to its carcinogenicity to humans). <u>Toluene</u> is listed as IARC Group 3 (Not classifiable as to its carcinogenicity to humans). <u>Ethylbenzene</u> is listed as ACGIH Group A3 (Confirmed animal carcinogen with unknown relevance to human); IARC Group 2B (Possibly carcinogenic to humans); CA65 (cancer).		
11.6	Reproductive Toxicity:	<u>Toluene</u> is reported to cause reproductive toxicity in humans (CA Proposition 65: males).		
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.		
	Embryotoxicity:	There is ample evidence to suggest that <u>Xylene</u> produces embryotoxicity and fetotoxicity in mice and rats.		
	Teratogenicity:	<u>Toluene</u> may cause possible risk of harm to the unborn child.		
	Reproductive Toxicity:	<u>Toluene</u> is reported to cause reproductive toxicity in humans (CA Proposition 65: males).		
11.7	Irritancy of Product:	The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.		
11.8	Biological Exposure Indices:	NE		
11.9	Physician Recommendations:	Treat symptomatically.		

12. ECOLOGICAL INFORMATION

12.1	Environmental Stability:	There are no specific data available for this product.
12.2	Effects on Plants & Animals:	There are no specific data available for this product.
12.3	Effects on Aquatic Life:	There are no specific data available for this product.

13. DISPOSAL CONSIDERATIONS

13.1	Waste Disposal:	Dispose of in accordance with federal, state, provincial and local regulations.
13.2	Special Considerations:	NA

SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 12/24/2015

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND):	CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) – until 12/31/20 UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	
14.2	IATA (AIR):	CONSUMER COMMODITY, 9, ID8000 (IP VOL ≤ 0.5 L) UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	or
14.3	IMDG (OCN):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	
14.4	TDGR (Canadian GND):	MARK PACKAGE ("LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT L TÉE" (IP VOL ≤ 1.0 L) or UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	
14.5	ADR/RID (EU):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	
14.6	SCT (MEXICO):	UN1950, AEROSOLS, 2.1 (CANTIDAD LIMITADA, IP VOL ≤ 1.0 L)	
14.7	ADGR (AUS):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	

15. REGULATORY INFORMATION



15.1	SARA Reporting Requirements:	This product contains <u>Xylene</u> , <u>Toluene</u> , <u>Isopropanol</u> and <u>Ethylbenzene</u> , substances subject to SARA Title III, Section 313 reporting requirements.	
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.	
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory or are otherwise exempt.	
15.4	CERCLA Reportable Quantity (RQ):	<u>Acetone</u> : 2,270 kg (5,000 lbs); <u>Toluene</u> : 454 kg (1,000 lbs); <u>Xylene</u> : 45.4 kg (100 lbs); <u>Ethylbenzene</u> : 454 kg (1,000 lbs)	
15.5	Other Federal Requirements:	<u>Xylene</u> , <u>Ethylbenzene</u> and <u>Toluene</u> are listed as Hazardous Air Pollutants (HAPs). <u>Ethylbenzene</u> , <u>Toluene</u> , and <u>Xylene</u> are listed as Toxic Pollutants under the Clean Water Act (CWA). <u>Toluene</u> is listed as Priority Pollutants under the CWA. This product does not contain any Class 1 or Class 2 ozone depleters.	
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDL. <u>Toluene</u> and <u>Xylene</u> are listed on the Priorities Substances List. WHMIS Class B5, D2B (Flammable Aerosol, Other Toxic Effects).	
15.7	State Regulatory Information:	<u>Acetone</u> is found on the following state criteria lists: California OSHA Hazardous Substances List (CA), Delaware Air Quality Management List (DE), Massachusetts Hazardous Substances List (MA), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA) and Wisconsin Hazardous Substances List (WI). <u>Talc</u> is found on the following state criteria list: FL, MA, MN, NJ, PA and WA. <u>Isobutyl Acetate</u> is found on the following state criteria lists: FL, MA, MN, NJ, PA and WA. <u>Toluene</u> is found on the following state criteria list: CA65, DE, MA, NJ, NY, PA, WA, and WI. <u>Xylene</u> is found on the following state criteria list: CA65, FL, MA, MI, MN, NJ, NY, PA, WA and WI. <u>Ethylbenzene</u> is found on the following state criteria list: CA65, FL, MA, MN, PA and WA. No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). WARNING: This product contains a substance(s) known to the State of California to cause cancer, birth defects or other reproductive harm. California law requires this warning be given to customers in the State of California.	

SAFETY DATA SHEET


Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 12/24/2015

15.8	Other Requirements:	<p>The primary components of this product are listed in Annex I of EU Directive 67/548/EEC:</p> <p>Acetone: Flammable, Harmful (F, Xn). Risk Phrases (R): 11-36-66-67 – Highly flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Vapors may cause dizziness or drowsiness. Safety Phrases (S): (2-)9-16-26-46 – Keep out of the reach of children. Keep container in a well-ventilated place. Keep away from sources of ignition – No smoking. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, seek medical advice immediately and show this container or label.</p> <p>Isobutyl Acetate: Flammable (F). Risk Phrases (R): Flammable. Safety Phrases (S): 9-16-33 – Keep container in a well-ventilated place. Keep away from sources of ignition – No smoking. Take precautionary measures against static discharges.</p> <p>Toluene: Flammable, Harmful (F, Xn). Risk Phrases (R): 11-48/20-65-38 – Highly Flammable. Harmful: Danger of serious damage to health by prolonged exposure through inhalation. Harmful may cause lung damage if swallowed. Irritation to skin. Safety Phrases (S) 2-36/37-46-62 – Keep out of reach of children. Wear suitable protective clothing and gloves. If swallowed, seek medical advice immediately and show container or label. If swallowed do not induce vomiting; seek medical advice immediately and show this container or label.</p> <p>Xylene: Harmful (XN). Risk Phrases (R): 10-20/21-38 – Flammable. Harmful by inhalation and in contact with skin. Irritating to skin. Safety Phrases (S): 2-25 – Keep out of reach of children. Avoid contact with eyes.</p> <p>Ethylbenzene: Flammable (F), Harmful (Xn). Risk Phrases (R): 11-20 – Highly flammable. Harmful by inhalation. Safety Phrases (S): 2-16-24/25-29 – Keep out of reach of children. Keep away from sources of ignition. Avoid contact with skin and eyes. Do not empty into drains.</p>	 
------	---------------------	--	---

16. OTHER INFORMATION

16.1	Other Information:	<p>DANGER! EXTREMELY FLAMMABLE AEROSOL. PRESSURIZED CONTAINER MAY BURST IF HEATED. HARMFUL IF SWALLOWED, IN CONTACT WITH SKIN, OR IF INHALED. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION. Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °F (122 °F). Avoid breathing fume/mist/vapors/spray. Wash thoroughly with soap and water after handling. Do not eat, drink or smoke when using this product. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice/attention. KEEP OUT OF REACH OF CHILDREN.</p> <p>WARNING: This product contains a substance(s) known to the State of California to cause cancer, birth defects or other reproductive harm.</p>	
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Harbor Freight Tools USA, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.	
16.4	Prepared for:	Harbor Freight Tools USA, Inc. 26541 Agoura Road Calabasas, CA 91302 USA Tel: +1 (805) 388-1000 http://www.harborfreight.com	
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com	

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 12/24/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
---------	----------------------------------

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
C	Ceiling Limit
ES	Exposure Standard (Australia)
IDLH	Immediately Dangerous to Life and Health
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
-----	--

HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard	HEALTH
1	Slight Hazard	FLAMMABILITY
2	Moderate Hazard	PHYSICAL HAZARDS
3	Severe Hazard	PERSONAL PROTECTION
4	Extreme Hazard	

PERSONAL PROTECTION RATINGS:

A		G													
B		H													
C		I													
D		J													
E		K													
F		X	Consult your supervisor or SOPs for special handling directions.												
<table><tr><td> Safety Glasses</td><td> Splash Goggles</td><td> Face Shield & Protective Eyewear</td><td> Gloves</td></tr><tr><td> Boots</td><td> Synthetic Apron</td><td> Protective Clothing & Full Suit</td><td> Dust Respirator</td></tr><tr><td> Full Face Respirator</td><td> Dust & Vapor Half-Mask Respirator</td><td> Full Face Respirator</td><td> Airline Hood/Mask or SCBA</td></tr></table>				Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves	Boots	Synthetic Apron	Protective Clothing & Full Suit	Dust Respirator	Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA
Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves												
Boots	Synthetic Apron	Protective Clothing & Full Suit	Dust Respirator												
Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA												

OTHER STANDARD ABBREVIATIONS:

ML	Maximum Limit
mg/m3	milligrams per cubic meter
NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR	No Results
ppm	parts per million
SCBA	Self-Contained Breathing Apparatus


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD ₁₀	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD ₁₀ , LD ₁₀ , & LD ₀ or TC, TC ₀ , LC ₁₀ , & LC ₀	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NOHSC	National Occupational Health and Safety Commission (Australia)
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

C	E	F	N	O	T	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment