

Page 1 of 6 HFT-61232

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 7/29/2015

1.	PRODUCT &	COMPANY IDEI	NTIFICATION
	11100001 0	COMIL AND IDE	

Product Name:	AFOLD LOW LIFT TO A NEW ICCION LACK
	450 LB LOW LIFT TRANSMISSION JACK
Chemical Name:	Paraffin Oil
Synonyms:	P/N 61232
Trade Names:	Pittsburgh Automotive
Product Uses & Restrictions:	Hydraulic Oil
Distributor's Name:	Harbor Freight Tools USA, Inc.
Distributor's Address:	26541 Agoura Road, Calabasas, CA 91302 USA
Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687)
Business Phone / Fax:	+1 (805) 388-1000
	Synonyms: Trade Names: Product Uses & Restrictions: Distributor's Name: Distributor's Address: Emergency Phone:

2. HAZARDS IDENTIFICATION

Hazard Identification: This product is classified as a HAZARDOUS SUBSTANCE but not as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia). DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION.

Classification: Asp. Tox. 1, Skin Irrit. 2, Eye Irrit. 2

Hazard Statements (H): H304 - May be fatal if swallowed and enters airways. H315 - Causes skin irritation. H319 – Causes serious eye irritation.

Precautionary Statements (P): P264 - Wash hands and exposed skin areas with soap and warm water thoroughly after handling. P280 - Wear protective gloves/eye protection. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor. P302+P352 - IF ON SKIN: Wash with plenty of water. P321 - Specific treatment - See Section 4 of this Safety Data Sheet. P331 -Do NOT induce vomiting, P332+P313 - If skin irritation occurs: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. P337+P313 – If eye irritation persists: Get medical advice/attention. P405 - Store locked up. P501 - Dispose of contents/ container to an approved waste disposal plant.



3. COMPOSITION & INGREDIENT INFORMATION

								EXPO	SURE LI	MITS IN	AIR (m	g/m³)	
					AC	GIH		NOHSC			OSHA		
					pp	m		ppm			ppm		
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	OTHER
PARAFFIN OILS	8012-95-1	PY8030000	232-384-2	60-100	(5)	(10)	NF	(5)	NF	(5)	(10)	2500	OIL MIST
PARAFFIN OILS	Asp. Tox.1; H3	04											
TRIS(2,4-DITERT-BUTYLPHENYL)	31570-04-4	NA	250-709-6	1-5	NA	NA	NF	NF	NF	NA	NA	NA	
PHOSPHITE													
2.6-DI-TERT-BUTYL-P-CRESOL	128-37-0	GO7875000	204-881-4	0.5-1.5	NA	NA	NF	10	NF	NA	NA	NA	
2,0-DI-TERT-BUTTL-P-CRESOL	Aquatic Acute 1	l; Aquatic Chronic	: 1; H400, H410										

4.1	First Aid:	Ingestion:	DO NOT INDUCE VOMITING. Contact ChemTrec at +1 (703) 527-3887 or the nearest Poison Control Center or local emergency telephone number for assistance and instructions. Seek immediate medical
			attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.
		Eyes:	If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 minutes, holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately.
		Skin:	Remove contaminated clothing and wash affected areas with soap and water. If irritation persists, seek prompt medical attention. Do not wear contaminated clothing until after it has been properly cleaned.
		Inhalation:	Remove victim to fresh air at once. If breathing is difficult, administer supplemental oxygen and seek immediate medical attention. If breathing stops, perform artificial respiration.
4.2	Effects of Exposure:	Ingestion: Eyes: Skin: Inhalation:	If product is swallowed, may cause nausea, vomiting and/or diarrhea. May cause transient mild-eye irritation with short-term contact with liquid, spray or mist. This product can cause mild, transient skin irritation with short-term exposure. This product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. No significant adverse health effects are expected to occur upon short-term exposure to this product.
			Aspiration of liquid into the lungs can cause severe lung damage or death. Drowsiness, dizziness, headaches and nausea.
4.3	Symptoms of Overexposure:	<u>Eyes</u> : <u>Skin</u> :	Overexposure in eyes may cause redness, itching and watering. Symptoms of skin overexposure may include redness, itching, and irritation of affected areas The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.



Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SAFETY DATA SHEET

SDS Revision: 1.1

Page 2 of 6 HFT-61232

SDS Revision Date: 7/29/2015

4. FIRST AID MEASURES 44 Acute Health Effects: Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea 4.5 Chronic Health Effects Contains a petroleum-based mineral oil. Prolonged or repeated skin contact can cause mild irritation and inflammation characterized by drying, cracking, (dermatitis) or oil acne. Repeated or prolonged inhalation of petroleum-based mineral oil mists at concentrations above applicable workplace exposure levels can cause respiratory irritation or other pulmonary Eyes, Skin, Respiratory System, Central Nervous System (CNS). 4.6 Target Organs: 4.7 Medical Conditions Pre-existing dermatitis, other skin conditions, and disorders of the **HEALTH** Aggravated by Exposure target organs (eyes, skin, and respiratory system). **FLAMMABILITY** 1 **PHYSICAL HAZARDS** 0 PROTECTIVE EQUIPMENT X **EYES** SKIN LUNGS 5. FIREFIGHTING MEASURES Fire & Explosion Hazards: This material can burn but will not readily ignite. This material will release vapors when heated above the flash point temperature that can ignite when exposed to a source of ignition. In enclosed spaces, heated vapor can ignite with explosive force. Mists or sprays may burn at temperatures below the flash point. Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and trace oxides of sulfur, phosphorus, zinc and nitrogen. Also, depending upon the conditions of use, low concentrations of hydrogen sulfide can be released. 5.2 Extinguishing Methods Dry Chemical, Foam, Carbon Dioxide, Water Fog. 5.3 Firefighting Procedures Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Avoid spraying water directly into storage containers because of danger of boil over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES Spills: Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Use normal hygiene practices. Avoid breathing vapors. Avoid direct skin contact. Wash hands thoroughly after using this product and before eating, drinking, or smoking. 7.2 Storage & Handling: Use and store in a cool, dry, well-ventilated area. Keep away from excessive heat, open flames, sparks, and other possible sources of ignition. Do not store in unmarked containers or storage devices. Recommended maximum shelf life: 36 months. 7.3 Special Precautions: Empty containers may contain product residue. Do not pressurize, cut, heat or weld empty containers. Do not reuse empty containers without commercial cleaning or reconditioning.



Page 3 of 6 **HFT-61232**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 7/29/2015

		8. EXPOSURE CONT			PERSC		KOIE	CHC			
8.1	Exposure Limits:			GIH		NOHSC	ı		OSHA	1	OTHER
	ppm (mg/m ³)	CHEMICAL NAME(S)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		PARAFFIN OILS	(5)	(10)	NF	(5)	NF	(5)	(10)	2500	OIL MIST
3.2	Ventilation 9 Engineering	2,6-DI-TERT-BUTYL-P-CRESOL	NA	NA	NF	10	NF	NA	NA	NA	
0.2	Ventilation & Engineering Controls:	The use of mechanical dilution vi									
		occupational exposure limits, wh (up to 38 °C) or is agitated.	enever	tnis ma	teriai is us	ed in a co	niinea spa	ice, is i	neated a	above n	ormai temperatur
8.3 Respiratory Protection: Vaporization or misting is not expected at ambient temperatures. Therefore, the need for respiratory											
	,	protection is not anticipated und									
		airborne concentrations above									
		approved organic vapor respirat									
		factors vary depending upon the									
		with OSHA requirements (29 CFF									
8.4	Eye Protection:	Wear protective eyewear (e.g.,									
		product. Always use protective									
		shield if splashing or spraying is									
		absorb and concentrate irritants. protection tested and approved u									
		166(EU).	nuer ap	ргорпа	te governii	ieni stanu	arus sucri	as MO	SH (US) OI EIN	
8.5	Hand Protection:	Use gloves constructed of chem	ical-res	istant m	naterials si	ich as ne	onrene or	heavy	nitrile rı	ihher if	
		frequent or prolonged contact is									
		appropriate standards of Canada					. 0011/12	0 01 10	31010.1	00, 1110	
8.6	Body Protection:	Avoid prolonged and/or repeated					ervious pro	otective	clothin	a (e a	
	,	neoprene or Tyvek®) if splashir									de la
		include long-sleeves, apron, boo									
		standards of Canada, the EU me						•		•	
		9. PHYSICAL	& CI	HEMI	CAL P	ROPE	RTIES				
9.1	Appearance:	Transparent rose-colored liquid									
9.2	Odor:	Mild petroleum odor									
9.3	Odor Threshold:	NA									
9.4	pH:	NA									
9.5	Melting Point/Freezing Point:	- 41.0 °C (- 41.8) °F									
9.6	Initial Boiling Point/Boiling	NA									
	Range:										
9.7	Flashpoint:	176 °C (348.8 °F)									
9.8	Upper/Lower Flammability Limits:	NA									
9.9	Vapor Pressure:	NA									
9.10	Vapor Density:	NA									
9.11	Relative Density:	0.8345 g/cm ³									
9.12	Solubility:	Insoluble									
9.13	Partition Coefficient (log Pow):	NA									
9.14	Autoignition Temperature:										
9.14	Decomposition Temperature:	206 °C (402.8 °F)									
9.15	Viscosity:	NA 12.02 mBs									
	Other Information:	13.83 mPa									
9.17	Other information:	NA NA									
		10. STA	BII I	TY &	RFAC	TIVITY	7				
10.1	Stability:	Stable at normal temperatures.	·~:LI	u	LAU						
10.1	Hazardous Decomposition	Fumes, smoke, carbon monoxide	eilicer	ovidos							
10.2	Products:	i unies, smoke, carbon monoxide	, SHICOF	oxides	•						
10.3	Hazardous Polymerization:	Will not occur.									
10.4	Conditions to Avoid:	Open flames, sparks, high heat,	and clos	se proxii	mity to inco	ompatible :	substance	s.			
	Incompatible Substances:	Strong oxidizing agents.									



Page 4 of 6 HFT-61232

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 7/29/2015 11. TOXICOLOGICAL INFORMATION Ingestion: YES 11.1 Routes of Entry: Inhalation: NO Absorption: YES 11 2 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product and is presented below: Based on animal testing from similar materials & products, the acute toxicity of this product is expected to be: Paraffin \underline{Oil} – LD₅₀ (oral, rat) > 5,000 mg/kg. $\underline{2,6-Di-tert-Butyl-p-Cresol}$ - LD₅₀ (oral, mouse) > 850 mg/kg 11.3 Acute Toxicity: Mineral oil mists derived from highly refined oils are reported to have low acute and sub-acute toxicities in animals. Effects from single and short-term repeated exposures to high concentrations of mineral oil mists well above applicable workplace exposure levels include lung inflammatory reaction, lipoid granuloma formation and lipoid pneumonia. In acute and sub-acute studies involving exposures to lower concentrations of mineral oil mists at or near current work place exposure levels produced no significant toxicological effects. 11.4 Chronic Toxicity: NA 11.5 Suspected Carcinogen: NA Reproductive Toxicity: 11.6 This product is not reported to produce reproductive toxicity in humans Mutagenicity This product is not reported to produce mutagenic effects in humans Embryotoxicity This product is not reported to produce embryotoxic effects in humans. Teratogenicity This product is not reported to produce teratogenic effects in humans. Reproductive Toxicity: This product is not reported to produce reproductive effects in humans. 11.7 Irritancy of Product See Section 4.3 11.8 Biological Exposure Indices: NE 11.9 Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: There are no specific data available for this product. 122 Effects on Plants & Animals: There are no specific data available for this product. 12.3 Effects on Aquatic Life: There are no specific data available for this product. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal Dispose of in accordance with federal, state, provincial and local regulations. Special Considerations 13.2 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 14.1 49 CFR (GND): **NOT REGULATED** 14.2 IATA (AIR): **NOT REGULATED** 14.3 IMDG (OCN): **NOT REGULATED** 14.4 TDGR (Canadian GND): NOT REGULATED 14.5 ADR/RID (EU): NOT REGULATED SCT (MEXICO): 14.6 **NOT REGULATED** 14.7 ADGR (AUS): **NOT REGULATED** 15. REGULATORY INFORMATION SARA Reporting 15.1 This product does not contain any substances subject to SARA Title III, section 313 reporting requirements. Requirements 15.2 SARA Threshold Planning There are no specific Threshold Planning Quantities for the components of this product. Quantity: TSCA Inventory Status: 15.3 The components of this product are listed on the TSCA Inventory or are otherwise exempt. 15.4 **CERCLA Reportable Quantity** 15.5 Other Federal Requirements: None of the ingredients are listed as Hazardous Air Pollutants (HAPs). None of the ingredients are listed as Toxic Pollutants under the Clean Water Act (CWA). None of the ingredients are listed as Priority Pollutants under the Clean Water Act (CWA). This product does not contain any Class 1 or Class 2 ozone depletors Other Canadian Regulations: 15.6 This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS D2B (Other Toxic Effects)



Page 5 of 6 HFT-61232

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 7/29/2015 15. REGULATORY INFORMATION – cont'd Paraffin Oil is found on the following state criteria lists: Massachusetts Hazardous Substances List (MA), Minnesota 15.7 State Regulatory Information: Hazardous Substances List (MN) and Washington Permissible Exposures List (WA). No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). Other Requirements: The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC: Paraffin Oil: Harmful (Xn). Risk Phrases (R): 36-65 - Irritating to eyes. Harmful: may cause lung damage if swallowed. Safety Phrases (S): 53-45 - Avoid exposure - obtain special instructions before use. In case of accident or if you feel unwell seek medical advice immediately (show the label where possible) 16. OTHER INFORMATION Other Information: DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION. Wash hands and exposed skin areas with soap and warm water thoroughly after handling. Wear protective gloves/eye protection. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Store locked up. Dispose of contents/ container to an approved waste disposal plant. KEEP OUT OF REACH OF CHILDREN. Terms & Definitions: 16.2 See last page of this Safety Data Sheet. This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other Disclaimer: 16.3 government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Harbor Freight Tools USA, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. Prepared for: 16.4 Harbor Freight Tools USA, Inc. 26541 Agoura Road **HARBOR FREIGHT TOOLS** Calabasas, CA 91302 USA Tel: +1 (805) 388-1000 http://www.harborfreight.com/ Prepared by: 16.5 ShipMate, Inc. P.O. Box 787

Sisters, Oregon 97759-0787 USA

Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com

Page 6 of 6 HFT-61232

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision Date: 7/29/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number				
EXPOSURE	EXPOSURE LIMITS IN AIR:				
ACGIH	American Conference on Governmental Industrial Hygienists				
С	Ceiling Limit				
ES	Exposure Standard (Australia)				
IDLH	Immediately Dangerous to Life and Health				
OSHA	U.S. Occupational Safety and Health Administration				
PEL	Permissible Exposure Limit				
STEL	Short-Term Exposure Limit				
TLV	Threshold Limit Value				
TWA	Time Weighted Average				

FIRST AID MEASURES:

CPR Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body

HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:

	 -		
Α			
В			
С			
D			
Е			
F		4	











Full Face Respirator



Protective Clothing & Full Suit

Dust Respirator

Dust & Vapor Half-Mask Respirator

Full Face

Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:

ML	Maximum Limit
mg/m3	milligrams per cubic meter
NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR	No Results
ppm	parts per million
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:						
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition					
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					

HAZARD RATINGS:

0	Minimal Hazard		
1	Slight Hazard		
2	Moderate Hazard		
3	Severe Hazard		
4	Extreme Hazard		
ACD	Acidic		
ALK	Alkaline		
COR	Corrosive		
₩	Use No Water		
ОХ	Oxidizer		
TREFOIL	Radioactive		



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{io}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC _o , LC _{lo} , & LC _o	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System					
DOT	U.S. Department of Transportation					
TC	Transport Canada					
EPA	EPA U.S. Environmental Protection Agency					
DSL	DSL Canadian Domestic Substance List					
NOHSC	National Occupational Health and Safety Commission (Australia)					
NDSL	NDSL Canadian Non-Domestic Substance List					
PSL	Canadian Priority Substances List					
TSCA	U.S. Toxic Substance Control Act					
EU	European Union (European Union Directive 67/548/EEC)					
WGK	Wassergefährdungsklassen (German Water Hazard Class)					
HMIS-III	HMIS-III National Paint & Coatings Association Hazardous Materials Identification System					

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

TOTAL ENGLISHED CO INSTITUTE IDENTITION (WITHING) CTCTEIN.								
0	((2)		\odot	(1)		R	
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F	
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive	

EC (67/548/EEC) INFORMATION:

The state of the s		M	*			X	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\Diamond		*
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment