

Page 1 of 6 HFT-61279

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 4/30/2015 SDS Revision: 1.0

#### 1. PRODUCT & COMPANY IDENTIFICATION Product Name: **D ALKALINE BATTERIES** 1.2 Chemical Name: Alkaline Battery 1.3 Synonyms: P/N 61279 14 Trade Names Thunderbolt Magnum 1.5 Product Uses & Restrictions: **Electric Storage Battery** 1.6 Distributor's Name: Harbor Freight Tools USA, Inc. 1.7 Distributor's Address: 26541 Agoura Road, Calabasas, CA 91302 USA 1.8 Emergency Phone: CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687) 1.9 Business Phone / Fax: +1 (805) 388-1000

### 2. HAZARDS IDENTIFICATION

2.1 Hazard Identification: This product is classified as a hazardous substance and as dangerous goods according to the classification criteria of [NOHSC: 1088 (2004)] and ADG Code (Australia).

WARNING! HARMFUL IF SWALLOWED. TOXIC TO AQUATIC LIFE WITH LONG LASTING

Hazard Statements (H): H302 - Harmful if swallowed. H411 - Toxic to aquatic life with long lasting effects.

Precautionary Statements (P): P264 - Wash hands and exposed skin areas with soap and warm water thoroughly after handling. P270 – Do not eat, drink or smoke while sing this product. P273 – Avoid release to the environment. P280 - Wear protective gloves/eye protection. P301+P312 - IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. P330 - Rinse mouth. P391 -Collect spillage. P501 - Dispose of contents/container to licenses treatment, storage and disposal facility (TSDF).

IF INGESTED: Call the NATIONAL BATTERY INGESTION HOTLINE at +1 (202) 625-3333 collect, day or night. In Canada, call +1 (416) 813-5900.



# 3. COMPOSITION & INGREDIENT INFORMATION

					EXPOSURE LIMITS IN AIR (mg/m³)								
					ACGIH		NOHSC		OSHA				
					ppm		ppm		ppm				
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	OTHER
MANGANESE DIOXIDE	1313-13-9	OP0350000	215-202-6	20-60	(5)	NA	(5)	NF	NF	(5)	NA	NA	
MANGANESE DIOXIDE	Acute Tox. Ora	al 4; Acute Tox. In	nh. 4; H302, H33	2									
IRON (STEEL)	7439-89-6	NO4565500	231-096-4	10-20	(5)	NA	NF	NF	NF	(10)	NA	NA	0.5 - NIOSH
IRON (STEEL)	Acute Tox. 4 *;	; Skin Corr. 1A; H	l302, H314										
ZINC	7440-66-6	ZG8600000	231-175-3	10-20	NA	NA	NF	NF	NF	NA	NA	NA	
ZINC	Aquatic Acute	1; Aquatic Chron	ic 1; H400, H410	)									
WATER	7732-18-5	ZC0110000	231-791-2	10-20	NA	NA	NF	NF	NF	NA	NA	NA	
WATER													
POTASSIUM HYDROXIDE	1310-58-3	TT2100000	215-181-3	7-13	NA	NA	(2)	NF	NF	NA	NA	NA	
POTASSIUM HYDROXIDE	Acute Tox. Ora	Acute Tox. Oral 4; Acute Tox. Inh. 4; H302, H332											
GRAPHITE	7782-42-5	MD9659600	231-955-3	1-5	(2.0)	NA	(2.0)	NF	NF	(5)*	NA	NA	RESP FRAC
GRAFIIIL													
BRASS	12597-71-6	NA	NA	0.1-1	(1)	NA	NF	NF	NF	(1)	NA	NA	
BRASS													
NICKEL	7440-02-0	QR5950000	231-111-4	0.1-1	(1.5)	NA	(1)	NF	NA	NA	NA	(10)	
NIONEL	Carc. 2; STOT	RE 1; Skin Sens	s. 1; Aquatic Chro	onic 3; H35	1, H372	2**, H31	17, H412	2					
LEAD	7439-92-1	OF7525000	231-100-4	< 0.0030	(0.05)	NA	NF	(0.15)	NF	NA	100	NA	
LEAD	Acute Tox. 4; A	Acute Tox. 4; Rep	or. 1A; STOT RE	2; Aquatic	Acute '	1; Aqua	tic Chro	nic 1; F	1302, H	1332, H	360, H3	373, H4	00, H410
CADMIUM	7440-43-9	NA	231-152-8	< 0.0003	(0.01)	NA	NF	NF	NF	(0.1)	0.3	(9)	(0.02) RESP FRAC
CADINION	Acute Tox. 2; I	Muta. 2; Carc. 1B	; Repr. 2; STOT	SE 1; Aq. /	Acute 1	; Aq. Cl	hronic 1	; H330,	H341,	H350,	H361fd	, H372,	H400, H410
MERCURY	7439-97-6	OV4550000	231-106-7	< 0.0001	NA	NA	(0.003)	(0.025)	NA	NA	NA	(10)	
MERCURY	Repr. 1B; Acut	te Tox. 2 *; STOT	RE 1; Aquatic A	cute 1; Aq	uatic Ch	ronic 1	I; H360[	D***, H3	330, H3	72**, H	400, H	110	
ADSENIC	7440-38-2	CG0525000	231-148-6	< 0.0001	NA	NA	NF	(0.05)	NF	(0.002)	NA	5	
ARSENIC	Acute Tox. 3 *:	Acute Tox. 3 *;	Aquatic Acute 1;	Aquatic Ch	ronic 1	; H331,	H301, I	H400, F	1410				



Page 2 of 6

HFT-61279 Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 4/30/2015 4. FIRST AID MEASURES 4 1 First Aid: Give large quantities of water, but do NOT induce vomiting. Never give anything by mouth to an Ingestion: unconscious person. Contact the nearest Poison Control Center or local emergency telephone number for assistance and instructions. Seek immediate medical attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration. If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 minutes, Eyes: holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately. If an open battery cell: Remove contaminated clothing and wash affected areas with soap and water. If Skin: discomfort persists and/or the skin reaction worsens, contact a physician immediately. Do not wear contaminated clothing until after it has been properly cleaned. Remove victim to fresh air at once. Under extreme conditions, if breathing stops, perform artificial Inhalation: respiration. Seek immediate medical attention. 42 Effects of Exposure: May cause severe irritation of mouth, throat, esophagus, and stomach. Acute ingestion of zinc Ingestion: compounds may cause abdominal pain, nausea, vomiting, diarrhea, and severe cramping. Eyes: Severe irritation, burns, cornea damage, blindness. Lead compounds may cause irritation. Skin: Severe irritation, burns, and ulceration if open battery cell comes into contact with skin. Inhalation: Inhalation of lead dust or fumes may cause irritation of upper respiratory tract and lungs. 4.3 Symptoms of Overexposure Ingestion: Severe discomfort, nausea, vomiting and headache. Harmful if swallowed. May cause corrosion and permanent tissue destruction of the esophagus and digestive tract. May cause irreversible eye injury. Contact with eyes may cause severe irritation, and possible eye burns. Eyes: Severe irritation, redness, and watering, Severe skin irritation, red, itching skin, burns and ulceration, if open battery cell comes into contact with Skin: Inhalation: May cause cyanosis (bluish discoloration of skin due to deficient oxygenation of the blood). Irritation may lead to chemical pneumonitis and pulmonary edema. Inhalation of fumes may cause metal fume fever, which is characterized by flu-like symptoms with metallic taste, fever, chills, cough, weakness, chest pain, muscle pain and increased white blood cell count. Causes respiratory tract irritation with possible burns. 4.4 Acute Health Effects: Hazardous exposure can occur only when product is heated above the melting point, oxidized or otherwise processed or damaged to create dust, vapor, or fume. Chronic Health Effects: 4.5 Chronic exposure may cause effects similar to those of acute exposure. 4 6 Target Organs: Skin, Respiratory System, Central Nervous System (CNS) 47 Medical Conditions **HEALTH** 1 Aggravated by Exposure: **FLAMMABILITY** 0 PHYSICAL HAZARDS 0 PROTECTIVE EQUIPMENT X **EYES** SKIN **LUNGS** 5. FIREFIGHTING MEASURES Fire & Explosion Hazards: 5.1 This material can burn but will not readily ignite. However, if involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO, CO<sub>x</sub>, Hydrocarbons). 52 Extinguishing Methods: CO<sub>2</sub>, Dry Chemical, Alcohol Foam, Dry Chemical. Use water spray to cool containers. 5.3 Firefighting Procedures: Use extinguishing media most appropriate for the surrounding fire. Do NOT get water inside containers. For small fires, use dry chemical, carbon dioxide, or water spray. For large fires, use dry chemical, carbon dioxide, alcohol-resistant foam, or water spray. Cool containers with flooding

### quantities of water until well after fire is out. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Spills Equipment, including protective gloves and eyewear. Plastic or rubber gloves, respirator, eye/face protection and chemical-resistant apron may be required for clean-up of large spills. Small Spills: Wear appropriate protective equipment including gloves and protective eyewear. Use a non-combustible material such as vermiculite or sand to soak up the product and place into a container for later disposal. Large Spills: Keep incompatible materials away from spill. Stay upwind and away from spill or release. Isolate immediate hazard area and keep unauthorized personnel out of area. Stop spill or release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant. Collect in acidresistant container.



8.5

8.6

Hand Protection:

Body Protection:

be available.

# SAFETY DATA SHEET

Page 3 of 6 **HFT-61279** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 4/30/2015 7. HANDLING & STORAGE INFORMATION Work & Hygiene Practices: Do not eat, drink or smoke when handling this product. Handle as to avoid puncturing container(s). 7.2 Storage & Handling Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Keep away from incompatible substances. Protect containers from physical damage. Store product in wellfilled, appropriate coated and tightly closed containers avoiding influence of oxygen/air, light and humidity. Store at a cool and constant temperature. This battery is not designed for recharging. Recharging can cause battery leakage or high pressure rupture, in some 7.3 Special Precautions: cases. Inadvertent charging can happen if a battery is installed backwards. Accidental short circuit for a few seconds will not seriously affect the battery. But prolonged short circuit will cause the battery to lose energy, and can cause the safety release vent to open. Sources of short circuit include jumbled batteries in bulk containers, metal jewelry, metal covered tables or metal belts used for assembly of batteries in devices. 8. EXPOSURE CONTROLS & PERSONAL PROTECTION ACGIH NOHSC OSHA OTHER **Exposure Limits:** ppm (mg/m<sup>3</sup>) ES-STEL **CHEMICAL NAME(S)** STEL ES-TWA **ES-PEAK** STEL **IDLH** TLV PEL MANGANESE DIOXIDE (5) NA (5) NF NF (5) NA NA RESP FRAC **GRAPHITE** (2.0)NA (2.0)NF NF (5)\* NA NA POTASSIUM HYDROXIDE NA NA NF NF NA NA NA (2) IRON (STEEL) NF NF NF (10)NA NA 0.5 - NIOSH (5) NA LEAD (0.15)NF (0.05)NA NF NA 100 NA CADMIUM (0.01)NA NF NF NF (0.1) 0.3 (9) (0.02) RESP FRAC **MERCURY** NA NA (0.003)(0.025)NA NA NA (10)**ARSENIC** NA NA NF (0.05)NF (0.002)NA 8.2 Ventilation & Engineering General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Use local or general Controls exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station) 8.3 Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. In instances where mist or vapors of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia. 8.4 Eve Protection: Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

### 9. PHYSICAL & CHEMICAL PROPERTIES

Where contact is likely, impervious gloves are recommended. Do not wear rings, watches or jewelry. When handling large quantities of fluid (e.g., ≥ 1 gallon (3.8 L)), wear corrosion-resistant gloves.

No apron required when handling sealed undamaged battery. Where contact is likely, corrosion-resistant apron, clothing and boots should be worn. Eye wash stations and deluge showers should

		01 1 111 010/12 & 011211110/12 1 1101
9.1	Appearance:	Stainless steel top battery. Contents dark and gray in color.
9.2	Odor:	No apparent odor (sealed).
9.3	Odor Threshold:	NA
9.4	pH:	NA NA
9.5	Melting Point/Freezing Point:	NA NA
9.6	Initial Boiling Point/Boiling Range:	NA NA
9.7	Flashpoint:	NA NA
9.8	Upper/Lower Flammability Limits:	NA NA
9.9	Vapor Pressure:	NA NA
9.10	Vapor Density:	NA NA
9.11	Relative Density:	NA NA
9.12	Solubility:	Sealed electric battery: Insoluble.
9.13	Partition Coefficient (log Pow):	NA NA
9.14	Autoignition Temperature:	NA .
9.15	Decomposition Temperature:	NA NA
9.16	Viscosity:	NA NA
9.17	Other Information:	NA .



Page 4 of 6 HFT-61279

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 4/30/2015 10. STABILITY & REACTIVITY 10.1 Stability: Stable under normal conditions; unstable with heat or contamination. 10.2 Hazardous Decomposition Oxides of carbon (CO, CO<sub>2</sub>). Thermal degradation may produce hazardous fumes of zinc and manganese, hydrogen Products: gas, caustic vapors of potassium hydroxide and other hazardous by-products 10.3 Hazardous Polymerization: 10.4 Conditions to Avoid: Open flames, sparks, high heat, incompatible substances and direct sunlight, and incompatible substances. 10.5 Incompatible Substances: Avoid extreme heat and ignition sources. Store away from oxidizers. Do not exceed heat, crush, disassemble, shortcircuit or recharge. 11. TOXICOLOGICAL INFORMATION 11.1 Routes of Entry Ingestion: YFS Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product and is presented below: Manganese Dioxide: LD<sub>50</sub> (oral, rat): 3,478 mg/kg. 11.3 Acute Toxicity: See section 4.4 11 4 Chronic Toxicity See section 4.5 Nickel is listed as IARC Group 2B (Possibly carcinogenic to humans); NTP13 Group 1 (Known human carcinogen); CA65 11.5 Suspected Carcinogen: (cancer). Lead is listed as ACGIH Group A3 (Confirmed animal carcinogen with unknown relevance to human); IARC Group 2B (Possibly carcinogenic to humans): NTP13 Group 2 (Reasonably Anticipated to be a Human Carcinogen); CA65 (cancer). Cadmium is listed as ACGIH Group A2 (Suspected human carcinogen); IARC Group 1 (Carcinogenic to humans); NTP13 Group 1 (Known human carcinogen); CA65 (cancer). Arsenic is listed as ACGIH Group A1 (Confirmed human carcinogen); IARC Group 1 (Carcinogenic to humans); NTP13 Group 1 (Known human carcinogen); CA65 (cancer) 11.6 Reproductive Toxicity: This product contains Lead, which is suspected of causing reproductive toxicity in humans. Mutagenicity: This product is not reported to produce mutagenic effects in humans. Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product contains Lead, which is suspected of causing reproductive toxicity in humans 11.7 Irritancy of Product: The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. 11.8 Biological Exposure Indices NΑ 11.9 Physician Recommendations: Treat symptomatically and supportively. 12. ECOLOGICAL INFORMATION 12 1 Environmental Stability: There are no specific data available for this product. There are no specific data available for this product. 122 Effects on Plants & Animals: There are no specific data available for this product. 12.3 Effects on Aquatic Life: 13. DISPOSAL CONSIDERATIONS Waste Disposal: 13.1 Dispose of in accordance with federal, state, provincial and local regulations. Special Considerations: 13.2 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR 49 CFR (GND): 14.1 **NOT REGULATED** 14.2 IATA (AIR): **NOT REGULATED** 14.3 IMDG (OCN): NOT REGULATED 14.4 TDGR (Canadian GND): NOT REGULATED ADR/RID (EU): NOT REGULATED 14.5 SCT (MEXICO): NOT REGULATED 14.6 14.7 ADGR (AUS): NOT REGULATED 15. REGULATORY INFORMATION SARA Reporting 15.1 This product contains Lead, Mercury, Zinc and Nickel, substances subject to SARA Title III, section 313 reporting requirements SARA Threshold Planning 15.2 There are no specific Threshold Planning Quantities for the components of this product. 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory or are otherwise exempt. CERCLA Reportable Quantity 15.4 Zinc: 454 kg (1,000 lbs); Mercury: 0.454 kg (1.0 lbs); Nickel: 45.4 kg (100 lbs) (RQ):



Page 5 of 6

HFT-61279 Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 4/30/2015 15. REGULATORY INFORMATION – cont'd 15.5 Other Federal Requirements: Mercury, Lead, Cadmium and Nickel are listed as Hazardous Air Pollutants (HAPs) under the Clean Air Act (CAA). Zinc, Nickel, Arsenic, Cadmium and Mercury are listed as Priority Pollutants under the Clean Water Act (CWA). Zinc. Lead. Arsenic, Cadmium and Mercury are listed as Toxic Pollutants under the CWA. This product does not contain any Class 1 or Class 2 ozone depletors. 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the Safety Data Sheet contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS D2B (Other Toxic Effects) 15.7 State Regulatory Information: Lead can be found on the following state criteria list: California Proposition 65 (CA65), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), and Washington Permissible Exposures List (WA). Nickel is listed on the following state criteria lists: fl, MA, MI, MN, NJ, PA, and WA. Potassium Hydroxide is found on the following state criteria lists: FL, MA, MN, PA, and WA. Graphite is found on the following state criteria lists: FL, MA, MN, PA, and WA. Manganese Dioxide is found on the following state criteria lists: IL, MA, PA, and RI. Zinc is found on the following state criteria lists: IL, MA, NJ, and PA. No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Illinois Hazardous Substances List (IL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Rhode Island Hazardous Substances List (RI), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). WARNING: This product contains a substance(s) known to the State of California to cause cancer, birth defects or other reproductive harm. California law requires this warning be given to customers in the State of California. 15.8 Other Requirements: The primary component of this product is listed in Annex I of EU Directive 67/548/EEC: Harmful, Environmental Danger (Xn, N). Risk Phrases (R): 22-34-50/53 - Harmful if swallowed. Causes burns. Very toxic to aquatic organisms may cause long-term adverse effects in the aquatic environment. Safety Phrases (S): 1/2-26-36/37/39-45-60-61 - Keep locked up and out of reach of children. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable protective clothing/ gloves and eye/face protection. In case of accident or if you feel unwell seek medical advice immediately (show label where possible). This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Refer to special instructions/SDS. 16. OTHER INFORMATION WARNING! HARMFUL IF SWALLOWED. TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS. Other Information: Wash hands and exposed skin areas with soap and warm water thoroughly after handling. Do not eat, drink or smoke while sing this product. Avoid release to the environment. P280 – Wear protective gloves/eye protection. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth. Collect spillage. IF INGESTED: Call the NATIONAL BATTERY INGESTION HOTLINE at +1 (202) 625-3333 collect, day or night. In Canada, call +1 (416) 813-5900. KEEP OUT OF REACH OF CHILDREN. WARNING: This product contains a substance(s) known to the State of California to cause cancer, birth defects or other reproductive harm. 16.2 Terms & Definitions: See last page of this Safety Data Sheet. 16.3 Disclaimer: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Harbor Freight Tools USA, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. 16.4 Prepared for: Harbor Freight Tools USA, Inc. 26541 Agoura Road HARBOR FREIGHT TOOLS

Quality Tools at Ridiculously Low Prices Calabasas, CA 91302 USA Tel: +1 (805) 388-1000 http://www.harborfreight.com/ 16.5 Prepared by: ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA

Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com

Page 6 of 6 HFT-61279

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 4/30/2015

### **DEFINITION OF TERMS**

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

#### **GENERAL INFORMATION:**

CAS No.	Chemical Abstract Service Number

#### **EXPOSURE LIMITS IN AIR:**

ACGIH	American Conference on Governmental Industrial Hygienists
С	Ceiling Limit
ES	Exposure Standard (Australia)
IDLH	Immediately Dangerous to Life and Health
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

#### FIRST AID MEASURES:


CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.


#### HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard			
1	Slight Hazard			
2	Moderate Hazard			
3	Severe Hazard			
4	Extreme Hazard			



#### PERSONAL PROTECTION RATINGS:























Dust & Vapor Half-Mask Respirator

Full Face

Airline Hood/Mask or SCBA

### OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit
mg/m3	milligrams per cubic meter
NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR	No Results
ppm	parts per million
SCBA	Self-Contained Breathing Apparatus

#### NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILI	FLAMMABILITY LIMITS IN AIR:					
Autoignition	Minimum temperature required to initiate combustion in air with no other					
Temperature	source of ignition					
LEL	LEL Lower Explosive Limit - lowest percent of vapor in air, by volume, that will					
	explode or ignite in the presence of an ignition source					
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will					
	explode or ignite in the presence of an ignition source					

#### **HAZARD RATINGS:**

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
₩	Use No Water
ОХ	Oxidizer
TREFOIL	Radioactive



#### TOXICOLOGICAL INFORMATION:

LD <sub>50</sub>	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC <sub>50</sub>	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD <sub>io</sub>	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD <sub>Io</sub> , LD <sub>Io</sub> , & LD <sub>o</sub> or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC <sub>o</sub> , LC <sub>io</sub> , & LC <sub>o</sub>	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL <sub>m</sub>	Median threshold limit
log K <sub>ow</sub> or log K <sub>oc</sub>	Coefficient of Oil/Water Distribution

#### **REGULATORY INFORMATION:**

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NOHSC	National Occupational Health and Safety Commission (Australia)
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System

### WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	<b>*</b>	<b>(A)</b>	<b>(3)</b>	$\odot$	<b>®</b>	(F)	R
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

### EC (67/548/EEC) INFORMATION:

		M	*		<b>®</b>	×	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

### CLP/GHS (1272/2008/EC) PICTOGRAMS:

			$\Diamond$			<b>\limits</b>	<b>***</b>	
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environ- ment