

Product Name:

Chemical Name:

Synonyms:

Trade Names

Distributor's Name:

Emergency Phone:

Distributor's Address:

Business Phone / Fax:

Hazard Identification:

Product Uses & Restrictions:

1.1

12

1.3

1.4

1.5

1.6

1.7

1.8

1.9

2.1

SAFETY DATA SHEET

Page 1 of 6 HFT-61405

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 5/14/2015

1. PRODUCT & COMPANY IDENTIFICATION					
500 LB CAPACITY HYDRAULIC TABLE CART					
Hydraulic Oil					
P/N 61405					
Pittsburgh Automotive					
Hydraulic Oil					
Harbor Freight Tools USA, Inc.					

CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687) +1 (805) 388-1000

2. HAZARDS IDENTIFICATION

This product is classified as a HAZARDOUS SUBSTANCE but not as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia). DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. Classification: Asp. Tox. 1 Hazard Statements (H): H304 – May be fatal if swallowed and enters airways. Precautionary Statements (P): P280 - Wear protective gloves/eye protection. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331 - Do NOT induce vomiting. P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. P405 - Store locked up. P501 - Dispose of contents/ container to an approved waste disposal plant.

26541 Agoura Road, Calabasas, CA 91302 USA



3. COMPOSITION & INGREDIENT INFORMATION

							EXPOSURE LIMITS IN AIR (mg/m³)						
					AC	GIH		NOHSC			OSHA		
					pp	m		ppm			ppm]
							ES-	ES-	ES-]
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER
DISTILLATES (PETROLEUM),	64741-51-4 NA	NA NA	60-100	NA	5	5	NF	NF	5	NA	NA	OIL MIST	
PARAFFINIC `	Asp. Tox.1; H3	04								·			

FIRST AID MEASURES

		4. FIRST AID WEASURES
4.1	First Aid:	Ingestion: DO NOT INDUCE VOMITING. Contact ChemTrec at +1 (703) 527-3887 or the nearest Poison Control Center or local emergency telephone number for assistance and instructions. Seek immediate medical attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.
		Eyes: If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 minutes, holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately.
		Skin: Remove contaminated clothing and wash affected areas with soap and water. If irritation persists, seek prompt medical attention. Do not wear contaminated clothing until after it has been properly cleaned.
		Inhalation: Remove victim to fresh air at once. If breathing is difficult, administer supplemental oxygen and seek immediate medical attention. If breathing stops, perform artificial respiration.
4.2	Effects of Exposure:	Ingestion: If product is swallowed, may cause nausea, vomiting and/or diarrhea. Eyes: May cause transient mild-eye irritation with short-term contact with liquid, spray or mist. Skin: This product can cause mild, transient skin irritation with short-term exposure. This product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. Inhalation: No significant adverse health effects are expected to occur upon short-term exposure to this product. Aspiration of liquid into the lungs can cause severe lung damage or death. Drowsiness, dizziness, headaches and nausea.
4.3	Symptoms of Overexposure:	Eyes: Overexposure in eyes may cause redness, itching and watering. Skin: Symptoms of skin overexposure may include redness, itching, and irritation of affected areas The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.
4.4	Acute Health Effects:	Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.
4.5	Chronic Health Effects:	Contains a petroleum-based mineral oil. Prolonged or repeated skin contact can cause mild irritation and inflammation characterized by drying, cracking, (dermatitis) or oil acne. Repeated or prolonged inhalation of petroleum-based mineral oil mists at concentrations above applicable workplace exposure levels can cause respiratory irritation or other pulmonary effects.
4.6	Target Organs:	Eyes, Skin, Respiratory System, Central Nervous System (CNS).

HARBOR FREIGHT TOOLS

Quality Tools at Ridiculously Low Prices

SAFETY DATA SHEET

Page 2 of 6 **HFT-61405**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 5/14/2015

		4. FIRST	AID MEAS	SURES	<u> </u>	t'd					
4.7	Medical Conditions	Pre-existing dermatitis, other			rders of t	he HEAL	.TH				1
	Aggravated by Exposure:	target organs (eyes, skin, and re	espiratory systen	۱).		FLAN	/IMAB	ILITY			1
						PHYS	SICAL	HAZA	RDS		0
						PRO	ГЕСТІ	VE EC	UIPME	ENT	Х
						EYES		SKIN	Ll	JNGS	
			EFIGHTING								
5.1	Fire & Explosion Hazards:	This material can burn but will r the flash point temperature that heated vapor can ignite with e flash point. Carbon dioxide, coxides of sulfur, phosphorus, a concentrations of hydrogen sulf	t can ignite when explosive force. Nearbon monoxide zinc and nitroge	exposed factoring exposed factoring factoring exposed factoring exposed factoring exposed factoring exposed factoring factoring exposed factoring exposed factoring	to a source brays may fumes, un	e of ignition burn at ten burned hyd	. In en nperat drocart	closed : ures be oons an	spaces, low the ld trace		1
5.2	Extinguishing Methods:	Dry Chemical, Foam, Carbon D								1	0
5.3	Firefighting Procedures:	Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Avoid spraying water directly into storage containers because of danger of boil over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.									
		6. ACCIDEI	NTAL RELI	FASE	MEASI	IRFS					
6.1	Spills:	Before cleaning any spill or I					et was	r annra	nriata I	Dersonal	Protoctive
		absorbent material and place in local, state and federal regulat soap. Remove any contaminate For large spills (e.g., ≥ 1 gallo material (e.g., sand or earth). recovery or disposal and solid of promptly and wash affected sk sewers and open bodies of water	tions. Wash all ed clothing and von (3.8 L)), deny Use ONLY non-sdiking material to in areas with so	affected a vash thoro vash entry to sparking to separate	areas and oughly before all unprote ools for recontainers	outside of re reuse. ected indiv overy and for proper	contair iduals. cleanu dispos	Dike p. Trar al. Rer	and consider liques	of warm ntain spill uid to con ontaminate	water and with inert tainers for ed clothing
		7. HANDLING	G & STOR	AGF IN	IFORM	ATION					
7.1	Work & Hygiene Practices:	Use normal hygiene practices. this product and before eating,	Avoid breathing	vapors.			tact. \	Wash h	ands the	oroughly a	after using
7.2	Storage & Handling:	Use and store in a cool, dry, possible sources of ignition. Do Recommended maximum shelf	not store in unn					it, open	flames	, sparks,	and other
7.3	Special Precautions:	Empty containers may contain empty containers without comm	product residue			cut, heat	or wel	d empty	/ contail	ners. Do	not reuse
		8. EXPOSURE CON	ITROLS &	PERSO	DNAL F	PROTE	CTIC	N			
8.1	Exposure Limits:		ACGIH		NOHSC		Ī	OSHA		OTHER	
	ppm (mg/m ³)	CHEMICAL NAME(S)	TLV STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH		
		DISTILLATES (PETROLEUM), PARAFFINIC	NA 5	5	NF	NF	5	NA	NA	OIL MIST	Г
8.2	Ventilation & Engineering Controls:	The use of mechanical dilution occupational exposure limits, w (up to 38 °C) or is agitated.									
8.3	Respiratory Protection:	Vaporization or misting is not e protection is not anticipated un airborne concentrations above approved organic vapor respir factors vary depending upon th with OSHA requirements (29 Cl	ider normal use e applicable wor ator equipped w ne type of respira	conditions kplace ex ith a dust	and with posure level/mist pre-f	adequate v vels are ar ilter should	entilat nticipat l be us	ion. If e ed, a I sed. Pro	elevated NIOSH- otection		
8.4	Eye Protection:	Wear protective eyewear (e.g product. Always use protective shield if splashing or spraying is absorb and concentrate irritant protection tested and approved 166(EU).	., safety glasses e eyewear when s anticipated. Co s. Have suitable	cleaning ontact lens e eye was	spills or le ses pose a h water av	aks. Wear special ha ailable. Us	goggl zard; s se equ	es and oft lens ipment	or face ses may for eye		B



Page 3 of 6 **HFT-61405**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 5/14/2015

	, , ,	
	8. E	EXPOSURE CONTROLS & PERSONAL PROTECTION – cont'd
8.5	Hand Protection:	Use gloves constructed of chemical-resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, or the EU member states.
8.6	Body Protection:	Avoid prolonged and/or repeated skin contact. Use clean and impervious protective clothing (e.g., neoprene or Tyvek®) if splashing or spraying conditions are present. Protective clothing should include long-sleeves, apron, boots and additional facial protection. If necessary, refer to appropriate standards of Canada, the EU member states, or U.S. OSHA.
		9. PHYSICAL & CHEMICAL PROPERTIES
9.1	Appearance:	Clear liquid
9.2	Odor:	Characteristic mild petroleum odor
9.3	Odor Threshold:	NA
9.4	pH:	NA NA
9.5	Melting Point/Freezing Point:	Pour Point: -44.0 °C
9.6	Initial Boiling Point/Boiling Range:	NA NA
9.7	Flashpoint:	> 150 °C (> 302 °F)
9.8	Upper/Lower Flammability Limits:	LEL: 0.9%; UEL: 7.0%
9.9	Vapor Pressure:	NA NA
9.10	Vapor Density:	NA NA
9.11	Relative Density:	0.8337 g/cm ³ @ 15 °C (59 °F)
9.12	Solubility:	Insoluble
9.13	Partition Coefficient (log Pow):	NA
9.14	Autoignition Temperature:	NA NA
9.15	Decomposition Temperature:	NA NA
9.16	Viscosity:	15.21 @ 40 °C SUS; 2.28 @ 100 °C
9.17	Other Information:	NA NA
		10. STABILITY & REACTIVITY
10.1	Stability:	Stable at normal temperatures.
10.2	Hazardous Decomposition Products:	Fumes, smoke, carbon monoxide, silicon oxides.
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Open flames, sparks, high heat, and close proximity to incompatible substances.
10.5	Incompatible Substances:	Strong oxidizing agents.
		11. TOXICOLOGICAL INFORMATION
11.1	Routes of Entry:	Inhalation: NO Absorption: YES Ingestion: YES
11.2	Toxicity Data:	This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product and is presented below: Based on animal testing from similar materials & products, the acute toxicity of this product is expected to be: <u>Distillates</u> , <u>Petroleum, Paraffinic</u> – LD ₅₀ (oral, rat) > 5,000 mg/kg; LD ₅₀ (dermal, rabbit) > 2,000 mg/kg.
11.3	Acute Toxicity:	Mineral oil mists derived from highly refined oils are reported to have low acute and sub-acute toxicities in animals. Effects from single and short-term repeated exposures to high concentrations of mineral oil mists well above applicable workplace exposure levels include lung inflammatory reaction, lipoid granuloma formation and lipoid pneumonia. In acute and sub-acute studies involving exposures to lower concentrations of mineral oil mists at or near current work place exposure levels produced no significant toxicological effects.
11.4	Chronic Toxicity:	NA NA
11.5	Suspected Carcinogen:	NA .
11.6	Reproductive Toxicity: Mutagenicity:	This product is not reported to produce reproductive toxicity in humans. This product is not reported to produce mutagenic effects in humans.
	Embryotoxicity:	This product is not reported to produce midragenic effects in humans.
	Teratogenicity:	This product is not reported to produce emblyotoxic effects in humans. This product is not reported to produce teratogenic effects in humans.
	Reproductive Toxicity:	This product is not reported to produce readogenic effects in humans. This product is not reported to produce reproductive effects in humans.
11.7	Irritancy of Product:	See Section 4.3
11.8	Biological Exposure Indices:	NE
11.9	Physician Recommendations:	Treat symptomatically.
		•



Page 4 of 6 HFT-61405

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 5/14/2015 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: There are no specific data available for this product. 12 2 Effects on Plants & Animals: There are no specific data available for this product. 12.3 Effects on Aquatic Life: There are no specific data available for this product. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Dispose of in accordance with federal, state, provincial and local regulations. 13.2 Special Considerations: 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): **NOT REGULATED** 14.1 14.2 IATA (AIR): **NOT REGULATED** 14.3 IMDG (OCN): **NOT REGULATED** 14.4 TDGR (Canadian GND): **NOT REGULATED** ADR/RID (EU): 14.5 **NOT REGULATED** SCT (MEXICO): 14.6 NOT REGULATED ADGR (AUS): NOT REGULATED 15. REGULATORY INFORMATION SARA Reporting 15.1 This product does not contain any substances subject to SARA Title III, section 313 reporting requirements. Requirements SARA Threshold Planning 15.2 There are no specific Threshold Planning Quantities for the components of this product. Quantity: 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory or are otherwise exempt. 15.4 CERCLA Reportable Quantity 15.5 Other Federal Requirements: None of the ingredients are listed as Hazardous Air Pollutants (HAPs). None of the ingredients are listed as Toxic Pollutants under the Clean Water Act (CWA). None of the ingredients are listed as Priority Pollutants under the Clean Water Act (CWA). This product does not contain any Class 1 or Class 2 ozone depletors. 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS D2B (Other Toxic Effects) 15.7 State Regulatory Information: No ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). 15.8 Other Requirements: The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC: <u>Distillates (Petroleum), Paraffinic</u>: Harmful (Xn). <u>Risk Phrases</u> (R): 65 – Harmful: may cause lung damage if swallowed. Safety Phrases (S): 53-45 - Avoid exposure - obtain special instructions before use. In case of accident or if you feel unwell seek medical advice immediately (show the

label where possible)



Page 5 of 6 **HFT-61405**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 5/14/2015 16. OTHER INFORMATION DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. Wash exposed skin areas thoroughly with 16.1 Other Information: soap and water after handling. Avoid eye contact. Wear protective gloves/eye protection/face protection. IF ON SKIN: Wash with soap and water. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. If skin irritation or a rash occurs - Get medical advice/attention. Store in a well-ventilated place. Keep cool. Use only as directed. KEEP OUT OF REACH OF CHILDREN. 16.2 Terms & Definitions: See last page of this Safety Data Sheet. 16.3 Disclaimer: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Harbor Freight Tools USA, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. 16.4 Prepared for: Harbor Freight Tools USA, Inc. 26541 Agoura Road **HARBOR FREIGHT TOOLS** Calabasas, CA 91302 USA Tel: +1 (805) 388-1000 http://www.harborfreight.com/ 16.5 Prepared by: ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700

http://www.shipmate.com

Page 6 of 6 HFT-61405

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 5/14/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number					
EXPOSURE	EXPOSURE LIMITS IN AIR:					
ACGIH American Conference on Governmental Industrial Hygienists						
С	C Ceiling Limit					
ES Exposure Standard (Australia)						
IDLH Immediately Dangerous to Life and Health						
OSHA U.S. Occupational Safety and Health Administration						
PEL	Permissible Exposure Limit					
STEL Short-Term Exposure Limit						
TLV Threshold Limit Value						
TWA	Time Weighted Average					

FIRST AID MEASURES:

Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body

HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:

PERSONAL PROTECTION NATINGS.					
Α					
В					
С					
D	固				
Е					
F					













Protective Clothing & Full Suit

Dust Respirator





Full Face

Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit			
mg/m3	mg/m3 milligrams per cubic meter			
NA Not Available				
ND	Not Determined			
NE	Not Established			
NF	Not Found			
NR	No Results			
ppm parts per million				
SCBA	Self-Contained Breathing Apparatus			

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:							
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition						
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source						
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source						

HAZARD RATINGS:

0	Minimal Hazard			
1	Slight Hazard			
2	Moderate Hazard			
3	Severe Hazard			
4	Extreme Hazard			
ACD	Acidic			
ALK	Alkaline			
COR	Corrosive			
₩	Use No Water			
ОХ	Oxidizer			
TREFOIL	Radioactive			



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s					
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal					
ppm	Concentration expressed in parts of material per million parts					
TD _{io}	Lowest dose to cause a symptom					
TCLo	Lowest concentration to cause a symptom					
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects					
TC, TC _o , LC _{lo} , & LC _o						
IARC	International Agency for Research on Cancer					
NTP	National Toxicology Program					
RTECS	Registry of Toxic Effects of Chemical Substances					
BCF	Bioconcentration Factor					
TL _m	Median threshold limit					
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution					

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System				
DOT	U.S. Department of Transportation				
TC	Transport Canada				
EPA	EPA U.S. Environmental Protection Agency				
DSL	Canadian Domestic Substance List				
NOHSC	NOHSC National Occupational Health and Safety Commission (Australia)				
NDSL	NDSL Canadian Non-Domestic Substance List				
PSL	Canadian Priority Substances List				
TSCA	U.S. Toxic Substance Control Act				
EU	European Union (European Union Directive 67/548/EEC)				
WGK	Wassergefährdungsklassen (German Water Hazard Class)				
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System				

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

TOTAL ENGLISHER WESTERN ENGLISHED IN THE TOTAL OF THE TENER OF THE TEN							
	((2)	(3)	\odot	(18)		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

15. To 15.		M	*			X	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\Diamond		*
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment