HARBOR FREIGHT TOOLS

Product Name:

Chemical Name:

Synonyms:

Trade Names:

Distributor's Name:

Emergency Phone:

Distributor's Address:

Business Phone / Fax:

Product Uses & Restrictions:

1.2

1.3

1.4

1.5

1.6

1.7

1.8

19

SAFETY DATA SHEET

Page 1 of 6 HFT-61525

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

+1 (805) 388-1000

SDS Revision: 1.1

SDS Revision Date: 7/25/2015

1. PRODUCT & COMPANY IDENTIFICATION
4 IN 40 GRIT METAL CUT-OFF WHEEL WITH 3/8 IN ARBOR 10 PC
Aluminum Oxide
P/N 61525
Central Pneumatics
Abrasive Wheel
Harbor Freight Tools USA, Inc.
26541 Agoura Road, Calabasas, CA 91302 USA
CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687)

2. HAZARDS IDENTIFICATION

This product is classified as a HAZARDOUS SUBSTANCE, but not as DANGEROUS GOODS Hazard Identification: according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia). WARNING! MAY CAUSE AN ALLERGIC SKIN REACTION. MAY BE HARMFUL IF INHALED. Classification: Skin Sens. 1B; Acute Tox. Inh. 5 Hazard Statements (H): H317 - May cause an allergic skin reaction. H333 - May be harmful if Precautionary Statements (P): P261 - Avoid breathing dust. P304 + P312 - IF INHALED: Call a POISON CENTER/doctor if you feel unwell. P280 - Wear protective gloves/eye protection/face protection. P302+P352 - IF ON SKIN - Wash with soap and water. P333+P313 - If skin irritation occurs: Get medical advice/attention. P501 - Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).



3. COMPOSITION & INGREDIENT INFORMATION

					EXPOSURE LIMITS IN AIR (mg/m³)								
					AC	GIH		NOHSC			OSHA		
					pp	m		ppm			ppm		
							ES-	ES-	ES-				
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA		PEAK	PEL	STEL	IDLH	OTHER
ALUMINUM OXIDE	1344-28-1	BD1200000	215-691-6	60-100	(10)	NA	NF	NF	NF	(10)	NA	NA	
ALOMINOM OXIDE	Skin Sens. 1B;	Acute Tox. Inh. 5	; H317, H333										
PHENOLIC RESIN	9003-35-4	NA	500-005-2	10-30									
PHENOLIC RESIN													
CALCIUM SULFATE DIHYDRATE	1010-41-4	EW4150000	231-900-3	1-5	NA	NA	NF	NF	NF	NA	NA	NA	·
CALCIUM SULFATE DINTURATE													

			4. FIRST AID MEASURES
4.1	First Aid:	Ingestion:	Ingestion unlikely; however, if ingested, do not induce vomiting. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
		Eyes:	If product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes lifting upper and lower lids, occasionally.
		<u>Skin</u> :	Wash thoroughly with soap and water. In case of contact, immediately flush skin with plenty of water for at least 15 minutes.
		Inhalation:	Remove victim to fresh air at once. If breathing is difficult, administer oxygen. If breathing stops give artificial respiration. Keep person warm, quiet and get medical attention.
4.2	Effects of Exposure:	Ingestion:	If product is swallowed, may cause gastrointestinal disturbance.
		Eyes:	Exposure to dust may cause eye irritation. Symptoms of overexposure may include redness, itching, irritation and watering.
		<u>Skin</u> :	May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.
		Inhalation:	Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract.
	•		

HARBOR FREIGHT TOOLS
Quality Tools at Ridiculously Low Prices

SAFETY DATA SHEET

Page 2 of 6 **HFT-61525**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 7/25/2015 4. FIRST AID MEASURES - cont'd 4.3 Symptoms of Overexposure: If product is swallowed, may cause gastrointestinal disturbance. Ingestion: Exposure to dust may cause eye irritation. Symptoms of overexposure may include redness, itching, Eyes: irritation and watering. May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in Skin: some sensitive individuals. Inhalation: Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. 4.4 Acute Health Effects Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of dust can cause coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. 4.5 Chronic Health Effects: Possible allergic dermatitis in some sensitive individuals. 4.6 Target Organs: Eyes, Skin, Lungs, Respiratory System. 4.7 Medical Conditions Pre-existing dermatitis, other skin conditions. **HEALTH** 1 Aggravated by Exposure: **FLAMMABILITY** 0 0 PHYSICAL HAZARDS PROTECTIVE EQUIPMENT В **EYES** SKIN 5. FIREFIGHTING MEASURES 5.1 Fire & Explosion Hazards: This material can burn but will not readily ignite. However, if involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO, CO2, Hydrocarbons). Burning or thermal decomposition can produce the following combustion or decomposition products: Phenol, Formaldehyde, Carbon Monoxide and/or carbon dioxide. Carbon Monoxide is highly toxic if inhaled Carbon dioxide in sufficient concentration can act as an asphyxiant. 5.2 Extinguishing Methods: CO₂, Dry Chemical, Foam. Use water spray to cool containers. 5.3 Firefighting Procedures: Keep containers cool until well after the fire is out. Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fireexposed surfaces and to protect personnel. Fight fire upwind. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen 6. ACCIDENTAL RELEASE MEASURES Before cleaning any spill individuals involved in cleanup must wear appropriate Personal Protective Equipment. Plastic Spills or rubber gloves, respirator, eye protection and apron may be required for clean-up of large spills. No special precautions are required for intact packaging containing this product. If product is crushed, use respiratory protection equipment. Do not use compressed air to clean up any residue. Use a wet method or vacuums equipped with High Efficiency Particulate (HEPA) filters to clean up any residues from this product. Waste must be placed in dust tight containers or sealed plastic bags for disposal. Label properly. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Do not eat, drink or smoke when handling this product. Wash unintentional residues with soap and warm water. 7.2 Storage & Handling Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Avoid temperatures above 120 °F. Keep away from incompatible substances. 7.3 Special Precautions: Clean all dusts and particulates promptly as they present a slip and fall hazard. 8. EXPOSURE CONTROLS & PERSONAL PROTECTION Exposure Limits: ACGIH NOHSC OSHA OTHER 8.1 ppm (ma/m³) STE STEL ES-TWA ES-STEL ES-PEAK IDLH CHEMICAL NAME(S) **ALUMINIUM OXIDE** (10) NF NF (10) NA NF NA NA 8.2 Ventilation & Engineering General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Use local or general Controls exhaust ventilation to effectively remove and prevent buildup of dusts generated from the use of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station). 8.3 Respiratory Protection: In instances where dusts are generated when using this product, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia.



Reproductive Toxicity:

Biological Exposure Indices:

Physician Recommendations:

NE

Treat symptomatically.

Irritancy of Product:

11.7

11.8

11.9

SAFETY DATA SHEET

Page 3 of 6

HFT-61525 SDS Revision: 1.1 Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 7/25/2015 8. EXPOSURE CONTROLS & PERSONAL PROTECTION 8.4 Eye Protection: Avoid eye contact. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU) 8.5 Hand Protection: Heavy-duty work gloves recommended under normal conditions of use to avoid abrasions and reduce risk of exposure to hands. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, or the EU member states. Body Protection: 8.6 No apron required under normal circumstances; however, it is recommended. Upon completion of work activities using this product), wash any exposed areas thoroughly with soap and water. If necessary, refer to appropriate standards of Canada, the EU member states, or U.S. OSHA. 9. PHYSICAL & CHEMICAL PROPERTIES Dark brown to black solid article Appearance: 9.2 Odor: Odorless 9.3 Odor Threshold: NA 9.4 NA 9.5 Melting Point/Freezing Point: 2100 °C (3812 °F) - Alumina 9.6 Initial Boiling Point/Boiling NA Range: 9.7 Flashpoint: NA 9.8 Upper/Lower Flammability NA Limits: 9.9 Vapor Pressure: NA 9.10 Vapor Density: NA 9.11 Relative Density: 2.0 9.12 Solubility: Insoluble 9.13 Partition Coefficient (log Pow): NA 9.14 Autoignition Temperature: NA 9.15 Decomposition Temperature: NA 9.16 Viscosity NA 9.17 Other Information: NA 10. STABILITY & REACTIVITY 10.1 Stability: Stable under normal conditions. 10.2 Hazardous Decomposition Oxides of carbon (CO, CO₂), metal oxides, particulates. Products: Hazardous Polymerization: 10.3 10.4 Conditions to Avoid: Open flames, high heat, incompatible substances and direct sunlight. 10.5 Incompatible Substances: Avoid extreme heat and ignition sources. Store away from oxidizers, strong acids and alkalis. 11. TOXICOLOGICAL INFORMATION Routes of Entry: Inhalation: YES 11.1 Absorption: YES Ingestion: YES 11.2 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product, but is not presented in this document. 11.3 Acute Toxicity: See Section 4.4 11.4 Chronic Toxicity: See Section 4.5 11.5 Suspected Carcinogen: Burning or thermal decomposition can produce Formaldehyde which is listed as Formaldehyde is listed as ACGIH Group A2 (Suspected human carcinogen); NIOSH (Occupational Carcinogen); NTP13 Group 2 (Reasonably Anticipated to be a Human Carcinogen); OSHA (Possible select carcinogen); CA65 (cancer). Reproductive Toxicity: 11.6 This product is not reported to produce reproductive toxicity in humans. Mutagenicity This product is not reported to produce mutagenic effects in humans. Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans.

This product is not reported to cause reproductive effects in humans.

The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.

HARBOR FREIGHT TOOLS
Quality Tools at Midiculously Low Prices

SAFETY DATA SHEET

Page 4 of 6 HFT-61525

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 7/25/2015 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: There are no specific data available for this product Effects on Plants & Animals: 122 There are no specific data available for this product 12.3 Effects on Aquatic Life: There are no specific data available for this product. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Dispose of in accordance with federal, state, provincial and local regulations. 13.2 Special Considerations: 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): **NOT REGULATED** 14.1 14.2 IATA (AIR): **NOT REGULATED** 14.3 IMDG (OCN): NOT REGULATED TDGR (Canadian GND): 14.4 **NOT REGULATED** ADR/RID (EU): 14.5 **NOT REGULATED** SCT (MEXICO): 14.6 NOT REGULATED 14.7 ADGR (AUS): NOT REGULATED 15. REGULATORY INFORMATION SARA Reporting 15.1 This product contains Aluminum Oxide, a substance subject to SARA Title III, Section 313 reporting requirements. Requirements SARA Threshold Planning 15.2 There are no specific Threshold Planning Quantities for the components of this product. Quantity: 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory or are otherwise exempt. 15.4 CERCLA Reportable Quantity Formaldehyde (thermal decomposition product) is listed as Hazardous Air Pollutants (HAPs). Formaldehyde (thermal 15.5 Other Federal Requirements: decomposition product) is listed as Toxic Pollutants under the Clean Water Act (CWA). None of the ingredients are listed as Priority Pollutants under the Clean Water Act (CWA). This product does not contain any Class 1 or Class 2 ozone depletors. 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS D2B (Other Toxic Effects). 15.7 State Regulatory Information: Alumina (Aluminum Oxide) is found on the following state criteria list: Massachusetts Hazardous Substances List (MA, Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), and Washington Permissible Exposures List (WA). Formaldehyde (thermal decomposition product) is found on the following state criteria lists: CA65, FL, MA, NJ, PA, WA No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). NOTE: This product contains a substance(s) known to the State of California to cause cancer, birth defects, or other reproductive harm. 15.8 Other Requirements: The primary components of this product are listed in Annex I of EU Directive 67/548/EEC: Harmful (Xn). Risk Phrases (R): 20-38 - Harmful if inhaled. Irritating to skin. Safety Phrases (S): 2-

23-24-62 - Keep away from children. Do not breathe dust. Avoid contact with skin. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label where

possible.

HARBOR FREIGHT TOOLS

Quality Tests at Ridiculously Low Prices

SAFETY DATA SHEET

Page 5 of 6 **HFT-61525**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 7/25/2015 16. OTHER INFORMATION Other Information: WARNING! MAY CAUSE AN ALLERGIC SKIN REACTION. MAY BE HARMFUL IF INHALED. Avoid breathing dust. IF INHALED: Call a POISON CENTER/doctor if you feel unwell. Wear protective gloves/eye protection/face protection. IF ON SKIN - Wash with soap and water. If skin irritation occurs: Get medical advice/attention. KEEP OUT OF REACH OF CHILDREN. NOTE: This product contains a substance(s) known to the State of California to cause cancer, birth defects, or other reproductive harm. 16.2 Terms & Definitions: See last page of this Safety Data Sheet. 16.3 Disclaimer: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Harbor Freight Tools USA, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. 16.4 Prepared for: Harbor Freight Tools USA, Inc. 26541 Agoura Road HARBOR FREIGHT TOOLS

Quality Tools at Ridiculously Low Prices Calabasas, CA 91302 USA Tel: +1 (805) 388-1000 http://www.harborfreight.com Prepared by: ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700

http://www.shipmate.com

SAFETY DATA SHEET

Page 6 of 6 HFT-61525

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 7/25/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number				
EXPOSURE LIMITS IN AIR:					
ACGIH	American Conference on Governmental Industrial Hygienists				
С	Ceiling Limit				
ES	Exposure Standard (Australia)				
IDLH	Immediately Dangerous to Life and Health				
OSHA	U.S. Occupational Safety and Health Administration				
PEL	Permissible Exposure Limit				
STEL	Short-Term Exposure Limit				
TLV	Threshold Limit Value				
TWA	Time Weighted Average				

FIRST AID MEASURES:

CPR Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.


HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:

1 LIV	JONALI	KOILC	IION IX	1111400.
Α				
В				
С				
D	固			
Е				
F			4	





Splash Goggle









Dust Respirator

Full Face Respirator



Full Face Respirator

Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit				
mg/m3	g/m3 milligrams per cubic meter				
NA Not Available					
ND Not Determined					
NE Not Established					
NF Not Found					
NR	No Results				
ppm	parts per million				
SCBA	Self-Contained Breathing Apparatus				

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:						
Autoignition Temperature Minimum temperature required to initiate combustion in air with no other source of ignition						
LEL Lower Explosive Limit - lowest percent of vapor in air, by volume, the explode or ignite in the presence of an ignition source						
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					

HAZARD RATINGS:

TO LES TO				
0	Minimal Hazard			
1	Slight Hazard			
2	Moderate Hazard			
3	Severe Hazard			
4	Extreme Hazard			
ACD	Acidic			
ALK	Alkaline			
COR	Corrosive			
₩	Use No Water			
ох	Oxidizer			
TREFOIL	Radioactive			



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
	S
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{io}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC _o , LC _{lo} , & LC _o	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NOHSC	National Occupational Health and Safety Commission (Australia)
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

***************************************	WORLD ENGLANDED MATERIALS IDENTIFICATION (WILLIAM) CTOTEM								
0	(3)	(②	(T)	®		R		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F		
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive		

EC (67/548/EEC) INFORMATION:

The state of the s		M	*			X	X
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\Leftrightarrow		*
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment