

Hazard Identification:

SAFETY DATA SHEET

Page 1 of 6 **HFT-61907**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 7/25/2015

| 1. PRODUCT & COMPANY IDENTIFICATION | | | | | | |
|-------------------------------------|------------------------------|--|---|--|--|--|
| 1.1 | Product Name: | SYNTHETIC TWO CYCLE ENGINE OIL 8 OZ | | | | |
| 1.2 | Chemical Name: | Synthetic Oil | | | | |
| 1.3 | Synonyms: | P/N 61907 | | | | |
| 1.4 | Trade Names: | Synthetic Two Cycle Engine Oil 8 oz. | | | | |
| 1.5 | Product Uses & Restrictions: | Lubricant | | | | |
| 1.6 | Distributor's Name: | Harbor Freight Tools USA, Inc. | | | | |
| 1.7 | Distributor's Address: | 26541 Agoura Road, Calabasas, CA 91302 USA | • | | | |
| 1.8 | Emergency Phone: | CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687) | • | | | |
| 1.9 | Business Phone / Fax: | +1 (805) 388-1000 | | | | |

2. HAZARDS IDENTIFICATION

This product is classified as a HAZARDOUS SUBSTANCE but not as DANGEROUS GOODS

according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia).

DANGER! MAY CAUSE CANCER. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

Classification: Carc. 1B; Asp. Tox. 1; Aquatic Chronic 1

Hazard Statements (H): H351 – May cause cancer. H304 – May be fatal if swallowed and enters airways.

Precautionary Statements (P): P201 – Obtain special instruction before use. P202 – Do not handle until all safety precautions have been read and understood. P280 – Wear protective gloves/eye protection. P301+P310 – IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331 – Do NOT induce vomiting. P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. P308+P313 – IF exposed of concerned: Get medical attention. P405 – Store locked up. P501 – Dispose of contents/ container to an approved waste disposal plant.



3. COMPOSITION & INGREDIENT INFORMATION

| | | | | | | | | EXPC | SURE L | IMITS IN | N AIR (m | g/m³) | |
|--------------------------|------------------|----------------------|-------------------|------------|---------|-------|------------|---------------------|-------------|----------|----------|-------|-------|
| I | | | | | AC | GIH | | NOHSC | | | OSHA | | |
| | | | | | pp | m | | ppm | | | ppm | | |
| CHEMICAL NAME(S) | CAS No. | RTECS No. | EINECS No. | % | TLV | STEL | ES- TWA | ES- STEL | ES- PEAK | PEL | STEL | IDLH | OTHER |
| SYNTHETIC BASE OILS | NA | NA | NA | 50-60 | (5) | NA | (5) | NF | NF | (5) | (10) | NA | MIST |
| STIVINE TIC BASE OILS | | | | | | | | | | | | | |
| DISTILLATES (PETROLEUM), | 64741-86-2 | NA | 265-088-7 | 20-30 | (5) | NA | (5) | NF | NF | (5) | (10) | NA | MIST |
| SWEETENED MIDDLE | Carc. 1B; H35 | 50 | | | | | | | | | | | |
| POLYBUTENE | 9003-29-6 | EM9032000 | 500-004-7 | 10-20 | NA | NA | NF | NF | NF | NA | NA | NA | |
| POLTBUTENE | Asp. Tox. 1; S | Skin Irrit. 2; H304, | H315 | | | | | | | | | | |
| PROPRIETARY ADDITIVES | NA | NA | NA | 5-15 | NA | NA | NF | NF | NF | NA | NA | NA | |
| PROPRIETARY ADDITIVES | | | | | | | | | | | | | |
| p-DODECYLPHENOL | 74499-35-7 | NA | NA | 0.0-1.0 | NA | NA | NF | NF | NF | NA | NA | NA | |
| p-DODECTEPHENOL | Skin Irrit. 2; E | ye Irrit. 2; Repr. 2 | ; Auatic Acute 1; | Aquatic Ch | ronic1; | H315, | H319, F | 1 361, ⊦ | 1400, H | 410 | | | |
| | | | | | | | | | | | | | |

| | | | 4. FIRST AID MEASURES |
|-----|---------------------------|--------------------------------|---|
| 4.1 | First Aid: | Ingestion: | DO NOT INDUCE VOMITING. Contact ChemTrec at +1 (703) 527-3887 or the nearest Poison Control Center or local emergency telephone number for assistance and instructions. Seek immediate medical attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration. |
| | | Eyes: | If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 minutes, holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately. |
| | | Skin: | Remove contaminated clothing and wash affected areas with soap and water. If irritation persists, seek prompt medical attention. Do not wear contaminated clothing until after it has been properly cleaned. |
| | | Inhalation: | Remove victim to fresh air at once. If breathing is difficult, administer supplemental oxygen and seek immediate medical attention. If breathing stops, perform artificial respiration. |
| 4.2 | Effects of Exposure: | Ingestion: | If product is swallowed, may cause nausea, vomiting and/or diarrhea. |
| | | <u>Eyes</u> : <u>Skin</u> : | May cause transient mild-eye irritation with short-term contact with liquid, spray or mist. This product can cause mild, transient skin irritation with short-term exposure. This product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. |
| | | Inhalation: | No significant adverse health effects are expected to occur upon short-term exposure to this product. Aspiration of liquid into the lungs can cause severe lung damage or death. |
| 4.3 | Symptoms of Overexposure: | Eyes: | Overexposure in eyes may cause redness, itching and watering. |
| | | Skin: | Symptoms of skin overexposure may include redness, itching, and irritation of affected areas The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. |



Page 2 of 6 HFT-61907

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 7/25/2015 4. FIRST AID MEASURES - cont'd 44 Acute Health Effects: Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea 4.5 Chronic Health Effects Contains a petroleum-based mineral oil. Prolonged or repeated skin contact can cause mild irritation and inflammation characterized by drying, cracking, (dermatitis) or oil acne. Repeated or prolonged inhalation of petroleum-based mineral oil mists at concentrations above applicable workplace exposure levels can cause respiratory irritation or other pulmonary 4.6 Target Organs: Eyes, Skin, Respiratory System. 4.7 Medical Conditions Pre-existing dermatitis, other skin conditions, and disorders of the **HEALTH** Aggravated by Exposure target organs (eyes, skin, and respiratory system). **FLAMMABILITY** 1 **PHYSICAL HAZARDS** 0 PROTECTIVE EQUIPMENT В **EYES** SKIN 5. FIREFIGHTING MEASURES Fire & Explosion Hazards: This material can burn but will not readily ignite. This material will release vapors when heated above the flash point temperature that can ignite when exposed to a source of ignition. In enclosed spaces, heated vapor can ignite with explosive force. Mists or sprays may burn at temperatures below the flash point. Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and trace oxides of sulfur, phosphorus, zinc and nitrogen. Also, depending upon the conditions of use, low concentrations of hydrogen sulfide can be released. 5.2 Extinguishing Methods: Dry Chemical, Foam, Carbon Dioxide, Water Fog. 5.3 Firefighting Procedures: Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Avoid spraying water directly into storage containers because of danger of boil over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies 6. ACCIDENTAL RELEASE MEASURES Spills Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Use normal hygiene practices. Avoid breathing vapors. Avoid direct skin contact. Wash hands thoroughly after using this product and before eating, drinking, or smoking. 7.2 Storage & Handling: Use and store in a cool, dry, well-ventilated area. Keep away from excessive heat, open flames, sparks, and other possible sources of ignition. Do not store in unmarked containers or storage devices. Recommended maximum shelf life: 36 months. 7.3 Special Precautions: Empty containers may contain product residue. Do not pressurize, cut, heat or weld empty containers. Do not reuse empty containers without commercial cleaning or reconditioning. 8. EXPOSURE CONTROLS & PERSONAL PROTECTION NOHSC OTHER 8.1 Exposure Limits: **ACGIH OSHA** ppm (mg/m³) CHEMICAL NAME(S) TLV STEL **ES-TWA ES-STEL ES-PEAK** PEL STEL IDLH SYNTHETIC BASE OILS MIST (5) NA (5) NF NF (5) (10)NA DISTILLATES (PETROLEUM). NA (5) NF NF (5) (10)NA MIST (5) SWEETENED MIDDLE 8.2 Ventilation & Engineering The use of mechanical dilution ventilation is recommended to maintain airborne concentrations below the recommended occupational exposure limits, whenever this material is used in a confined space, is heated above normal temperatures (up to 38 °C) or is agitated.



11.4

11.5

Chronic Toxicity:

Suspected Carcinogen:

SAFETY DATA SHEET

Page 3 of 6

HFT-61907 Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 7/25/2015 8. EXPOSURE CONTROLS & PERSONAL PROTECTION – cont'd 8.3 Respiratory Protection: Vaporization or misting is not expected at ambient temperatures. Therefore, the need for respiratory protection is not anticipated under normal use conditions and with adequate ventilation. If elevated airborne concentrations above applicable workplace exposure levels are anticipated, a NIOSHapproved organic vapor respirator equipped with a dust/mist pre-filter should be used. Protection factors vary depending upon the type of respirator used. Respirators should be used in accordance with OSHA requirements (29 CFR 1910.134). Eye Protection: Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this 8.4 product. Always use protective eyewear when cleaning spills or leaks. Wear goggles and/or face shield if splashing or spraying is anticipated. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants. Have suitable eye wash water available. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 8.5 Hand Protection Use gloves constructed of chemical-resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, or the EU member states. 8.6 Body Protection: Avoid prolonged and/or repeated skin contact. Use clean and impervious protective clothing (e.g., neoprene or Tyvek®) if splashing or spraying conditions are present. Protective clothing should include long-sleeves, apron. boots and additional facial protection. If necessary, refer to appropriate standards of Canada, the EU member states, or U.S. OSHA. 9. PHYSICAL & CHEMICAL PROPERTIES 9 1 Appearance: Amber liquid 9.2 Characteristic mild petroleum odor 9.3 Odor Threshold: NA 9.4 NA Melting Point/Freezing Point NA Initial Boiling Point/Boiling 9.6 NA 9.7 Flashpoint: 93.3 °C (200.1 °F) 9.8 Upper/Lower Flammability NA Limits: 9.9 Vapor Pressure: NA 9 10 Vapor Density Heavier than air 9.11 Relative Density: NA 9.12 Solubility: Insoluble Partition Coefficient (log Pow): 9.13 NA **Autoignition Temperature** 9.14 NA 9.15 Decomposition Temperature NA Viscosity NA Other Information: 9.17 NA 10. STABILITY & REACTIVITY 10.1 Stability Stable at normal temperatures. 10.2 Hazardous Decomposition Fumes, smoke, carbon monoxide, silicon oxides. Products: Hazardous Polymerization: 10.3 Will not occur. 10.4 Conditions to Avoid Open flames, sparks, high heat, and close proximity to incompatible substances 10.5 Incompatible Substances Strong oxidizing agents. 11. TOXICOLOGICAL INFORMATION Absorption: YES Routes of Entry 11.2 Toxicity Data: Based on animal testing from similar materials & products, the acute toxicity of this product is expected to be: Petroleum Oils - LD₅₀ (oral, rat) > $\overline{5}$,000 mg/kg; LD₅₀ (dermal, rabbit) > 2,000 mg/kg; LD₅₀ (inhalation, rat) > $\overline{5}$,000 mg/m3. 11.3 Acute Toxicity: Mineral oil mists derived from highly refined oils are reported to have low acute and sub-acute toxicities in animals. Effects from single and short-term repeated exposures to high concentrations of mineral oil mists well above applicable workplace exposure levels include lung inflammatory reaction, lipoid granuloma formation and lipoid pneumonia. In acute and sub-acute studies involving exposures to lower concentrations of mineral oil mists at or near current work place

exposure levels produced no significant toxicological effects.

See Section 4.5

NA



Page 4 of 6 **HFT-61907**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 7/25/2015 11. TOXICOLOGICAL INFORMATION – cont'd 11.6 Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans. Mutagenicity This product is not reported to produce mutagenic effects in humans. Embryotoxicity This product is not reported to produce embryotoxic effects in humans Teratogenicity: This product is not reported to produce teratogenic effects in humans. Reproductive Toxicity: This product is not reported to produce reproductive effects in humans. 11.7 Irritancy of Product: The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. 11.8 Biological Exposure Indices ΝE Physician Recommendations: Treat symptomatically. Careful gastric lavage or emesis may be considered to evacuate large quantities of material. Subcutaneous or intramuscular injection requires prompt surgical debridement. 12. ECOLOGICAL INFORMATION There are no specific data available for this product 12.1 **Environmental Stability** 12.2 Effects on Plants & Animals: There are no specific data available for this product 12.3 Effects on Aquatic Life: There are no specific data available for this product 13. DISPOSAL CONSIDERATIONS Waste Disposal: 13.1 Dispose of in accordance with federal, state, provincial and local regulations. 13.2 Special Considerations NA 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): **NOT REGULATED** 14.2 IATA (AIR): NOT REGULATED 14.3 IMDG (OCN): **NOT REGULATED** TDGR (Canadian GND): 14.4 **NOT REGULATED** ADR/RID (EU): 14.5 **NOT REGULATED** SCT (MEXICO): 14.6 **NOT REGULATED** ADGR (AUS): 14.7 **NOT REGULATED** 15. REGULATORY INFORMATION 15.1 SARA Reporting This product does not contain any substances subject to SARA Title III, Section 313 reporting requirements. Requirements 15.2 SARA Threshold Planning There are no specific Threshold Planning Quantities for the components of this product. Quantity: 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory or are otherwise exempt. 15.4 CERCLA Reportable Quantity NA (RQ) None of the ingredients are listed as Hazardous Air Pollutants (HAPs). None of the ingredients are listed as Toxic 15.5 Other Federal Requirements: Pollutants under the Clean Water Act (CWA). None of the ingredients are listed as Priority Pollutants under the Clean Water Act (CWA). This product does not contain any Class 1 or Class 2 ozone depletors. Other Canadian Regulations: 15.6 This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS D2B (Other Toxic Effects) 15.7 State Regulatory Information: No ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). 15.8 Other Requirements: The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC: Distillates (Petroleum), Sweetened Middle: Toxic (T). Risk Phrases (R): 45 - May cause cancer. Safety Phrases (S): 53-45 - Avoid exposure - obtain special instructions before use. In case of

accident or if you feel unwell seek medical advice immediately (show the label where possible)



Page 5 of 6 **HFT-61907**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 7/25/2015 16. OTHER INFORMATION DANGER! MAY CAUSE CANCER. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. VERY TOXIC TO 16 1 Other Information: AQUATIC LIFE WITH LONG LASTING EFFECTS. Obtain special instruction before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/eye protection. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. IF exposed of concerned: Get medical attention. Store locked up. KEEP OUT OF REACH OF CHILDREN. 16.2 Terms & Definitions: See last page of this Safety Data Sheet 16.3 Disclaimer: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Harbor Freight Tools USA, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. 16.4 Prepared for: Harbor Freight Tools USA, Inc. 26541 Agoura Road **HARBOR FREIGHT TOOLS** Calabasas, CA 91302 USA **Quality Tools at Ridiculously Low Prices** Tel: +1 (805) 388-1000 http://www.harborfreight.com 16.5 Prepared by: ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700

http://www.shipmate.com

Page 6 of 6 HFT-61907

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 7/25/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

| CAS No. | Chemical Abstract Service Number |
|---------|----------------------------------|

EXPOSURE LIMITS IN AIR:

| ACGIH | American Conference on Governmental Industrial Hygienists |
|----------------------------------|---|
| С | Ceiling Limit |
| ES Exposure Standard (Australia) | |
| IDLH | Immediately Dangerous to Life and Health |
| OSHA | U.S. Occupational Safety and Health Administration |
| PEL | Permissible Exposure Limit |
| STEL | Short-Term Exposure Limit |
| TLV Threshold Limit Value | |
| TWA | Time Weighted Average |

FIRST AID MEASURES:


| CPR | Cardiopulmonary resuscitation - method in which a person whose heart has |
|-----|---|
| | stopped receives manual chest compressions and breathing to circulate blood |
| | and provide oxygen to the body. |


HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

| 0 | Minimal Hazard | | | |
|---|-----------------|--|--|--|
| 1 | Slight Hazard | | | |
| 2 | Moderate Hazard | | | |
| 3 | Severe Hazard | | | |
| 4 | Extreme Hazard | | | |



PERSONAL PROTECTION RATINGS:

























Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


| ML | Maximum Limit |
|---|----------------------------|
| mg/m3 | milligrams per cubic meter |
| NA Not Available | |
| ND | Not Determined |
| NE Not Established | |
| NF | Not Found |
| NR | No Results |
| ppm parts per million | |
| SCBA Self-Contained Breathing Apparatus | |

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

| FLAMMABILITY LIMITS IN AIR: | | | | | |
|-----------------------------|---|--|--|--|--|
| | Minimum temperature required to initiate combustion in air with no other | | | | |
| Temperature | source of ignition | | | | |
| LEL | Lower Explosive Limit - lowest percent of vapor in air, by volume, that will | | | | |
| | explode or ignite in the presence of an ignition source | | | | |
| UEL | Upper Explosive Limit - highest percent of vapor in air, by volume, that will | | | | |
| | explode or ignite in the presence of an ignition source | | | | |

HAZARD RATINGS:

| 0 | Minimal Hazard |
|---------|-----------------|
| 1 | Slight Hazard |
| 2 | Moderate Hazard |
| 3 | Severe Hazard |
| 4 | Extreme Hazard |
| ACD | Acidic |
| ALK | Alkaline |
| COR | Corrosive |
| ₩ | Use No Water |
| ОХ | Oxidizer |
| TREFOIL | Radioactive |



TOXICOLOGICAL INFORMATION:

| LD ₅₀ | Lethal Dose (solids & liquids) which kills 50% of the exposed animals |
|--|---|
| | S |
| LC ₅₀ | Lethal concentration (gases) which kills 50% of the exposed animal |
| ppm | Concentration expressed in parts of material per million parts |
| TD _{Io} | Lowest dose to cause a symptom |
| TCLo | Lowest concentration to cause a symptom |
| TD _{Io} , LD _{Io} , & LD _o or | Lowest dose (or concentration) to cause lethal or toxic effects |
| TC, TC _o , LC _{lo} , & LC _o | |
| IARC | International Agency for Research on Cancer |
| NTP | National Toxicology Program |
| RTECS | Registry of Toxic Effects of Chemical Substances |
| BCF | Bioconcentration Factor |
| TL _m | Median threshold limit |
| log K _{ow} or log K _{oc} | Coefficient of Oil/Water Distribution |

REGULATORY INFORMATION:

| WHMIS | Canadian Workplace Hazardous Material Information System | | | |
|----------|---|--|--|--|
| DOT | U.S. Department of Transportation | | | |
| TC | TC Transport Canada | | | |
| EPA | EPA U.S. Environmental Protection Agency | | | |
| DSL | Canadian Domestic Substance List | | | |
| NOHSC | NOHSC National Occupational Health and Safety Commission (Australia) | | | |
| NDSL | NDSL Canadian Non-Domestic Substance List | | | |
| PSL | PSL Canadian Priority Substances List | | | |
| TSCA | U.S. Toxic Substance Control Act | | | |
| EU | EU European Union (European Union Directive 67/548/EEC) | | | |
| WGK | Wassergefährdungsklassen (German Water Hazard Class) | | | |
| HMIS-III | National Paint & Coatings Association Hazardous Materials Identification System | | | |

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

| 0 | * | (A) | | \odot | ® | (F) | R |
|------------|-----------|------------|----------|------------|------------|-----------|----------|
| Class A | Class B | Class C | Class D1 | Class D2 | Class D3 | Class E | Class F |
| Compressed | Flammable | Oxidizing | Toxic | Irritation | Infectious | Corrosive | Reactive |

EC (67/548/EEC) INFORMATION:

| FU FU | | M | * | | | X | X |
|-----------|-----------|-----------|---------|-----------|-------|----------|---------|
| С | Е | F | N | 0 | Т | Xi | Xn |
| Corrosive | Explosive | Flammable | Harmful | Oxidizing | Toxic | Irritant | Harmful |

CLP/GHS (1272/2008/EC) PICTOGRAMS:

| | | ® | \Diamond | | | | | * |
|-----------|-----------|----------|-------------|-----------|-------|-----------------------|------------------|------------------|
| GHS01 | GHS02 | GHS03 | GHS04 | GHS05 | GHS06 | GHS07 | GHS08 | GHS09 |
| Explosive | Flammable | Oxidizer | Pressurized | Corrosive | Toxic | Harmful Irritating | Health Hazard | Environ- ment |