HARBOR FREIGHT TOOLS

Quality Tools at Ridiculously Low Prices

Product Name:

Chemical Name:

Synonyms

Trade Names

Distributor's Name

Emergency Phone:

Distributor's Address:

Business Phone / Fax:

Product Uses & Restrictions:

1.1

12

1.3

1.4

1.5

1.6

1.7

1.8

1.9

SAFETY DATA SHEET

Page 1 of 6 **HFT-62226**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

+1 (805) 388-1000

SDS Revision: 1.0

SDS Revision Date: 4/30/2015

1. PRODUCT & COMPANY IDENTIFICATION
HI-TECH YELLOW LIQUID WAX
NA
P/N 62226
Meguiars [®]
Premium, high-gloss automotive wax.
Harbor Freight Tools USA, Inc.
26541 Agoura Road, Calabasas, CA 91302 USA

2. HAZARDS IDENTIFICATION

CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687)

2.1 Hazard Identification: This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia).

DANGER! MAY BE HARMFUL IF SWALLOWED AND ENTERS AIRWAYS. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES EYE IRRITATION.

Classification: Asp. Tox. 1; Skin Sens. 1B; Eye Irrit. 2B

<u>Hazard Statements</u> (H): H304 – May be fatal if swallowed and enters airways. H317 – May cause an allergic skin reaction. H320 – Causes eye irritation.

Precautionary Statements (P): P210 – Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. P261 – Avoid breathing fume/mist/vapors/spray. P272 – Contaminated work clothing should not be allowed out of the workplace. P264 – Wash thoroughly with soap and water after handling. P280 – Wear protective gloves/protective clothing/ eye protection/ face protection. P301+P310 – IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331 – Do NOT induce vomiting. P302+P352 – IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse with water or shower. P333 + P313 – If skin irritation or rash occurs: get medical advice/attention. P321 – Specific treatment: see Section 4 of this Safety Data Sheet. P362+ P364 – Take off contaminated clothing and was before reuse. P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 – If eye irritation persists: Get medical advice/attention. P403+P235 – Store in a well-ventilated place. Keep cool. P405 – Store locked up. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).



3. COMPOSITION & INGREDIENT INFORMATION

		JIVII OSIII	1	1								. 3.	
					—				SURE L	IMITS IN		g/m°)	
					AC	GIH		NOHSC			OSHA		
					p	om		ppm			ppm		
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	OTHER
AOUA (MATER/EAU)	7732-18-5	ZC0110000	231-791-2	50-70	NA	NA	NF	NF	NF	NA	NA	NA	
AQUA (WATER/EAU)													
NAPTHA, PETROLEUM	64742-48-9	NA	265-150-3	10-30	NA	5	NF	NF	NF	NA	5	10	OIL MIST
HYDROTREATED HEAVY	Carc. 1B; Mut	a. 1B; Asp. Tox.	1; H350, H340, H	304									
ALIPHATIC PETROLEUM	64742-47-8	OA5504000	265-149-8	3-7	(5)	NA	NF	NF	NF	(5)	NA	NA	MIST
DISTILLATES	Asp. Tox.1; SI	Asp. Tox.1; Skin Sens. 1B; Eye Irrit. 2B; Acute Aq. Tox. 3; H305, H317, H320, H402											
DOLLY/DILASTINA OU OVANIS	63148-62-9	JT6484500	213-915-7	1-5	NA	NA	NF	NF	NF	NA	NA	NA	
POLY(DIMETHYLSILOXANE)													
DISTILLATES, PETROLEUM,	64742-46-7	NA	264-148-2	1-5	NA	5	NF	NF	NF	NA	5	10	OIL MIST
HYDROTREATED MIDDLE	Carc. 1B; H350												
MEGUIARS™ CONDITIONERS -	NA	NA	NA	1-5	NA	NA	NF	NF	NF	NA	NA	NA	
PROPIETARY													
CALCINED OLAY	66402-68-4	NA	266-340-9	1-5	NA	NA	NF	NF	NF	NA	NA	NA	
CALCINED CLAY	Eye Dam. 1; E	Eve Dam. 1: Eve Irrit. 2: H318.H319											
ODODI ECC MINEDAL ODIDITO	8052-41-3	WJ8925000	232-489-3	0.1-1	100	NA	NF	790	NF	500	NA	20000	(350) NIOSH
ODORLESS MINERAL SPIRITS	Flam. Liq. 3; A	sp. Tox. 1; Eye I	rrit. 2; Aquatic To	x. 1; H226	, H304,	H340,	H350						•
NAPHTHA (PETROLEUM),	64742-82-1	NA	265-185-4	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA	
HYDRODESULFURIZED HEAVY	Carc. 1B; Mut	a. 1B; Asp. Tox.	1; H350, H340. H	304									

HARBOR FREIGHT TOOLS

SAFETY DATA SHEET

Page 2 of 6 **HFT-62226**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 4/30/2015 4. FIRST AID MEASURES DO NOT INDUCE VOMITING. Contact ChemTrec at +1 (703) 527-3887 or the nearest Poison Control 4 1 First Aid: Ingestion: Center or local emergency telephone number for assistance and instructions. Seek immediate medical attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration. Flush eyes thoroughly with copious amounts of water for at least 15 minutes, holding eyelid(s) open to Eyes: ensure complete flushing. If irritation persists, seek immediate medical attention. Remove contaminated clothing and wash affected areas with soap and water. If irritation persists, seek Skin: prompt medical attention. Do not wear contaminated clothing until after it has been properly cleaned. Remove victim to fresh air at once. If breathing is difficult, administer supplemental oxygen and seek Inhalation: immediate medical attention. If breathing stops, perform artificial respiration. 4.2 Effects of Exposure: If product is swallowed, may cause nausea, vomiting and/or diarrhea. Ingestion: This product can cause transient mild eye irritation with short-term contact with liquid sprays or mists. Eyes: Skin: This product can cause mild, transient skin irritation with short-term exposure. Exposure may cause respiratory tract irritation in some sensitive individuals Inhalation: 4.3 Symptoms of Overexposure Overexposure in eyes may cause redness, itching and watering (risk of serious damage to eyes). Eyes: Contact may cause serious eye irritation including stinging, watering, redness. Prolonged contact with skin may result in bleaching and irritation of skin. The product can cause allergic Skin: skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals. Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. 4.4 Acute Health Effects: Moderate irritation to eyes. Moderate irritation to skin near affected areas. Acute health hazards may be delayed. Most common symptoms include irritating properties to eyes, respiratory system and skin. 4.5 Chronic Health Effects No harmful or chronic health effects are expected to occur from a single accidental ingestion. These ingredients may be irritating to skin and mucous membrane of the eye and respiratory system. Overexposure may trigger asthma-like symptoms in some sensitive individuals. May also induce skin sensitization and respiratory hypersensitivity. Possible allergic dermatitis. Target Organs 4.6 Eyes, Skin, Respiratory System, Central Nervous System (CNS), Kidneys Medical Conditions 4.7 Pre-existing dermatitis, other skin conditions, and disorders of the **HEALTH** 1 Aggravated by Exposure: target organs (eyes, skin) or impaired kidney function may be more **FLAMMABILITY** 0 susceptible to the effects of this substance. PHYSICAL HAZARDS 0 PROTECTIVE EQUIPMENT X **EYES** LUNGS SKIN 5. FIREFIGHTING MEASURES 5.1 Fire & Explosion Hazards: Will not burn, but decomposition, which may be caused by heat, will release oxygen which will increase the explosive limit range and burning rate of flammable vapors. As a result of combustion and thermal decomposition, oxidation products may form and exposure to such products may result in health hazards 5.2 Extinguishing Methods: Foam, CO₂, Water Fog or Dry Chemical 5.3 Firefighting Procedures: Fight fires as for surrounding materials. Firefighters should wear a MSHA/NIOSH approved or equivalent self-contained breathing apparatus (SCBA) and protective clothing. Fire should be fought from a safe distance. Keep containers cool until well after the fire is out. Cool containers with water spray to prevent pressure build-up, auto-ignition or explosion. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. 6. ACCIDENTAL RELEASE MEASURES Spills: Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water.

HARBOR FREIGHT TOOLS

Quality Tools at Ridiculously Low Prices

SAFETY DATA SHEET

Page 3 of 6 **HFT-62226**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 4/30/2015 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Use normal hygiene practices. Avoid direct skin contact. Wash hands thoroughly after using this product and before eating, drinking, or smoking. Good personal hygiene practices, such as washing any skin contact areas and removing contaminated clothing, are recommended. 7.2 Storage & Handling: Keep away from sources of heat 7.3 Special Precautions: Follow all instructions on product label. Keep container closed when not in use. Keep this and all chemicals out of reach of children. 8. EXPOSURE CONTROLS & PERSONAL PROTECTION Exposure Limits: NOHSC OSHA OTHER ES-PEAK ppm (mg/m³) CHEMICAL NAME(S) TI V STEL ES-STEL PEL STFI IDLH NAPTHA, PETROLEUM OIL MIST NA NF NF NF NA 10 5 HYDROTREATED HEAVY ALIPHATIC PETROLEUM (5) NA NF NF NF (5) NA NA MIST **DISTILLATES** DISTILLATES, PETROLEUM. NA 5 NF NF NF NA 5 10 OIL MIST HYDROTREATED MIDDLE **ODORLESS MINERAL SPIRITS** 100 NA NF 790 NF 500 20000 (350) NIOSH 8.2 Ventilation & Engineering General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Use local or general Controls exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station) 8.3 Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. In instances where mist or vapors of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia. 8.4 Eye Protection: Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Wear goggles and/or face shield if splashing or spraying is anticipated. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants. Have suitable eye wash water available. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). 8.5 Hand Protection: Use gloves constructed of chemical-resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, or the EU member states. 8.6 Body Protection: Avoid prolonged and/or repeated skin contact. Use clean and impervious protective clothing (e.g., neoprene or Tyvek®) if splashing or spraying conditions are present. Protective clothing should include long-sleeves, apron, boots and additional facial protection. If necessary, refer to appropriate standards of Canada, the EU 9. PHYSICAL & CHEMICAL PROPERTIES Light yellow lotion. 9.1 Appearance: 9.2 Banana fragrance. 9.3 Odor Threshold: NA 9.4 pH: 7.5-8.5 9.5 Melting Point/Freezing Point: NA 9.6 Initial Boiling Point/Boiling 198.8 °C (390 °F) Range: 9.7 Flashpoint > 93.3 °C (200 °F) PMCC 9.8 Upper/Lower Flammability NA 9.9 Vapor Pressure: NA 9.10 Vapor Density NA 9.11 Relative Density: 0.95 9.12 Solubility: Moderate 9.13 Partition Coefficient (log Pow): NA 9.14 Autoignition Temperature: NA 9.15 Decomposition Temperature: NA Viscosity: 9.16 NA Other Information: 9.17 VOC: 543.59 g/L; 14.97%

HARBOR FREIGHT TOOLS

Quality Tools at Ridiculously Low Prices

SAFETY DATA SHEET

Page 4 of 6 **HFT-62226**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 4/30/2015 10. STABILITY & REACTIVITY 10.1 Stability Stable under normal conditions of use Hazardous Decomposition 10.2 During combustion may produce irritant vapors and gases (formaldehyde, carbon monoxide, carbon dioxide). **Products** 10.3 Hazardous Polymerization: Will not occur. 10.4 Conditions to Avoid: Strong oxidizers. 10.5 Incompatible Substances: Strong oxidizing agents, strong acids and bases 11. TOXICOLOGICAL INFORMATION Ingestion: YES 11.1 Routes of Entry: Inhalation: YES Absorption: YES 112 Toxicity Data: This product has not been tested on animals to obtain toxicological data. There are toxicology data for the components of this product, which are found in the scientific literature. This data has not been presented in this document. This product is neither a primary eye nor primary skin irritant per Federal Hazardous Substances Act (FHSA) regulations. Odorless Mineral Spirits: LD₅₀ (oral, rat): 5,000 mg/kg. Naphtha (Petroleum): LD₅₀ (oral, rat): > 5,000 mg/kg, OECD 401 11.3 Acute Toxicity See section 4.5 11.4 Chronic Toxicity See section 4.6 11.5 Suspected Carcinogen No. Reproductive Toxicity: 11.6 This product is not reported to produce reproductive toxicity in humans Mutagenicity: This product is not reported to produce mutagenic effects in humans Embryotoxicity This product is not reported to produce embryotoxic effects in humans. Teratogenicity This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. 11.7 Irritancy of Product: The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. 11.8 Biological Exposure Indices: ΝE 11.9 Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION **Environmental Stability** There are no specific data available for this product 12.1 122 Effects on Plants & Animals There are no specific data available for this product. 12.3 Effects on Aquatic Life Naphtha (Petroleum): EC₅₀ (Daphnia Magna, 48h): > 100 mg/L 13. DISPOSAL CONSIDERATIONS Waste Disposal: Dispose of in accordance with federal, state, provincial and local regulations. 13.1 13.2 Special Considerations: 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 14.1 49 CFR (GND): **NOT REGULATED** 14.2 IATA (AIR)*: **NOT REGULATED** IMDG (OCN): 14.3 **NOT REGULATED** TDGR (Canadian GND): 14.4 NOT REGULATED 14.5 ADR/RID (EU): **NOT REGULATED** 14.6 SCT (MEXICO): NOT REGULATED ADGR (AUS): NOT REGULATED 15. REGULATORY INFORMATION 15.1 SARA Reporting This product does not contain any substances subject to SARA Title III, section 313 reporting requirements. Requirements 15.2 SARA Threshold Planning There are no specific Threshold Planning Quantities for the components of this product. Quantity 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory or are otherwise exempt. 15.4 **CERCLA Reportable Quantity** NA 15.5 Other Federal Requirements NA 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS D2B (Other Toxic Effects).

HARBOR FREIGHT TOOLS

Quality Teols at Ridiculously Low Prices

SAFETY DATA SHEET

Page 5 of 6 **HFT-62226**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 4/30/2015

		45 DEOLU ATODY NEO	DIATION (III
	1	15. REGULATORY INFO	
15.7	State Regulatory Information:	Jersey Right-to-Know List (NJ), and Pennsylvania No other ingredients in this product, present in a criteria lists: California Proposition 65 (CA65), L List (FL), Massachusetts Hazardous Substances Substances List (MN), New Jersey Right-to-Know	ate criteria lists: Massachusetts Hazardous Substances List (MA), New Right-to-Know List (PA). Concentration of 1.0% or greater, are listed on any of the following state Delaware Air Quality Management List (DE), Florida Toxic Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous W List (NJ), New York Hazardous Substances List (NY), Pennsylvania Exposures List (WA), Wisconsin Hazardous Substances List (WI).
15.8	Other Requirements:	cancer. May cause inheritable genetic damage. Safety Phrases (S): 53-45 – Avoid exposure – caccident or if you feel unwell seek medical advice Petroleum Distillate: Flammable, Harmful (F, Xn), may cause lung damage if swallowed. Safety Ph Do not breathe gas, fumes, vapor or spray. Avo vomiting: seek medical advice immediately and Flammable aerosol. Colorless, volatile liquid with may cause dizziness and loss of concentration arrhythmia may result from exposure. Vapors dispaces. Odorless Mineral Spirits: Flammable (F). Risk may cause lung damage if swallowed. Safety	(T). Risk Phrases (R): 45-46-65 – May cause Harmful may cause lung damage if swallowed. bbtain special instructions before use. In case of
			·
16.1	Other Information:	EYE IRRITATION. Use only as directed. At thoroughly with soap and water after handling. WIF ON SKIN: Wash with soap and water. IF It contact lenses if present and easy to do – or	AY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS void breathing fume/ mist/vapors/spray. Wash exposed skin areas /ear protective gloves/protective clothing/eye protection/face protection. YEYES: Rinse continuously with water for several minutes. Remove continue rinsing. If skin irritation or a rash occurs — Get medical fore reuse. Store in a well-ventilated place. Keep cool. KEEP OUT
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	government regulations must be reviewed for ap Tools USA, Inc.'s knowledge, the information accuracy, suitability or completeness is not guara provided. The information contained herein rela	SHA's Hazard Communication Standard, 29 CFR §1910.1200. Other plicability to this product. To the best of ShipMate's & Harbor Freight contained herein is reliable and accurate as of this date; however, anteed and no warranties of any type, either expressed or implied, are tes only to the specific product(s). If this product(s) is combined with be considered. Data may be changed from time to time. Be sure to
16.4	Prepared for:	Harbor Freight Tools USA, Inc. 26541 Agoura Road Calabasas, CA 91302 USA Tel: +1 (805) 388-1000 http://www.harborfreight.com	HARBOR FREIGHT TOOLS Quality Tools at Ridiculously Low Prices
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com	

SAFETY DATA SHEET

Page 6 of 6 HFT-62226

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision Date: 4/30/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number				
EXPOSURE	EXPOSURE LIMITS IN AIR:				
ACGIH	American Conference on Governmental Industrial Hygienists				
С	Ceiling Limit				
ES	Exposure Standard (Australia)				
IDLH	Immediately Dangerous to Life and Health				
OSHA	U.S. Occupational Safety and Health Administration				
PEL	Permissible Exposure Limit				
STEL	Short-Term Exposure Limit				
TLV	Threshold Limit Value				
TWA	Time Weighted Average				

FIRST AID MEASURES:

CPR Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body

HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:

Α		
В		
С		
D		
Е		
F		





Cy Face Shield & Protective Eyewear









Full Face Respirator



Dust & Vapor Half-

Full Face

Airline Hood/Mask or SCBA

Mask Respirator OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit			
mg/m3	milligrams per cubic meter			
NA Not Available				
ND	Not Determined			
NE	NE Not Established			
NF	Not Found			
NR	No Results			
ppm parts per million				
SCBA	Self-Contained Breathing Apparatus			

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:					
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition				
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source				
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source				

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
₩	Use No Water
ОХ	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{io}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC _o , LC _{lo} , & LC _o	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NOHSC	National Occupational Health and Safety Commission (Australia)
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

***********	WORKE ENGLISHED COO MINTERNALO IDENTIFICATION (WITHING) CTOTEMI								
	((2)	(3)	\odot	(18)				
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F		
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive		

EC (67/548/EEC) INFORMATION:

15. To 15.		M	*			X	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\Diamond		*
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment