
SAFETY DATA SHEET

Page 1 of 6 HFT-62231



SAFETY DATA SHEET

Page 2 of 6 HFT-62231

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 12/24/2015 4. FIRST AID MEASURES – cont'd 42 Effects of Exposure: If product is swallowed, may cause gastrointestinal disturbance. Ingestion: Exposure to dust may cause eye irritation. Symptoms of overexposure may include redness, itching, Eyes: irritation and watering. May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in Skin: some sensitive individuals. Inhalation: Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. Drowsiness, dizziness, headaches and nausea. 4.3 Symptoms of Overexposure: If product is swallowed, may cause gastrointestinal disturbance. Ingestion: Eyes: Exposure to dust may cause eye irritation. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in Skin: some sensitive individuals. Inhalation: Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. 44 Acute Health Effects: Non-irritating when used as directed. Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of dust can cause coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. Chronic Health Effects: 4.5 Non-irritating when used as directed. Possible allergic dermatitis in some sensitive individuals. 46 Target Organs: Eyes, Skin, Respiratory System, Central Nervous System (CNS). Medical Conditions 47 Pre-existing dermatitis, other skin conditions, and disorders of the HEALTH 2 Aggravated by Exposure: target organs (eyes, skin) or impaired kidney function may be more FLAMMABILITY 3 susceptible to the effects of this substance. PHYSICAL HAZARDS 0 **PROTECTIVE EQUIPMENT** Х LUNGS EYES SKIN 5. FIREFIGHTING MEASURES Fire & Explosion Hazards: 5.1 Level 3 Aerosol (NFPA 30B). Aerosols may burst at temperatures above 120 °F. Cool uninvolved containers to prevent possible bursting. Aerosols may be projectile hazards when bursting. If aerosols are bursting, stay clear until bursting is complete. Do not use in presence of open flames or sparks. Do not place in hot water or near radiators, stoves or other sources of heat. Exposure to heat or sunlight may cause cans to burst and propel contents. Water from fog nozzles may be helpful in cooling un-ruptured containers to prevent build-up. Water Fog, Foam, Dry Chemical, CO₂ 5.2 Extinguishing Methods: As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) Firefighting Procedures 5.3 and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES 6.1 Spills Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For large spills (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Do not eat, drink or smoke when handling this product. Handle as to avoid puncturing container(s). Wash unintentional residues with soap and warm water. Keep tightly closed when not in use. Avoid contact with skin and clothing 72 Storage & Handling: Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Avoid temperatures above 120 °F. Keep away from incompatible substances. Protect containers from physical damage. Avoid breathing vapor. 7.3 Special Precautions: Clean all spills promptly. Spilled material may present a slipping hazard

SAFETY DATA SHEET

Page 3 of 6 HFT-62231

		8. EXPOSURE CONT	ROL	.S & P	ERSC	DNAL F	PROT	ЕСТ	ION				
.1	Exposure Limits:			GIH		NOHSC			OSHA		OTHER		
	ppm (mg/m ³)	CHEMICAL NAME(S)	TLV	STEL	ES- TWA	ES-STEL	ES- PEAK	PEL	STEL	IDLH			
		ALIPHATIC PETROLEUM									MICT		
		DISTILLATES	(5)	NA	NF	NF	NF	(5)	NA	NA	MIST		
			(5)	NA	(5)	NF	NF	(5)	10	NA	MIST		
		(MIXTURE) LVP ALIPHATIC HYDROCARBON	(5)	NA	NF	NF	NF	(5)	NA	NA	MIST		
		CARBON DIOXIDE	5000	30000	5000	9000	NF	5000	30000	40000			
.2	Ventilation & Engineering	General mechanical (e.g., fans)	or natu	iral venti	lation is	sufficient	when th	nis prod	uct is in	use. U	se local or gene		
	Controls: exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the l product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash												
0	D D										ash station).		
.3	Respiratory Protection:	No special respiratory protection											
		instances where mist or vapors use only protection authorized	by 29 (CFR 819	re genera 10 134	ateo, ano i applicable	US S	State re	aulations	or the			
		Canadian CAS Standard Z94.4-											
		States, or Australia.							, -				
.4	Eye Protection:	Wear protective eyewear (e.g.,											
		product. Always use protective											
		shield if splashing or spraying is											
		absorb and concentrate irritants.											
		protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).											
.5	Hand Protection:		ical-res	istant ma	aterials su	uch as ne	oprene	or heav	y nitrile	rubber if			
		frequent or prolonged contact is	Use gloves constructed of chemical-resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the										
		appropriate standards of Canada											
.6	Body Protection:	Avoid prolonged and/or repeate	d skin o	ontact. L	Jse clear	n and imp	ervious	protecti	ve clothi	ng (e.g.,			
neoprene or Tyvek [®]) if splashing or spraying conditions are present. Protective clothing													
		include long-sleeves, apron, boo	ts and a	additiona	l facial pr	otection. I							
			ts and a	additiona	l facial pr	otection. I							
		include long-sleeves, apron, boo standards of Canada, the EU me	ts and a mber st	additiona ates, or l	l facial pr J.S. OSH	otection. I	f neces	sary, re					
.1	Appearance:	include long-sleeves, apron, boo	ts and a mber st	additiona ates, or l	l facial pr J.S. OSH	otection. I	f neces	sary, re					
	Appearance: Odor:	include long-sleeves, apron, boo standards of Canada, the EU me 9. PHYSICAL	ts and a mber st	additiona ates, or l	l facial pr J.S. OSH	otection. I	f neces	sary, re					
.2		include long-sleeves, apron, boo standards of Canada, the EU me 9. PHYSICAL Aerosol. Light amber liquid.	ts and a mber st	additiona ates, or l	l facial pr J.S. OSH	otection. I	f neces	sary, re					
.2 .3	Odor:	include long-sleeves, apron, boo standards of Canada, the EU me 9. PHYSICAL Aerosol. Light amber liquid. Mild petroleum odor.	ts and a mber st	additiona ates, or l	l facial pr J.S. OSH	otection. I	f neces	sary, re					
.2 .3 .4	Odor: Odor Threshold:	include long-sleeves, apron, boo standards of Canada, the EU me 9. PHYSICAL Aerosol. Light amber liquid. Mild petroleum odor. NA	ts and a mber st	additiona ates, or l	l facial pr J.S. OSH	otection. I	f neces	sary, re					
.2 .3 .4 .5	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling	include long-sleeves, apron, boo standards of Canada, the EU me 9. PHYSICAL Aerosol. Light amber liquid. Mild petroleum odor. NA NA	ts and a mber st	additiona ates, or l	l facial pr J.S. OSH	otection. I	f neces	sary, re					
.2 .3 .4 .5 .6	Odor: Odor Threshold: pH: Melting Point/Freezing Point:	include long-sleeves, apron, boo standards of Canada, the EU me 9. PHYSICAL Aerosol. Light amber liquid. Mild petroleum odor. NA NA NA 183-187 °C (361-369 °F)	ts and a mber st	additiona ates, or l	l facial pr J.S. OSH	otection. I	f neces	sary, re					
.2 .3 .4 .5 .6 .7	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range:	include long-sleeves, apron, boo standards of Canada, the EU me 9. PHYSICAL Aerosol. Light amber liquid. Mild petroleum odor. NA NA NA NA 183-187 °C (361-369 °F) 59 °C (138 °F) CC (for liquid)	ts and a mber st	additiona ates, or l HEMIC	l facial pr J.S. OSH	otection. I	f neces	sary, re					
.2 .3 .4 .5 .6 .7 .8	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits:	include long-sleeves, apron, boo standards of Canada, the EU me 9. PHYSICAL Aerosol. Light amber liquid. Mild petroleum odor. NA NA NA 183-187 °C (361-369 °F) 59 °C (138 °F) CC (for liquid) UEL 8.0%; LEL 0.6% (for solvent	ts and a mber st	additiona ates, or l HEMIC	l facial pr J.S. OSH	otection. I	f neces	sary, re					
.2 .3 .4 .5 .6 .7 .8 .9	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure:	include long-sleeves, apron, boo standards of Canada, the EU me 9. PHYSICAL Aerosol. Light amber liquid. Mild petroleum odor. NA NA NA 183-187 °C (361-369 °F) 59 °C (138 °F) CC (for liquid) UEL 8.0%; LEL 0.6% (for solvent 95-115 PSI @ 70 °F	ts and a mber st	additiona ates, or l HEMIC	l facial pr J.S. OSH	otection. I	f neces	sary, re					
.2 .3 .4 .5 .6 .7 .8 .9 .10	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density:	include long-sleeves, apron, boo standards of Canada, the EU me 9. PHYSICAL Aerosol. Light amber liquid. Mild petroleum odor. NA NA NA 183-187 °C (361-369 °F) 59 °C (138 °F) CC (for liquid) UEL 8.0%; LEL 0.6% (for solvent 95-115 PSI @ 70 °F > 1	ts and a mber st	additiona ates, or l HEMIC	l facial pr J.S. OSH	otection. I	f neces	sary, re					
.2 .3 .4 .5 .6 .7 .8 .9 .10 .11	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density:	include long-sleeves, apron, boo standards of Canada, the EU me 9. PHYSICAL Aerosol. Light amber liquid. Mild petroleum odor. NA NA NA 183-187 °C (361-369 °F) 59 °C (138 °F) CC (for liquid) UEL 8.0%; LEL 0.6% (for solvent 95-115 PSI @ 70 °F > 1 0.8-0.82 @ 60 °F	ts and a mber st	additiona ates, or l HEMIC	l facial pr J.S. OSH	otection. I	f neces	sary, re					
.2 .3 .4 .5 .6 .7 .8 .9 .10 .11 .12	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility:	include long-sleeves, apron, boo standards of Canada, the EU me 9. PHYSICAL Aerosol. Light amber liquid. Mild petroleum odor. NA NA NA 183-187 °C (361-369 °F) 59 °C (138 °F) CC (for liquid) UEL 8.0%; LEL 0.6% (for solvent 95-115 PSI @ 70 °F > 1 0.8-0.82 @ 60 °F Insoluble	ts and a mber st	additiona ates, or l HEMIC	l facial pr J.S. OSH	otection. I	f neces	sary, re					
.2 .3 .4 .5 .6 .7 .8 .9 .10 .11 .12 .13	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log P _{ow}):	include long-sleeves, apron, boo standards of Canada, the EU me 9. PHYSICAL Aerosol. Light amber liquid. Mild petroleum odor. NA NA NA 183-187 °C (361-369 °F) 59 °C (138 °F) CC (for liquid) UEL 8.0%; LEL 0.6% (for solvent 95-115 PSI @ 70 °F > 1 0.8-0.82 @ 60 °F Insoluble NA	ts and a mber st	additiona ates, or l HEMIC	l facial pr J.S. OSH	otection. I	f neces	sary, re					
	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log P _{ow}): Autoignition Temperature:	include long-sleeves, apron, boo standards of Canada, the EU me 9. PHYSICAL Aerosol. Light amber liquid. Mild petroleum odor. NA NA NA 183-187 °C (361-369 °F) 59 °C (138 °F) CC (for liquid) UEL 8.0%; LEL 0.6% (for solvent 95-115 PSI @ 70 °F > 1 0.8-0.82 @ 60 °F Insoluble NA NA	ts and a mber st	additiona ates, or l HEMIC	l facial pr J.S. OSH	otection. I	f neces	sary, re					
.2 .3 .4 .5 .6 .7 .7 .8 .9 .10 .11 .12 .13 .14 .15	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log P _{ow}): Autoignition Temperature: Decomposition Temperature:	include long-sleeves, apron, boo standards of Canada, the EU me 9. PHYSICAL Aerosol. Light amber liquid. Mild petroleum odor. NA NA NA 183-187 °C (361-369 °F) 59 °C (138 °F) CC (for liquid) UEL 8.0%; LEL 0.6% (for solvent 95-115 PSI @ 70 °F > 1 0.8-0.82 @ 60 °F Insoluble NA NA NA NA	ts and a mber st	additiona ates, or l HEMIC	l facial pr J.S. OSH	otection. I	f neces	sary, re					
.2 .3 .4 .5 .6 .7 .8 .9 .10 .11 .12 .13 .14 .15 .16	Odor: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log P _{ow}): Autoignition Temperature: Decomposition Temperature: Viscosity:	include long-sleeves, apron, boo standards of Canada, the EU me 9. PHYSICAL Aerosol. Light amber liquid. Mild petroleum odor. NA NA 183-187 °C (361-369 °F) 59 °C (138 °F) CC (for liquid) UEL 8.0%; LEL 0.6% (for solvent 95-115 PSI @ 70 °F > 1 0.8-0.82 @ 60 °F Insoluble NA NA NA NA NA NA	ts and a mber st & CI	additiona ates, or l HEMI(l facial pr J.S. OSH	otection. I	f neces	sary, re					
2 3 4 5 6 7 8 9 10 11 12 13 14 15 16	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log P _{ow}): Autoignition Temperature: Decomposition Temperature:	include long-sleeves, apron, boo standards of Canada, the EU me 9. PHYSICAL Aerosol. Light amber liquid. Mild petroleum odor. NA NA NA 183-187 °C (361-369 °F) 59 °C (138 °F) CC (for liquid) UEL 8.0%; LEL 0.6% (for solvent 95-115 PSI @ 70 °F > 1 0.8-0.82 @ 60 °F Insoluble NA NA NA NA	ts and a mber st & CI	additiona ates, or l HEMI(l facial pr J.S. OSH	otection. I	f neces	sary, re					
.2 .3 .4 .5 .5 .6 .7 .8 .9 .10 .11 .12 .13 .14 .15 .16	Odor: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log P _{ow}): Autoignition Temperature: Decomposition Temperature: Viscosity:	include long-sleeves, apron, boo standards of Canada, the EU me 9. PHYSICAL Aerosol. Light amber liquid. Mild petroleum odor. NA NA NA 183-187 °C (361-369 °F) 59 °C (138 °F) CC (for liquid) UEL 8.0%; LEL 0.6% (for solvent 95-115 PSI @ 70 °F > 1 0.8-0.82 @ 60 °F Insoluble NA NA NA NA NA NA NA NA	ts and a mber st & CI	additiona ates, or l HEMI()) 0-75%	I facial pr J.S. OSH	rotection. I	RTIE	sary, re					
.2 .3 .4 .5 .6 .7 .8 .9 .10 .11 .12 .13 .14 .15 .16 .17	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log P _{ow}): Autoignition Temperature: Decomposition Temperature: Viscosity: Other Information:	include long-sleeves, apron, boo standards of Canada, the EU me 9. PHYSICAL Aerosol. Light amber liquid. Mild petroleum odor. NA NA NA NA 183-187 °C (361-369 °F) 59 °C (138 °F) CC (for liquid) UEL 8.0%; LEL 0.6% (for solvent 95-115 PSI @ 70 °F > 1 0.8-0.82 @ 60 °F Insoluble NA NA NA NA NA NA NA NA NA NA	ts and a mber st & CI	additiona ates, or l HEMI()) 0-75% TY & I	REAC		RTIE	sary, re					
.2 .3 .4 .5 .6 .7 .8 .9 .10 .11 .12 .13 .14 .15 .16 .17	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log P _{ow}): Autoignition Temperature: Decomposition Temperature: Viscosity: Other Information: Stability:	include long-sleeves, apron, boo standards of Canada, the EU me 9. PHYSICAL Aerosol. Light amber liquid. Mild petroleum odor. NA NA NA 183-187 °C (361-369 °F) 59 °C (138 °F) CC (for liquid) UEL 8.0%; LEL 0.6% (for solvent 95-115 PSI @ 70 °F > 1 0.8-0.82 @ 60 °F Insoluble NA NA NA NA NA NA NA NA NA NA	ts and a mber st & CI	additiona ates, or l HEMI()) 0-75% TY & I	REAC	TIVITY amination.	RTIE	S	fer to app				
.2 .3 .4 .5 .6 .7 .8 .9 .10 .11 .12 .13 .14 .15 .16 .17 .0.1	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log P _{ow}): Autoignition Temperature: Decomposition Temperature: Viscosity: Other Information:	include long-sleeves, apron, boo standards of Canada, the EU me 9. PHYSICAL Aerosol. Light amber liquid. Mild petroleum odor. NA NA NA 183-187 °C (361-369 °F) 59 °C (138 °F) CC (for liquid) UEL 8.0%; LEL 0.6% (for solvent 95-115 PSI @ 70 °F > 1 0.8-0.82 @ 60 °F Insoluble NA NA NA NA NA NA NA NA NA NA	ts and a mber st & CI	additiona ates, or l HEMI()) 0-75% TY & I	REAC	TIVITY amination.	RTIE	S	fer to app				
2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 0.1 0.2	Odor: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log P _{ow}): Autoignition Temperature: Decomposition Temperature: Viscosity: Other Information: Stability: Hazardous Decomposition Products:	include long-sleeves, apron, boo standards of Canada, the EU me 9. PHYSICAL Aerosol. Light amber liquid. Mild petroleum odor. NA NA NA 183-187 °C (361-369 °F) 59 °C (138 °F) CC (for liquid) UEL 8.0%; LEL 0.6% (for solvent 95-115 PSI @ 70 °F > 1 0.8-0.82 @ 60 °F Insoluble NA NA NA NA NA NA NA NA NA Stable under normal conditions; I Change in color signifies expos Discard solution.	ts and a mber st & CI	additiona ates, or l HEMI()) 0-75% TY & I	REAC	TIVITY amination.	RTIE	S	fer to app				
.2 .3 .4 .5 .6 .7 .8 .9 .10 .11 .12 .13 .14 .15 .16 .17	Odor: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log P _{ow}): Autoignition Temperature: Decomposition Temperature: Viscosity: Other Information: Stability: Hazardous Decomposition	include long-sleeves, apron, boo standards of Canada, the EU me 9. PHYSICAL Aerosol. Light amber liquid. Mild petroleum odor. NA NA NA 183-187 °C (361-369 °F) 59 °C (138 °F) CC (for liquid) UEL 8.0%; LEL 0.6% (for solvent 95-115 PSI @ 70 °F > 1 0.8-0.82 @ 60 °F Insoluble NA NA NA NA NA NA NA NA NA NA	ts and a mber st & CI	Additiona ates, or l HEMIC)) 0-75% TY & I e with hea ultraviolet	REAC	TIVITY amination.	RTIE	S ife. Wi	fer to app				

SAFETY DATA SHEET

Page 4 of 6 HFT-62231

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 12/24/2015

		11. TOXICOLOGICAL INFORMATION										
11.1	Routes of Entry:	Inhalation: YES Absorption: YES Ingestion: YES										
11.2	Toxicity Data:	This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific litera available for some of the components of the product, but is not presented in this document.										
1.3	Acute Toxicity:	Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can drowsiness, dizziness, headaches and nausea.	cause									
1.4	Chronic Toxicity:	This material may aggravate any pre-existing skin condition (e.g., dermatitis).										
1.5	Suspected Carcinogen:	No.										
1.6	Reproductive Toxicity:	This product is not reported to produce reproductive toxicity in humans.										
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.										
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.										
	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.										
	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.										
1.7	Irritancy of Product:	The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposur	re.									
1.8	Biological Exposure Indices:	NE										
1.9	Physician Recommendations:	Treat symptomatically.										
	-	12. ECOLOGICAL INFORMATION										
2.1	Environmental Stability:	There is no specific data available for this product.										
12.2	Effects on Plants & Animals:	There are no specific data available for this product.										
12.3	Effects on Aquatic Life:	$\frac{\text{Aliphatic Petroleum Distillates}: EC_{50} \text{ (Algae, 72h) > 100 mg/L; } LC_{50} \text{ (Daphnia Magna, 48h) > 100 mg/L; } LC_{50} (Fisle of the second $	sh, 96									
		13. DISPOSAL CONSIDERATIONS										
3.1	Waste Disposal:	Dispose of in accordance with federal, state, provincial and local regulations.										
3.2	Special Considerations:	NA										
desc	criptive information may be	14. TRANSPORTATION INFORMATION mber, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Ad be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.	ditiona									
14.1	49 CFR (GND):	CONSUMER COMMODITY, ORM-D (≤ 1.0 L) – until 12/31/20 UN1950, AEROSOLS, 2.1 (LTD QTY, IP ≤ 1.0 L)										
4.2	IATA (AIR):	CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) UN1950, AEROSOLS, FLAMMABLE, 2.1 (> 1.0 L)	n 🆑									
4.3	IMDG (OCN):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP \leq 1.0 L)										
4.4	TDGR (Canadian GND):	MARK PACKAGE ("LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" ≤ 1.0 L) or UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP ≤ 1.0 L)										
4.5	ADR/RID (EU):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP \leq 1.0 L)										
4.6	SCT (MEXICO):	UN1950, AEROSOLES, 2.1 (CANTIDAD LIMITADA, IP \leq 1.0 L)										
4 7	ADGR (AUS):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP \leq 1.0 L)										
4.7												
	D-40™ does not test aero	osol cans to assure they meet pressure requirements for transportation by air.										
* W[-	15. REGULATORY INFORMATION										
* W[SARA Reporting Requirements:											
* W[5.1 5.2	SARA Reporting Requirements: SARA Threshold Planning Quantity:	15. REGULATORY INFORMATION This product does not contain any substances subject to SARA Title III, Section 313 reporting requirements. There are no specific Threshold Planning Quantities for the components of this product.										
* W[5.1 5.2 5.3	SARA Reporting Requirements: SARA Threshold Planning Quantity: TSCA Inventory Status:	15. REGULATORY INFORMATION This product does not contain any substances subject to SARA Title III, Section 313 reporting requirements.										
* W[5.1 5.2 5.3	SARA Reporting Requirements: SARA Threshold Planning Quantity: TSCA Inventory Status: CERCLA Reportable Quantity	15. REGULATORY INFORMATION This product does not contain any substances subject to SARA Title III, Section 313 reporting requirements. There are no specific Threshold Planning Quantities for the components of this product.										
14.7 * W[15.1 15.2 15.3 15.4 15.5	SARA Reporting Requirements: SARA Threshold Planning Quantity: TSCA Inventory Status:	15. REGULATORY INFORMATION This product does not contain any substances subject to SARA Title III, Section 313 reporting requirements. There are no specific Threshold Planning Quantities for the components of this product. The components of this product are listed on the TSCA Inventory or are otherwise exempt.										

SAFETY DATA SHEET

Page 5 of 6 **HFT-62231**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 12/24/2015 **15. REGULATORY INFORMATION** 15.7 State Regulatory Information: Carbon Dioxide can be found on the following state criteria lists: FL, MA, MN, PA and WA. No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). 15.8 Other Requirements: The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC: Flammable, Harmful (F, Xn). Risk Phrases (R): 10-20 - Flammable. Harmful by inhalation. Safety Phrases (S): 2-23-24-62 - Keep away from children. Do not breathe fumes/spray. Avoid contact with skin. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label where possible. **16. OTHER INFORMATION** DANGER! EXTREMELY FLAMMABLE AEROSOL. PRESSURIZED CONTAINER MAY BURST IF HEATED. 16.1 Other Information HARMFUL IF SWALLOWED. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION. Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °F (122 °F). Wash thoroughly with soap and water after handling. Do not eat, drink or smoke when using this product. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice/attention. KEEP OUT OF REACH OF CHILDREN. Terms & Definitions 16.2 See last page of this Safety Data Sheet. 16.3 Disclaimer: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Harbor Freight Tools USA. Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. 16.4 Prepared for: Harbor Freight Tools USA, Inc. 26541 Agoura Road HARBOR FREIGHT TOOLS Calabasas, CA 91302 USA Tel: +1 (805) 388-1000 http://www.harborfreight.com 16.5 Prepared by: ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com

SAFETY DATA SHEET

Page 6 of 6 HFT-62231

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 12/24/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No. Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:							
ACGIH	American Conference on Governmental Industrial Hygienists						
C Ceiling Limit							
ES	Exposure Standard (Australia)						
IDLH	Immediately Dangerous to Life and Health						
OSHA	U.S. Occupational Safety and Health Administration						
PEL	Permissible Exposure Limit						
STEL	Short-Term Exposure Limit						
TLV	Threshold Limit Value						
TWA	Time Weighted Average						
FIRST AID M	EASURES:						

FIRST AID MEASURES

CPR Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.

HMIS	HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:								
0	Minimal Hazard		HEALTH						
1	Slight Hazard		FLAMMABILITY						
2	Moderate Hazard		PHYSICAL HAZARDS						
3	Severe Hazard		PERSONAL PROTECTION						
4	Extreme Hazard								

PERSONAL PROTECTION RATINGS:

ppm parts per million

FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature

> LEL UEL

SCBA Self-Contained Breathing Apparatus
NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

source of ignition

Α						G					
в						н			品		
С	0		E.			I	0)	
D	B		E.			J					
Е						к	3				
F			Ę.			х			ipervisor g directio	or SOPs fo ns.	
Sa	fety Glasse	es	Splash	Goggles	F	Face Shield & Protective Eyewear			Gloves		
	Boots		Syntheti	c Apron	F		tive Cloth	ing	Dust Re	spirator	
			8	3					?		
1	Full Face Respirator OTHER STANDARD ABBREVIATIONS						ull Face spirator		Airline Hood/Mask or SCBA		
				ATIONS) :						
<u> </u>	ML Maximum Limit mg/m3 milligrams per cubic meter										
	NA	Not Av									
<u> </u>	ND		etermined								
	NE		tablished								
	NF	Not Fo	und								
	NR	No Re	sults								

Minimum temperature required to initiate combustion in air with no other

Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

Upper Explosive Limit - highest percent of vapor in air, by volume, that will

explode or ignite in the presence of an ignition source

HAZARD	RATINGS										
	0 Minimal	Hazard									
	1 Slight H	azard									
	2 Moderat	te Hazard			X	1	/				
	3 Severe	Hazard			\wedge						
	4 Extreme	e Hazard			1	2					
ACI	D Acidic					<u> </u>	/				
ALI	K Alkaline										
CO	R Corrosiv	/e			/ <u> </u>	₩ /					
v	Use No	Water		HE	EALTH	X					
0	X Oxidizer	r	SPECIAL								
TREFO	L Radioad	tive	PRECAUTIO								
тохісоі		NFORMAT	ION:								
			Dose (solids	& liquids) wh	iich kills 50%	of the expos	sed animals				
	LC	C ₅₀ Lethal	concentration	(gases) whi	ch kills 50% d	of the expose	d animal				
			ntration expre			-					
			dose to caus								
	тс		concentratio								
TD	LD _{io} , & LD _o		dose (or con			l or toxic effe	inte				
	LD _{io} , & LD _o C _o , LC _{io} , & L		. uuse (UI UUI	เออาแลแบบ) แ	o cause letild		0.0				
70, 10			tional Agency	/ for Researc	h on Cancer						
			al Toxicology								
	RTE		y of Toxic Eff		nical Substan	1005					
			centration Fa		แอละ อนมรเสท	650					
			threshold lin	-							
-	K _{ow} or log K		ient of Oil/Wa	ater Distributi	on						
		ORMATIO									
WHMI			e Hazardous I		mation Syste	m					
DO	T U.S. De	partment of	Transportatio	1							
T	C Transpo	ort Canada									
EP/	U.S. En	vironmental I	Protection Ag	ency							
DS	L Canadia	an Domestic	Substance Li	st							
NOHS	C National	I Occupation	al Health and	Safety Com	mission (Aus	tralia)					
NDS			estic Substan	-							
PS	L Canadia	an Priority Su	bstances List	t							
TSC			Substance Control Act								
E			ropean Unior		/548/EEC)						
WG			klassen (Gerr		,						
HMIS-I			tings Associa				1 Svstem				
			MATERIAL				-				
\bigcirc	۲	٨	$\textcircled{\begin{subarray}{c} \end{subarray}}$	()	۲		Ŕ				
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F				
Compressed	Flammable	Oxidizing	Dxidizing Toxic Irritation Infectious Corrosive Reactive								
EC (67/54	8/EEC) IN	FORMATI	ON:	I	I						
		N	Ł	8	.	×	×				
С	E	F	Ν	0	т	Xi	Xn				
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful				
CLP/GHS	(1272/200	08/EC) PIC	TOGRAMS	3:							

			\Diamond			\diamond		
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment