

Page 1 of 5 **HFT-65198** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 7/25/2015 1. PRODUCT & COMPANY IDENTIFICATION 1.1 Product Name: **RED MARKING CRAYONS 6 PC** 1.2 Chemical Name: Paraffin Wax 1.3 Synonyms P/N 65198 1.4 Trade Names: Pittsburgh 1.5 Product Uses & Restrictions: Marking for Wood and Metal 1.6 Distributor's Name Harbor Freight Tools USA, Inc. 1.7 Distributor's Address: 26541 Agoura Road, Calabasas, CA 91302 USA 1.8 Emergency Phone: CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687) 1.9 Business Phone / Fax +1 (805) 388-1000 2. HAZARDS IDENTIFICATION Hazard Identification: This product is not classified as a HAZARDOUS SUBSTANCE or as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (1999) and ADG Code (Australia). WARNING! MAY BE HARMFUL IF SWALLOWED. Classification: Acute Tox.5 Hazard Statements (H): H303 - May be harmful if swallowed. Precautionary Statements (P): P312 - Call a POISON CENTER/doctor if you feel unwell. 3. COMPOSITION & INGREDIENT INFORMATION EXPOSURE LIMITS IN AIR (mg/m3) ACGIH NOHSC **OSHA** ppm ppm ppm ES-ES-ES-STEL CHEMICAL NAME(S) CAS No. RTECS No. EINECS No. TLV TWA PEAK STEL IDLH OTHER STEL 8002-74-2 NA NA FUME RV0350000 40-70 (2) NA NF NF (5) 232-315-6 NF PARAFFIN WAX 238-877-9 2.5 14807-96-6 WW2710000 10-30 2 NF NF NΑ 1000 NA 2 TALC 9002-88-4 TQ3325000 NA 7-13 NA NA NF NF NF NA NA NA POLYETHYLENE POLYMER WITH EICOSYL 2-27029-57-8 NA NA 3-7 NA NA NF NF NF NA NA NA PROPENOATE AND OCTADECYL 2-PROPENOATE NA 4531-49-1 224-867-1 0.0-5.0 NA NA NF NF NF NA NA NA PIGMENT YELLOW 6410-26-0 NA 229-096-4 0.0-5.0 NA NA NF NF NF NA NA NA PIGMENT RED 4. FIRST AID MEASURES 4.1 First Aid: If ingested, do not induce vomiting. Contact the nearest Poison Control Center or local emergency Ingestion: number. Provide an estimate of the time and amount of the substance that was swallowed. If product is in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Open and Eyes: close eyelid(s) to ensure thorough irrigation. If problem persists, consult a physician. Skin: If redness, dryness or other signs of irritation to the skin develop, wash affected skin areas with plenty of warm water and soap. If irritation persists, consult a physician. Inhalation: Remove victim to fresh air at once. 42 Effects of Exposure: If product is swallowed, may cause nausea, vomiting and/or diarrhea. Ingestion: Unlikely however dust may cause irritation. Eves: May be irritating to skin in some sensitive individuals. Skin: Inhalation is unlikely; however, vapors of this product may be slightly irritating to some sensitive individuals Inhalation: 4.3 Symptoms of Overexposure: Symptoms of overexposure may include redness, itching, and irritation. Acute Health Effects: None reported by the manufacturer. Redness, itching, and irritation of skin at the site of contact for some sensitive 4.4 individuals. Chronic Health Effects: May be harmful if swallowed 4.5 4.6 Target Organs: None reported by the manufacturer 4.7 Medical Conditions None reported by the manufacturer HEALTH 1 Aggravated by Exposure: **FLAMMABILITY** 0 **PHYSICAL HAZARDS** 0 PROTECTIVE EQUIPMENT Α **EYES** 



Page 2 of 5 **HFT-65198** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 7/25/2015

	1		FIREFIGE								
5.1	Fire & Explosion Hazards:	This product is non-flammable. When exposed to high temperatures, may produce hazardous decomposition products such as oxides of carbon (e.g., CO, CO <sub>2</sub> ) and nitrogen (e.g., NO <sub>x</sub> ) and smoke.									
5.2	Extinguishing Methods:	Water, Foam, CO <sub>2</sub> , Dry Chemical									
5.3	Firefighting Procedures:	equipment and MSHA/l runoff water from entering	First responders should wear eye protection. Structural fire fighters must wear full protective equipment and MSHA/NIOSH-approved self-contained breathing apparatus. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas. If necessary, rinse contaminated equipment with soapy water before returning to service.								
		necessary, mise contain	milated equipme	it with 30a	by water be	JOIC ICIU	iriirig to sc	TVICC.		l .	
		6. ACC	IDENTAL	RELEA	SE ME	ASUF	RES				
6.1	Spills:	Before cleaning any s Equipment. For small recovery or disposal. K	spills or large s	<u>pills</u> : use a	appropriate	material	to put the	e spilled	solid in	suitable	container fo
		7 HAND	DLING & S		E INEC	JDMV.	TION				
7.1	Work & Hygiene Practices:	Avoid contact to eyes, use. Do not smoke, ear tobacco products, gum	skin, and muco t, drink, chew gu	us membra m or tobac	nes. Avoid	l inhalation	on of dust	he workir	ng area.	Do not	store or bring
		industrial hygiene practi									
7.2	Storage & Handling:	Keep Cool. Store in a identity labels. Preferre Keep away from incomp	d storage is a s	heltered co	ool area wit						
7.3	Special Precautions:	Read and understand the excessive heat. Store in	ne manufacturer	s instructio	ns and the						
		8. EXPOSURE	CONTROL	S & DE	DSON	AI DE	OTEC	TION			
8.1	Exposure Limits:	6. EXPOSURE	CONTROL	ACGIH	KSUN	NOHSC	OIEC	HON	OSHA		OTHER
0.1	ppm (mg/m <sup>3</sup> )			ACCIII					OULIA		OTTLEK
						ES-	ES-				
		CHEMICAL NAME(S) PARAFFIN WAX	TLV (2)	STEL NA	ES-TWA NF	STEL NF	ES- PEAK NF	<b>PEL</b> (5)	STEL NA	IDLH NA	FUME
8.2	Ventilation & Engineering Controls:	PARAFFIN WAX TALC General mechanical (e. exhaust ventilation to e	.g., fans) or nat	NA NA ural ventilare and pre	NF NF tion is suff vent buildu	STEL NF 2.5 icient whip of vap	PEAK NF NF en this pr ors or mis	(5) 2 oduct is st genera	NA NA in use. ted from	NA 1000 Use loo the ha	cal or genera
8.2	Ventilation & Engineering	PARAFFIN WAX TALC General mechanical (e. exhaust ventilation to e. product. Ensure appropriate to the product of the product o	.g., fans) or nateffectively removariate decontaming. In instance use only protected adian CAS Standard (2)	NA NA ural ventila e and pre nation equi s where di ion author	NF NF tion is suff vent buildu pment is av ust of this ized by 29	NF 2.5 icient while product of CFR §	PEAK NF NF en this pr ors or mis e.g., sink, s are gene	(5) 2 oduct is st genera safety sho rated, an applicable	NA NA in use. ted from ower, eye d respira	NA 1000 Use loo the had-wash satory State	cal or genera
	Ventilation & Engineering Controls:	PARAFFIN WAX TALC General mechanical (e. exhaust ventilation to e product. Ensure appropriate in the product of	.g., fans) or nateffectively removeriate decontaming. In instance use only protected adian CAS Standaustralia.	NA NA NA ural ventila e and pre nation equi s where di ion author lard Z94.4-	NF NF tion is suffivent buildupment is avust of this ized by 29 93 and appare equipment	STEL NF 2.5 icient while por vapidable (expression of the product	PEAK NF NF en this pr ors or mis e.g., sink, s are gene 1910.134, tandards of	(5) 2 oduct is st genera safety sho rated, an applicable Canadia	NA NA in use. ted from ower, eye d respira e U.S. S an Provir	NA 1000 Use loc the had e-wash atory State nces,	cal or genera
8.3	Ventilation & Engineering Controls:  Respiratory Protection:	PARAFFIN WAX TALC  General mechanical (e. exhaust ventilation to e product. Ensure appropriate protection is needed, uregulations, or the Cana EC member States, or A Normally not necessary under appropriate gover None required under not the appropriate standard	g., fans) or nateffectively removeriate decontaming. In instance use only protected adian CAS Standaustralia.  A Avoid eye comment standard ormal conditions ds of Canada, or	NA NA NA ural ventila e and pre nation equi s where d ion author lard Z94.4- ntact. Use s such as N of use. If the EU me	NF NF tion is suffivent buildupment is avait of this ized by 29 93 and apperentions (IOSH (US)) necessary	STEL NF 2.5 icient whip of vapidable (expression of context) CFR § 2001 of context of co	PEAK NF NF en this pr ors or mis e.g., sink, s are gene 1910.134, tandards of protection 66(EU). U.S. OSH	(5) 2 oduct is st general safety short rated, an applicable of Canadian tested and 29 CF	NA NA in use. ted from ower, eye d respire e U.S. S an Provir and appr	NA 1000 Use loo the hawash satory State nces, roved	cal or genera
8.3	Ventilation & Engineering Controls:  Respiratory Protection:  Eye Protection:	PARAFFIN WAX TALC  General mechanical (e. exhaust ventilation to e product. Ensure appropriate protection is needed, tregulations, or the Cana EC member States, or A Normally not necessary under appropriate gover None required under no	g., fans) or nateffectively removeriate decontaming. In instance use only protected adian CAS Standaustralia.  A Avoid eye comment standard ormal conditions ds of Canada, or	NA NA NA ural ventila e and pre nation equi s where d ion author lard Z94.4- ntact. Use s such as N of use. If the EU me	NF NF tion is suffivent buildupment is avait of this ized by 29 93 and apperentions (IOSH (US)) necessary	STEL NF 2.5 icient whip of vapidable (expression of context) CFR § 2001 of context of co	PEAK NF NF en this pr ors or mis e.g., sink, s are gene 1910.134, tandards of protection 66(EU). U.S. OSH	(5) 2 oduct is st general safety short rated, an applicable of Canadian tested and 29 CF	NA NA in use. ted from ower, eye d respire e U.S. S an Provir and appr	NA 1000 Use loo the hawash satory State nces, roved	cal or genera
8.3 8.4 8.5	Ventilation & Engineering Controls:  Respiratory Protection:  Eye Protection:  Hand Protection:	PARAFFIN WAX TALC  General mechanical (e. exhaust ventilation to e product. Ensure appropriate protection is needed, to regulations, or the Canal EC member States, or A Normally not necessary under appropriate governone required under not the appropriate standard None required under navailable.	g., fans) or nateffectively removeriate decontaming. In instance use only protected adian CAS Standaustralia.  A Avoid eye comment standard ormal conditions ds of Canada, or	NA NA NA ural ventila e and pre nation equi s where d ion author lard Z94.4- ntact. Use s such as N of use. If the EU me s of use.	NF NF tion is sufficient buildupment is avaist of this ized by 29 93 and apperent in the company of the company	STEL NF 2.5 icient whip of vapprailable (expression of context) CFR § 2011 of context of	PEAK NF NF en this pr ors or mis e.g., sink, s are gene 1910.134, tandards of protection 66(EU). U.S. OSH	(5) 2 oduct is st general safety short rated, an applicable of Canadian tested and 29 CF	NA NA in use. ted from ower, eye d respire e U.S. S an Provir and appr	NA 1000 Use loo the hawash satory State nces, roved	cal or genera
88.4	Ventilation & Engineering Controls:  Respiratory Protection:  Eye Protection:  Hand Protection:  Body Protection:	PARAFFIN WAX TALC  General mechanical (e. exhaust ventilation to e product. Ensure appropriate protection is needed, uregulations, or the Cana EC member States, or A Normally not necessary under appropriate gover None required under not the appropriate standard None required under navailable.  9. PHYS	g., fans) or nateffectively removariate decontaming. In instance use only protected and CAS Standaustralia.  A Avoid eye comment standard ormal conditions ds of Canada, or ormal condition	NA NA NA ural ventila e and pre nation equi s where d ion author lard Z94.4- ntact. Use s such as N of use. If the EU me s of use.	NF NF tion is sufficient buildupment is avaist of this ized by 29 93 and apperent in the company of the company	STEL NF 2.5 icient whip of vapprailable (expression of context) CFR § 2011 of context of	PEAK NF NF en this pr ors or mis e.g., sink, s are gene 1910.134, tandards of protection 66(EU). U.S. OSH	(5) 2 oduct is st general safety short rated, an applicable of Canadian tested and 29 CF	NA NA in use. ted from ower, eye d respire e U.S. S an Provir and appr	NA 1000 Use loo the hawash satory State nces, roved	cal or genera
88.4 88.5 88.6	Ventilation & Engineering Controls:  Respiratory Protection:  Eye Protection:  Hand Protection:  Body Protection:  Appearance: Odor:	PARAFFIN WAX TALC  General mechanical (e. exhaust ventilation to e product. Ensure appropriate protection is needed, uregulations, or the Cana EC member States, or A Normally not necessary under appropriate gover None required under not the appropriate standard None required under navailable.  9. PHYS Solid, red Odorless	g., fans) or nateffectively removariate decontaming. In instance use only protected and CAS Standaustralia.  A Avoid eye comment standard ormal conditions ds of Canada, or ormal condition	NA NA NA ural ventila e and pre nation equi s where d ion author lard Z94.4- ntact. Use s such as N of use. If the EU me s of use.	NF NF tion is sufficient buildupment is avaist of this ized by 29 93 and apperent in the company of the company	STEL NF 2.5 icient whip of vapprailable (expression of context) CFR § 2011 of context of	PEAK NF NF en this pr ors or mis e.g., sink, s are gene 1910.134, tandards of protection 66(EU). U.S. OSH	(5) 2 oduct is st general safety short rated, an applicable of Canadian tested and 29 CF	NA NA in use. ted from ower, eye d respire e U.S. S an Provir and appr	NA 1000 Use loo the hawash satory State nces, roved	cal or genera
8.4 8.5 8.6 9.1 9.2 9.3	Ventilation & Engineering Controls:  Respiratory Protection:  Eye Protection:  Hand Protection:  Body Protection:  Appearance: Odor: Odor Threshold:	PARAFFIN WAX TALC  General mechanical (e. exhaust ventilation to e product. Ensure appropriate protection is needed, uregulations, or the Cana EC member States, or A Normally not necessary under appropriate gover None required under not the appropriate standard None required under navailable.  9. PHYS Solid, red Odorless NA	g., fans) or nateffectively removariate decontaming. In instance use only protected and CAS Standaustralia.  A Avoid eye comment standard ormal conditions ds of Canada, or ormal condition	NA NA NA ural ventila e and pre nation equi s where d ion author lard Z94.4- ntact. Use s such as N of use. If the EU me s of use.	NF NF tion is sufficient buildupment is avaist of this ized by 29 93 and apperent in the company of the company	STEL NF 2.5 icient whip of vapprailable (expression of context) CFR § 2011 of context of	PEAK NF NF en this pr ors or mis e.g., sink, s are gene 1910.134, tandards of protection 66(EU). U.S. OSH	(5) 2 oduct is st general safety short rated, an applicable of Canadian tested and 29 CF	NA NA in use. ted from ower, eye d respire e U.S. S an Provir and appr	NA 1000 Use loo the hawash satory State nces, roved	cal or genera
8.4 8.5 8.6 9.1 9.2 9.3 9.4	Ventilation & Engineering Controls:  Respiratory Protection:  Eye Protection:  Hand Protection:  Body Protection:  Appearance: Odor: Odor Threshold: pH:	PARAFFIN WAX TALC  General mechanical (e. exhaust ventilation to e product. Ensure appropriate protection is needed, uregulations, or the Cana EC member States, or A Normally not necessary under appropriate gover None required under not the appropriate standard None required under navailable.  9. PHYS Solid, red Odorless NA NA	g., fans) or nateffectively removariate decontaming. In instance use only protected and CAS Standaustralia.  A Avoid eye comment standard ormal conditions ds of Canada, or ormal condition	NA NA NA ural ventila e and pre nation equi s where d ion author lard Z94.4- ntact. Use s such as N of use. If the EU me s of use.	NF NF tion is sufficient buildupment is avaist of this ized by 29 93 and apperent in the company of the company	STEL NF 2.5 icient whip of vapprailable (expression of context) CFR § 2011 of context of	PEAK NF NF en this pr ors or mis e.g., sink, s are gene 1910.134, tandards of protection 66(EU). U.S. OSH	(5) 2 oduct is st general safety short rated, an applicable of Canadian tested and 29 CF	NA NA in use. ted from ower, eye d respire e U.S. S an Provir and appr	NA 1000 Use loo the hawash satory State nces, roved	cal or genera
8.4 8.5 8.6 9.1 9.2 9.3 9.4 9.5	Ventilation & Engineering Controls:  Respiratory Protection:  Eye Protection:  Hand Protection:  Body Protection:  Appearance: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling	PARAFFIN WAX TALC  General mechanical (e. exhaust ventilation to exhaust ventilation is needed, uregulations, or the Cana EC member States, or A Normally not necessary under appropriate governone required under not the appropriate standard None required under navailable.  9. PHYS  Solid, red Odorless NA NA NA	g., fans) or nateffectively removariate decontaming. In instance use only protected and CAS Standaustralia.  A Avoid eye comment standard ormal conditions ds of Canada, or ormal condition	NA NA NA ural ventila e and pre nation equi s where d ion author lard Z94.4- ntact. Use s such as N of use. If the EU me s of use.	NF NF tion is sufficient buildupment is avaist of this ized by 29 93 and apperent in the company of the company	STEL NF 2.5 icient whip of vapprailable (expression of context) CFR § 2011 of context of	PEAK NF NF en this pr ors or mis e.g., sink, s are gene 1910.134, tandards of protection 66(EU). U.S. OSH	(5) 2 oduct is st general safety short rated, an applicable of Canadian tested and 29 CF	NA NA in use. ted from ower, eye d respire e U.S. S an Provir and appr	NA 1000 Use loo the hawash satory State nces, roved	cal or genera
8.4 8.5 8.6 9.1 9.2 9.3 9.4 9.5 9.6	Ventilation & Engineering Controls:  Respiratory Protection:  Eye Protection:  Hand Protection:  Body Protection:  Appearance: Odor: Odor Threshold: pH: Melting Point/Freezing Point:	PARAFFIN WAX TALC  General mechanical (e. exhaust ventilation to exhaust ventilation in the canal EC member States, or A Normally not necessary under appropriate govern None required under not the appropriate standard None required under navailable.  9. PHYS Solid, red Odorless NA NA NA NA	g., fans) or nateffectively removariate decontaming. In instance use only protected and CAS Standaustralia.  A Avoid eye comment standard ormal conditions ds of Canada, or ormal condition	NA NA NA ural ventila e and pre nation equi s where d ion author lard Z94.4- ntact. Use s such as N of use. If the EU me s of use.	NF NF tion is sufficient buildupment is avaist of this ized by 29 93 and apperent in the company of the company	STEL NF 2.5 icient whip of vapprailable (expression of context) CFR § 2011 of context of	PEAK NF NF en this pr ors or mis e.g., sink, s are gene 1910.134, tandards of protection 66(EU). U.S. OSH	(5) 2 oduct is st general safety short rated, an applicable of Canadian tested and 29 CF	NA NA in use. ted from ower, eye d respire e U.S. S an Provir and appr	NA 1000 Use loo the hawash satory State nces, roved	cal or genera
8.4 8.5 8.6 9.1 9.2 9.3 9.4 9.5 9.6 9.7	Ventilation & Engineering Controls:  Respiratory Protection:  Eye Protection:  Hand Protection:  Body Protection:  Appearance: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability	PARAFFIN WAX TALC  General mechanical (e. exhaust ventilation to exhaust ventilation is needed, uregulations, or the Cana EC member States, or A Normally not necessary under appropriate governone required under not the appropriate standard None required under navailable.  9. PHYS  Solid, red Odorless NA NA NA	g., fans) or nateffectively removariate decontaming. In instance use only protected and CAS Standaustralia.  A Avoid eye comment standard ormal conditions ds of Canada, or ormal condition	NA NA NA ural ventila e and pre nation equi s where d ion author lard Z94.4- ntact. Use s such as N of use. If the EU me s of use.	NF NF tion is sufficient buildupment is avaist of this ized by 29 93 and apperent in the company of the company	STEL NF 2.5 icient whip of vapprailable (expression of context) CFR § 2011 of context of	PEAK NF NF en this pr ors or mis e.g., sink, s are gene 1910.134, tandards of protection 66(EU). U.S. OSH	(5) 2 oduct is st general safety short rated, an applicable of Canadian tested and 29 CF	NA NA in use. ted from ower, eye d respire e U.S. S an Provir and appr	NA 1000 Use loo the hawash satory State nces, roved	cal or genera
8.4 8.5 8.6 9.1 9.2 9.3 9.4 9.5 9.6 9.7	Ventilation & Engineering Controls:  Respiratory Protection:  Eye Protection:  Hand Protection:  Body Protection:  Appearance: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint:	PARAFFIN WAX TALC  General mechanical (e. exhaust ventilation to exhaust ventilation is needed, used to regulations, or the Canafec member States, or Anomally not necessary under appropriate gover None required under not the appropriate standard None required under not available.  9. PHYS Solid, red Odorless NA NA NA NA NA NA NA NA NA	g., fans) or nateffectively removariate decontaming. In instance use only protected and CAS Standaustralia.  A Avoid eye comment standard ormal conditions ds of Canada, or ormal condition	NA NA NA ural ventila e and pre nation equi s where d ion author lard Z94.4- ntact. Use s such as N of use. If the EU me s of use.	NF NF tion is sufficient buildupment is avaist of this ized by 29 93 and apperent in the company of the company	STEL NF 2.5 icient whip of vapprailable (expression of context) CFR § 2011 of context of	PEAK NF NF en this pr ors or mis e.g., sink, s are gene 1910.134, tandards of protection 66(EU). U.S. OSH	(5) 2 oduct is st general safety short rated, an applicable of Canadian tested and 29 CF	NA NA in use. ted from ower, eye d respire e U.S. S an Provir and appr	NA 1000 Use loo the hawash satory State nces, roved	cal or genera
8.3 8.4 8.5 8.6 9.1 9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 9.10	Ventilation & Engineering Controls:  Respiratory Protection:  Eye Protection:  Hand Protection:  Body Protection:  Appearance: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density:	PARAFFIN WAX TALC  General mechanical (e. exhaust ventilation to exhaust ventilation is needed, useful to regulations, or the Canafec member States, or Anormally not necessary under appropriate gover None required under not the appropriate standard None required under not available.  9. PHYS Solid, red Odorless NA	g., fans) or nateffectively removariate decontaming. In instance use only protected and CAS Standaustralia.  A Avoid eye comment standard ormal conditions ds of Canada, or ormal condition	NA NA NA ural ventila e and pre nation equi s where d ion author lard Z94.4- ntact. Use s such as N of use. If the EU me s of use.	NF NF tion is sufficient buildupment is avaist of this ized by 29 93 and apperent in the company of the company	STEL NF 2.5 icient whip of vapprailable (expression of context) CFR § 2011 of context of	PEAK NF NF en this pr ors or mis e.g., sink, s are gene 1910.134, tandards of protection 66(EU). U.S. OSH	(5) 2 oduct is st general safety shorted, an applicable of Canadian tested and 29 CF	NA NA in use. ted from ower, eye d respire e U.S. S an Provir and appr	NA 1000 Use loo the hawash satory State nces, roved	cal or genera
8.4 8.5 8.6 9.1 9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 9.10 9.11	Ventilation & Engineering Controls:  Respiratory Protection:  Eye Protection:  Hand Protection:  Body Protection:  Appearance: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density:	PARAFFIN WAX TALC  General mechanical (e. exhaust ventilation to exhaust ventilation in the cassary protection is needed, to regulations, or the Canabet EC member States, or A Normally not necessary under appropriate gover None required under not the appropriate standard None required under navailable.  9. PHYS  Solid, red Odorless NA	g., fans) or nateffectively removariate decontaming. In instance use only protected and CAS Standaustralia.  A Avoid eye comment standard ormal conditions ds of Canada, or ormal condition	NA NA NA ural ventila e and pre nation equi s where d ion author lard Z94.4- ntact. Use s such as N of use. If the EU me s of use.	NF NF tion is sufficient buildupment is avaist of this ized by 29 93 and apperent in the company of the company	STEL NF 2.5 icient whip of vapprailable (expression of context) CFR § 2011 of context of	PEAK NF NF en this pr ors or mis e.g., sink, s are gene 1910.134, tandards of protection 66(EU). U.S. OSH	(5) 2 oduct is st general safety shorted, an applicable of Canadian tested and 29 CF	NA NA in use. ted from ower, eye d respire e U.S. S an Provir and appr	NA 1000 Use loo the hawash satory State nces, roved	cal or genera
8.3 8.4 8.5 8.6 9.1 9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 9.10 9.11 9.12	Ventilation & Engineering Controls:  Respiratory Protection:  Eye Protection:  Hand Protection:  Body Protection:  Appearance: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility:	PARAFFIN WAX TALC  General mechanical (e. exhaust ventilation to exhaust ventilation in the caper protection is needed, to regulations, or the Canage Commber States, or Anderson ventilation in the expropriate governote appropriate standard None required under note appropriate standard None required under note available.  9. PHYS  Solid, red Odorless NA	g., fans) or nateffectively removariate decontaming. In instance use only protected and CAS Standaustralia.  A Avoid eye comment standard ormal conditions ds of Canada, or ormal condition	NA NA NA ural ventila e and pre nation equi s where d ion author lard Z94.4- ntact. Use s such as N of use. If the EU me s of use.	NF NF tion is sufficient buildupment is avaist of this ized by 29 93 and apperent in the company of the company	STEL NF 2.5 icient whip of vapprailable (expression of context) CFR § 2011 of context of	PEAK NF NF en this pr ors or mis e.g., sink, s are gene 1910.134, tandards of protection 66(EU). U.S. OSH	(5) 2 oduct is st general safety shorted, an applicable of Canadian tested and 29 CF	NA NA in use. ted from ower, eye d respire e U.S. S an Provir and appr	NA 1000 Use loo the hawash satory State nces, roved	cal or genera
8.3 8.4 8.5 8.6 9.1 9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 9.10 9.11 9.12 9.13	Ventilation & Engineering Controls:  Respiratory Protection:  Eye Protection:  Hand Protection:  Body Protection:  Appearance: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow):	PARAFFIN WAX TALC  General mechanical (e. exhaust ventilation to exproduct. Ensure appropriate your regulations, or the Cana EC member States, or A Normally not necessary under appropriate governous ventilation of the appropriate standard None required under navailable.  9. PHYS Solid, red Odorless NA	g., fans) or nateffectively removariate decontaming. In instance use only protected and CAS Standaustralia.  A Avoid eye comment standard ormal conditions ds of Canada, or ormal condition	NA NA NA ural ventila e and pre nation equi s where d ion author lard Z94.4- ntact. Use s such as N of use. If the EU me s of use.	NF NF tion is sufficient buildupment is avaist of this ized by 29 93 and apperent in the company of the company	STEL NF 2.5 icient whip of vapprailable (expression of context) CFR § 2011 of context of	PEAK NF NF en this pr ors or mis e.g., sink, s are gene 1910.134, tandards of protection 66(EU). U.S. OSH	(5) 2 oduct is st general safety shorted, an applicable of Canadian tested and 29 CF	NA NA in use. ted from ower, eye d respire e U.S. S an Provir and appr	NA 1000 Use loo the hawash satory State nces, roved	cal or genera andling of this
8.3 8.4 8.5 8.6 9.1 9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 9.10 9.11 9.12	Ventilation & Engineering Controls:  Respiratory Protection:  Eye Protection:  Hand Protection:  Body Protection:  Appearance: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility:	PARAFFIN WAX TALC  General mechanical (e. exhaust ventilation to exhaust ventilation in the caper protection is needed, to regulations, or the Canage Commber States, or Anderson ventilation in the expropriate governote appropriate standard None required under note appropriate standard None required under note available.  9. PHYS  Solid, red Odorless NA	g., fans) or nateffectively removariate decontaming. In instance use only protected and CAS Standaustralia.  A Avoid eye comment standard ormal conditions ds of Canada, or ormal condition	NA NA NA ural ventila e and pre nation equi s where d ion author lard Z94.4- ntact. Use s such as N of use. If the EU me s of use.	NF NF tion is sufficient buildupment is avaist of this ized by 29 93 and apperent in the company of the company	STEL NF 2.5 icient whip of vapprailable (expression of context) CFR § 2011 of context of	PEAK NF NF en this pr ors or mis e.g., sink, s are gene 1910.134, tandards of protection 66(EU). U.S. OSH	(5) 2 oduct is st general safety shorted, an applicable of Canadian tested and 29 CF	NA NA in use. ted from ower, eye d respire e U.S. S an Provir and appr	NA 1000 Use loo the hawash satory State nces, roved	cal or genera
8.3 8.4 8.5 8.6 9.1 9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 9.10 9.11 9.12 9.13 9.14	Ventilation & Engineering Controls:  Respiratory Protection:  Eye Protection:  Hand Protection:  Body Protection:  Appearance: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature:	PARAFFIN WAX TALC  General mechanical (e. exhaust ventilation to exproduct. Ensure appropriate protection is needed, tregulations, or the Cana EC member States, or A Normally not necessary under appropriate governote appropriate standard None required under navailable.  9. PHYS Solid, red Odorless NA	g., fans) or nateffectively removariate decontaming. In instance use only protected and CAS Standaustralia.  A Avoid eye comment standard ormal conditions ds of Canada, or ormal condition	NA NA NA ural ventila e and pre nation equi s where d ion author lard Z94.4- ntact. Use s such as N of use. If the EU me s of use.	NF NF tion is sufficient buildupment is avaist of this ized by 29 93 and apperent in the company of the company	STEL NF 2.5 icient whip of vapprailable (expression of context) CFR § 2011 of context of	PEAK NF NF en this pr ors or mis e.g., sink, s are gene 1910.134, tandards of protection 66(EU). U.S. OSH	(5) 2 oduct is st general safety shorted, an applicable of Canadian tested and 29 CF	NA NA in use. ted from ower, eye d respire e U.S. S an Provir and appr	NA 1000 Use loo the hawash satory State nces, roved	cal or genera



Page 3 of 5 **HFT-65198** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 7/25/2015 10. STABILITY & REACTIVITY 10.1 Stability: This product is stable 10.2 Hazardous Decomposition Oxides of carbon and nitrogen. Products: 10.3 Hazardous Polymerization: Will not occur. 10.4 Conditions to Avoid: Open flames, sparks, high heat and direct sunlight. Incompatible Substances: 10.5 None known. 11. TOXICOLOGICAL INFORMATION Inhalation: NO 11.1 Routes of Entry: Absorption: 11.2 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product, but is not presented in this document 11.3 Acute Toxicity See Section 4.4 11.4 Chronic Toxicity: See Section 4.5 11.5 Suspected Carcinogen: No 11.6 Reproductive Toxicity This product is not reported to cause reproductive toxicity in humans Mutagenicity This product is not reported to produce mutagenic effects in humans. Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity This product is not reported to cause teratogenic effects in humans Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. 11.7 Irritancy of Product: See Section 4.3 11.8 Biological Exposure Indices: NE Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION 12.1 **Environmental Stability** There are no specific data available for this product. 12.2 Effects on Plants & Animals: There are no specific data available for this product. Effects on Aquatic Life: There are no specific data available for this product 12.3 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Waste disposal must be in accordance with appropriate Federal, state, provincial and local regulations. 13.2 Special Considerations NA 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): NOT REGULATED 14 2 IATA (AIR): NOT REGULATED 14.3 IMDG (OCN): **NOT REGULATED** 14.4 TDGR (Canadian GND): **NOT REGULATED** 14.5 ADR/RID (EU): NOT REGULATED SCT (MEXICO): 14.6 NOT REGULATED 14.7 ADGR (AUS): **NOT REGULATED** 15. REGULATORY INFORMATION SARA Reporting 15.1 This product does not contain any substances subject to SARA Title III, section 313 reporting requirements. Requirements 15.2 SARA Threshold Planning There are no specific Threshold Planning Quantities for the components of this product. Quantity: 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory or are otherwise exempt. 15.4 **CERCLA Reportable Quantity** NΑ Other Federal Requirements None of the ingredients are listed as Hazardous Air Pollutants (HAPs). None of the ingredients are listed as Toxic 15.5 Pollutants under the Clean Water Act (CWA). None of the ingredients are listed as Priority Pollutants under the Clean Water Act (CWA). This product does not contain any Class 1 or Class 2 ozone depletors. 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. The following chemicals are listed on the Ingredient Disclosure List: Chromium, Manganese, and Molybdenum, WHMIS Classification: D2B (Other Toxic Effects).



Page 4 of 5 HFT-65198

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1

SDS Revision Date: 7/25/2015

		15. REGULATORY I	NFORMATION				
15.7							
15.8	Other Requirements:		sted in Annex I of EU Directive 67/548/EEC: if swallowed. Safety Phrases (S):62 – If do not y and show this container or label where possible.				
		16. OTHER INFO	DRMATION				
16.1	Other Information:		NED. Use only as directed. May be harmful if swallowed. Call a				
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.					
16.3	Goo last page of this Carety Bata Grieci.						
16.4	Prepared for:	Harbor Freight Tools USA, Inc. 26541 Agoura Road Calabasas, CA 91302 USA Tel: +1 (805) 388-1000 http://www.harborfreight.com/	HARBOR FREIGHT TOOLS Quality Tools at Ridiculously Low Prices				
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com					

Page 5 of 5 HFT-65198

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 7/25/2015

## **DEFINITION OF TERMS**

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

#### **GENERAL INFORMATION:**

CAS No.	Chemical Abstract Service Number

#### **EXPOSURE LIMITS IN AIR:**

ACGIH	American Conference on Governmental Industrial Hygienists
С	Ceiling Limit
ES	Exposure Standard (Australia)
IDLH	Immediately Dangerous to Life and Health
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

#### FIRST AID MEASURES:


CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.


#### HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard			
1	1 Slight Hazard			
2	Moderate Hazard			
3	Severe Hazard			
4	Extreme Hazard			



#### PERSONAL PROTECTION RATINGS:























**Dust & Vapor Half-**Mask Respirator

**Full Face** 

Airline Hood/Mask or SCBA

### OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit			
mg/m3	mg/m3 milligrams per cubic meter			
NA	Not Available			
ND	Not Determined			
NE	NE Not Established			
NF	Not Found			
NR	No Results			
ppm	parts per million			
SCBA	Self-Contained Breathing Apparatus			

#### NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:					
Autoignition	Minimum temperature required to initiate combustion in air with no other				
Temperature	source of ignition				
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will				
	explode or ignite in the presence of an ignition source				
UEL Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					

#### **HAZARD RATINGS:**

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
₩	Use No Water
ОХ	Oxidizer
TREFOIL	Radioactive



#### TOXICOLOGICAL INFORMATION:

LD <sub>50</sub>	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC <sub>50</sub>	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD <sub>Io</sub>	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD <sub>Io</sub> , LD <sub>Io</sub> , & LD <sub>o</sub> or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC <sub>o</sub> , LC <sub>io</sub> , & LC <sub>o</sub>	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL <sub>m</sub>	Median threshold limit
log K <sub>ow</sub> or log K <sub>oc</sub>	Coefficient of Oil/Water Distribution

#### **REGULATORY INFORMATION:**

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NOHSC	National Occupational Health and Safety Commission (Australia)
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System

### WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	<b>*</b>	<b>(</b>		$\odot$	(18)		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

#### EC (67/548/EEC) INFORMATION:

		*	*		<b>®</b>	×	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

### CLP/GHS (1272/2008/EC) PICTOGRAMS:

			$\Diamond$			<b>\limits</b>	<b>***</b>	
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environ- ment