

## SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 &amp; 1272/2008/EC Standards

SDS Revision: 1.0



SDS Revision Date: 12/24/2015

## 1. PRODUCT &amp; COMPANY IDENTIFICATION

1.1	Product Name:	<b>BONDO® LIGHTWEIGHT BODY FILLER - PART A (RESIN)</b>
1.2	Chemical Name:	NA
1.3	Synonyms:	P/N 67721A
1.4	Trade Names:	3M®
1.5	Product Uses & Restrictions:	Resin Kit Resin
1.6	Distributor's Name:	Harbor Freight Tools USA, Inc.
1.7	Distributor's Address:	26541 Agoura Road, Calabasas, CA 91302 USA
1.8	Emergency Phone:	<b>CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687)</b>
1.9	Business Phone / Fax:	+1 (805) 388-1000

This product is a kit or multipart products which consist of multiple, independently packaged components. An SDS for each of these components is included. Please do not separate the component SDSs from this cover page. The document number of the SDSs for components of this product are: 67721A and 67721B

## 2. HAZARDS IDENTIFICATION

2.1	Hazard Identification:	<p>This product is classified as a HAZARDOUS SUBSTANCE but not as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia).</p> <p><b>WARNING! FLAMMABLE LIQUID AND VAPOR. HARMFUL IF INHALED. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION.</b></p> <p><u>Classification:</u> Flam. Liq. 3; Acute Tox. 4; Skin Irrit. 2; Eye Irrit. 2</p> <p><u>Hazard Statements</u> (H): H226 – Flammable liquid and vapor. H315 – Causes skin irritation. H332 – Harmful if inhaled.</p> <p><u>Precautionary Statements</u> (P): P210 – Keep away from heat, hot surfaces, sparks and open flames and other ignition sources. No smoking. P233 – Keep container tightly closed. P242 – Use non-sparking tools. P261 – Avoid breathing dust/vapors. P264 – Wash thoroughly with soap and water after handling. P271 – Use only outdoors or in a well-ventilated area. P280 – Wear protective gloves/ eye protection. P302+P352 – IF ON SKIN: Wash with plenty of soap and water. P332+P313 – If skin irritation occurs: Get medical advice/attention. P303+P361+P353 – IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P304 + P340 – IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P370+P378 – In case of fire: Use CO<sub>2</sub>, Dry Chemical, Alcohol foam, Dry Chemical. Use water spray to cool containers. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).</p>	 
-----	------------------------	--	---


## 3. COMPOSITION &amp; INGREDIENT INFORMATION

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m <sup>3</sup> )									OTHER
					ACGIH		NOHSC			OSHA				
					ppm		ppm			ppm				
					TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH		
1,3-ISOBENZOFURANDIONE, POLYMER WITH 2-5FURANDIONE AND 2,2-OXYBIS[ETHANOL]	26123-45-5	NA	NA	15-40	NA	NA	NF	NF	NF	NA	NA	NA		
STYRENE	100-42-5	WL3675000	202-851-5	10-30	20	40	50	213	Nf	100	100	700		
	Flam. Liq. 3; Acute Tox. 4 *: Eye Irrit. 2; Skin Irrit. 2; H226, H332, H319, H315													
TALC	14807-96-6	WW2710000	238-877-9	10-30	2	NA	NF	2.5	NF	2	NA	1000		
MAGNESIUM CARBONATE	546-93-0	OM2470000	208-915-9	7-15	NA	NA	NF	NF	NF	NA	NA	NA		
CALCIUM ALUMINUM BOROSILICATE	65997-17-3	NA	266-046-0	5-10	NA	NA	NF	NF	NF	NA	NA	NA		
	Skin Irrit. 2; Eye Irrit. 2A; Carc. 2; STOT-SE 3; H315, H319, H335, H351													
QUATERNARY AMMONIUM COMPOUNDS, BIS (HYDRO-GENATED TALLOW ALKYL) DIMETHYL, SALTS WITH MONT-MORILLONITE	68911-87-5	NA	272-790-7	1-5	NA	NA	NF	NF	NF	NA	NA	NA		
LIMESTONE	1317-65-3	EV9580000	215-279-6	1-5	(10)	NA	NF	NF	NF	(5)	NA	NA		
CHLORITE (MINERAL)	1318-59-8	NA	215-285-9	0.5-2	NA	NA	NF	NF	NF	NA	NA	NA		
TITANIUM DIOXIDE	13463-67-7	XR2275000	236-675-5	0.1-1	10	NA	NF	NF	NF	5	NA	5000	RESP FRAC	
CRYSTALLINE SILICA	14808-60-7	VV7330000	238-787-4	0.1-1	0.25	NA	NF	0.1	NF	0.1	NA	50		

## 4. FIRST AID MEASURES

4.1	First Aid:	<p><u>Ingestion:</u> If ingested, do not induce vomiting. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.</p> <p><u>Eyes:</u> Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes lifting upper and lower lids, occasionally.</p> <p><u>Skin:</u> Wash thoroughly with soap and water. In case of contact, immediately flush skin with plenty of water for at least 15 minutes.</p> <p><u>Inhalation:</u> Remove victim to fresh air at once. If breathing difficult, administer oxygen. If breathing stops give artificial respiration. Keep person warm, quiet and get medical attention.</p>															
4.2	Effects of Exposure:	<p><u>Ingestion:</u> If product is swallowed, may cause gastrointestinal disturbance.</p> <p><u>Eyes:</u> Exposure to dust may cause eye irritation. Symptoms of overexposure may include redness, itching, irritation and watering.</p> <p><u>Skin:</u> May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.</p> <p><u>Inhalation:</u> Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. Drowsiness, dizziness, headaches and nausea.</p>															
4.3	Symptoms of Overexposure:	<p><u>Ingestion:</u> If product is swallowed, may cause gastrointestinal disturbance.</p> <p><u>Eyes:</u> Exposure to dust may cause eye irritation. Symptoms of overexposure may include redness, itching, irritation and watering.</p> <p><u>Skin:</u> May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.</p> <p><u>Inhalation:</u> Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.</p>															
4.4	Acute Health Effects:	Non-irritating when used as directed. Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of dust can cause coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract.															
4.5	Chronic Health Effects:	Non-irritating when used as directed. Possible allergic dermatitis in some sensitive individuals.															
4.6	Target Organs:	Eyes, Skin, Respiratory System, Central Nervous System (CNS)															
4.7	Medical Conditions Aggravated by Exposure:	Pre-existing dermatitis, other skin conditions.															
		<table><tr><td colspan="2"><b>HEALTH</b></td><td><b>1</b></td></tr><tr><td colspan="2"><b>FLAMMABILITY</b></td><td><b>2</b></td></tr><tr><td colspan="2"><b>PHYSICAL HAZARDS</b></td><td><b>0</b></td></tr><tr><td colspan="2"><b>PROTECTIVE EQUIPMENT</b></td><td><b>X</b></td></tr><tr><td><b>EYES</b></td><td><b>SKIN</b></td><td><b>LUNGS</b></td></tr></table>	<b>HEALTH</b>		<b>1</b>	<b>FLAMMABILITY</b>		<b>2</b>	<b>PHYSICAL HAZARDS</b>		<b>0</b>	<b>PROTECTIVE EQUIPMENT</b>		<b>X</b>	<b>EYES</b>	<b>SKIN</b>	<b>LUNGS</b>
<b>HEALTH</b>		<b>1</b>															
<b>FLAMMABILITY</b>		<b>2</b>															
<b>PHYSICAL HAZARDS</b>		<b>0</b>															
<b>PROTECTIVE EQUIPMENT</b>		<b>X</b>															
<b>EYES</b>	<b>SKIN</b>	<b>LUNGS</b>															

## 5. FIREFIGHTING MEASURES

5.1	Fire & Explosion Hazards:	This material can burn but will not readily ignite. However, if involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO, CO <sub>x</sub> , Hydrocarbons). Class 1C Flammable Liquid.	
5.2	Extinguishing Methods:	CO <sub>2</sub> , Dry Chemical, Alcohol Foam, Dry Chemical. Use water spray to cool containers.	
5.3	Firefighting Procedures:	Keep containers cool until well after the fire is out. Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil-over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.	

## 6. ACCIDENTAL RELEASE MEASURES

6.1	Spills:	<p>Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.</p> <p>For <u>small spills</u> (e.g., &lt; 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.</p> <p>For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water.</p>
-----	---------	---

## SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 &amp; 1272/2008/EC Standards




SDS Revision: 1.0

SDS Revision Date: 12/24/2015

## 7. HANDLING &amp; STORAGE INFORMATION

7.1	Work & Hygiene Practices:	Do not eat, drink or smoke when handling this product. Handle as to avoid puncturing container(s). Wash unintentional residues with soap and warm water. Keep tightly closed when not in use. Avoid contact with skin and clothing.
7.2	Storage & Handling:	Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Avoid temperatures above 120 °F. Keep away from incompatible substances. Protect containers from physical damage. Avoid breathing vapor.
7.3	Special Precautions:	Clean all spills promptly. Spilled material may present a slipping hazard.

## 8. EXPOSURE CONTROLS &amp; PERSONAL PROTECTION

8.1	Exposure Limits: ppm (mg/m <sup>3</sup> )	CHEMICAL NAME(S)	ACGIH		NOHSC			OSHA			OTHER	
			TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH		
		STYRENE	20	40	50	213	NF	100	100	700		
		TALC	2	NA	NF	2.5	NF	2	NA	1000		
		LIMESTONE	(10)	NA	NF	NF	NF	(5)	NA	NA		
		TITANIUM DIOXIDE	10	NA	NF	NF	NF	5	NA	5000	RESP FRAC	
		CRYSTALLINE SILICA	0.25	NA	NF	0.1	NF	0.1	NA	50		
8.2	Ventilation & Engineering Controls:	General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).										
8.3	Respiratory Protection:	No special respiratory protection is required under typical circumstances of use or handling. In instances where mist or vapors of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia.										
8.4	Eye Protection:	Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Wear goggles and/or face shield if splashing or spraying is anticipated. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants. Have suitable eye wash water available. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).										
8.5	Hand Protection:	Use gloves constructed of chemical-resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, or the EU member states.										
8.6	Body Protection:	Avoid prolonged and/or repeated skin contact. Use clean and impervious protective clothing (e.g., neoprene or Tyvek®) if splashing or spraying conditions are present. Protective clothing should include long-sleeves, apron, boots and additional facial protection. If necessary, refer to appropriate standards of Canada, the EU member states, or U.S. OSHA.										

## 9. PHYSICAL &amp; CHEMICAL PROPERTIES

9.1	Appearance:	Colored liquid to paste.
9.2	Odor:	Pungent styrene odor.
9.3	Odor Threshold:	NA
9.4	pH:	NA
9.5	Melting Point/Freezing Point:	NA
9.6	Initial Boiling Point/Boiling Range:	145 °C (293 °F)
9.7	Flashpoint:	26.6-27.7 °C (80-82 °F) CC
9.8	Upper/Lower Flammability Limits:	LEL: 0.9% / UEL: 6.8%
9.9	Vapor Pressure:	5.2 mmHg
9.10	Vapor Density:	1.14 g/mL
9.11	Relative Density:	1.14
9.12	Solubility:	Negligible
9.13	Partition Coefficient (log P <sub>ow</sub> ):	NA
9.14	Autoignition Temperature:	NA
9.15	Decomposition Temperature:	NA
9.16	Viscosity:	NA
9.17	Other Information:	VOC: 203 g/L (17.8 % w/w). VOC (less H <sub>2</sub> O & exempt solvents): 204 g/L (1.71 lbs/gal). Evaporation Rate: 0.1-0.5

## SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 &amp; 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 12/24/2015

## 10. STABILITY &amp; REACTIVITY

10.1	Stability:	Stable under normal conditions; unstable with heat or contamination.
10.2	Hazardous Decomposition Products:	Oxides of carbon (CO, CO <sub>2</sub> ) during combustion.
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Open flames, sparks, high heat, incompatible substances (strong acids, strong bases, oxidizing agents, alkaline earth metals), and direct sunlight, incompatible substances and heavily trafficked areas.
10.5	Incompatible Substances:	Avoid extreme heat and ignition sources. Oxidizing agents, strong acids, strong bases

## 11. TOXICOLOGICAL INFORMATION

11.1	Routes of Entry:	Inhalation: YES	Absorption: YES	Ingestion: YES
11.2	Toxicity Data:	This product has not been tested on animals to obtain toxicological data. Toxicology data for some of the components in this mixture, found in scientific literature, are presented below:		
11.3	Acute Toxicity:	See section 4.4		
11.4	Chronic Toxicity:	See section 4.5		
11.5	Suspected Carcinogen:	Styrene is listed as IARC Group 2B (Possibly carcinogenic to humans). Titanium Dioxide is listed as IARC Group 2B (Possibly carcinogenic to humans). Crystalline Silica is listed as ACGIH Group A2 (Suspected human carcinogen); NIOSH (Occupational carcinogen); NTP13 (Reasonably Anticipated to be a Human Carcinogen); CA65 (cancer).		
11.6	Reproductive Toxicity:	The mixture of phthalate esters contained within this product has been shown to cause developmental effects at high doses in laboratory animals when administered orally by gavage in a developmental study and developmental and fertility effects when administered at high doses by feed in tow-generation reproductive study. The potential risk from occupational consumer exposure is considered to be very low, based on limited relevance of the rodent findings to humans and the large safety margins between exposures and effect levels.		
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.		
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.		
	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.		
	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.		
11.7	Irritancy of Product:	The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.		
11.8	Biological Exposure Indices:	NE		
11.9	Physician Recommendations:	Treat symptomatically.		

## 12. ECOLOGICAL INFORMATION

12.1	Environmental Stability:	There are no specific data available for this product.
12.2	Effects on Plants & Animals:	There are no specific data available for this product.
12.3	Effects on Aquatic Life:	There are no specific data available for this product.

## 13. DISPOSAL CONSIDERATIONS

13.1	Waste Disposal:	Dispose of in accordance with federal, state, provincial and local regulations.
13.2	Special Considerations:	NA

## 14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND):	CONSUMER COMMODITY, ORM-D (IP VOL ≤ 0.5 L) – until 12/31/2020 UN3269, POLYESTER RESIN KIT, 3, III (LTD QTY, IP VOL ≤ 5.0 L) *	
14.2	IATA (AIR)*:	UN3269, POLYESTER RESIN KIT, 3, III (LTD QTY, IP VOL ≤ 5.0 L, PI Y370) *	
14.3	IMDG (OCN):	UN3269, POLYESTER RESIN KIT, 3, III (LTD QTY, IP VOL ≤ 5.0 L) *	
14.4	TDGR (Canadian GND):	MARK PACKAGE "LIMITED QUANTITY," or "LTD QTY," or "QUANT LTÉE" or "QUANTITÉ LIMITÉE; or UN3269, POLYESTER RESIN KIT, 3, III (LTD QTY, IP VOL ≤ 5.0 L) *	
14.5	ADR/RID (EU):	UN3269, POLYESTER RESIN KIT, 3, III (LTD QTY, IP VOL ≤ 5.0 L) *	
14.6	SCT (MEXICO):	UN3269, BOLSAS DE RESINA DE POLIESTER, 3, III (CANT. LTDA., IP VOL ≤ 5.0 L) *	
14.7	ADGR (AUS):	UN3269, POLYESTER RESIN KIT, 3, III (LTD QTY, IP VOL ≤ 5.0 L) *	

\* This classification applies only when shipped as a Kit (Parts A and Part B).





## SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 &amp; 1272/2008/EC Standards


SDS Revision: 1.0

SDS Revision Date: 12/24/2015

## 15. REGULATORY INFORMATION

15.1	SARA Reporting Requirements:	This product contains <u>Styrene</u> , a substance subject to SARA Title III, section 313 reporting requirements.	
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.	
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.	
15.4	CERCLA Reportable Quantity (RQ):	<u>Styrene</u> : 454kg (1,000 lbs)	
15.5	Other Federal Requirements:	None of the ingredients are listed as Hazardous Air Pollutants (HAPs). Styrene is listed as a Toxic Pollutant under the Clean Water Act (CWA). None of the ingredients are listed as Priority Pollutants under the CWA.	
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDL. <u>Styrene</u> is listed on the Priorities Substances List. WHMIS B2, D2B (Flammable Liquid, Other Toxic Effects).	 
15.7	State Regulatory Information:	<u>Styrene</u> is found on the following state criteria lists: Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Minnesota Hazardous Substances List (MN), Pennsylvania Right-to-Know List (PA), and Washington Permissible Exposures List (WA). <u>Talc</u> is found on the following state criteria list: FL, MA, MN, NJ, PA and WA. <u>Magnesium Carbonate</u> is found on the following state criteria list: MA, MN and WA. <u>Titanium Dioxide</u> is found on the following state criteria list: MA, MN, PA and WA. <u>Crystalline Silica</u> can be found on the following state criteria list: CA65, FL, MA, MN, PA, and WA. No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). <b>WARNING:</b> This product contains a substance(s) known to the State of California to cause cancer, birth defects or other reproductive harm. California law requires this warning be given to customers in the State of California.	
15.8	Other Requirements:	The primary components of this product are listed in Annex I of EU Directive 67/548/EEC: <u>Styrene</u> : Flammable, Harmful (F, Xn) <u>Risk Phrases</u> (R): 10-20-36/38 – Flammable. Harmful by inhalation. Irritating to eyes and skin. <u>Safety Phrases</u> (S): (2)-23 – Keep out of reach of children. Do not breathe fumes/vapor/spray.	 

## 16. OTHER INFORMATION

16.1	Other Information:	<b>WARNING! FLAMMABLE LIQUID AND VAPOR. HARMFUL IF INHALED. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION.</b> Keep away from heat, hot surfaces, sparks and open flames and other ignition sources. No smoking. Keep container tightly closed. Use non-sparking tools. Avoid breathing dust/vapors. Wash thoroughly with soap and water after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/eye protection. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of fire: Use CO <sub>2</sub> , Dry Chemical, Alcohol foam, Dry Chemical. Use water spray to cool containers. Store in a well-ventilated place. Keep cool. Use only as directed. <b>KEEP OUT OF REACH OF CHILDREN.</b> <b>WARNING:</b> This product contains a substance(s) known to the State of California to cause cancer, birth defects or other reproductive harm.	
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Harbor Freight Tools USA, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.	
16.4	Prepared for:	Harbor Freight Tools USA, Inc. 26541 Agoura Road Calabasas, CA 91302 USA Tel: +1 (805) 388-1000 <a href="http://www.harborfreight.com">http://www.harborfreight.com</a>	
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 <a href="http://www.shipmate.com">http://www.shipmate.com</a>	



Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 &amp; 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 12/24/2015

## DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

## GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
---------	----------------------------------

## EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
C	Ceiling Limit
ES	Exposure Standard (Australia)
IDLH	Immediately Dangerous to Life and Health
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

## FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
-----	--

## HMIS-III HEALTH, FLAMMABILITY &amp; REACTIVITY RATINGS:

0	Minimal Hazard	HEALTH
1	Slight Hazard	FLAMMABILITY
2	Moderate Hazard	PHYSICAL HAZARDS
3	Severe Hazard	PERSONAL PROTECTION
4	Extreme Hazard	

## PERSONAL PROTECTION RATINGS:

A		G													
B		H													
C		I													
D		J													
E		K													
F		X	Consult your supervisor or SOPs for special handling directions.												
<table><tr><td> Safety Glasses</td><td> Splash Goggles</td><td> Face Shield &amp; Protective Eyewear</td><td> Gloves</td></tr><tr><td> Boots</td><td> Synthetic Apron</td><td> Protective Clothing &amp; Full Suit</td><td> Dust Respirator</td></tr><tr><td> Full Face Respirator</td><td> Dust &amp; Vapor Half-Mask Respirator</td><td> Full Face Respirator</td><td> Airline Hood/Mask or SCBA</td></tr></table>				Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves	Boots	Synthetic Apron	Protective Clothing & Full Suit	Dust Respirator	Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA
Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves												
Boots	Synthetic Apron	Protective Clothing & Full Suit	Dust Respirator												
Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA												

## OTHER STANDARD ABBREVIATIONS:

ML	Maximum Limit
mg/m3	milligrams per cubic meter
NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR	No Results
ppm	parts per million
SCBA	Self-Contained Breathing Apparatus


## NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

## FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

## HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



## TOXICOLOGICAL INFORMATION:

LD <sub>50</sub>	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC <sub>50</sub>	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD <sub>10</sub>	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD <sub>10</sub> , LD <sub>10</sub> , & LD <sub>50</sub> or TC, TC <sub>50</sub> , LC <sub>10</sub> , & LC <sub>50</sub>	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL <sub>m</sub>	Median threshold limit
log K <sub>ow</sub> or log K <sub>oc</sub>	Coefficient of Oil/Water Distribution

## REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NOHSC	National Occupational Health and Safety Commission (Australia)
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System

## WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

## EC (67/548/EEC) INFORMATION:

C	E	F	N	O	T	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

## CLP/GHS (1272/2008/EC) PICTOGRAMS:

GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment

## SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 &amp; 1272/2008/EC Standards

SDS Revision: 1.0



SDS Revision Date: 12/24/2015

## 1. PRODUCT &amp; COMPANY IDENTIFICATION

1.1	Product Name:	<b>BONDO® LIGHTWEIGHT BODY FILLER</b>
1.2	Chemical Name:	NA
1.3	Synonyms:	P/N 67721B
1.4	Trade Names:	3M®
1.5	Product Uses & Restrictions:	Resin Kit Hardener
1.6	Distributor's Name:	Harbor Freight Tools USA, Inc.
1.7	Distributor's Address:	26541 Agoura Road, Calabasas, CA 91302 USA
1.8	Emergency Phone:	<b>CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687)</b>
1.9	Business Phone / Fax:	+1 (805) 388-1000

This product is kit or multipart products which consist of multiple, independently packaged components. An SDS for each of these components is included. Please do not separate the component SDSs from this cover page. The document numbers for the SDSs for components of this product are: **67721A** and **67721B**.

## 2. HAZARDS IDENTIFICATION

2.1	Hazard Identification:	<p>This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia).</p> <p><b>WARNING! HEATING MAY CAUSE A FIRE. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION.</b></p> <p><u>Classification:</u> Org. Perox. E; Skin Sens. 1; Eye Irrit.2</p> <p><u>Hazard Statements</u> (H): H242 – Heating may cause a fire. H317 – May cause an allergic skin reaction. H319 – Causes serious eye irritation.</p> <p><u>Precautionary Statements</u> (P): P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P234 – Keep only in original packaging. P235 – Keep cool. P280 – Wear protective gloves/protective clothing/eye protection/face protection. P370+P378 – In case of fire: Use CO<sub>2</sub>, dry chemical, alcohol foam, or dry chemical to extinguish. P261 – Avoid breathing dust/vapors. P264 – Wash thoroughly after handling. P272 – Contaminated work clothing should not be allowed out of the workplace. P280 – Wear protective gloves/ eye protection/ face protection. P302+P352 – IF ON SKIN: Wash with plenty of water. P333+P313 – If skin irritation or rash occurs: Get medical advice/attention. P321 – Specific treatment see this container label. P305 + P351 + P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 – If eye irritation persists: Get medical advice/attention. P403 – Store in a well-ventilated place. P410 – Protect from sunlight. P411 – Store at temperatures not exceeding 50°C/122°F. P420 – Store separately. P501 – Dispose of contents/container to a licensed treatment, storage and disposal facility TSDF).</p>	 
-----	------------------------	---	---


## 3. COMPOSITION &amp; INGREDIENT INFORMATION

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m <sup>3</sup> )									OTHER
					ACGIH		NOHSC			OSHA				
					ppm		ppm			ppm				
					TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH		
BENZOYL PEROXIDE	94-36-0	DM8575000	202-327-6	30-60	(5)	NE	(5)	NF	NF	(5)	NA	1500		
	Org. Perox. B; Skin Sens. 1; Eye Irrit.2, H241, H317, H319													
WATER (AQUA)	7732-18-5	ZC0110000	231-791-2	10-30	NA	NA	NF	NF	NF	NA	NA	NA		
BRANCHED C10-ALKYL BENZOATES	131298-44-7	NA	NA	10-30	NA	NA	NF	NF	NF	NA	NA	NA		
ZINC STEARATE	557-05-1	ZH5200000	209-151-9	3-7	NA	NA	NF	NF	NF	NA	NA	NA		
POLYAKYLENE GLYCOL	9038-95-3	MD091000	NA	1-5	NA	NA	NF	NF	NF	NA	NA	NA		
CALCIUM SULFATE	7778-18-9	WS6920000	231-900-3	1-5	NA	NA	NF	NF	NF	NA	NA	NA		
IRON (III) OXIDE	1309-37-1	NO7400000	215-168-2	1-5	5	NA	NF	5	NF	5	NA	2500	FUME	

## 4. FIRST AID MEASURES

4.1	First Aid:	<p><u>Ingestion:</u> If ingested, do not induce vomiting. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.</p> <p><u>Eyes:</u> Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes lifting upper and lower lids, occasionally.</p> <p><u>Skin:</u> Wash thoroughly with soap and water. In case of contact, immediately flush skin with plenty of water for at least 15 minutes.</p> <p><u>Inhalation:</u> Remove victim to fresh air at once. If breathing difficult, administer oxygen. If breathing stops give artificial respiration. Keep person warm, quiet and get medical attention.</p>															
4.2	Effects of Exposure:	<p><u>Ingestion:</u> If product is swallowed, may cause gastrointestinal disturbance.</p> <p><u>Eyes:</u> Exposure to dust may cause eye irritation. Symptoms of overexposure may include redness, itching, irritation and watering.</p> <p><u>Skin:</u> May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.</p> <p><u>Inhalation:</u> Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract.</p>															
4.3	Symptoms of Overexposure:	<p><u>Ingestion:</u> If product is swallowed, may cause gastrointestinal disturbance.</p> <p><u>Eyes:</u> Exposure to dust may cause eye irritation. Symptoms of overexposure may include redness, itching, irritation and watering.</p> <p><u>Skin:</u> May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.</p> <p><u>Inhalation:</u> Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.</p>															
4.4	Acute Health Effects:	Non-irritating when used as directed. Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of dust can cause coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract.															
4.5	Chronic Health Effects:	Non-irritating when used as directed. Possible allergic dermatitis in some sensitive individuals															
4.6	Target Organs:	Eyes, Skin.															
4.7	Medical Conditions Aggravated by Exposure:	Pre-existing dermatitis, other skin conditions.															
		<table><tr><td colspan="2">HEALTH</td><td>2</td></tr><tr><td colspan="2">FLAMMABILITY</td><td>1</td></tr><tr><td colspan="2">PHYSICAL HAZARDS</td><td>1</td></tr><tr><td colspan="2">PROTECTIVE EQUIPMENT</td><td>B</td></tr><tr><td>EYES</td><td>SKIN</td><td></td></tr></table>	HEALTH		2	FLAMMABILITY		1	PHYSICAL HAZARDS		1	PROTECTIVE EQUIPMENT		B	EYES	SKIN	
HEALTH		2															
FLAMMABILITY		1															
PHYSICAL HAZARDS		1															
PROTECTIVE EQUIPMENT		B															
EYES	SKIN																

## 5. FIREFIGHTING MEASURES

5.1	Fire & Explosion Hazards:	Closed containers exposed to heat from fire may build pressure and explode. Dust clouds of this material in combination with an ignition source may be explosive.	
5.2	Extinguishing Methods:	CO <sub>2</sub> , Dry Chemical, Alcohol Foam, Dry Chemical. Use water spray to cool containers.	
5.3	Firefighting Procedures:	Keep containers cool until well after the fire is out. Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil-over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.	

## 6. ACCIDENTAL RELEASE MEASURES

6.1	Spills:	<p>Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.</p> <p>For <u>small spills</u> (e.g., &lt; 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.</p> <p>For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water.</p>
-----	---------	---



## SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 &amp; 1272/2008/EC Standards




SDS Revision: 1.0

SDS Revision Date: 12/24/2015

## 7. HANDLING &amp; STORAGE INFORMATION

7.1	Work & Hygiene Practices:	Do not eat, drink or smoke when handling this product. Handle as to avoid puncturing container(s). Wash unintentional residues with soap and warm water. Keep tightly closed when not in use. Avoid contact with skin and clothing.
7.2	Storage & Handling:	Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Avoid temperatures above 120 °F. Keep away from incompatible substances. Protect containers from physical damage. Avoid breathing vapor.
7.3	Special Precautions:	Clean all spills promptly. Keep container tightly closed until ready to use. Store in cool dry place.

## 8. EXPOSURE CONTROLS &amp; PERSONAL PROTECTION

8.1	Exposure Limits: ppm (mg/m <sup>3</sup> )	ACGIH			NOHSC			OSHA			OTHER	
		CHEMICAL NAME(S)		TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		BENZOYL PEROXIDE		(5)	NE	(5)	NF	NF	(5)	NA	1500	
		IRON (III) OXIDE		5	NA	NF	5	NF	5	NA	2500	FUME
8.2	Ventilation & Engineering Controls:	General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).										
8.3	Respiratory Protection:	No special respiratory protection is required under typical circumstances of use or handling. In instances where mist or vapors of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia.										
8.4	Eye Protection:	Safety glasses equipped with side shields should be adequate protection under most conditions of use. Wear goggles and/or face shield if splashing or spraying is anticipated. Wear goggles and face shield if material is heated above 125 °F (51 °C). Have suitable eye wash water available.										
8.5	Hand Protection:	Use gloves constructed of chemical-resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected.										
8.6	Body Protection:	Avoid prolonged and/or repeated skin contact. Use clean and chemical resistant, impermeable protective clothing (e.g., neoprene or Tyvek®). Protective clothing should include long-sleeves, apron, boots and additional facial protection. Contaminated leather goods should be removed promptly and discarded.										

## 9. PHYSICAL &amp; CHEMICAL PROPERTIES

9.1	Appearance:	Viscous red paste
9.2	Odor:	Slight ester odor
9.3	Odor Threshold:	NA
9.4	pH:	NA
9.5	Melting Point/Freezing Point:	NA
9.6	Initial Boiling Point/Boiling Range:	NA
9.7	Flashpoint:	111 °C (231.8 °F) estimated
9.8	Upper/Lower Flammability Limits:	NA
9.9	Vapor Pressure:	NA
9.10	Vapor Density:	NA
9.11	Relative Density:	1.2
9.12	Solubility:	Negligible
9.13	Partition Coefficient (log P <sub>ow</sub> ):	NA
9.14	Autoignition Temperature:	NA
9.15	Decomposition Temperature:	NA
9.16	Viscosity:	NA
9.17	Other Information:	VOC – Not available for individual hardener. Percent volatile 20% (water is the volatile component).

## 10. STABILITY &amp; REACTIVITY

10.1	Stability:	Stable under normal conditions; unstable with heat or contamination.
10.2	Hazardous Decomposition Products:	Oxides of carbon (CO, CO <sub>2</sub> ).
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Open flames, sparks, high heat, incompatible substances and direct sunlight, incompatible substances and heavily trafficked areas. Heat is generated when mixed with water.
10.5	Incompatible Substances:	Avoid extreme heat and ignition sources, metals, acids and acrylates. Heat is generated when mixed water.

## SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 &amp; 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 12/24/2015

## 11. TOXICOLOGICAL INFORMATION

11.1	Routes of Entry:	Inhalation: YES	Absorption: YES	Ingestion: YES
11.2	Toxicity Data:	This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product but is not presented in this document.		
11.3	Acute Toxicity:	See section 4.4		
11.4	Chronic Toxicity:	See section 4.5		
11.5	Suspected Carcinogen:	NA		
11.6	Reproductive Toxicity:	This product is not reported to produce reproductive toxicity in humans.		
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.		
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.		
	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.		
	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.		
11.7	Irritancy of Product:	The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.		
11.8	Biological Exposure Indices:	NE		
11.9	Physician Recommendations:	Treat symptomatically.		

## 12. ECOLOGICAL INFORMATION

12.1	Environmental Stability:	There are no specific data available for this product.
12.2	Effects on Plants & Animals:	There are no specific data available for this product.
12.3	Effects on Aquatic Life:	There are no specific data available for this product.

## 13. DISPOSAL CONSIDERATIONS

13.1	Waste Disposal:	Dispose of in accordance with federal, state, provincial and local regulations.
13.2	Special Considerations:	NA

## 14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND):	CONSUMER COMMODITY, ORM-D (IP VOL ≤ 500 g) – until 12/31/2020 UN3269, POLYESTER RESIN KIT, 3, III (LTD QTY, IP VOL ≤ 500 g) *	
14.2	IATA (AIR)*:	UN3269, POLYESTER RESIN KIT, 3, III (LTD QTY, IP VOL ≤ 0.1 kg, PI Y370) *	
14.3	IMDG (OCN):	UN3269, POLYESTER RESIN KIT, 3, III (LTD QTY, IP VOL ≤ 500 g) *	
14.4	TDGR (Canadian GND):	MARK PACKAGE "LIMITED QUANTITY," or "LTD QTY," or "QUANT LTÉE" or "QUANTITÉ LIMITÉE UN3269, POLYESTER RESIN KIT, 3, III (LTD QTY, IP VOL ≤ 500 g) *	
14.5	ADR/RID (EU):	UN3269, POLYESTER RESIN KIT, 3, III (LTD QTY, IP VOL ≤ 500 g) *	
14.6	SCT (MEXICO):	UN3269, BOLSAS DE RESINA DE POLIESTER, 3, III (CANT. LTDA., IP VOL ≤ 500 g) *	
14.7	ADGR (AUS):	UN3269, POLYESTER RESIN KIT, 3, III (LTD QTY, IP VOL ≤ 500 g) *	

\* This classification applies only when shipped as a Kit (Parts A and Part B).

## 15. REGULATORY INFORMATION

15.1	SARA Reporting Requirements:	This product contains <u>Benzoyl Peroxide</u> , a substance subject to SARA Title III, section 313 reporting requirements.
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.
15.4	CERCLA Reportable Quantity (RQ):	NA
15.5	Other Federal Requirements:	NA
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDL. None of the components of this product are listed on the Priorities Substances List. WHMIS C, D2B, F (Oxidizing Material, Other Toxic Effects, Reactive Material) 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 &amp; 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 12/24/2015

## 15. REGULATORY INFORMATION

15.7	State Regulatory Information:	<p><u>Benzoyl Peroxide</u> is found on the following state criteria lists: Florida Toxic Substances List (FL), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), Pennsylvania Right-to-Know List (PA) and Washington Permissible Exposures List (WA).</p> <p><u>Zinc Stearate</u> is found on the following state criteria list: MA, MN, PA and WA.</p> <p><u>Calcium Sulfate</u> is found on the following state criteria list: MA, MN, PA and WA.</p> <p>Hazardous Substances List (MA), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), Pennsylvania Right-to-Know List (PA), and Rhode Island Hazardous Substances List (RI).</p> <p>No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).</p>
15.8	Other Requirements:	<p>The primary components of this product are listed in Annex I of EU Directive 67/548/EEC:</p> <p><u>Benzoyl Peroxide</u>: Irritant (Xi). <u>Risk Phrases</u> (R): 36-43 Irritation to eyes. May cause sensitization by skin contact. <u>Safety Phrases</u> (S): (2-)3/7-14-36/37/39 Keep out of reach of children. Keep container tightly closed in a cool place. Keep away from extreme high temperatures, strong oxides, peroxides or strong acids. Wear suitable protective clothing, gloves, and eye/face protection.</p> <p><u>Branched C10-Alkyl Benzoates</u>: Harmful (Xn) <u>Risk Phrases</u> (R): 20 – Harmful by inhalation.</p> <p><u>Safety Phrases</u> (S): (2-)23 – Keep out of reach of children. Do not breathe fumes/vapors.</p>



## 16. OTHER INFORMATION

16.1	Other Information:	<p><b>WARNING! HEATING MAY CAUSE A FIRE. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION.</b> Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep only in original packaging. Keep cool. Wear protective gloves/protective clothing/eye protection/face protection. In case of fire: Use CO<sub>2</sub>, dry chemical, alcohol foam, or dry chemical to extinguish. Avoid breathing dust/vapors. P264 – Wash thoroughly after handling. Wear protective gloves/ eye protection/ face protection. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Store in a well-ventilated place. Protect from sunlight. Store at temperatures not exceeding 50°C/122°F. Store separately. Use only as directed. <b>KEEP OUT OF REACH OF CHILDREN.</b></p>
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Harbor Freight Tools USA, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.
16.4	Prepared for:	<p><b>Harbor Freight Tools USA, Inc.</b> 26541 Agoura Road Calabasas, CA 91302 USA Tel: +1 (805) 388-1000 <a href="http://www.harborfreight.com">http://www.harborfreight.com</a></p>
16.5	Prepared by:	<p><b>ShipMate, Inc.</b> P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 <a href="http://www.shipmate.com">http://www.shipmate.com</a></p>

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 &amp; 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 12/24/2015

## DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

## GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
---------	----------------------------------

## EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
C	Ceiling Limit
ES	Exposure Standard (Australia)
IDLH	Immediately Dangerous to Life and Health
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

## FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
-----	--

## HMIS-III HEALTH, FLAMMABILITY &amp; REACTIVITY RATINGS:

0	Minimal Hazard	HEALTH
1	Slight Hazard	FLAMMABILITY
2	Moderate Hazard	PHYSICAL HAZARDS
3	Severe Hazard	PERSONAL PROTECTION
4	Extreme Hazard	

## PERSONAL PROTECTION RATINGS:

A		G													
B		H													
C		I													
D		J													
E		K													
F		X	Consult your supervisor or SOPs for special handling directions.												
<table><tr><td> Safety Glasses</td><td> Splash Goggles</td><td> Face Shield &amp; Protective Eyewear</td><td> Gloves</td></tr><tr><td> Boots</td><td> Synthetic Apron</td><td> Protective Clothing &amp; Full Suit</td><td> Dust Respirator</td></tr><tr><td> Full Face Respirator</td><td> Dust &amp; Vapor Half-Mask Respirator</td><td> Full Face Respirator</td><td> Airline Hood/Mask or SCBA</td></tr></table>				Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves	Boots	Synthetic Apron	Protective Clothing & Full Suit	Dust Respirator	Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA
Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves												
Boots	Synthetic Apron	Protective Clothing & Full Suit	Dust Respirator												
Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA												

## OTHER STANDARD ABBREVIATIONS:

ML	Maximum Limit
mg/m3	milligrams per cubic meter
NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR	No Results
ppm	parts per million
SCBA	Self-Contained Breathing Apparatus


## NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

## FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

## HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



## TOXICOLOGICAL INFORMATION:

LD <sub>50</sub>	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC <sub>50</sub>	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD <sub>10</sub>	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD <sub>10</sub> , LD <sub>10</sub> , & LD <sub>50</sub> or TC, TC <sub>50</sub> , LC <sub>10</sub> , & LC <sub>50</sub>	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL <sub>m</sub>	Median threshold limit
log K <sub>ow</sub> or log K <sub>oc</sub>	Coefficient of Oil/Water Distribution

## REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NOHSC	National Occupational Health and Safety Commission (Australia)
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System

## WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

## EC (67/548/EEC) INFORMATION:

C	E	F	N	O	T	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

## CLP/GHS (1272/2008/EC) PICTOGRAMS:

GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment