HARBOR FREIGHT TOOLS

1.1

12

1.3

1.4

15

1.6

1.7

1.8

19

2.1

SAFETY DATA SHEET

Page 1 of 6 HFT-68366

OTHER

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 12/24/2015 1. PRODUCT & COMPANY IDENTIFICATION Product Name: FLUID FOR I-BEAM LEVEL Chemical Name Low Boiling Point Naphtha Synonyms: P/N 68366 Trade Names Pittsburgh Product Uses & Restrictions: Sight-Glass Distributor's Name: Harbor Freight Tools USA, Inc. Distributor's Address: 26541 Agoura Road, Calabasas, CA 91302 USA Emergency Phone: CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687) Business Phone / Fax: +1 (805) 388-1000 2. HAZARDS IDENTIFICATION Hazard Identification: This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1008 (2004) and ADG Code (Australia). DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES SERIOUS EYE IRRITATION. Classification: Flam. Liq. 1; Asp. Tox. 1; Skin Irrit. 2; STOT SE 3; Aq. Chronic 2. Hazard Statements (H): H224 - Extremely flammable liquid and vapor. H304 - May be fatal if swallowed and enters airways. H319 - Causes serious eye irritation. Precautionary Statements (P): P201 - Obtain special instruction before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat/sparks/open flame/hot surfaces - No Smoking. P233 - Keep container tightly closed. P243 Take precautionary measures against static discharge. P261 – Avoid breathing fume/mist/vapors/spray. P264 - Wash exposed skin areas thoroughly with soap and water after handling. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 -Avoid release to the environment. P280 - Wear protective gloves/eye protection/face protection. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331 - Do NOT induce vomiting. P303+P361+P353 – IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water (or shower). P305+P351+P338 - IF IN EYES -Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention. P370+P378 – In case of fire: use CO₂, Halon (if permitted), dry chemical, or foam for extinction. P391 - Collect spillage. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF). 3. COMPOSITION & INGREDIENT INFORMATION EXPOSURE LIMITS IN AIR (mg/m³) ACGIH NOHSC OSHA ppm ppm ppm ES-ES-ES-PEL STEL IDLH CAS No. τιν STEL RTECS No. EINECS No PEAK CHEMICAL NAME(S) TWA STEL 0/_ 100 NA NF 790 NF 200 NA 2000 MIST 8006-61-9 LX3300000 232-349-1 60-100 LOW BOILING POINT NAPHTHA Flam. Liq. 1; Asp. Tox. 1; Skin Irrit. 2; STOT SE 3; Aq. Chronic 2; H224, H304, H315, H336, H411

4. FIRST AID MEASURES

4.1	First Aid:	Ingestion:	If ingested, do not induce vomiting. Contact the nearest Poison Control Center or local emergency
1			number. Provide an estimate of the time at which the material was ingested and the amount of the
			substance that was swallowed.
I		<u>Eyes</u> :	Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. If irritation occurs, contact a physician.
		<u>Skin</u> :	If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately.
		Inhalation:	Remove victim to fresh air at once.

HAR	BOR FREIGHT TOOLS ality Tools at Ridiculously Low Prices	SAFETY DATA SHE	ET	Page 2 of 6 HFT-68366				
Prepa	Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 12/24/2015							
4.2	Effects of Exposure:	Ingestion: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression. Eves: The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or						
		transient eye inflammation, ulceration. The vapor is discoveredeye irritation, possible corneal burns and eye damage.overexposure may include redness, itching, irritation andSkin:May be irritating to skin, especially after prolonged conta(e.g., rashes, welts, dermatitis) upon prolonged or repeat	omforting to the eye. Splashe Moderately irritating to the e watering. Int. The product can cause al ed exposure.	s may cause severe eyes. Symptoms of llergic skin reactions				
		Inhalation: Vapors of this product may be moderately irritating to the system. Symptoms of overexposure can include coug breathing. Inhalation of concentrated vapors can ca drowsiness, dizziness, headaches, nausea). Odor may may occur.	phing, wheezing, nasal conge ause central nervous syster give some warning of expose	estion, and difficulty n depression (e.g., ure, but odor fatigue				
4.3	Symptoms of Overexposure:	Symptoms of skin overexposure may include redness, itching, and irr may cause redness, itching and watering. The product can cause alle upon prolonged or repeated exposure.	rgic skin reactions (e.g., rashe	es, welts, dermatitis)				
4.4	Acute Health Effects:	Moderate irritation to eyes and skin near affected areas. Addition drowsiness, dizziness, headaches and nausea.	nally, high concentrations of	vapors can cause				
4.5	Chronic Health Effects:	The material may accentuate any pre-existing dermatitis condition.						
4.6	Target Organs:	Eyes, Skin, Respiratory System, Central Nervous System, Liver, Kidne						
4.7	Medical Conditions Aggravated by Exposure:	Pre-existing dermatitis, other skin conditions, and disorders of the target organs (eyes, skin, and respiratory system).		2				
		arger organs (eyes, skin, and respiratory system).	FLAMMABILITY	3				
			PHYSICAL HAZARDS	0				
			PROTECTIVE EQUIPME	NT X				
			EYES SKIN LU	NGS				
		5. FIREFIGHTING MEASURES						
5.1	Fire & Explosion Hazards:	DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR! Key open flame/ hot surfaces – No Smoking. Keep container tightly c measures against static discharge.						
5.2	Extinguishing Methods:	CO ₂ , Halon (if permitted), Dry Chemical, Foam, as authorized.						
5.3	Firefighting Procedures:	This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container.						
		First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product. <u>HazChem Code</u> : 3[Y]E. <u>Hazard Identification Number</u> : 33						
		6. ACCIDENTAL RELEASE MEASUR	RES					
6.1	Spills:	Before cleaning any spill or leak, individuals involved in spill clean Equipment.		Personal Protective				
		For <u>small spills</u> (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.						
		For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water.						
		7. HANDLING & STORAGE INFORMA	TION					
7.1	Work & Hygiene Practices:	Avoid prolonged contact with the product. Avoid breathing vapors of the local exhaust ventilation, fans). After use, wash hands and exposed	is product. Use in a well-ven					
7.2	Storage & Handling:	smoke while handling product. Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Storage temperature: 32-120 °F (0-49 °C). Take precautionary measures against static discharge. Store away from incompatible materials (see Section 10).						
7.3	Special Precautions:	Open containers slowly on a stable surface. Keep container tightly contain residual amounts of this product; therefore, empty containers sl	closed when not in use. Em	npty containers may				

HARBOR FREIGHT TOOLS

SAFETY DATA SHEET

Page 3 of 6 HFT-68366

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1 SI

SDS Revision Date: 12/24/2015

		8. EXPOSURE CO	ONTR	OLS	& PER	SONA		ГЕСТ	ION		
8.1	Exposure Limits:			GIH		NOHSC			OSHA		OTHER
	ppm (mg/m ³)	CHEMICAL NAME(S)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		LOW BOILING POINT	100	NA	NF	790	NF	200	NA	2000	MIST
		NAPHTHA									
8.2	Ventilation & Engineering Controls:	When working with large qu exposure below the airborn exposure to eyes.									
8.3	Respiratory Protection:	No special respiratory prot necessary, use only respira §1910.134, or applicable I provinces, EU member state	atory pro U.S. stat	otection te regul	authorized	per U.S	. OSHA's r	equirer	nent in	29 CFR	
8.4	Eye Protection:	Wear protective eyewear (product. Always use prote special hazard; soft lenses r	e.g., saf ctive eye	ety glas ewear w	hen clean	ing spills	or leaks.				
8.5	Hand Protection:	If anticipated that prolonge latex or rubber gloves for §1910.138, the appropriate	d & repe routine	eated sk industria	in contact al use. I	will occu f necessa	r during us ary, refer to				
8.6	Body Protection:	No special body protection appropriate protective clotl needed. If necessary, refe OSHA.	ning to i	prevent	skin cont	act, (boot	s, lab coa	t, apro	n, covei	ralls) as	
		9. PHYSIC	AL &	CHE	MICAL	. PRO	PERTIE	S			
9.1	Appearance:	Transparent liquid (may be		-				-			
9.2	Odor:	Penetrating hydrocarbon od		00.1)							
9.3	Odor Threshold:	NA									
9.4	pH:	NA									
9.5	Melting Point/Freezing Point:	NA									
9.6	Initial Boiling Point/Boiling	> 60 °C (> 140 °F)									
9.7	Range: Flashpoint:	< 0 °C (< 32 °F)									
9.8	Upper/Lower Flammability Limits:	LEL: 0.7% / UEL 7.0%									
9.9	Vapor Pressure:	NA									
9.10	Vapor Density:	NA									
9.11	Relative Density:	NA									
9.12 9.13	Solubility:	Insoluble in water									
9.13	Partition Coefficient (log P _{ow}): Autoignition Temperature:	NA									
9.14	Decomposition Temperature:	NA NA									
9.16	Viscosity:	NA									
9.17	Other Information:	NA									
••••											
					& RE/						
10.1	Stability:	Relatively stable under amb						aition -	nov inclu	ido inita	ting vanore and taxis
10.2	Hazardous Decomposition Products:	If exposed to <u>extremely hig</u> gases (e.g., oxides of carbo			products	oi inerma	ii uecompos	Short II	ay inclu		ung vapors and toxic
10.3	Hazardous Polymerization:	Will not occur.		gen).							
10.4	Conditions to Avoid:	Exposure or contact to extre	eme temp	perature	s, incompa	tible cher	nicals, stror	ng light	sources	, sparks	, flame.
10.5	Incompatible Substances:	Strong oxidizers, peroxides			•						
		11. TOX		OGIC	AL IN	FORM	ATION				
11.1	Routes of Entry:	Inhalation: YE				bsorption:				Ingest	ion: YES
11.2	Toxicity Data:	This product has NOT beer available for some of the co	n tested o mponen	ts of the	als to obtai product a	n toxicolo nd is pres	gy data. To		gy data,	0	120
11.3	Acute Toxicity:	Moderate irritation to eyes	Low Boiling Point Naphtha: LD ₅₀ (oral, rat): 5,000 mg/kg. Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.								
11.4	Chronic Toxicity:	The material may accentuat	te any pr			is conditio	on.				

HARBOR FREIGHT TOOLS

SAFETY DATA SHEET

Page 4 of 6 **HFT-6836**

Qu	ABOR FREIGHT TOOLS	SAFELY DATA SHEET	HFT-68366
Prepa	ared to OSHA, ACC, ANSI, N	OHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revi	sion Date: 12/24/2015
		11. TOXICOLOGICAL INFORMATION – cont'd	
1.6	Reproductive Toxicity:		
1.6		This product is not reported to produce reproductive toxicity in humans.	
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.	
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.	
	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.	
_	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.	
.7	Irritancy of Product:	The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged c	r repeated exposure.
.8	Biological Exposure Indices:	NE	
.9	Physician Recommendations:	Treat symptomatically.	
		12. ECOLOGICAL INFORMATION	
2.1	Environmental Stability:	There are no specific data available for this product.	
2.2	Effects on Plants & Animals:	There are no specific data available for this product.	
2.3	Effects on Aquatic Life:	There are no specific data available for this product.	
	1	13. DISPOSAL CONSIDERATIONS	
3.1	Waste Disposal:	Dispose of in accordance with federal, state, provincial and local regulations.	
3.2	Special Considerations:	NA	
		14. TRANSPORTATION INFORMATION	
The	basic description (ID Nun	nber, proper shipping name, hazard class & division, packing group) is shown for each mode of	transportation. Additior
lesc	riptive information may be	e required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.	
4.1	49 CFR (GND):	UN1993, FLAMMABLE LIQUIDS, N.O.S. (NAPHTHA), 3, II (LTD QTY, IP VOL \leq 1.0 L); or CONSUMER COMMODITY, ORM-D – until 01/01/2021	\diamond
4.2	IATA (AIR)*:	ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 0.5 L); or	
		UN1993, FLAMMABLE LIQUIDS, N.O.S. (NAPHTHA), 3, II (LTD QTY, IP VOL \leq 0.5 L)	
4.3	IMDG (OCN):	UN1993, FLAMMABLE LIQUIDS, N.O.S. (NAPHTHA), 3, II (LTD QTY, IP VOL \leq 1.0 L)	\diamond
4.4	TDGR (Canadian GND):	UN1993, FLAMMABLE LIQUIDS, N.O.S. (NAPHTHA), 3, II (LTD QTY, IP VOL ≤ 1.0 L); or "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (IP VOL ≤ 1.0 L)	◇
4.5	ADR/RID (EU):	UN1993, FLAMMABLE LIQUIDS, N.O.S. (NAPHTHA), 3, II (LTD QTY, IP VOL ≤ 1.0 L)	\diamond
4.6	SCT (MEXICO):	UN1993, LIQUIDOS, INFLAMABLES, N.E.P. (NAFTA), 3, II (CANT. LTDA., IP VOL ≤ 1.0 L)	\diamond
4.7	ADGR (AUS):	UN1993, FLAMMABLE LIQUIDS, N.O.S. (NAPHTHA), 3, II (LTD QTY, IP VOL \leq 1.0 L)	\diamond
		15. REGULATORY INFORMATION	
5.1	SARA Reporting	This product does not contain any substances subject to SARA Title III, section 313 reporting re	equirements.
5.2	Requirements: SARA Threshold Planning		
	Quantity:	There are no specific Threshold Planning Quantities for the components of this product.	
5.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory or are otherwise exempt.	
5.4	CERCLA Reportable Quantity	NA	
5.5	(RQ): Other Federal Requirements:	None of the ingredients are listed as Hazardous Air Pollutants (HAPs). None of the ingred Pollutants under the Clean Water Act (CWA). None of the ingredients are listed as Priority P Water Act (CWA). This product does not contain any Class 1 or Class 2 ozone depletors.	
5.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the Safety Sheet contains all of the information required by the CPR. The components of this product are on the DSL/NDSL. None of the components of this product are listed on the Priorities Subst. List. WHMIS B2, D2B (Flammable Liquid, Other Toxic Effects).	listed
5.7	State Regulatory Information:	Low Boiling Point Naphtha (as Natural Gasoline) is found on the following state criteria lists: List (FL), Massachusetts Hazardous Substances List (MA), Minnesota Hazardous Substance Right-to-Know List (PA), and Washington Permissible Exposures List (WA). No other ingredients in this product, present in a concentration of 1.0% or greater, are listed or criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (I Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous S WARNING! This product contains a substance(s) known to the State of California to cause car	s List (MN), Pennsylvan nany of the following sta Florida Toxic Substanc MI), Minnesota Hazardo s List (NY), Pennsylvan Substances List (WI).

SAFETY DATA SHEET

Page 5 of 6 **HFT-68366**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 12/24/2015

	15. REGULATORY INFORMATION – cont'd						
15.8 Other Requ	rements:	The primary components of this product are listed in Annex I of EU Directive 67/548/EEC: <u>Low Boiling Point Naphtha</u> : Highly Flammable, Harmful (F+, Xn). <u>Risk Phrases</u> (R): R11-36/37/38- 65 – Highly flammable. Irritating to eyes, skin and respiratory system. Harmful: may cause lung damage if swallowed. <u>Safety Phrases</u> (S): (2-)9-16-26-46 – Keep out of reach of children. Keep container in a well-ventilated place. Keep away from sources of ignition – No smoking. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, seek medical advice immediately (show the label where possible).					

16. OTHER INFORMATION

		16. OTHER INFORMATION				
16.1	Other Information:	DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES SERIOUS EYE IRRITATION. Obtain special instruction before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flame/hot surfaces – No Smoking. Keep container tightly closed. Take precautionary measures against static discharge. Avoid breathing fume/mist/vapors/spray. Wash exposed skin areas thoroughly with soap and water after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/eye protection/face protection. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water (or shower). IF IN EYES – Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire: use CO ₂ , Halon (if permitted), dry chemical, or foam for extinction. Store in a well-ventilated place. Keep cool. Store locked up. KEEP LOCKED UP AND OUT OF REACH OF CHILDREN. WARNING! This product contains a substance(s) known to the State of California to cause cancer, birth defects or other reproductive harm.				
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.				
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Harbor Freight Tools USA, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.				
16.4	Prepared for:	Harbor Freight Tools USA, Inc. 26541 Agoura Road Calabasas, CA 91302 USA Tel: +1 (805) 388-1000 http://www.harborfreight.com				
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com				

SAFETY DATA SHEET

Page 6 of 6 **HFT-68366**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 12/24/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No. Chemical Abstract Service Number
--

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists	
C	Ceiling Limit	
ES	Exposure Standard (Australia)	
IDLH Immediately Dangerous to Life and Health		
OSHA U.S. Occupational Safety and Health Administration		
PEL Permissible Exposure Limit		
STEL Short-Term Exposure Limit		
TLV Threshold Limit Value		
TWA	Time Weighted Average	

FIRST AID MEASURES:

CPR	CPR Cardiopulmonary resuscitation - method in which a person whose heart h				
	stopped receives manual chest compressions and breathing to circulate blood				
	and provide oxygen to the body.				

HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard	HEALTH
1	Slight Hazard	FLAMMABILITY
2	Moderate Hazard	PHYSICAL HAZARDS
3	Severe Hazard	PERSONAL PROTECTION
4	Extreme Hazard	

PERSONAL PROTECTION RATINGS:

Α	6		G				
В			н				
С			I				
D	B		J				
Е		\bigcirc	к				
F			X	Consult you special hand	r supervisor or Iling directions	r SOPs foi s.	
Sa	Safety Glasses Splash Goggles			e Shield & tive Eyewear	Glove) s	
	Boots	Synthetic Apron		tive Clothing Full Suit	Dust Resp	Dirator	
Full Face Respirator				ull Face espirator	Airline Hoo or SCI		
отн	OTHER STANDARD ABBREVIATIONS:						

OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit
mg/m3	milligrams per cubic meter
NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR	No Results
ppm	parts per million
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:							
Autoignition	Minimum temperature required to initiate combustion in air with no other						
Temperature	source of ignition						
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will						
	explode or ignite in the presence of an ignition source						
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will						
	explode or ignite in the presence of an ignition source						

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
₩	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{lo}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC _o , LC _{io} , & LC _o	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NOHSC	National Occupational Health and Safety Commission (Australia)
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

\bigcirc	۲	٨		Ð	۲		R
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

N		×	¥	8	e X	×	×
С	E	F	N	0	т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizina	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\diamondsuit					
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environ- ment