HARBOR FREIGHT TOOLS

Quality Teols at Ridicalously Low Prices

## SAFETY DATA SHEET

Page 1 of 6 **HFT-90024** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 7/27/2015

1	PRODUCT.	R. COMPANY	IDENTIFICATION

Product Name:	3 OZ RTV SILICONE - BLACK
Chemical Name:	Dimethiconol
Synonyms:	P/N 90024
Trade Names:	Pro Seal
Product Uses & Restrictions:	Silicone Sealant
Distributor's Name:	Harbor Freight Tools USA, Inc.
Distributor's Address:	26541 Agoura Road, Calabasas, CA 91302 USA
Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687)
Business Phone / Fax:	+1 (805) 388-1000
	Chemical Name: Synonyms: Trade Names: Product Uses & Restrictions: Distributor's Name: Distributor's Address: Emergency Phone:

### 2. HAZARDS IDENTIFICATION

2.1 Hazard Identification:

This product is classified as a HAZARDOUS SUBSTANCE but not as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia). In the event of an exposure or medical inquiry involving this product, please contact a physician or local poison control center, who may seek advice from the U.S. manufacturer, and show them this SDS. DANGER! MAY CAUSE CANCER. HARMFUL IF SWALLOWED. CAUSES SEVERE SKIN

Classification: Carc. 1B. 1; Acute Tox. 4; Eye Dam. 1; Skin Corr. 1C

**BURNS AND EYE DAMAGE.** 

<u>Hazard Statements</u> (H): H350 – May cause cancer. H302 – Harmful if swallowed. H314 – Causes severe skin burns and eye damage.

Precautionary Statements (P): P201 – Obtain special instructions before use. P202 – Do not handle until all safety precautions have been read and understood. P260 – Do not breathe dust or mist. P264 – Wash thoroughly with soap and water after handling. P270 – Do not eat, drink or smoke when using this product. P280 – Wear protective gloves/eye protection/face protection. P301+P310 + P331 – IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. P303 + P361 + P353 – IF ON SKIN (or hair): Take off immediately al contaminated clothing. Rinse skin with water or shower. P363 – Wash contaminated clothing before reuse. P304 + P340 – IF INHALED: Remove person to fresh air and keep comfortable for breathing. P310 – immediately call a POISON CENTER/doctor. P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. P308 + P313 – IF exposed or concerned: Get medical advice/attention. P405 – Store locked up. P501 – Dispose of contents/container to an approved waste disposal plant.



#### 3. COMPOSITION & INGREDIENT INFORMATION

<u> </u>	<u> </u>	<del></del>		J. (			<u> </u>	***					
								EXPC	SURE L	IMITS IN	I AIR (m	g/m³)	
					AC	GIH		NOHSC			OSHA		
					p	om		ppm			ppm		
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	OTHER
CHEMICAE NAME(3)					-								OTTLK
DIMETHICONOL	70131-67-8	VW3157812	NA	60-100	NA	NA	NF	NF	NF	NA	NA	NA	
BINIETTIIOOTTOE													
DISTILLATES, PETROLEUM,	64742-46-7	NA	264-148-2	5-10	NA	5	NF	NF	NF	NA	5	10	OIL MIST
HYDROTREATED MIDDLE	Carc. 1B; H35	Carc. 1B; H350											
CILICA	7631-86-9	NA	231-545-4	7-13	NA	NA	NF	NF	NF	NA	NA	NA	
SILICA													
METLINA TRIA CETOVACII ANIE	4253-34-3	VV4500000	224-221-9	1-5	NA	NA	NF	NF	NF	NA	NA	NA	
METHYLTRIACETOXYSILANE	Acute Tox. 4;	Skin Corr. 1C; H3	302, H314										
ETUVI TDIA CETOVVCII ANIE	17689-77-9	NA	241-677-4	1-5	NA	NA	NF	NF	NF	NA	NA	NA	
ETHYLTRIACETOXYSILANE	Acute Tox. 4;	Skin Corr. 1B; Ey	e Dam. 1; H302,	H314, H31	8								
*ACETIC ACID is formed upon cont	ACETIC ACID is formed upon contact with water or humid air												
ACETIC ACID	64-19-7	AF12225000	200-580-7	NA	10	15	10	25	NF	10	15	50	
ACETIC ACID	Flam. Liq. 3; §	Skin Corr. 1A; H22	26, H314							·			

#### 4 FIRST AID MEASURES

			4. I INOT AID MEAGURES
4.1	First Aid:	Ingestion:	If ingested, do not induce vomiting. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
		Eyes:	Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes lifting upper and lower lids, occasionally.
		<u>Skin</u> :	Wash thoroughly with soap and water. In case of contact, immediately flush skin with plenty of water for at least 15 minutes.
		Inhalation:	Remove victim to fresh air at once. If breathing is difficult, administer oxygen. If breathing stops give artificial respiration. Keep person warm, quiet and get medical attention.

HARBOR FREIGHT TOOLS

Quality Tools at Midiculously Low Prices

## SAFETY DATA SHEET

Page 2 of 6 **HFT-90024** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 7/27/2015 4. FIRST AID MEASURES - cont'd 42 Effects of Exposure: If product is swallowed, may cause gastrointestinal disturbance. Ingestion: Exposure to dust may cause eye irritation. Symptoms of overexposure may include redness, itching, Eyes: irritation and watering. May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in Skin: some sensitive individuals. Inhalation: Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. If material is heated or high vapor concentration is attained, central nervous system depression, confusion, or loss of coordination. 4.3 Symptoms of Overexposure: Ingestion: If product is swallowed, may cause gastrointestinal disturbance. Exposure to dust may cause eye irritation. Symptoms of overexposure may include redness, itching, Eyes: irritation and watering. Skin: May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals. Inhalation: Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. 4.4 Acute Health Effects: Non-irritating when used as directed. Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of dust can cause coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. 4.5 Chronic Health Effects: Non-irritating when used as directed. Possible allergic dermatitis in some sensitive individuals 4.6 Target Organs: Eyes, Skin. Medical Conditions Pre-existing dermatitis, other skin conditions. **HEALTH** 2 Aggravated by Exposure: **FLAMMABILITY** 1 PHYSICAL HAZARDS 0 PROTECTIVE EQUIPMENT В EYES SKIN 5. FIREFIGHTING MEASURES 5 1 Fire & Explosion Hazards: This material can burn but will not readily ignite. However, if involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO, CO<sub>x</sub>, Hydrocarbons). When heated above 150 °C (300 °F) in the presence of air, product can form formaldehyde vapors. CO<sub>2</sub>, Dry Chemical, Alcohol Foam. Use water spray to cool containers. 5.2 Extinguishing Methods: 5.3 Firefighting Procedures: Keep containers cool until well after the fire is out. Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fireexposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil-over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES 6.1 Spills: Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Use normal hygiene practices. Avoid breathing vapors. Avoid direct skin contact. Wash hands thoroughly after using this product and before eating, drinking, or smoking. 7.2 Storage & Handling: Use and store in a cool, dry, well-ventilated area. Keep away from excessive heat, open flames, sparks, and other possible sources of ignition. Do not store in unmarked containers or storage devices. Recommended maximum shelf life: 36 months. 7.3 Special Precautions: Empty containers may contain product residue. Do not pressurize, cut, heat or weld empty containers. Use reasonable care and store away from oxidizing materials. Keep away from water and moisture.



# **SAFETY DATA SHEET**

Page 3 of 6 **HFT-90024** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 7/27/2015

.1	Exposure Limits:		AC	CIH		NOHSC		<u> </u>	OSHA		OTHER
	ppm (mg/m <sup>3</sup> )	CHEMICAL NAME(S)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	OTHER
		DISTILLATES, PETROLEUM,									OII MIOT
		HYDROTREATED MIDDLE	5	10	NF	NF	NF	5	10	NA	OIL MIST
		*ACETIC ACID is formed upon contact									
		ACETIC ACID	NA	5	NF	NF	NF	NA	5	10	OIL MIST
2	Ventilation & Engineering Controls:	The use of mechanical dilution v									
		occupational exposure limits, who (up to 38 °C) or is agitated. Who									
		vapors. Acetic Acid is formed u									
		within guidelines.	pori con	itaot wit	ii watei oi	nama an	. I lovido c	acque	ato vont	ilation t	o control exposur
3	Respiratory Protection:	No special respiratory protectio	n is red	uired u	nder typic	al circums	stances of	use o	r handli	na. In	
		instances where mist or vapors	of this p	roduct	are genera	ated, and i	respiratory	orotec	tion is r	needed,	
		use only protection authorized									
		Canadian CAS Standard Z94.4-	-93 and	applica	ble stand	ards of Ca	anadian Pro	vinces	s, EC n	nember	
	5 D	States, or Australia.									
4	Eye Protection:	Safety glasses equipped with si									
		use. Wear goggles and/or face s shield if material is heated abov	nieid ii i	spiasnir ⊏ /51 °/	ig or sprag	yıng is antı suitabla ov	icipated. we	ear go	ggies ai	na race	
		equipment for eye protection tes	ted and	annrov	o). Have s ed under a	annronriate	e dovernme	nt star	allable. Idards s	. USE	
		NIOSH (US) or EN 166(EU).	tou unu	арргот	ca anaci t	арргорпак	governine	iii otai	iddi do c	Juon uo	
.5	Hand Protection:	Use gloves constructed of chem	nical res	istant n	naterials s	uch as ne	oprene or h	neavv	nitrile ru	ubber if	
		frequent or prolonged contact is									
		appropriate standards of Canada	, or the	EU mer	mber state	S.					
6	Body Protection:	Avoid prolonged and/or repeate	d skin c	contact.	Use clear	n and impe	ervious prof	ective	clothin	g (e.g.,	
		neoprene or Tyvek®) if splashi	ng or s	praying	condition	s are pres	sent. Proteo	ctive o	lothing	should	
		include long-sleeves, apron, b									
clothing. Launder oil contaminated clothing before reusing. Contaminated leather goods should be											
											<u> </u>
		removed promptly and discarde									<u>an</u>
											PB
		removed promptly and discarded member states, or U.S. OSHA.	d. If ne	cessary	/, refer to	appropriat	e standards				PA .
		removed promptly and discarde member states, or U.S. OSHA.  9. PHYSICAL	d. If ne	cessary	/, refer to	appropriat	e standards				
	Appearance:	removed promptly and discarde member states, or U.S. OSHA.  9. PHYSICAL Black colored paste	d. If ne	cessary	/, refer to	appropriat	e standards				
.2	Odor:	removed promptly and discarde member states, or U.S. OSHA.  9. PHYSICAL  Black colored paste Acetic acid odor (vinegar-like)	d. If ne	cessary	/, refer to	appropriat	e standards				
.1 .2 .3	Odor: Odor Threshold:	removed promptly and discarde member states, or U.S. OSHA.  9. PHYSICAL  Black colored paste  Acetic acid odor (vinegar-like)  NA	d. If ne	cessary	/, refer to	appropriat	e standards				
3	Odor: Odor Threshold: pH:	removed promptly and discarde member states, or U.S. OSHA.  9. PHYSICAL Black colored paste Acetic acid odor (vinegar-like) NA NA	d. If ne	cessary	/, refer to	appropriat	e standards				
2 3 4 5	Odor: Odor Threshold: pH: Melting Point/Freezing Point:	removed promptly and discarde member states, or U.S. OSHA.  9. PHYSICAL  Black colored paste  Acetic acid odor (vinegar-like)  NA	d. If ne	cessary	, refer to	appropriat	e standards				
.2 .3 .4 .5	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling	removed promptly and discarde member states, or U.S. OSHA.  9. PHYSICAL Black colored paste Acetic acid odor (vinegar-like) NA NA	d. If ne	cessary	, refer to	appropriat	e standards				
.2	Odor: Odor Threshold: pH: Melting Point/Freezing Point:	removed promptly and discarder member states, or U.S. OSHA.  9. PHYSICAL Black colored paste Acetic acid odor (vinegar-like) NA NA NA NA	d. If ne	cessary	, refer to	appropriat	e standards				
2 3 4 5 6	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability	removed promptly and discarde member states, or U.S. OSHA.  9. PHYSICAL  Black colored paste Acetic acid odor (vinegar-like) NA	d. If ne	cessary	, refer to	appropriat	e standards				
2 3 4 5 6 7	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits:	removed promptly and discarde member states, or U.S. OSHA.  9. PHYSICAL  Black colored paste Acetic acid odor (vinegar-like) NA	d. If ne	cessary	, refer to	appropriat	e standards				
.2 .3 .4 .5 .6 .7	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure:	removed promptly and discarde member states, or U.S. OSHA.  9. PHYSICAL  Black colored paste Acetic acid odor (vinegar-like) NA	d. If ne	cessary	, refer to	appropriat	e standards				
2 3 4 5 6 7 8 9	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density:	removed promptly and discarder member states, or U.S. OSHA.  9. PHYSICAL  Black colored paste Acetic acid odor (vinegar-like) NA NA NA NA > 100 °C (212 °F) closed cup NA NA NA NA	d. If ne	cessary	, refer to	appropriat	e standards				
2 3 4 5 6 7 8 9 10	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density:	removed promptly and discarder member states, or U.S. OSHA.  9. PHYSICAL  Black colored paste Acetic acid odor (vinegar-like) NA NA NA NA > 100 °C (212 °F) closed cup NA	d. If ne	cessary	, refer to	appropriat	e standards				
2 3 4 5 6 7 8 9 10 11	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility:	PHYSICAL  Black colored paste Acetic acid odor (vinegar-like) NA NA NA NA > 100 °C (212 °F) closed cup NA	d. If ne	cessary	, refer to	appropriat	e standards				
2 3 4 5 6 7 8 9 10 11 12	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow):	PHYSICAL  Black colored paste Acetic acid odor (vinegar-like) NA NA NA NA > 100 °C (212 °F) closed cup NA	d. If ne	cessary	, refer to	appropriat	e standards				
2 3 4 5 6 7 8 9 10 11 11 12 13	Odor: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature:	removed promptly and discarder member states, or U.S. OSHA.  9. PHYSICAL Black colored paste Acetic acid odor (vinegar-like) NA NA NA > 100 °C (212 °F) closed cup NA	d. If ne	cessary	, refer to	appropriat	e standards				
2 3 4 5 6 7 8 9 10 11 11 12 13	Odor: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature:	PHYSICAL  Black colored paste Acetic acid odor (vinegar-like) NA NA NA NA > 100 °C (212 °F) closed cup NA	d. If ne	cessary	, refer to	appropriat	e standards				
2 3 4 5 6 7 8 8 9 10 11 12 13 14	Odor: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature:	removed promptly and discarder member states, or U.S. OSHA.  9. PHYSICAL Black colored paste Acetic acid odor (vinegar-like) NA NA NA > 100 °C (212 °F) closed cup NA	d. If ne	cessary	, refer to	appropriat	e standards				
2 3 4 5 6 7 8 9 10 11 12 13 14 15	Odor: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature:	removed promptly and discarder member states, or U.S. OSHA.  9. PHYSICAL  Black colored paste Acetic acid odor (vinegar-like) NA NA NA > 100 °C (212 °F) closed cup NA	d. If ne	cessary	, refer to	appropriat	e standards				
2 3 4 5 6 7 8 9 110 111 12 13 14 15	Odor: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature: Viscosity:	removed promptly and discarder member states, or U.S. OSHA.  9. PHYSICAL  Black colored paste Acetic acid odor (vinegar-like) NA NA NA > 100 °C (212 °F) closed cup NA	d. If ne	cessary	, refer to	appropriat	e standards				
2 3 4 5 6 7 8 9 110 111 12 13 14 15	Odor: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature: Viscosity:	removed promptly and discarder member states, or U.S. OSHA.  9. PHYSICAL Black colored paste Acetic acid odor (vinegar-like) NA NA NA > 100 °C (212 °F) closed cup NA NA NA NA 1.007 Insoluble NA	. & CI	HEMI	/, refer to	PROPE	RTIES				
2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17	Odor: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature: Viscosity:	removed promptly and discarder member states, or U.S. OSHA.  9. PHYSICAL  Black colored paste Acetic acid odor (vinegar-like) NA NA NA NA > 100 °C (212 °F) closed cup NA NA NA NA NA NA 1.007 Insoluble NA	. & CI	HEMI	/, refer to	PROPE	RTIES				
2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature: Viscosity: Other Information:	removed promptly and discarder member states, or U.S. OSHA.  9. PHYSICAL  Black colored paste Acetic acid odor (vinegar-like) NA NA NA NA > 100 °C (212 °F) closed cup NA NA NA NA NA NA 1.007 Insoluble NA	ABILI	HEMI	REAC	ROPE	RTIES	s of C	anada,	the EU	
2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17	Odor: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature: Viscosity: Other Information:	removed promptly and discarder member states, or U.S. OSHA.  9. PHYSICAL Black colored paste Acetic acid odor (vinegar-like) NA NA NA NA > 100 °C (212 °F) closed cup NA NA NA NA 1.007 Insoluble NA	ABILITIES, SILICO	HEMI TY &	REAC	PROPE  TIVITY  tes of inco	RTIES  mpletely bu	arned of	anada,	the EU	
2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17	Odor: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log P <sub>ow</sub> ): Autoignition Temperature: Decomposition Temperature: Viscosity: Other Information:  Stability: Hazardous Decomposition Products:	removed promptly and discarder member states, or U.S. OSHA.  9. PHYSICAL  Black colored paste Acetic acid odor (vinegar-like) NA NA NA NA > 100 °C (212 °F) closed cup NA NA NA NA NA 1.007 Insoluble NA	ABILITIES, SILICO	HEMI TY &	REAC	PROPE  TIVITY  tes of inco	RTIES  mpletely bu	arned of	anada,	the EU	
2 3 4 5 6 7 8 9 10	Odor: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature: Viscosity: Other Information:  Stability: Hazardous Decomposition	removed promptly and discarder member states, or U.S. OSHA.  9. PHYSICAL Black colored paste Acetic acid odor (vinegar-like) NA NA NA NA > 100 °C (212 °F) closed cup NA NA NA NA 1.007 Insoluble NA	ABILITIE, silico sence of	TY &	REAC	PROPE  TIVITY  Tees of inco form forma	RTIES  mpletely buildehyde val	urned coors.	anada,	the EU	

HARBOR FREIGHT TOOLS
Quality Tools at Ridiculously Low Prices

## SAFETY DATA SHEET

Page 4 of 6 **HFT-90024** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 7/27/2015 11. TOXICOLOGICAL INFORMATION Ingestion: YES 11.1 Routes of Entry: Inhalation: YES Absorption: YES 112 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product, but is not presented in this document 11.3 Acute Toxicity: See Section 4.4 11.4 Chronic Toxicity: See Section 4.5 11.5 Suspected Carcinogen: NA Reproductive Toxicity: 11.6 This product is not reported to produce reproductive toxicity in humans. Mutagenicity: This product is not reported to produce mutagenic effects in humans. **Embryotoxicity**: This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to produce teratogenic effects in humans. Reproductive Toxicity: This product is not reported to produce reproductive effects in humans. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. 11.7 Irritancy of Product: 11.8 Biological Exposure Indices: NE Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: There are no specific data available for this product Effects on Plants & Animals: 12.2 There are no specific data available for this product. Effects on Aquatic Life 12.3 There are no specific data available for this product. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Dispose of in accordance with federal, state, provincial and local regulations. 13.2 Special Considerations 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): 14.1 NOT REGULATED 14.2 IATA (AIR): NOT REGULATED 14.3 IMDG (OCN): NOT REGULATED TDGR (Canadian GND): 14.4 NOT REGULATED ADR/RID (EU): 14.5 NOT REGULATED 14.6 SCT (MEXICO): **NOT REGULATED** 14 7 ADGR (AUS): **NOT REGULATED** 15. REGULATORY INFORMATION 15.1 SARA Reporting This product does not contain any substances subject to SARA Title III, Section 313 reporting requirements. Requirements 15.2 SARA Threshold Planning There are no specific Threshold Planning Quantities for the components of this product. Quantity: 15.3 TSCA Inventory Status The components of this product are listed on the TSCA Inventory or are otherwise exempt. 15.4 CERCLA Reportable Quantity 15.5 Other Federal Requirements: None of the ingredients are listed as Hazardous Air Pollutants (HAPs). None of the ingredients are listed as Toxic Pollutants under the Clean Water Act (CWA). None of the ingredients are listed as Priority Pollutants under the Clean Water Act (CWA). This product does not contain any Class 1 or Class 2 ozone depletors. 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS D2B (Other Toxic Effects) 15.7 State Regulatory Information: Ethyltriacetoxysilane is found on the following state criteria list: New Jersey Right-to-Know List (NJ). Methyltriacetoxysilane is found on the following state criteria list: MA, NJ and PA. No ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI)

HARBOR FREIGHT TOOLS

Quality Teols at Ridiculously Low Prices

# **SAFETY DATA SHEET**

Page 5 of 6 **HFT-90024** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 7/27/2015

op.		i, iterios, irilino, 200 nos a 1212200020 standardo	ODG TOTAL TO
		45 DECLII ATODY INC	DIMATION control
	1	15. REGULATORY INFO	-
15.8	Other Requirements:	may cause lung damage if swallowed. Safety P Do not breathe gas, fumes, vapor or spray. Av vomiting: seek medical advice immediately and Flammable aerosol. Colorless, volatile liquid wi may cause dizziness and loss of concentration	listed in Annex I of EU Directive 67/548/EEC:  ). Risk Phrases (R): 10-65 – Flammable. Harmful: Phrases (S): 2-23-24-62 – Keep away from children. Void contact with skin. If swallowed, do not induce show this SDS or the container label. WARNING! ith ethereal and faint sweetish odor. Overexposure n. At higher levels, CNS depression and cardiac displace air and can cause asphyxiation in confined
		16. OTHER INFO	ORMATION
16.1	Other Information:	DANGER! MAY CAUSE CANCER. HARMF DAMAGE. Use only as directed. Obtain special been read and understood. Do not breathe dust eat, drink or smoke when using this product. William Institute Immediately call a POISON CENTER/doctor. Contaminated clothing. Rinse skin with water Remove person to fresh air and keep comfortate EYES: Rinse cautiously with water for several institute.	FUL IF SWALLOWED. CAUSES SEVERE SKIN BURNS AND EYE all instructions before use. Do not handle until all safety precautions have st or mist. Wash thoroughly with soap and water after handling. Do not wear protective gloves/eye protection/face protection. IF SWALLOWED: Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all or shower. Wash contaminated clothing before reuse. IF INHALED: able for breathing, immediately call a POISON CENTER/doctor. IF IN minutes. Remove contact lenses if present and easy to do. Continue cal advice/attention. KEEP LOCKED UP AND OUT OF REACH OF
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	government regulations must be reviewed for a Tools USA, Inc.'s knowledge, the information accuracy, suitability or completeness is not gual provided. The information contained herein reli	OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other pplicability to this product. To the best of ShipMate's & Harbor Freight contained herein is reliable and accurate as of this date; however, ranteed and no warranties of any type, either expressed or implied, are ates only to the specific product(s). If this product(s) is combined with be considered. Data may be changed from time to time. Be sure to
16.4	Prepared for:	Harbor Freight Tools USA, Inc. 26541 Agoura Road Calabasas, CA 91302 USA Tel: +1 (805) 388-1000 http://www.harborfreight.com	HARBOR FREIGHT TOOLS Quality Tools at Ridiculously Low Prices
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com	

## **SAFETY DATA SHEET**

Page 6 of 6 HFT-90024

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision Date: 7/27/2015

### **DEFINITION OF TERMS**

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

#### **GENERAL INFORMATION:**

CAS No.	Chemical Abstract Service Number			
EXPOSURE LIMITS IN AIR:				
ACGIH	American Conference on Governmental Industrial Hygienists			
С	Ceiling Limit			
ES	Exposure Standard (Australia)			
IDLH	Immediately Dangerous to Life and Health			
OSHA	U.S. Occupational Safety and Health Administration			
PEL	Permissible Exposure Limit			
STEL	Short-Term Exposure Limit			
TLV	Threshold Limit Value			
TWA	Time Weighted Average			

#### FIRST AID MEASURES:

CPR Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body

#### HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



#### PERSONAL PROTECTION RATINGS:

Α			
В			
С			
D	图		
Е			
F			





(Ty Face Shield & Protective Eyewear







**Full Face Respirator** 

**Dust & Vapor Half-**Mask Respirator

Synthetic Apron



Airline Hood/Mask or SCBA

#### OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit
mg/m3	milligrams per cubic meter
NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR	No Results
ppm	parts per million
SCBA	Self-Contained Breathing Apparatus

#### NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:				
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition			
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source			
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source			

#### HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
₩	Use No Water
ОХ	Oxidizer
TREFOIL	Radioactive



#### TOXICOLOGICAL INFORMATION:

TOXICOEOGICAE IN ORMATION:					
LD <sub>50</sub>	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s				
LC <sub>50</sub>	Lethal concentration (gases) which kills 50% of the exposed animal				
ppm	Concentration expressed in parts of material per million parts  Lowest dose to cause a symptom  Lowest concentration to cause a symptom				
TD <sub>io</sub>					
TCLo					
TD <sub>Io</sub> , LD <sub>Io</sub> , & LD <sub>o</sub> or	Lowest dose (or concentration) to cause lethal or toxic effects				
TC, TC <sub>o</sub> , LC <sub>lo</sub> , & LC <sub>o</sub>					
IARC	International Agency for Research on Cancer				
NTP	National Toxicology Program				
RTECS	Registry of Toxic Effects of Chemical Substances				
BCF	Bioconcentration Factor				
TL <sub>m</sub>	Median threshold limit				
log K <sub>ow</sub> or log K <sub>oc</sub>	Coefficient of Oil/Water Distribution				

#### **REGULATORY INFORMATION:**

WHMIS	Canadian Workplace Hazardous Material Information System					
DOT	U.S. Department of Transportation					
TC	Transport Canada					
EPA	U.S. Environmental Protection Agency					
DSL	Canadian Domestic Substance List					
NOHSC National Occupational Health and Safety Commission (Australia)						
NDSL Canadian Non-Domestic Substance List						
PSL Canadian Priority Substances List						
TSCA	U.S. Toxic Substance Control Act					
EU	European Union (European Union Directive 67/548/EEC)					
WGK	Wassergefährdungsklassen (German Water Hazard Class)					
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System					

#### WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

	WORKE EXCE TREE RESOLUTION TO THE RESOLUTION OF THE PROPERTY O							
0			<b>②</b>	<b>(T)</b>	<b>®</b>		R	
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F	
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive	

#### EC (67/548/EEC) INFORMATION:

The Table		M	*				X	
С	E	F	N	0	Т	Xi	Xn	
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful	

### CLP/GHS (1272/2008/EC) PICTOGRAMS:

			$\Diamond$			$\Diamond$		*
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment