HARBOR FREIGHT TOOLS

SAFETY DATA SHEET

Page 1 of 6 HFT-90026

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 7/27/2015

1 PRODUCT & COMPANY IDENTIFIC

11 1 1 1 1 1 2 2 2 3 1 1 1 1 1 1 2 2 1 1 1 1				
Product Name:	3 OZ RTV SILICONE - RED			
Chemical Name:	Silicone Elastomer			
Synonyms:	P/N 90026			
Trade Names:	Pro Seal			
Product Uses & Restrictions:	Silicone Sealant			
Distributor's Name:	Harbor Freight Tools USA, Inc.			
Distributor's Address:	26541 Agoura Road, Calabasas, CA 91302 USA			
Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687)			
Business Phone / Fax:	+1 (805) 388-1000			
	Chemical Name: Synonyms: Trade Names: Product Uses & Restrictions: Distributor's Name: Distributor's Address: Emergency Phone:			

2. HAZARDS IDENTIFICATION

Hazard Identification:

This product is classified as a HAZARDOUS SUBSTANCE but not as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia). In the event of an exposure or medical inquiry involving this product, please contact a physician or local poison control center, who may seek advice from the U.S. manufacturer, and show them this SDS. DANGER! MAY CAUSE CANCER. HARMFUL IF SWALLOWED. CAUSES SEVERE SKIN

BURNS AND EYE DAMAGE. Classification: Carc. 1B. 1; Acute Tox. 4; Eye Dam. 1; Skin Corr. 1C

Hazard Statements (H): H350 - May cause cancer. H302 - Harmful if swallowed. H314 - Causes severe skin burns and eye damage.

Precautionary Statements (P): P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P260 - Do not breathe dust or mist. P264 - Wash thoroughly with soap and water after handling. P270 - Do not eat, drink or smoke when using this product. P280 – Wear protective gloves/eye protection/face protection. P301+P310 + P331 – IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately al contaminated clothing. Rinse skin with water or shower. P363 - Wash contaminated clothing before reuse. P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P310 – immediately call a POISON CENTER/doctor. P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. P308 + P313 - IF exposed or concerned: Get medical advice/attention. P405 -Store locked up. P501 - Dispose of contents/ container to an approved waste disposal plant.



3. COMPOSITION & INGREDIENT INFORMATION

					EXPOSURE LIMITS IN AIR (mg/m³)								
					AC	GIH		NOHSC			OSHA		
					pp	om		ppm			ppm		
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	OTHER
OTEMICAE NAME(O)	70131-67-8	VW3157812	NA	60-100	NA	NA	NF	NF	NF	NA	NA	NA	OTHER
DIMETHICONONOL	70101 07 0	V V O 107 O 12	147 (100 100	14/1	14/1	1 1 1	1 1 1	1 141	14/ (14/ (14/ (
DISTILLATES, PETROLEUM,	64742-46-7	NA	264-148-2	5-10	NA	5	NF	NF	NF	NA	5	10	OIL MIST
HYDROTREATED MIDDLE	Carc. 1B; H35	Carc. 1B; H350											
SILICA	7631-86-9	NA	231-545-4	7-13	NA	NA	NF	NF	NF	NA	NA	NA	
SILICA													
METHYLTRIACETOXYSILANE	4253-34-3	VV4500000	224-221-9	1-5	NA	NA	NF	NF	NF	NA	NA	NA	
WETHTLIRIACETOXTSILANE	Acute Tox. 4;	Skin Corr. 1C; H3	302, H314										
ETLIVI TDIA CETOVVCII ANE	17689-77-9	NA	241-677-4	1-5	NA	NA	NF	NF	NF	NA	NA	NA	
ETHYLTRIACETOXYSILANE	Acute Tox. 4;	Acute Tox. 4; Skin Corr. 1B; Eye Dam. 1; H302, H314, H318											
*ACETIC ACID is formed upon contact with water or humid air													
A OFTIO A OID	64-19-7	AF12225000	200-580-7	NA	10	15	10	25	NF	10	15	50	
ACETIC ACID	Flam. Liq. 3; S	Skin Corr. 1A; H22	26, H314										
		•		•									

			4. FIRST AID MEASURES
4.1	First Aid:	Ingestion:	If ingested, do not induce vomiting. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
		Eyes:	Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes lifting upper and lower lids, occasionally.
		Skin:	Wash thoroughly with soap and water. In case of contact, immediately flush skin with plenty of water for at least 15 minutes.
		Inhalation:	Remove victim to fresh air at once. If breathing is difficult, administer oxygen. If breathing stops give artificial respiration. Keep person warm, quiet and get medical attention.

HARBOR FREIGHT TOOLS

Quality Teols at Ridicalously Low Prices

SAFETY DATA SHEET

Page 2 of 6 **HFT-90026**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 7/27/2015 4. FIRST AID MEASURES - cont'd 42 Effects of Exposure: If product is swallowed, may cause gastrointestinal disturbance. Ingestion: Exposure to dust may cause eye irritation. Symptoms of overexposure may include redness, itching, Eyes: irritation and watering. May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in Skin: some sensitive individuals. Inhalation: Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. If material is heated or high vapor concentration is attained, central nervous system depression, confusion, or loss of coordination. 4.3 Symptoms of Overexposure: Ingestion: If product is swallowed, may cause gastrointestinal disturbance. Exposure to dust may cause eye irritation. Symptoms of overexposure may include redness, itching, Eyes: irritation and watering. Skin: May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals. Inhalation: Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. 4.4 Acute Health Effects: Non-irritating when used as directed. Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of dust can cause coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. 4.5 Chronic Health Effects: Non-irritating when used as directed. Possible allergic dermatitis in some sensitive individuals 4.6 Target Organs: Eyes, Skin. Medical Conditions Pre-existing dermatitis, other skin conditions. **HEALTH** 2 Aggravated by Exposure: **FLAMMABILITY** 1 PHYSICAL HAZARDS 0 PROTECTIVE EQUIPMENT В EYES SKIN 5. FIREFIGHTING MEASURES 5 1 Fire & Explosion Hazards: This material can burn but will not readily ignite. However, if involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO, CO_x, Hydrocarbons). When heated above 150 °C (300 °F) in the presence of air, product can form formaldehyde vapors. CO₂, Dry Chemical, Alcohol Foam. Use water spray to cool containers. 5.2 Extinguishing Methods: 5.3 Firefighting Procedures: Keep containers cool until well after the fire is out. Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fireexposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil-over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES 6.1 Spills: Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Use normal hygiene practices. Avoid breathing vapors. Avoid direct skin contact. Wash hands thoroughly after using this product and before eating, drinking, or smoking. 7.2 Storage & Handling: Use and store in a cool, dry, well-ventilated area. Keep away from excessive heat, open flames, sparks, and other possible sources of ignition. Do not store in unmarked containers or storage devices. Recommended maximum shelf life: 36 months. 7.3 Special Precautions: Empty containers may contain product residue. Do not pressurize, cut, heat or weld empty containers. Use reasonable care and store away from oxidizing materials. Keep away from water and moisture.

11.5

Suspected Carcinogen:

NA

Page 3 of 6

SAFETY DATA SHEET HARBOR FREIGHT TOOLS HFT-90026 Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 7/27/2015 8. EXPOSURE CONTROLS & PERSONAL PROTECTION 8.1 Exposure Limits: ACGIH NOHSC OSHA OTHER ppm (mg/m³) TLV CHEMICAL NAME(S) STEL **ES-TWA ES-STEL ES-PEAK** PEL STEL **IDLH** DISTILLATES, PETROLEUM, 5 10 NF NF NF 5 10 NA OIL MIST HYDROTREATED MIDDLE *ACETIC ACID is formed upon contact with water or humid air ACETIC ACID NA NF NF NA 5 10 OIL MIST 5 NF 8.2 Ventilation & Engineering The use of mechanical dilution ventilation is recommended to maintain airborne concentrations below the recommended Controls: occupational exposure limits, whenever this material is used in a confined space, is heated above normal temperatures (up to 38 °C) or is agitated. When heated above 150 °C (302 °F) in the presence of air, product can form formaldehyde vapors. Acetic Acid is formed upon contact with water or humid air. Provide adequate ventilation to control exposures within guidelines. Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. In 8.3 instances where mist or vapors of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia. 8.4 Eye Protection: Safety glasses equipped with side shields should be adequate protection under most conditions of use. Wear goggles and/or face shield if splashing or spraying is anticipated. Wear goggles and face shield if material is heated above 125 °F (51 °C). Have suitable eye wash water available. Hand Protection: 8.5 Use gloves constructed of chemical resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. 8.6 Body Protection: Avoid prolonged and/or repeated skin contact. Use clean and impervious protective clothing (e.g., neoprene or Tyvek®) if splashing or spraying conditions are present. Protective clothing should include long-sleeves, apron, boots and additional facial protection. Remove oil contaminated clothing. Launder oil contaminated clothing before reusing. Contaminated leather goods should be removed promptly and discarded. 9. PHYSICAL & CHEMICAL PROPERTIES Red colored paste 9.1 Appearance: 9.2 Acetic acid odor (vinegar-like) Odor: 9.3 Odor Threshold: NA 9.4 NA 9.5 Melting Point/Freezing Point: NA 9.6 Initial Boiling Point/Boiling NA Range: 9.7 Flashpoint > 100 °C (212 °F) closed cup 9.8 Upper/Lower Flammability NA Limits: Vapor Pressure: 9.9 NA Vapor Density: 9.10 NA 9.11 Relative Density: 1.007 9.12 Solubility Insoluble 9.13 Partition Coefficient (log Pow): NA 9.14 **Autoignition Temperature** NA 9.15 Decomposition Temperature: NA 9.16 Viscosity NA Other Information: 9.17 NA 10. STABILITY & REACTIVITY 10.1 Stability: Stable at normal temperatures. 10.2 Hazardous Decomposition Fumes, smoke, carbon monoxide, silicon oxides and traces of incompletely burned carbon compounds. When heated Products: above 150 °C (302 °F) in the presence of air, product can form formaldehyde vapors. 10.3 Hazardous Polymerization: Will not occur. 10.4 Conditions to Avoid: Open flames, sparks, high heat, and close proximity to incompatible substances. 10.5 Incompatible Substances: Strong oxidizing agents, water, moisture or humid air cause curing with acetic acid vapors being formed. 11. TOXICOLOGICAL INFORMATION Routes of Entry Inhalation: YES Absorption: YES Ingestion: YES 11.1 11.2 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product, but is not presented in this document. 11.3 Acute Toxicity: See Section 4.4 114 Chronic Toxicity See Section 4.5

HARBOR FREIGHT TOOLS

Quality Teols at Ridiculously Low Prices

SAFETY DATA SHEET

Page 4 of 6 **HFT-90026**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 7/27/2015 11. TOXICOLOGICAL INFORMATION - cont'd 11.6 Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans. Mutagenicity This product is not reported to produce mutagenic effects in humans. Embryotoxicity This product is not reported to produce embryotoxic effects in humans Teratogenicity: This product is not reported to produce teratogenic effects in humans. Reproductive Toxicity: This product is not reported to produce reproductive effects in humans. 11.7 Irritancy of Product: The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. 11.8 Biological Exposure Indices: ΝE Physician Recommendations Treat symptomatically. 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: There are no specific data available for this product. 12.2 Effects on Plants & Animals There are no specific data available for this product. 12.3 Effects on Aquatic Life There are no specific data available for this product. 13. DISPOSAL CONSIDERATIONS Waste Disposal: 13.1 Dispose of in accordance with federal, state, provincial and local regulations Special Considerations: 13.2 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR 49 CFR (GND): 14.1 **NOT REGULATED** IATA (AIR): 14.2 **NOT REGULATED** IMDG (OCN): 14.3 **NOT REGULATED** TDGR (Canadian GND): 14.4 **NOT REGULATED** ADR/RID (EU): 14.5 **NOT REGULATED** SCT (MEXICO): 14 6 **NOT REGULATED** 14.7 ADGR (AUS): NOT REGULATED 15. REGULATORY INFORMATION SARA Reporting 15.1 This product does not contain any substances subject to SARA Title III, Section 313 reporting requirements. Requirements 15.2 SARA Threshold Planning There are no specific Threshold Planning Quantities for the components of this product. The components of this product are listed on the TSCA Inventory or are otherwise exempt. 15.3 TSCA Inventory Status: 15.4 CERCLA Reportable Quantity NA (RQ): 15.5 Other Federal Requirements None of the ingredients are listed as Hazardous Air Pollutants (HAPs). None of the ingredients are listed as Toxic Pollutants under the Clean Water Act (CWA). None of the ingredients are listed as Priority Pollutants under the Clean Water Act (CWA). This product does not contain any Class 1 or Class 2 ozone depletors. 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS D2B (Other Toxic Effects) 15.7 State Regulatory Information: Ethyltriacetoxysilane is found on the following state criteria list: New Jersey Right-to-Know List (NJ). Methyltriacetoxysilane is found on the following state criteria list: MA, NJ and PA. No ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY). Pennsvlvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI)

HARBOR FREIGHT TOOLS

Quality Teols at Ridiculously Low Prices

SAFETY DATA SHEET

Page 5 of 6 **HFT-90026**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 7/27/2015

		15. REGULATORY INFO	PRMATION – cont'd
15.8	Other Requirements:	The primary components of this product are not Petroleum Distillate: Flammable, Harmful (F, Xn) may cause lung damage if swallowed. Safety P Do not breathe gas, fumes, vapor or spray. Av vomiting: seek medical advice immediately and Flammable aerosol. Colorless, volatile liquid wit may cause dizziness and loss of concentration	
		16. OTHER INFO	ORMATION
16.1	Other Information:	DANGER! MAY CAUSE CANCER. HARMF DAMAGE. Use only as directed. Obtain special been read and understood. Do not breathe dus eat, drink or smoke when using this product. W Immediately call a POISON CENTER/doctor. D contaminated clothing. Rinse skin with water Remove person to fresh air and keep comforta EYES: Rinse cautiously with water for several results.	UL IF SWALLOWED. CAUSES SEVERE SKIN BURNS AND EYE instructions before use. Do not handle until all safety precautions have to or mist. Wash thoroughly with soap and water after handling. Do not fear protective gloves/eye protection/face protection. IF SWALLOWED: The Normal of Not induce vomiting. IF ON SKIN (or hair): Take off immediately all or shower. Wash contaminated clothing before reuse. IF INHALED: ble for breathing, immediately call a POISON CENTER/doctor. IF IN minutes. Remove contact lenses if present and easy to do. Continue all advice/attention. KEEP LOCKED UP AND OUT OF REACH OF
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	government regulations must be reviewed for all Tools USA, Inc.'s knowledge, the information accuracy, suitability or completeness is not guar provided. The information contained herein rela	OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other oplicability to this product. To the best of ShipMate's & Harbor Freight contained herein is reliable and accurate as of this date; however, ranteed and no warranties of any type, either expressed or implied, are ates only to the specific product(s). If this product(s) is combined with be considered. Data may be changed from time to time. Be sure to
16.4	Prepared for:	Harbor Freight Tools USA, Inc. 26541 Agoura Road Calabasas, CA 91302 USA Tel: +1 (805) 388-1000 http://www.harborfreight.com	HARBOR FREIGHT TOOLS Quality Tools at Ridiculously Low Prices
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com	

SAFETY DATA SHEET

Page 6 of 6 HFT-90026

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision Date: 7/27/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number		
EXPOSURE	EXPOSURE LIMITS IN AIR:		
ACGIH	American Conference on Governmental Industrial Hygienists		
С	Ceiling Limit		
ES	Exposure Standard (Australia)		
IDLH	Immediately Dangerous to Life and Health		
OSHA	U.S. Occupational Safety and Health Administration		
PEL	Permissible Exposure Limit		
STEL	Short-Term Exposure Limit		
TLV	Threshold Limit Value		
TWA	Time Weighted Average		

FIRST AID MEASURES:

Cardiopulmonary resuscitation - method in which a person whose heart has CPR stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body

HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:

		 	111100.
Α			
В			
С			
D	图		
Е			
F			











Synthetic Apron

Protective Clothing & Full Suit

Dust Respirator

Full Face Respirator



Full Face



OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit
mg/m3	milligrams per cubic meter
NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR	No Results
ppm	parts per million
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:		
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition	
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source	
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source	

HAZARD RATINGS:

Minimal Hazard Slight Hazard Moderate Hazard Severe Hazard Extreme Hazard AcD Acidic ALK Alkaline COR Corrosive W Use No Water			
2 Moderate Hazard 3 Severe Hazard 4 Extreme Hazard ACD Acidic ALK Alkaline COR Corrosive Use No Water	0	Minimal Hazard	
3 Severe Hazard 4 Extreme Hazard ACD Acidic ALK Alkaline COR Corrosive Use No Water	1	Slight Hazard	
4 Extreme Hazard ACD Acidic ALK Alkaline COR Corrosive Use No Water	2	Moderate Hazard	
ACD Acidic ALK Alkaline COR Corrosive Use No Water	3	Severe Hazard	
ALK Alkaline COR Corrosive Use No Water	4	Extreme Hazard	
COR Corrosive ₩ Use No Water	ACD	Acidic	
₩ Use No Water	ALK	Alkaline	
	COR	Corrosive	
O . I.	₩	Use No Water	
OX Oxidizer	ох	Oxidizer	
TREFOIL Radioactive	TREFOIL	Radioactive	



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{io}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC _o , LC _{lo} , & LC _o	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NOHSC	National Occupational Health and Safety Commission (Australia)
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

***************************************	World Erioz The Area and International Control (Williams) and International							
	*	(2)	(3)	\odot	(18)			
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F	
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive	

EC (67/548/EEC) INFORMATION:

		M	*			X	X
С	Е	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			(••)		(*)
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment