

Hazard Identification:

SAFETY DATA SHEET

Page 1 of 6 HFT-90631A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 7/29/2015

1. PRODUCT & COMPANY IDENTIFICATION

	1. I RODGOT & GOMIN ANTI IDENTIFICATION								
1.1	Product Name:	EPOXY QUICK SET – PART A (RESIN)							
1.2	Chemical Name:	Epoxy Resin							
1.3	Synonyms:	P/N 90631A							
1.4	Trade Names:	Harbor Freight Tools							
1.5	Product Uses & Restrictions:	Part A of a 2-Part Epoxy Resin Kit							
1.6	Distributor's Name:	Harbor Freight Tools USA, Inc.							
1.7	Distributor's Address:	26541 Agoura Road, Calabasas, CA 91302 USA							
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687)							
1.9	Business Phone / Fax:	+1 (805) 388-1000							

This product is a kit or multipart products, which consist of multiple, independently packaged components. An SDS for each of these components is included. Please do not separate the component SDSs from this cover page. The document numbers of the SDSs for components of this product are: 90631A and 90631B.

2. HAZARDS IDENTIFICATION

This product is classified as a HAZARDOUS SUBSTANCE but not as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia). WARNING! CAUSES SERIOUS EYE IRRITATION. CAUSES SKIN IRRITATION. TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS. Classification: Eye Irrit. 2; Skin Irrit. 2; Skin Sens. 1; Aq. Chronic 2 Hazard Statements (H): H319 - Causes serious eye irritation. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H411 - Toxic to aquatic life with long lasting effects. Precautionary Statements (P): P264 – Wash thoroughly after handling. P273 – Avoid release to the environment. P280 – Wear eye protection/ wear protective gloves. P302 + P352 - IF ON SKIN: Wash with plenty of soap and water. P333+P313 - If skin irritation occurs: Get medical advice/attention. P305 + P351 + P338 -IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice/attention. P501 - Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).



3. COMPOSITION & INGREDIENT INFORMATION

	51 55111511 & 1115112111 1111 511111 1111												
					EXPOSURE LIMITS IN AIR (mg/m³)								
					AC	ACGIH NOHSC ppm ppm		OSHA					
					pp			ppm					
							ES-	ES-	ES-				
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER
EPOXY RESIN	25068-38-6	SL6475000	500-033-5	60-100	NA	NA	NF	NF	NF	NA	NA	NA	
EPOXT RESIN	Eve Irrit 2: Skin Irrit 2: Skin Sens 1: Aquatic Chronic 2: H319, H315, H317, H4							1					

			4. FIRST AID MEASURES							
4.1	First Aid:	Ingestion:	If ingested, do not induce vomiting. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.							
		Eyes:	Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes lifting upper and lower lids, occasionally.							
		Skin:	Wash thoroughly with soap and water. In case of contact, immediately flush skin with plenty of water for at least 15 minutes.							
		Inhalation:	Remove victim to fresh air at once. If breathing is difficult, administer oxygen. If breathing stops give artificial respiration. Keep person warm, quiet and get medical attention.							
4.2	Effects of Exposure:	Ingestion:	If product is swallowed, may cause gastrointestinal disturbance.							
		Eyes:	Exposure to dust/fumes/vapors may cause eye irritation. Symptoms of overexposure may include redness, itching, irritation and watering.							
		Skin:	May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.							
		Inhalation:	Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract.							
4.3	Symptoms of Overexposure:	Ingestion:	If product is swallowed, may cause gastrointestinal disturbance.							
		Eyes:	Exposure to dust/fumes/vapors may cause eye irritation. Symptoms of overexposure may include redness, itching, irritation and watering.							
		Skin:	May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.							
		Inhalation:	Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. Additionally, high concentrations of dust/fumes/vapors can cause drowsiness, dizziness, headaches and nausea.							

SAFETY DATA SHEET

Page 2 of 6 HFT-90631A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 7/29/2015 4. FIRST AID MEASURES - cont'd Non-irritating when used as directed. Moderate irritation to eyes and skin near affected areas. 44 Acute Health Effects: concentrations of dust/fumes/vapors can cause coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. 4.5 Chronic Health Effects: Possible allergic dermatitis in some sensitive individuals. 4.6 Target Organs: Eyes, Skin, Respiratory System. 47 Medical Conditions HEALTH Pre-existing dermatitis, other skin conditions. 2 Aggravated by Exposure: FLAMMABILITY 1 PHYSICAL HAZARDS 1 PROTECTIVE EQUIPMENT В **EYES** SKIN 5. FIREFIGHTING MEASURES 5.1 Fire & Explosion Hazards: This material can burn but will not readily ignite. However, if involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO, CO_X, Hydrocarbons). Extinguishing Methods: 5.2 CO₂, Dry Chemical, Alcohol Foam. Use water spray to cool containers 5.3 Firefighting Procedures: Keep containers cool until well after the fire is out. Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fireexposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil-over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES Spills Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For large spills (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION 7 1 Work & Hygiene Practices: Do not eat, drink or smoke when handling this product. Handle as to avoid puncturing container(s). Wash unintentional residues with soap and warm water. Keep tightly closed when not in use. Avoid contact with skin and clothing 7.2 Storage & Handling: Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Avoid temperatures above 120 °F. Keep away from incompatible substances. Protect containers from physical damage. Avoid breathing vapor. 7.3 Special Precautions: Clean all spills promptly. Spilled material may present a slipping hazard. 8. EXPOSURE CONTROLS & PERSONAL PROTECTION Exposure Limits: ACGIH NOHSC OTHER 8.1 OSHA ppm (mg/m³) CHEMICAL NAME(S) TLV STEL ES-TWA ES-STEL ES-PEAK STEL NA NA NA NF NF NF NA NA NA 8.2 Ventilation & Engineering General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station) 8.3 Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. In instances where mist or vapors of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia.

Reproductive Toxicity:

Biological Exposure Indices

Physician Recommendations:

Irritancy of Product:

11.7

11.8

11.9

SAFETY DATA SHEET

Page 3 of 6

HARBOR FREIGHT TOOLS HFT-90631A Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 7/29/2015 8. EXPOSURE CONTROLS & PERSONAL PROTECTION – cont'd Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this 8.4 Eye Protection: product. Always use protective eyewear when cleaning spills or leaks. Wear goggles and/or face shield if splashing or spraying is anticipated. Contact lenses pose a special hazard: soft lenses may absorb and concentrate irritants. Have suitable eye wash water available. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(FU) Hand Protection: 8.5 Use gloves constructed of chemical-resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, or the EU member states. 8.6 Body Protection: Avoid prolonged and/or repeated skin contact. Use clean and impervious protective clothing (e.g., neoprene or Tyvek®) if splashing or spraying conditions are present. Protective clothing should include long-sleeves, apron, boots and additional facial protection. If necessary, refer to appropriate standards of Canada, the EU member states, or U.S. OSHA 9. PHYSICAL & CHEMICAL PROPERTIES 9.1 Appearance: Light yellow colored viscous liquid 9.2 Odor: Mild amine odor 9.3 Odor Threshold: NA 9.4 pH: NA Melting Point/Freezing Point: 9.5 NA Initial Boiling Point/Boiling 96 > 248.8 °C (480 °F) Range: 9.7 > 260 °C (500 °F) Flashpoint: 9.8 Upper/Lower Flammability NA Limits: 9.9 Vapor Pressure: 0.03 @77 °F 9.10 Vapor Density NΑ Relative Density: 9.11 1.16 Solubility: 9.12 Negligible 9.13 Partition Coefficient (log Pow): NA 9.14 Autoignition Temperature NA 9.15 Decomposition Temperature: NA 9 16 Viscosity NA Other Information 9 17 This product is VOC compliant for sale in California. 10. STABILITY & REACTIVITY 10.1 Stability Stable under normal conditions; unstable with heat or contamination. Hazardous Decomposition 10.2 Oxides of carbon (CO, CO₂). 10.3 Hazardous Polymerization Will not occur. 10.4 Conditions to Avoid Open flames, sparks, high heat, incompatible substances and direct sunlight. 10.5 Incompatible Substances Avoid extreme heat and ignition sources. Oxidizing agents, strong acids, strong bases 11. TOXICOLOGICAL INFORMATION Inhalation: YES Absorption: YES 11.1 Routes of Entry Ingestion: YES 11.2 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product and is not presented in this document 11.3 Acute Toxicity: See Section 4.4 11.4 Chronic Toxicity: See Section 4.5 11.5 Suspected Carcinogen: 11.6 Reproductive Toxicity This product is not reported to produce reproductive toxicity in humans. Mutagenicity This product is not reported to produce mutagenic effects in humans Embryotoxicity This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans.

This product is not reported to cause reproductive effects in humans.

Treat symptomatically.

The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.

SAFETY DATA SHEET

Page 4 of 6 HFT-90631A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 7/29/2015 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: There are no specific data available for this product 12.2 Effects on Plants & Animals: There are no specific data available for this product 12.3 Effects on Aquatic Life: There are no specific data available for this product. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Dispose of in accordance with federal, state, provincial and local regulations. 13.2 Special Considerations: 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): **NOT REGULATED** 14.1 IATA (AIR): 14.2 **NOT REGULATED** 14.3 IMDG (OCN): NOT REGULATED 14.4 TDGR (Canadian GND): **NOT REGULATED** ADR/RID (EU): 14.5 **NOT REGULATED** SCT (MEXICO): 14.6 **NOT REGULATED** ADGR (AUS): NOT REGULATED 15. REGULATORY INFORMATION SARA Reporting 15.1 This product does not contain any substances subject to SARA Title III, section 313 reporting requirements. Requirements 15.2 SARA Threshold Planning There are no specific Threshold Planning Quantities for the components of this product. Quantity: The components of this product are listed on the TSCA Inventory or are otherwise exempt. 15.3 TSCA Inventory Status: 15.4 CERCLA Reportable Quantity NA Other Federal Requirements: 15.5 NA 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. 15.7 State Regulatory Information: No ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). 15.8 Other Requirements: The primary components of this product are listed in Annex I of EU Directive 67/548/EEC: Epoxy Resin: Irritant (Xi); Environmental Danger (N). Risk Phrases (R): 36/38-43-51/53 - Irritating to eyes and skin. May cause sensitization by skin contact. Toxic to aquatic organisms. Safety Phrases (S): (2-)28-37/39-61 - Keep out of reach of children. After contact with skin, was immediately with plenty of soap and water. Wear suitable gloves and eye/face protection. Avoid release to the environment. Refer to special instructions/SDS

SAFETY DATA SHEET

Page 5 of 6 **HFT-90631A**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 7/29/2015 16. OTHER INFORMATION WARNING! CAUSES SERIOUS EYE IRRITATION. CAUSES SKIN IRRITATION. TOXIC TO AQUATIC LIFE WITH 16.1 Other Information: LONG LASTING EFFECTS. Use only as directed. Do not breathe fumes. Avoid contact with skin. If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label where possible. Avoid release to the environment. KEEP LOCKED UP AND OUT OF REACH OF CHILDREN. 16.2 Terms & Definitions: See last page of this Safety Data Sheet. 16.3 Disclaimer: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Harbor Freight Tools USA, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition 16.4 Prepared for: Harbor Freight Tools USA, Inc. 26541 Agoura Road HARBOR FREIGHT TOOLS

Quality Tools at Ridiculously Low Prices Calabasas, CA 91302 USA Tel: +1 (805) 388-1000 http://www.harborfreight.com/ 16.5 Prepared by: ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700

http://www.shipmate.com

HARBOR FREIGHT TOOLS

SAFETY DATA SHEET

Page 6 of 6 **HFT-90631A**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 7/29/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
EXPOSURE	LIMITS IN AIR:
ACGIH	American Conference on Governmental Industrial Hygienists
С	Ceiling Limit
ES	Exposure Standard (Australia)
IDLH	Immediately Dangerous to Life and Health
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

FIRST AID MEASURES:


CPR Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.

HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard			
1	Slight Hazard			
2	2 Moderate Hazard			
3 Severe Hazard				
4 Extreme Hazard				



PERSONAL PROTECTION RATINGS:







Splash Goggles





Synthetic Apron

Protective Clothing & Full Suit

Dust Respirator









OTHER STANDARD ABBREVIATIONS:


ML	ML Maximum Limit			
mg/m3	milligrams per cubic meter			
NA	Not Available			
ND Not Determined				
NE Not Established				
NF Not Found				
NR	No Results			
ppm parts per million				
SCBA Self-Contained Breathing Apparatus				

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:								
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition							
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source							
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source							

HAZARD RATINGS:

0	Minimal Hazard				
1	Slight Hazard				
2	Moderate Hazard				
3	Severe Hazard				
4	Extreme Hazard				
ACD	Acidic				
ALK	Alkaline				
COR	Corrosive				
₩	Use No Water				
ох	Oxidizer				
TREFOIL	Radioactive				



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s			
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal			
ppm	Concentration expressed in parts of material per million parts			
TD _{io}	Lowest dose to cause a symptom			
TCLo	Lowest concentration to cause a symptom			
TD _{io} , LD _{io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects			
TC, TC _o , LC _{lo} , & LC _o				
IARC	International Agency for Research on Cancer			
NTP	National Toxicology Program			
RTECS	Registry of Toxic Effects of Chemical Substances			
BCF	Bioconcentration Factor			
TL _m	Median threshold limit			
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution			

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NOHSC	National Occupational Health and Safety Commission (Australia)
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

	③	(2)		\odot	(1)		R
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

		M	*			×	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\		
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environ- ment



Hazard Identification:

SAFETY DATA SHEET

Page 1 of 6 **HFT-90631B**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 7/29/2015

1. PRODUCT & COMPANY IDENTIFICATION

		11 1 1(0) 001 & 001111 /11(1 1) 21(1) 11 10/(1) 01(
1.1	Product Name:	EPOXY PUTTY STICK – PART B (HARDENER)
1.2	Chemical Name:	Epoxy Resin Hardener
1.3	Synonyms:	P/N 90631B
1.4	Trade Names:	Harbor Freight Tools
1.5	Product Uses & Restrictions:	Part B of 2-Part Epoxy Resin Kit
1.6	Distributor's Name:	Harbor Freight Tools USA, Inc.
1.7	Distributor's Address:	26541 Agoura Road, Calabasas, CA 91302 USA
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687)
1.9	Business Phone / Fax:	+1 (805) 388-1000

This product is a kit or multipart products, which consist of multiple, independently packaged components. An SDS for each of these components is included. Please do not separate the component SDSs from this cover page. The document number of the SDS's for components of this product are: 90631A and 90631B.

2. HAZARDS IDENTIFICATION

This product is classified as a HAZARDOUS SUBSTANCE but not as DANGEROUS GOODS

according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia).

WARNING! MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION.

Classification: Skin Sens. 1; Eye Irrit. 2

Hazard Statements (H): H317 – May cause an allergic skin reaction. H319 – Causes serious eye irritation.

Precautionary Statements (P): P261 – Avoid breathing dust/vapors. P264 – Wash thoroughly after handling. P272 – Contaminated work clothing should not be allowed out of the workplace. P280 – Wear protective gloves/ eye protection/ face protection. P302+P352 – IF ON SKIN: Wash with plenty of water. P333+P313 – If skin irritation or rash occurs: Get medical advice/attention. P321 – Specific treatment see this container label. P305 + P351 + P338 – IF IN EYES: Rinse cautiously



3. COMPOSITION & INGREDIENT INFORMATION

contents/container to a licensed treatment, storage or disposal facility (TSDF).

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 – If eye irritation persists: Get medical advice/attention. P501 – Dispose of

	0. 0	O OO		U. \ _ U.			O: \:	***	. • . •				
					EXPOSURE LIMITS IN AIR (mg/m³)								
					AC	GIH		NOHSC	:		OSHA		
					p	pm		ppm			ppm		
							ES-	ES-	ES-				
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER
MERCAPTAN-TERMINATED	NA	NA	NA	60-100	NA	NA	NF	NF	NF	NA	NA	NA	
POLYMER (PROPRIETARY)													

			4. FIRST AID MEASURES
4.1	First Aid:	Ingestion:	If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
		Eyes:	Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes lifting upper and lower lids, occasionally.
		Skin:	Wash thoroughly with soap and water. In case of contact, immediately flush skin with plenty of water for at least 15 minutes.
		Inhalation:	Remove victim to fresh air at once. If breathing is difficult, administer oxygen. If breathing stops give artificial respiration. Keep person warm, quiet and get medical attention.
4.2	Effects of Exposure:	Ingestion:	If product is swallowed, may cause gastrointestinal disturbance.
		Eyes:	Exposure to dust may cause eye irritation. Symptoms of overexposure may include redness, itching, irritation and watering.
		Skin:	May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.
		Inhalation:	Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract.
4.3	Symptoms of Overexposure:	Ingestion:	If product is swallowed, may cause gastrointestinal disturbance.
		Eyes:	Exposure to dust may cause eye irritation. Symptoms of overexposure may include redness, itching, irritation and watering.
		Skin:	May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.
		Inhalation:	Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.

SAFETY DATA SHEET

Page 2 of 6 **HFT-90631B**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 7/29/2015 4. FIRST AID MEASURES - cont'd 44 Acute Health Effects: Non-irritating when used as directed. Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of dust can cause coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. Non-irritating when used as directed. Possible allergic dermatitis in some sensitive individuals. 4.5 Chronic Health Effects: 4.6 Target Organs: Eves, Skin. 47 Medical Conditions HEALTH Pre-existing dermatitis, other skin conditions. 2 Aggravated by Exposure: **FLAMMABILITY** 1 PHYSICAL HAZARDS 1 PROTECTIVE EQUIPMENT В **EYES** SKIN 5. FIREFIGHTING MEASURES 5.1 Fire & Explosion Hazards: This material can burn but will not readily ignite. However, if involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO, CO_X, Hydrocarbons). Extinguishing Methods: 5.2 CO₂, Dry Chemical, Alcohol Foam. Use water spray to cool containers 5.3 Firefighting Procedures: Keep containers cool until well after the fire is out. Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fireexposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil-over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES Spills Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For large spills (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION 7 1 Work & Hygiene Practices: Do not eat, drink or smoke when handling this product. Handle as to avoid puncturing container(s). Wash unintentional residues with soap and warm water. Keep tightly closed when not in use. Avoid contact with skin and clothing 7.2 Storage & Handling: Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Avoid temperatures above 120 °F. Keep away from incompatible substances. Protect containers from physical damage. Avoid breathing vapor. 7.3 Special Precautions: Clean all spills promptly. Spilled material may present a slipping hazard. 8. EXPOSURE CONTROLS & PERSONAL PROTECTION Exposure Limits: ACGIH NOHSC OTHER 8.1 OSHA ppm (mg/m³) CHEMICAL NAME(S) TLV STEL ES-TWA ES-STEL ES-PEAK STEL NA NA NF NF NF NA NA NA 8.2 Ventilation & Engineering General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station) 8.3 Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. In instances where mist or vapors of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia.

SAFETY DATA SHEET

Page 3 of 6

HARBOR FREIGHT TOOLS HFT-90631B Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 7/29/2015 8. EXPOSURE CONTROLS & PERSONAL PROTECTION – cont'd Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. 8 4 Eye Protection: Always use protective eyewear when cleaning spills or leaks. Wear goggles and/or face shield if splashing or spraying is anticipated. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants. Have suitable eye wash water available. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU) 8.5 Hand Protection: Use gloves constructed of chemical-resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, or the EU member states. 8.6 Body Protection: Avoid prolonged and/or repeated skin contact. Use clean and impervious protective clothing (e.g., neoprene or Tyvek®) if splashing or spraying conditions are present. Protective clothing should include long-sleeves, apron, boots and additional facial protection. If necessary, refer to appropriate standards of Canada, the EU member states, or U.S. OSHA. 9. PHYSICAL & CHEMICAL PROPERTIES Appearance: Light colored transparent syrup 9.2 Odor: Mild sulfur odor 9.3 Odor Threshold: NA 9.4 pH: NA Melting Point/Freezing Point: 9.5 NA Initial Boiling Point/Boiling 9.6 NA Range: 97 Flashpoint: > 110 °C (230 °F) DIN 51758 9.8 Upper/Lower Flammability NA 9.9 Vapor Pressure: < 0.1 Pa 9 10 Vapor Density: 1.1 g/cm3 @ 25 °C 9.11 Relative Density: 1.17 9.12 Solubility: Slightly soluble Partition Coefficient (log Pow): 9.13 NA 9.14 Autoignition Temperature NA 9.15 Decomposition Temperature NA NΑ 9.16 Viscosity 9.17 Other Information: This product is VOC compliant for sale in California. 10. STABILITY & REACTIVITY 10.1 Stability: Stable under normal conditions; unstable with heat or contamination. 10.2 Hazardous Decomposition Oxides of carbon (CO, CO₂). Products: 10.3 Hazardous Polymerization: Will not occur. 10.4 Conditions to Avoid: Open flames, sparks, high heat, incompatible substances and direct sunlight. 10.5 Incompatible Substances: Avoid extreme heat and ignition sources. Oxidizing agents, strong acids, strong bases 11. TOXICOLOGICAL INFORMATION Inhalation: Routes of Entry: YES Absorption: YES Ingestion: YES 11.1 11.2 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product, but is not presented in this document. 11.3 Acute Toxicity: See Section 4.4 11.4 Chronic Toxicity See Section 4.5 Suspected Carcinogen 11.5 No Reproductive Toxicity: 11.6 This product is not reported to produce reproductive toxicity in humans. Mutagenicity This product is not reported to produce mutagenic effects in humans. Embryotoxicity This product is not reported to produce embryotoxic effects in humans. Teratogenicity This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. Irritancy of Product: 11.7 The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. 11.8 Biological Exposure Indices NE 11.9 Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION Environmental Stability: There are no specific data available for this product 12.1

There are no specific data available for this product

There are no specific data available for this product

12.2

12.3

Effects on Plants & Animals:

Effects on Aquatic Life:

SAFETY DATA SHEET

Page 4 of 6 HFT-90631B

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 7/29/2015 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Dispose of in accordance with federal, state, provincial and local regulations. 13 2 Special Considerations: 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): 14.1 **NOT REGULATED** 14.2 IATA (AIR): NOT REGULATED 14.3 IMDG (OCN): **NOT REGULATED** TDGR (Canadian GND): 14.4 NOT REGULATED 14.5 ADR/RID (EU): NOT REGULATED 14.6 SCT (MEXICO) **NOT REGULATED** 14.7 ADGR (AUS): NOT REGULATED 15. REGULATORY INFORMATION 15.1 SARA Reporting This product does not contain any substances subject to SARA Title III, section 313 reporting requirements. Requirements 15.2 SARA Threshold Planning There are no specific Threshold Planning Quantities for the components of this product. Quantity: 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory or are otherwise exempt. CERCLA Reportable Quantity 15.4 NA 15.5 Other Federal Requirements: NA Other Canadian Regulations: This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. 15.7 State Regulatory Information: No ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). 15.8 Other Requirements: The primary components of this product are listed in Annex I of EU Directive 67/548/EEC:

<u>Mercaptan-Terminated Polymer</u>: Irritant (Xi); Environmental danger (N). <u>Risk Phrases</u> (R): 36/38-43-51/53 – Irritating to eyes and skin. May cause sensitization by skin contact. Toxic to aquatic organisms. <u>Safety Phrases</u> (S): (2-)28-37/39-61 – Keep out of reach of children. After contact with skin, was immediately with plenty of soap and water. Wear suitable gloves and eye/face protection.

Avoid release to the environment. Refer to special instructions/SDS

SAFETY DATA SHEET

Page 5 of 6 **HFT-90631B**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 7/29/2015 16. OTHER INFORMATION WARNING! CAUSES SERIOUS EYE IRRITATION. CAUSES SKIN IRRITATION. TOXIC TO AQUATIC LIFE WITH 16.1 Other Information: LONG LASTING EFFECTS. Use only as directed. Do not breathe fumes. Avoid contact with skin. If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label where possible. Avoid release to the environment. KEEP LOCKED UP AND OUT OF REACH OF CHILDREN. 16.2 Terms & Definitions: See last page of this Safety Data Sheet. 16.3 Disclaimer: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Harbor Freight Tools, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. 16.4 Prepared for: Harbor Freight Tools USA, Inc. 26541 Agoura Road HARBOR FREIGHT TOOLS

Quality Tools at Ridiculously Low Prices Calabasas, CA 91302 USA Tel: +1 (805) 388-1000 http://www.harborfreight.com/ 16.5 Prepared by: ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600

> Fax: +1 (310) 370-5700 http://www.shipmate.com

HARBOR FREIGHT TOOLS

SAFETY DATA SHEET

Page 6 of 6 HFT-90631B

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision Date: 7/29/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number						
EXPOSURE	EXPOSURE LIMITS IN AIR:						
ACGIH	American Conference on Governmental Industrial Hygienists						
С	Ceiling Limit						
ES	Exposure Standard (Australia)						
IDLH	Immediately Dangerous to Life and Health						
OSHA	U.S. Occupational Safety and Health Administration						
PEL	Permissible Exposure Limit						
STEL	Short-Term Exposure Limit						
TLV	Threshold Limit Value						
TWA	Time Weighted Average						

FIRST AID MEASURES:

Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.


HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard				
1	Slight Hazard				
2	Moderate Hazard				
3	Severe Hazard				
4	Extreme Hazard				



PERSONAL PROTECTION RATINGS:

F LIN	JONAL I	KOILC	IION IX	111100.
Α				
В				
С				
D				
E				
F				











Synthetic Apron







Dust & Vapor Half-Mask Respirator





OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit			
mg/m3	milligrams per cubic meter			
NA Not Available				
ND	Not Determined			
NE	Not Established			
NF	Not Found			
NR	No Results			
ppm	parts per million			
SCBA Self-Contained Breathing Apparatus				

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:					
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition				
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source				
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source				

HAZARD RATINGS:

0	Minimal Hazard			
1	Slight Hazard			
2	Moderate Hazard			
3	Severe Hazard			
4	Extreme Hazard			
ACD	Acidic			
ALK	Alkaline			
COR	Corrosive			
₩	Use No Water			
ох	Oxidizer			
TREFOIL	Radioactive			



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{io}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{io} , LD _{io} , & LD _o or TC, TC _o , LC _{io} , & LC _o	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NOHSC	National Occupational Health and Safety Commission (Australia)
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	(*)	(2)		\odot	(1)		R
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

T.		*	*			×	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

						\		
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environ- ment