

Page 1 of 6 **HFT-92581** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 12/24/2015

		1. PRODUCT & COMPANY IDENTIFICATION
1.1	Product Name:	CRC CUTTING OIL THREAD CUTTING LUBRICANT (AEROSOL)
1.2	Chemical Name:	NA
1.3	Synonyms:	P/N 92581
1.4	Trade Names:	CRC Thread Cutting Lubricant (Aerosol)
1.5	Product Uses & Restrictions:	Aerosol Lubricant
1.6	Distributor's Name:	Harbor Freight Tools USA, Inc.
1.7	Distributor's Address:	26541 Agoura Road, Calabasas, CA 91302 USA
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687)
1.9	Business Phone / Fax:	+1 (805) 388-1000

### 2. HAZARDS IDENTIFICATION

2.1 Hazard Identification: This product is classified as a hazardous substance and as dangerous goods according to the classification criteria of [NOHSC: 1088 (2004)] and ADG Code (Australia).

DANGER! EXTREMELY FLAMMABLE AEROSOL. PRESSURIZED CONTAINER MAY BURST IF HEATED. MAY BE HARMFUL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION.

Classification: Aerosol 1; Acute Tox. 4; Asp. Tox. 1; Skin Irrit. 2; Eye Irrit. 2.

<u>Hazard Statements</u> (H): H222 – Extremely flammable aerosol. H229 – Pressurized container may burst if heated. H304 – May be fatal if swallowed and enters airways. H315 – Causes skin irritation. H319 – Causes serious eye irritation.

Precautionary Statements (P): P210 – Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. P211 – Do not spray on an open flame or other ignition source. P251 – Do not pierce or burn, even after use. P410+P412 – Protect from sunlight. Do not expose to temperatures exceeding 50 °F (122 °F). P264 – Wash thoroughly with soap and water after handling. P270 – Do not eat, drink or smoke when using this product. P301+P312 – IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. P330 – Rinse mouth. P501 – Dispose of contents/container to licenses treatment, storage and disposal facility (TSDF). P280 – Wear protective gloves/protective clothing/eye protection/face protection. P302+P352 – IF ON SKIN: Wash with plenty of soap and water. P321 – Specific treatment – see Section 4 of this Safety Data Sheet. P332+P313 – If skin irritation occurs: Get medical advice/attention. P362+P364 – Take off contaminated clothing and wash it before reuse. P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 – If eye irritation persists: get medical advice/attention.



# 3. COMPOSITION & INGREDIENT INFORMATION

								EXPO	SURE L	MITS IN	AIR (mg	g/m³)	
					AC	GIH		NOHSC			OSHA		
					pp	m		ppm			ppm		
							ES-	ES-	ES-				
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER
SEVERELY HYDROTREATED	64742-52-5	NA	265-155-0	70-80	(5)	(10)	(5)	NA	NA	(5)	NA	NA	OIL MIST
NAPHTHENIC PETROLEUM OIL*	* contains less th	an 3% DMSO; As	p. Tox. 1; H304										
PETROLEUM GASES,	68476-86-8	NA	270-705-8	15-25	NA	NA	NF	NF	NF	5	NA	NA	MIST
LIQUEFIED, SWEETENED	Flam. Gas 1; Liq.	Gas 1; Acute Tox	x. 4; H220, H280	), H332									
PROPRIETARY ADDITIVE	NA	NA	NA	2-6	NA	NA	NF	NF	NF	NA	NA	NA	
PROPRIETART ADDITIVE						•							

## 4 FIRST AID MEASURES

			4. FIRST AID MEASURES
4.1	First Aid:	Ingestion:	DO NOT INDUCE VOMITING. Contact ChemTrec +1 (800) 424-9300 or the nearest Poison Control
			Center or local emergency telephone number for assistance and instructions. Seek immediate medical
			attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of
			aspiration.
		Eyes:	If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 minutes,
			holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following
			use, consult a physician or emergency room immediately.
		Skin:	Remove contaminated clothing and wash affected areas with soap and water. If discomfort persists
			and/or the skin reaction worsens, contact a physician immediately. Do not wear contaminated clothing until
			after it has been properly cleaned.
		Inhalation:	Remove victim to fresh air at once. Under extreme conditions, if breathing stops, perform artificial
			respiration. Seek immediate medical attention.



Page 2 of 6 **HFT-92581** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 12/24/2015 4. FIRST AID MEASURES - cont'd 42 Effects of Exposure: If product is swallowed, may cause gastrointestinal disturbance. Ingestion: Exposure to mist/fumes/vapors/spray may cause eye irritation. Symptoms of overexposure may include Eyes: redness, itching, irritation and watering. May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in Skin: some sensitive individuals. Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, Inhalation: nose and respiratory tract. 4.3 Symptoms of Overexposure: Ingestion: If product is swallowed, may cause gastrointestinal disturbance. Exposure to mist/fumes/vapors/spray may cause eye irritation. Symptoms of overexposure may include Eyes: redness, itching, irritation and watering. May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in Skin: some sensitive individuals. Inhalation: Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. 4.4 Acute Health Effects Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of mist/fumes/vapors/spray can cause coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. 4.5 Chronic Health Effects: Possible allergic dermatitis in some sensitive individuals. 4.6 Target Organs: Eyes, Skin, Respiratory System, Lungs, Central Nervous System (CNS) 4.7 Medical Conditions Pre-existing dermatitis, other skin conditions, and disorders of the **HEALTH** 1 Aggravated by Exposure: target organs (eyes, skin, respiratory system, CNS) or impaired kidney **FLAMMABILITY** 4 function may be more susceptible to the effects of this substance. 1 PHYSICAL HAZARDS PROTECTIVE EQUIPMENT X **EYES** SKIN LUNGS 5. FIREFIGHTING MEASURES Fire & Explosion Hazards: Level 3 Aerosol (NFPA 30B). Aerosols may burst at temperatures above 120 °F. Cool uninvolved containers to prevent possible bursting. Aerosols may be projectile hazards when bursting. If aerosols are bursting, stay clear until bursting is complete. Do not use in presence of open flames or sparks. Do not place in hot water or near radiators, stoves or other sources of heat. Exposure to heat or sunlight may cause cans to burst and propel contents. Water from fog nozzles may be helpful in cooling un-ruptured containers to prevent build-up. Water Fog, Foam, Dry Chemical, CO<sub>2</sub> 5.2 Extinguishing Methods: 5.3 Firefighting Procedures: As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES Spills Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing

promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal

sewers and open bodies of water.



Page 3 of 6 **HFT-92581** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 12/24/2015

		7. HANDLING 8	) STC	DAC	E INIEC	DMAT	TION!				
7.1	Work & Hygiona Dragtigas:	Avoid prolonged contact with the pr						Hoo in	o well vo	ntilated la	ootion (o.a.
7.1	Work & Hygiene Practices:	local exhaust ventilation, fans). At smoke while handling product.									
7.2	Storage & Handling:	Keep this material away from heat, closed tightly when not in use.	Empty (	container	may cor	tain resid	lual amou	nts of t	his produ	uct; there	fore, empty
		containers should be handled with sources, or sources of intense heat	t. Stora	age temp	erature: 3	2-120 °F (	0-49 °C).				
7.3	Special Precautions:	static discharge. Store away from in Open containers slowly on a stable	e surfac	e. Keep	containe	r tightly c	losed whe			mpty con	tainers may
		contain residual amounts of this pro	duct; the	erefore, e	empty conf	tainers sh	ould be ha	ndled w	ith care.		
		8. EXPOSURE CONTR	ROLS	& PE	RSON	AL PR	OTEC	ΓΙΟΝ			_
8.1	Exposure Limits: ppm (mg/m³)			GIH		NOHSC	T		OSHA	l	OTHER
1	ppin (ing/iii )	CHEMICAL NAME(S) SEVERELY HYDROTREATED	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		NAPHTHENIC PETROLEUM OIL	(5)	(10)	(5)	NA	NA	(5)	NA	NA	OIL MIST
		HYDROCARBON PROPELLANT	NA	NA	NF	NF	NF	5	NA	NA	MIST
8.2	Ventilation & Engineering Controls:	Use local or general exhaust ventil handling of this product. Ensure a wash station).									
8.3	Respiratory Protection:	No special respiratory protection necessary, use only respiratory §1910.134, or applicable U.S. state EU member states, or Australia.	protection	on autho	rized per	U.S. 08	SHA's req	uiremer	it in 29	CFR	
8.4	Eye Protection:	Wear protective eyewear (e.g., safe Always use protective eyewear wh soft lenses may absorb and concen	en clea	ning spill							
8.5	Hand Protection:	If anticipated that prolonged & reperubber gloves for routine industria	ated ski I use.	in contact	sary, refei						D
8.6	Body Protection:	appropriate standards of Canada, o  No special body protection is re- appropriate protective clothing to proceed to appropriate standards.	quired in revent s	under ty kin conta	pical circu act, (boots	, lab coat,	apron, co	veralls)	as neede	Wear ed. If	
		9. PHYSICAL 8	k CHE		AL PRO	PERI	IE9				
9.1	Appearance: Odor:	Aerosol, brown liquid									
9.2	Odor Threshold:	Petroleum odor									
9.4	pH:	NA NA									
9.4	Melting Point/Freezing Point:	NA NA									
9.6	Initial Boiling Point/Boiling	NA									
	Range:	>260 °C (500 °F)									
9.7	Flashpoint:	>149 °C (300 °F) COC									
9.8	Upper/Lower Flammability Limits:	NA									
9.9	Vapor Pressure:	NA									
9.10	Vapor Density:	>5									
9.11	Relative Density:	0.924									
9.12	Solubility:	Negligible									
9.13	Partition Coefficient (log Pow):	NA NA									
9.14	Autoignition Temperature:	>315 °C (600 °F)									
9.15	Decomposition Temperature:	NA NA									
9.16	Viscosity:	NA									
9.17	Other Information:	VOC Content: 20%; 184.8 g/L; 1.54	lbs/gal.								
		10. STAB	BILITY	/ & RI	EACTI	VITY					
10.1	Stability:	Stable under normal conditions; uns	stable w	ith heat c	r contamii	nation.					
10.2	Hazardous Decomposition Products:	Change in color signifies exposure Discard solution.	e to ultra	aviolet liç	ght or exc	eeding sh	nelf life. V	Vill not	degrade	to unstab	le products.
10.3	Hazardous Polymerization:	Will not occur.									
10.4	Conditions to Avoid:	Open flames, sparks, high heat, inc	ompatib	le substa	nces and	direct sun	light.				
10.5	Incompatible Substances:	Avoid extreme heat and ignition sou	ırces. St	ore away	from oxio	lizers.					
		<u>-</u>		•							



Page 4 of 6 **HFT-92581** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 12/24/2015 11. TOXICOLOGICAL INFORMATION 11.1 Routes of Entry: Inhalation: NO Absorption: YES Ingestion: YES 11 2 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product, but is not presented in this document 11.3 Acute Toxicity: Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. 11.4 Chronic Toxicity: This material may aggravate any pre-existing skin condition (e.g., dermatitis). 11.5 Suspected Carcinogen NA 11.6 Reproductive Toxicity This product is not reported to cause reproductive toxicity in humans. Mutagenicity This product is not reported to produce mutagenic effects in humans. Embryotoxicity This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. 11.7 Irritancy of Product: The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. 11.8 Biological Exposure Indices: 11.9 Physician Recommendations: Treat symptomatically 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: An environmental hazard cannot be excluded in the event of improper handling or disposal. Effects on Plants & Animals 12.2 NA 12.3 Effects on Aquatic Life: There are no specific data available for this product. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Dispose of in accordance with federal, state, provincial and local regulations. Special Considerations: 13.2 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L) - until 12/31/20 UN1950, AEROSOLS, 2.1 (LTD QTY, IP ≤ 1.0 L) 14 2 IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) -∢flb√Y UN1950, AEROSOLS, FLAMMABLE, 2.1 (> 1.0 L) 14.3 IMDG (OCN): UN1950, AEROSOLS, 2.1 (LTD QTY, IP ≤ 1.0 L) 14.4 TDGR (Canadian GND): MARK PACKAGE ("LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE"  $\leq 1.0$  L) or UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP  $\leq 1.0$  L) 14.5 ADR/RID (EU): UN1950, AEROSOLS, 2.1 (LTD QTY, IP ≤ 1.0 L) 14.6 SCT (MEXICO): UN1950, AEROSOLES, 2.1 (CANTIDAD LIMITADA, IP ≤ 1.0 L) ADGR (AUS): 14.7 UN1950, AEROSOLS, 2.1 (LTD QTY, IP  $\leq$  1.0 L) 15. REGULATORY INFORMATION SARA Reporting 15.1 This product does not contain any substances subject to SARA Title III, Section 313 reporting requirements. 15.2 SARA Threshold Planning Quantity: 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory or are otherwise exempt. 15.4 CERCLA Reportable Quantity NA (RQ): 15.5 Other Federal Requirements: 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS Class B5, D2B (Flammable Aerosol, Other Toxic Effects).



Page 5 of 6 **HFT-92581** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS R

SDS Revision: 1.1

SDS Revision Date: 12/24/2015

		15. REGULATORY INFO	RMATION – cont'd
15.7	State Regulatory Information:	state criteria lists: California Proposition 65 Substances List (FL), Massachusetts Hazardo Minnesota Hazardous Substances List (MN), Nev	in a concentration of 1.0% or greater, are listed on any of the following (CA65), Delaware Air Quality Management List (DE), Florida Toxic Dus Substances List (MA), Michigan Critical Substances List (MI), W Jersey Right-to-Know List (NJ), New York Hazardous Substances List Washington Permissible Exposures List (WA), Wisconsin Hazardous
15.8	Other Requirements:	Phrases (S): 2-23-24-62 - Keep away from child	sted in Annex I of EU Directive 67/548/EEC:  10-20 – Flammable. Harmful by inhalation. Safety dren. Do not breathe fumes/spray. Avoid contact seek medical advice immediately and show this
		16. OTHER INFO	DRMATION
16.2	Other Information:  Terms & Definitions:	HARMFUL IF SWALLOWED. CAUSES SKIN II heat, hot surface, sparks, open flames and other ignition source. Do not pierce or burn, even after 50 °F (122 °F). Wash thoroughly with soap ar product. IF SWALLOWED: Call a POISON contents/container to licenses treatment, stora clothing/eye protection/face protection. IF ON S medical advice/attention. Take off contaminated water for several minutes. Remove contact lense get medical advice/attention. KEEP OUT OF RE See last page of this Safety Data Sheet.	
16.3	Disclaimer:	government regulations must be reviewed for an Tools USA, Inc.'s knowledge, the information accuracy, suitability or completeness is not guar provided. The information contained herein relationships to the information contained herein relationships the	OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other oplicability to this product. To the best of ShipMate's & Harbor Freight contained herein is reliable and accurate as of this date; however, anteed and no warranties of any type, either expressed or implied, are stee only to the specific product(s). If this product(s) is combined with be considered. Data may be changed from time to time. Be sure to
16.4	Prepared for:	Harbor Freight Tools USA, Inc. 26541 Agoura Road Calabasas, CA 91302 USA Tel: +1 (805) 388-1000 http://www.harborfreight.com/	HARBOR FREIGHT TOOLS  Quality Tools at Ridiculously Low Prices
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com	

Page 6 of 6 **HFT-92581** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 12/24/2015

# **DEFINITION OF TERMS**

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

#### **GENERAL INFORMATION:**

CAS No.	Chemical Abstract Service Number

#### **EXPOSURE LIMITS IN AIR:**

ACGIH	American Conference on Governmental Industrial Hygienists
С	Ceiling Limit
ES	Exposure Standard (Australia)
IDLH	Immediately Dangerous to Life and Health
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

#### FIRST AID MEASURES:


CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.


#### HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



#### PERSONAL PROTECTION RATINGS:





















Dust & Vapor Half-Mask Respirator

Full Face Respirato

Airline Hood/Mask or SCBA

## OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit
mg/m3	milligrams per cubic meter
NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR	No Results
ppm	parts per million
SCBA	Self-Contained Breathing Apparatus

#### NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILI <sup>*</sup>	TY LIMITS IN AIR:
	Minimum temperature required to initiate combustion in air with no other
Temperature	source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will
	explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will
	explode or ignite in the presence of an ignition source

#### **HAZARD RATINGS:**

Slight Hazard
Silgrit Hazaru
Moderate Hazard
Severe Hazard
Extreme Hazard
Acidic
Alkaline
Corrosive
Use No Water
Oxidizer
Radioactive



#### TOXICOLOGICAL INFORMATION:

LD <sub>50</sub>	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC <sub>50</sub>	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD <sub>io</sub>	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD <sub>Io</sub> , LD <sub>Io</sub> , & LD <sub>o</sub> or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC <sub>o</sub> , LC <sub>io</sub> , & LC <sub>o</sub>	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL <sub>m</sub>	Median threshold limit
log K <sub>ow</sub> or log K <sub>oc</sub>	Coefficient of Oil/Water Distribution

#### **REGULATORY INFORMATION:**

WHMIS	Canadian Workplace Hazardous Material Information System						
DOT	U.S. Department of Transportation						
TC	Transport Canada						
EPA	U.S. Environmental Protection Agency						
DSL	Canadian Domestic Substance List						
NOHSC	National Occupational Health and Safety Commission (Australia)						
NDSL	Canadian Non-Domestic Substance List						
PSL	Canadian Priority Substances List						
TSCA	U.S. Toxic Substance Control Act						
EU	European Union (European Union Directive 67/548/EEC)						
WGK	Wassergefährdungsklassen (German Water Hazard Class)						
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System						

## WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

	<b>*</b>	<b>(</b>		$\odot$	(18)		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

### EC (67/548/EEC) INFORMATION:

		*	*		<b>®</b>	×	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

## CLP/GHS (1272/2008/EC) PICTOGRAMS:

			$\Diamond$			<b>\limits</b>	<b>***</b>	
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environ- ment