

Hazard Identification:

SAFETY DATA SHEET

Page 1 of 6 HFT-93242

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0


SDS Revision Date: 4/30/2015

1.1	Product Name:	
1.1	Floudet Name.	BATTERY FOR LASER MARKER
1.2	Chemical Name:	Alkaline Battery
1.3	Synonyms:	P/N 93242
1.4	Trade Names:	Central Machinery
1.5	Product Uses & Restrictions:	Electric Storage Battery
1.6	Distributor's Name:	Harbor Freight Tools, Inc.
1.7	Distributor's Address:	26541 Agoura Road, Calabasas, CA 91302 USA
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687)
1.9	Business Phone / Fax:	+1 (805) 388-1000

2. HAZARDS IDENTIFICATION

classification criteria of [NOHSC: 1088 (2004)] and ADG Code (Australia). WARNING! HARMFUL IF SWALLOWED. TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS. Hazard Statements (H): H302 - Harmful if swallowed. H411 - Toxic to aquatic life with long lasting effects. Precautionary Statements (P): P264 - Wash hands and exposed skin areas with soap and warm water thoroughly after handling. P270 - Do not eat, drink or smoke while sing this product. P273 -Avoid release to the environment. P280 - Wear protective gloves/eye protection. P301+P312 - IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. P330 - Rinse mouth. P391 -Collect spillage. P501 - Dispose of contents/container to licenses treatment, storage and disposal facility (TSDF).

collect, day or night. In Canada, call +1 (416) 813-5900.



3. COMPOSITION & INGREDIENT INFORMATION

IF INGESTED: Call the NATIONAL BATTERY INGESTION HOTLINE at +1 (202) 625-3333

								EXPO	SURE L	IMITS IN	I AIR (m	g/m³)	
					AC	GIH		NOHSC			OSHA		
					pp	m		ppm			ppm		
0.1.5.4.0.1. 1.1.4.5.(0)		DTE 00 11					ES-	ES-	ES-				071150
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER
MANGANESE DIOXIDE	1313-13-9	OP0350000	215-202-6	20-60	(5)	NA	(5)	NF	NF	(5)	NA	NA	
WANGANESE DIOXIDE	Acute Tox. Oral 4; Acute Tox. Inh. 4; H302, H332												
ZINC	7440-66-6	ZG8600000	231-175-3	5-15	NA	NA	NF	NF	NF	NA	NA	NA	
ZINC	Aquatic Acute	1; Aquatic Chroni	c 1; H400, H410										
DOTA SSILIM LIVEDOVIDE	1310-58-3	TT2100000	215-181-3	0-22	NA	NA	(2)	NF	NF	NA	NA	NA	
POTASSIUM HYDROXIDE	Acute Tox. Oral 4; Acute Tox. Inh. 4; H302, H332												
GRAPHITE	7782-42-5	MD9659600	231-955-3	5-10	(2.0)	NA	(2.0)	NF	NF	(5)*	NA	NA	RESP FRAC
GRAPHITE													
SODILIM LIVEROVIDE	1310-73-2	WB4900000	215-185-5	10-30	(2)	NA	(2)	NF	NF	(2)	NA	(10)	(2) NIOSH
SODIUM HYDROXIDE	Skin Corrosion 1A; H314												

EIDST AID MEASIIDES

			4. FIRST AID MEASURES
4.1	First Aid:	Ingestion:	Give large quantities of water, but do NOT induce vomiting. Never give anything by mouth to an unconscious person. Contact the nearest Poison Control Center or local emergency telephone number for assistance and instructions. Seek immediate medical attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.
		Eyes:	If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 minutes, holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately.
		Skin:	If an open battery cell: Remove contaminated clothing and wash affected areas with soap and water. If discomfort persists and/or the skin reaction worsens, contact a physician immediately. Do not wear contaminated clothing until after it has been properly cleaned.
		Inhalation:	Remove victim to fresh air at once. Under extreme conditions, if breathing stops, perform artificial respiration. Seek immediate medical attention.
4.2	Effects of Exposure:	Ingestion:	May cause severe irritation of mouth, throat, esophagus, and stomach. Acute ingestion of zinc compounds may cause abdominal pain, nausea, vomiting, diarrhea, and severe cramping.
		Eyes:	Severe irritation, burns, cornea damage, blindness.
		Skin:	Severe irritation, burns, and ulceration if open battery cell comes into contact with skin.
		Inhalation:	Inhalation of dust or fumes may cause irritation of upper respiratory tract and lungs.



Page 2 of 6 **HFT-93242**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 4/30/2015 4. FIRST AID MEASURES - cont'd Severe discomfort, nausea, vomiting and headache. Harmful if swallowed. May cause corrosion and 4.3 Symptoms of Overexposure: Ingestion: permanent tissue destruction of the esophagus and digestive tract. May cause irreversible eye injury. Contact with eyes may cause severe irritation, and possible eye burns. Eyes: Severe irritation, redness, and watering. Severe skin irritation, red, itching skin, burns and ulceration, if open battery cell comes into contact with Skin: Inhalation: May cause cyanosis (bluish discoloration of skin due to deficient oxygenation of the blood). Irritation may lead to chemical pneumonitis and pulmonary edema. Inhalation of fumes may cause metal fume fever, which is characterized by flu-like symptoms with metallic taste, fever, chills, cough, weakness, chest pain, muscle pain and increased white blood cell count. Causes respiratory tract irritation with possible burns. Acute Health Effects: 4.4 Hazardous exposure can occur only when product is heated above the melting point, oxidized or otherwise processed or damaged to create dust, vapor, or fume. 4.5 Chronic Health Effects: Chronic exposure may cause effects similar to those of acute exposure. Target Organs: 4.6 Eyes, Skin, Respiratory System. Medical Conditions **HEALTH** NA 1 Aggravated by Exposure: **FLAMMABILITY** 0 **PHYSICAL HAZARDS** 0 PROTECTIVE EQUIPMENT В **EYES** SKIN 5. FIREFIGHTING MEASURES This material can burn but will not readily ignite. However, if involved in a fire, this product may 5.1 Fire & Explosion Hazards: decompose at high temperatures to form toxic gases (e.g., CO, CO_x, Hydrocarbons). 5.2 Extinguishing Methods: CO₂, Dry Chemical, Alcohol Foam, Dry Chemical. Use water spray to cool containers. 5.3 Firefighting Procedures: Use extinguishing media most appropriate for the surrounding fire. Do NOT get water inside containers. For small fires, use dry chemical, carbon dioxide, or water spray. For large fires, use dry chemical, carbon dioxide, alcohol-resistant foam, or water spray. Cool containers with flooding quantities of water until well after fire is out. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES 6.1 Spills Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment, including protective gloves and eyewear. Plastic or rubber gloves, respirator, eye/face protection and chemical-resistant apron may be required for clean-up of large spills. Small Spills: Wear appropriate protective equipment including gloves and protective eyewear. Use a non-combustible material such as vermiculite or sand to soak up the product and place into a container for later disposal. Large Spills: Keep incompatible materials away from spill. Stay upwind and away from spill or release. Isolate immediate hazard area and keep unauthorized personnel out of area. Stop spill or release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant. Collect in acidresistant container. 7. HANDLING & STORAGE INFORMATION Work & Hygiene Practices: 7.1 Do not eat, drink or smoke when handling this product. Handle as to avoid puncturing container(s). 7.2 Storage & Handling: Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Keep away from incompatible substances. Protect containers from physical damage. Store product in wellfilled, appropriate coated and tightly closed containers avoiding influence of oxygen/air, light and humidity. Store at a cool and constant temperature. This battery is not designed for recharging. Recharging can cause battery leakage or high pressure rupture, in some 7.3 Special Precautions: cases. Inadvertent charging can happen if a battery is installed backwards. Accidental short circuit for a few seconds will not seriously affect the battery. But prolonged short circuit will cause the battery to lose energy, and can cause the

safety release vent to open. Sources of short circuit include jumbled batteries in bulk containers, metal jewelry, metal

covered tables or metal belts used for assembly of batteries in devices.



Page 3 of 6 **HFT-93242**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 4/30/2015

2	Exposure Limits: ppm (mg/m³) Ventilation & Engineering Controls:	CHEMICAL NAME(S) MANGANESE DIOXIDE GRAPHITE POTASSIUM HYDROXIDE SODIUM HYDROXIDE	TLV (5) (2.0)	STEL NA	ES-TWA	NOHSC	1		OSHA		OTHER
2	Ventilation & Engineering	MANGANESE DIOXIDE GRAPHITE POTASSIUM HYDROXIDE	(5)		ES-TWA	EO OTEL					
		GRAPHITE POTASSIUM HYDROXIDE	. ,	NΔ		ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		POTASSIUM HYDROXIDE	(2.0)	14/1	(5)	NF	NF	(5)	NA	NA	
				NA	(2.0)	NF	NF	(5)*	NA	NA	RESP FRAC
		SODIUM HYDROXIDE	NA	NA	(2)	NF	NF	NA	NA	NA	
			(2)	NA	(2)	NF	NF	(2)	NA	(10)	(2) NIOSH
3		General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).									
	Respiratory Protection:	instances where mist or vapors use only protection authorized	No special respiratory protection is required under typical circumstances of use or handling. In instances where mist or vapors of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia.								
4	Eye Protection:		Avoid eye contact. ANSI approved safety glasses with side shields should be used when handling or using this sealed electric storage battery.								
.5	Hand Protection:	Where contact is likely, impervious When handling large quantities of	of fluid (e	.g., ≥ 1	gallon (3.8	3 L)), wear	corrosion-	resistan	t gloves.		
6	Body Protection:	No apron required when handling sealed undamaged battery. Where contact is likely, corrosion-resistant apron, clothing and boots should be worn. Eye wash stations and deluge showers should be available.									
		9. PHYSICAL	_ & CI	HEMI	CAL P	ROPE	RTIES				
.1	Appearance:	Stainless steel top battery. Con	tents dar	k and a	rav in colo	r					
2	Odor:	No apparent odor (sealed).									
.3	Odor Threshold:	NA									
	pH:	NA NA									
	Melting Point/Freezing Point:	NA NA									
.6	Initial Boiling Point/Boiling Range:	NA NA									
.7	Flashpoint:	NA									
	Upper/Lower Flammability Limits:	NA									
	Vapor Pressure:	NA									
.10	Vapor Density:	NA									
.11	Relative Density:	NA									
.12	Solubility:	Sealed electric battery: Insoluble	€.								
.13	Partition Coefficient (log Pow):	NA									
14	Autoignition Temperature:	NA									
.15	Decomposition Temperature:	NA									
16	Viscosity:	NA									
.17	Other Information:	NA									
		10. ST	۱ BII I	TV &	PEAC	TIVITV	7				
0.1	Stability:										
0.2	Hazardous Decomposition Products:	Stable under normal conditions; Oxides of carbon (CO, CO ₂).	Thermal	degrada	ation may	produce h	nazardous	fumes o	f zinc a	nd man	ganese, hydrog
	Hazardous Polymerization:	gas, caustic vapors of potassiun	TIYUTUXI	ue and	other Haza	ardous by-	products.				
	Conditions to Avoid:	Will not occur.	in agrees	tible e	hatares	and direct	ounliebt -	nd in a a :-	on atible	oubsts:	
		Open flames, sparks, high heat,							•		
0.5	Incompatible Substances:	Avoid extreme heat and ignition circuit or recharge.	1 source	s. Store	away fro	III OXIDIZEI	s. Do not	exceed	neat, c	rusn, di	sassemble, she



Page 4 of 6 HFT-93242

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 4/30/2015 11. TOXICOLOGICAL INFORMATION Routes of Entry Ingestion: YES This product has NOT been tested on animals to obtain toxicology data. Toxicity Data: Toxicology data, found in scientific literature, is available for some of the components of the product and is presented below: Manganese Dioxide: LD₅₀ (oral, rat): 3,478 mg/kg. Sodium Hydroxide: LD_{50} (oral, mouse) = 6,600 mg/kg; LD_{50} (oral, rabbit) = 500 mg/kg. Acute Toxicity: 11.3 See section 4.4 Chronic Toxicity: 11.4 See section 4.5 Suspected Carcinogen: 11.5 116 Reproductive Toxicity: This product is not reported to cause reproductive effects in humans Mutagenicity: This product is not reported to produce mutagenic effects in humans. Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. Irritancy of Product: 11.7 The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure 11.8 Biological NA Indices: 11 9 Physician Treat symptomatically and supportively. Recommendations 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: There are no specific data available for this product. 12.2 Effects on Plants There are no specific data available for this product. Animals Effects on Aquatic Life: There are no specific data available for this product. 12.3 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Dispose of in accordance with federal, state, provincial and local regulations. 13.2 Special NA . Considerations 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR 49 CFR (GND): NOT REGULATED IATA (AIR): 14 2 NOT REGULATED IMDG (OCN): NOT REGULATED 14.3 14.4 TDGR (Canadian NOT REGULATED GND): ADR/RID (EU): 14.5 **NOT REGULATED** 14.6 SCT (MEXICO) **NOT REGULATED** 14.7 ADGR (AUS): **NOT REGULATED** 15. REGULATORY INFORMATION SARA Reporting 15.1 This product contains Zinc, a substance subject to SARA Title III, section 313 reporting requirements. Requirements: 15.2 SARA Threshold There are no specific Threshold Planning Quantities for the components of this product. Planning Quantity: 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory or are otherwise exempt. CERCLA Reportable 15.4 Zinc: 454 kg (1,000 lbs) Quantity (RQ): Other Federal 15.5 Zinc is listed as priority pollutants under the CWA. Zinc is listed as toxic pollutants under the CWA. This product does not Requirements: contain any Class 1 or Class 2 ozone depletors. 15.6 Other Canadian This product has been classified according to the hazard criteria of the CPR and the Safety Data Sheet Regulations: contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS D2B (Other Toxic Effects)



Page 5 of 6 **HFT-93242**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revi

SDS Revision: 1.0

SDS Revision Date: 4/30/2015

		15. REGULATORY INFO	RMATION – cont'd
15.7	State Regulatory Information:	Hazardous Substances List (MA), Michigan Minn (NJ), Pennsylvania Right-to-Know List (PA), and Caphite is found on the following state criteria list Manganese Dioxide is found on the following state Criteria lists: IL No other ingredients in this product, present in a criteria lists: California Proposition 65 (CA65), De (FL), Illinois Hazardous Substances List (IL), Substances List (MI), Minnesota Hazardous Su	ts: FL, MA, MN, PA, and WA. e criteria lists: IL, MA, PA, and RI, MA, NJ, and PA. concentration of 1.0% or greater, are listed on any of the following state laware Air Quality Management List (DE), Florida Toxic Substances List Massachusetts Hazardous Substances List (MA), Michigan Critical libstances List (MN), New Jersey Right-to-Know List (NJ), New York Right-to-Know List (PA), Rhode Island Hazardous Substances List (RI),
		· ·	own to the State of California to cause cancer, birth defects or other
45.0	Other Benedictor		arning be given to customers in the State of California.
15.8	Other Requirements:	Causes burns. Very toxic to aquatic organisms nenvironment. Safety Phrases (S): 1/2-26-36/37/3 children. In case of contact with eyes, rinse imadvice. Wear suitable protective clothing/ gloves you feel unwell seek medical advice immediately	Annex For EU Directive 67/548/EEC: <u>Phrases</u> (R): 22-34-50/53 — Harmful if swallowed. nay cause long-term adverse effects in the aquatic 39-45-60-61 — Keep locked up and out of reach of amediately with plenty of water and seek medical and eye/face protection. In case of accident or if (show label where possible). This material and its liste. Avoid release to the environment. Refer to
	1	16. OTHER INFO	
16.1	Other Information:	Wash hands and exposed skin areas with soap while sing this product. Avoid release to the SWALLOWED: Call a POISON CENTER/doctor it	NGESTION HOTLINE at +1 (202) 625-3333 collect, day or night. In
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	government regulations must be reviewed for an Tools USA, Inc.'s knowledge, the information accuracy, suitability or completeness is not guar provided. The information contained herein relationships to the information contained herein relationships the	SHA's Hazard Communication Standard, 29 CFR §1910.1200. Other oplicability to this product. To the best of ShipMate's & Harbor Freight contained herein is reliable and accurate as of this date; however, anteed and no warranties of any type, either expressed or implied, are ites only to the specific product(s). If this product(s) is combined with the considered. Data may be changed from time to time. Be sure to
16.4	Prepared for:	Harbor Freight Tools USA, Inc. 26541 Agoura Road Calabasas, CA 91302 USA Tel: +1 (805) 388-1000 http://www.harborfreight.com	HARBOR FREIGHT TOOLS Quality Tools at Ridiculously Low Prices
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com	

Page 6 of 6 HFT-93242

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision Date: 4/30/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number				
EXPOSURE LIMITS IN AIR:					
ACGIH	American Conference on Governmental Industrial Hygienists				
С	Ceiling Limit				
ES	Exposure Standard (Australia)				
IDLH	Immediately Dangerous to Life and Health				
OSHA	U.S. Occupational Safety and Health Administration				
PEL	Permissible Exposure Limit				
STEL	Short-Term Exposure Limit				
TLV	Threshold Limit Value				
TWA	Time Weighted Average				

FIRST AID MEASURES:

Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body

HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:

	JOHAL	NO I LO	IION IX	1111400.
Α				
В				
С				
D				
Е				
F				









Synthetic Apron

Protective Clothing & Full Suit

Dust Respirator

Full Face Respirator



Mask Respirator

Full Face

Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit	
mg/m3	mg/m3 milligrams per cubic meter	
NA	Not Available	
ND	Not Determined	
NE	Not Established	
NF	Not Found	
NR	No Results	
ppm	parts per million	
SCBA	Self-Contained Breathing Apparatus	

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:				
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition			
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source			
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source			

HAZARD RATINGS:

0	Minimal Hazard			
1	Slight Hazard			
2	Moderate Hazard			
3	Severe Hazard			
4	Extreme Hazard			
ACD	Acidic			
ALK	Alkaline			
COR	Corrosive			
₩	Use No Water			
ох	Oxidizer			
TREFOIL	Radioactive			



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{io}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC _o , LC _{lo} , & LC _o	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System					
DOT	U.S. Department of Transportation					
TC	Transport Canada					
EPA	U.S. Environmental Protection Agency					
DSL	DSL Canadian Domestic Substance List					
NOHSC	NOHSC National Occupational Health and Safety Commission (Australia)					
NDSL	L Canadian Non-Domestic Substance List					
PSL	Canadian Priority Substances List					
TSCA	U.S. Toxic Substance Control Act					
EU	European Union (European Union Directive 67/548/EEC)					
WGK	Wassergefährdungsklassen (German Water Hazard Class)					
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System					

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	(*)	(\odot	®		(Ř
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

15.4		M	*			X	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\Diamond		*
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment