HARBOR FREIGHT TOOLS

Quality Tools at Ridiculously Low Prices

SAFETY DATA SHEET

Page 1 of 6 **HFT-95576**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 4/30/2015

1	PRODUCT	ጼ	COMPANY IDE	NTIFICATION
	1 110001	u		

1. I RODOOT & COMITANT IDENTIFICATION				
Product Name:	SLIME [™] SDS TIRE SEALANT			
Chemical Name:	NA NA			
Synonyms:	P/N 95576			
Trade Names:	SLIME [™]			
Product Uses & Restrictions:	Sealant			
Distributor's Name:	Harbor Freight Tools USA, Inc.			
Distributor's Address:	26541 Agoura Road, Calabasas, CA 91302 USA			
Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687)			
Business Phone / Fax:	+1 (805) 388-1000			
	Chemical Name: Synonyms: Trade Names: Product Uses & Restrictions: Distributor's Name: Distributor's Address: Emergency Phone:			

2. HAZARDS IDENTIFICATION

2.1 Hazard Identification:

This product is classified as a HAZARDOUS SUBSTANCE but not as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia).

WARNING! PRESSURIZED CONTAINER MAY BURST IF HEATED. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES EYE IRRITATION.

Classification: Aerosol 3; Skin Sens. 1; Eye Irrit. 2B

Hazard Statements (H): H229 – Pressurized container may burs if heated. H317 – May cause an allernic skin reaction. H320 – Causes eye irritation.

Allergic skin reaction. H320 – Causes eye irritation.

Precautionary Statements (P): P210 – Keep away from heat, hot surfaces, sparks, open flame and other ignition sources. No smoking. P251 – Do not pierce or burn, even after use. P264 – Wash thoroughly after handling. P280 – Wear eye protection/ wear protective gloves. P302+P352 – IF ON SKIN: Wash with plenty of soap and water. P333+P313 – If skin irritation occurs: Get medical advice/attention. P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 – If eye irritation persists: Get medical advice/attention. P410+P412 – Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).



3 COMPOSITION & INGREDIENT INFORMATION

C. COMIN CONTON & INCINEDIENT IN CHIMATION													
					EXPOSURE LIMITS IN AIR (mg/m³)								
					AC	GIH		NOHSC			OSHA		
					pp	m		ppm			ppm		
							ES-	ES-	ES-				
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER
CLIME™ DRODDIETA DV FODMULA	NA	NA	NA	60-100	NA	NA	NF	NF	NF	NA	NA	NA	
SLIME [™] PROPRIETARY FORMULA	Aerosol 3; Skin	Sens. 1; Eye Irrit	. 2B;										

			4. FIRST AID MEASURES
4.1	First Aid:	Ingestion:	If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
		Eyes:	Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes lifting upper and lower lids, occasionally.
		Skin:	Wash thoroughly with soap and water. In case of contact, immediately flush skin with plenty of water for at least 15 minutes.
		Inhalation:	Remove victim to fresh air at once. If breathing difficult, administer oxygen. If breathing stops give artificial respiration. Keep person warm, quiet and get medical attention.
4.2	Effects of Exposure:	Ingestion:	If product is swallowed, may cause gastrointestinal disturbance.
		Eyes:	Exposure to dust may cause eye irritation. Symptoms of overexposure may include redness, itching, irritation and watering.
		Skin:	May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.
		Inhalation:	Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract.
4.3	Symptoms of Overexposure:	Ingestion:	If product is swallowed, may cause gastrointestinal disturbance.
		Eyes:	Exposure to dust may cause eye irritation. Symptoms of overexposure may include redness, itching, irritation and watering.
		Skin:	May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.
		Inhalation:	Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.

HARBOR FREIGHT TOOLS

Quality Tools at Reliculously Low Prices

SAFETY DATA SHEET

Page 2 of 6 **HFT-95576**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 4/30/2015 4. FIRST AID MEASURES - cont'd 44 Acute Health Effects: Non-irritating when used as directed. Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of dust can cause ccoughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. Non-irritating when used as directed. Possible allergic dermatitis in some sensitive individuals 4.5 Chronic Health Effects: 4.6 Target Organs: Eves, Skin. 4.7 Medical Conditions Pre-existing dermatitis, other skin conditions. HEALTH 1 Aggravated by Exposure: **FLAMMABILITY** 0 PHYSICAL HAZARDS 0 PROTECTIVE EQUIPMENT Α **EYES** SKIN 5. FIREFIGHTING MEASURES Contents under pressure, exposure to temperatures above 120 °F (48.9 °C) may cause container to 5.1 Fire & Explosion Hazards: rupture. If involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO, CO_X, Hydrocarbons) Extinguishing Methods: 5.2 CO₂, Dry Chemical, Alcohol foam, Dry Chemical. Use water spray to cool containers. 5.3 Firefighting Procedures: Keep containers cool until well after the fire is out. Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fireexposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil-over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES 6.1 Spills: Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows). Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For large spills (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Do not eat, drink or smoke when handling this product. Handle as to avoid puncturing container(s). Wash unintentional residues with soap and warm water. Keep tightly closed when not in use. Avoid contact with skin and clothing. 7.2 Storage & Handling: Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Avoid temperatures above 120 °F. Keep away from incompatible substances. Protect containers from physical damage. Avoid breathing vapor. Special Precautions: 7.3 Clean all spills promptly. Keep container tightly closed until ready to use. Store in cool dry place. 8. EXPOSURE CONTROLS & PERSONAL PROTECTION NOHSC OTHER 8.1 Exposure Limits: ACGIH OSHA ppm (mg/m³) STEL ES-STEL STEL CHEMICAL NAME(S) TLV ES-TWA **ES-PEAK** PEL NA NF NF NF NA NA 8.2 Ventilation & Engineering General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station) 8.3 Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. In instances where mist or vapors of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia.

SAFETY DATA SHEET

Page 3 of 6

HARBOR FREIGHT TOOLS HFT-95576 Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 4/30/2015 8. EXPOSURE CONTROLS & PERSONAL PROTECTION – cont'd 8.4 Eye Protection: Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Wear goggles and/or face shield if splashing or spraying is anticipated. Contact lenses pose a special hazard: soft lenses may absorb and concentrate irritants. Have suitable eye wash water available. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU) Hand Protection: 8.5 Use gloves constructed of chemical-resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, or the EU member states. 8.6 Body Protection: Avoid prolonged and/or repeated skin contact. Use clean and impervious protective clothing (e.g., neoprene or Tyvek®) if splashing or spraying conditions are present. Protective clothing should include long-sleeves, apron, boots and additional facial protection. If necessary, refer to appropriate standards of Canada, the EU member states, or U.S. OSHA. 9. PHYSICAL & CHEMICAL PROPERTIES 9.1 Appearance: Paste, various colors. 9.2 Odor: Slight. 9.3 Odor Threshold: NA 9.4 pH: 8.8 ± 1.0 Melting Point/Freezing Point: 9.5 < -34.4 °C (< -30 °F) Initial Boiling Point/Boiling 96 > 104.4 °C (220 °F) Range: 9.7 > 93.3 °C (200 °F) Flashpoint: 9.8 Upper/Lower Flammability NA Limits: 9.9 Vapor Pressure: NA 9.10 Vapor Density NΑ Relative Density: 9.11 1.16 ± 0.1 9.12 Solubility: **Emulsifies** 9.13 Partition Coefficient (log Pow): NA 9.14 Autoignition Temperature: NA 9.15 Decomposition Temperature: > 150 °C (>302 °F) 9 16 Viscosity: Paste Other Information 9 17 VOC: 5% by weight 10. STABILITY & REACTIVITY 10.1 Stability Stable under normal conditions; unstable with heat or contamination. Hazardous Decomposition 10.2 Oxides of carbon (CO, CO₂). 10.3 Hazardous Polymerization Will not occur. 10.4 Conditions to Avoid Open flames, sparks, high heat, incompatible substances and direct sunlight. Heat is generated when mixed with water. 10.5 Incompatible Substances Avoid extreme heat and ignition sources, metals, acids and acrylates. Heat is generated when mixed water. 11. TOXICOLOGICAL INFORMATION Inhalation: YES 11.1 Routes of Entry Absorption: YES Ingestion: YES 11.2 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product, but is not presented in this document. 11.3 Acute Toxicity: Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. 11.4 Chronic Toxicity: This material may aggravate any pre-existing skin condition (e.g., dermatitis) 11.5 Suspected Carcinogen: NA This product is not reported to produce reproductive toxicity in humans 11.6 Reproductive Toxicity: Mutagenicity This product is not reported to produce mutagenic effects in humans Embryotoxicity This product is not reported to produce embryotoxic effects in humans.

This product is not reported to cause teratogenic effects in humans.

This product is not reported to cause reproductive effects in humans.

The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.

Teratogenicity

11.7

11.8

11.9

Reproductive Toxicity:

Biological Exposure Indices:

Physician Recommendations:

NE

Treat symptomatically.

Irritancy of Product:

HARBOR FREIGHT TOOLS
Quality Tools at Ridiculously Low Prices

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SAFETY DATA SHEET

Page 4 of 6 **HFT-95576**

SDS Revision Date: 4/30/2015

12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: There are no specific data available for this product. 122 Effects on Plants & Animals: There are no specific data available for this product. 12.3 Effects on Aquatic Life There are no specific data available for this product. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Dispose of in accordance with federal, state, provincial and local regulations. 13.2 Special Considerations: 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL ≤ 1.0 L); or CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) - until 12/31/2020 14.2 IATA (AIR): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2 (LTD QTY, IP VOL ≤ 0.82 L); or Alb. ID8000, CONSUMER COMMODITY, ORM-D (IP VOL ≤ 0.5 L) IMDG (OCN): 14.3 UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL ≤ 1.0 L) 14 4 TDGR (Canadian GND): UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL ≤ 1.0 L); or MARK PACKAGE "LIMITED QUANTITY," "LTD QTY," or "QUANT LTÉE" or "QUANTITÉ LIMITÉE" 14.5 ADR/RID (EU): UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL ≤ 1.0 L) 14.6 SCT (MEXICO): UN1950, AEROSOLES, 2.2 (CANTIDAD LIMITADA, IP VOL ≤ 1.0 L) ADGR (AUS): UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL \leq 1.0 L) 15. REGULATORY INFORMATION SARA Reporting 15.1 This product does not contain any substances subject to SARA Title III, section 313 reporting requirements. Requirements SARA Threshold Planning 15.2 There are no specific Threshold Planning Quantities for the components of this product. Quantity: 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory or are otherwise exempt. CERCLA Reportable Quantity 15.4 NA (RQ): 15.5 Other Federal Requirements: NA 15.6 Other Canadian Regulations This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. D2A - other toxic effects) 15.7 State Regulatory Information: No ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). 15.8 Other Requirements: The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC: Harmful (Xn) Risk Phrases (R): 21/22-43 - Harmful by inhalation and in contact with skin. May cause sensitization by skin contact. Safety Phrases (S): (1/2)-26-28-36/37/39-45 - Keep locked up and out of reach of children. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of soap and water. Wear suitable protective clothing, gloves and eye/face protection.

HARBOR FREIGHT TOOLS

Quality Teols at Midiculously Low Prices

SAFETY DATA SHEET

Page 5 of 6 **HFT-95576**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 4/30/2015 16. OTHER INFORMATION WARNING! PRESSURIZED CONTAINER MAY BURST IF HEATED. MAY CAUSE AN ALLERGIC SKIN REACTION. 16 1 Other Information: CAUSES EYE IRRITATION. Use only as directed. Do not breathe fumes. Avoid contact with skin. Wash thoroughly after handling. Avoid release to the environment. Wear eye protection/ wear protective gloves. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Use only as directed. KEEP OF REACH OF CHILDREN. 16.2 Terms & Definitions: See last page of this Safety Data Sheet. 16.3 Disclaimer: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Harbor Freight Tools USA, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. 16.4 Prepared for: Harbor Freight Tools USA, Inc. 26541 Agoura Road **HARBOR FREIGHT TOOLS** Calabasas, CA 91302 USA Quality Tools at Ridiculously Low Prices Tel: +1 (805) 388-1000 http://www.harborfreight.com Prepared by: ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700

http://www.shipmate.com

SAFETY DATA SHEET

Page 6 of 6 HFT-95576

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision Date: 4/30/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number					
EXPOSURE	EXPOSURE LIMITS IN AIR:					
ACGIH	American Conference on Governmental Industrial Hygienists					
С	Ceiling Limit					
ES Exposure Standard (Australia)						
IDLH Immediately Dangerous to Life and Health						
OSHA U.S. Occupational Safety and Health Administration						
PEL	Permissible Exposure Limit					
STEL	STEL Short-Term Exposure Limit					
TLV Threshold Limit Value						
TWA	Time Weighted Average					

FIRST AID MEASURES:

CPR Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body

HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:

PERSONAL PROTECTION RATINGS.				
Α				
В				
С				
D	固			
Е				
F				









Synthetic Apron

Protective Clothing & Full Suit

Dust Respirator

Full Face Respirator





Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit	
mg/m3	milligrams per cubic meter	
NA	NA Not Available	
ND	Not Determined	
NE	Not Established	
NF Not Found		
NR	No Results	
ppm parts per million		
SCBA	SCBA Self-Contained Breathing Apparatus	

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:						
Autoignition Minimum temperature required to initiate combustion in air with no other source of ignition						
LEL Lower Explosive Limit - lowest percent of vapor in air, by volume, explode or ignite in the presence of an ignition source						
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					

HAZARD RATINGS:

0	Minimal Hazard			
1	Slight Hazard			
2	Moderate Hazard			
3	Severe Hazard			
4	Extreme Hazard			
ACD	Acidic			
ALK	Alkaline			
COR	Corrosive			
₩	Use No Water			
ох	Oxidizer			
TREFOIL	Radioactive			



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{lo}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC _o , LC _{lo} , & LC _o	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System			
DOT	U.S. Department of Transportation			
TC	Transport Canada			
EPA	PA U.S. Environmental Protection Agency			
DSL	DSL Canadian Domestic Substance List			
NOHSC	DHSC National Occupational Health and Safety Commission (Australia)			
NDSL	DSL Canadian Non-Domestic Substance List			
PSL	Canadian Priority Substances List			
TSCA	U.S. Toxic Substance Control Act			
EU	EU European Union (European Union Directive 67/548/EEC)			
WGK	GK Wassergefährdungsklassen (German Water Hazard Class)			
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System			

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

************	WORKE ENGLISHED COOK IN CLEAN TO THE CONTROL (WITHING) CHOILEM.								
	((2)	(3)	\odot	(18)				
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F		
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive		

EC (67/548/EEC) INFORMATION:

The state of the s		M	*			X	X
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\Leftrightarrow		*
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment