

Hazard Identification:

SAFETY DATA SHEET

Page 1 of 6 HFT-95979

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 4/30/2015

1.1	Product Name:	10 TON HYDRAULIC SHORT BODY RAM	
1.2	Chemical Name:	NA NA	
1.3	Synonyms:	P/N 95979	
1.4	Trade Names:	Pittsburgh Automotive	
1.5	Product Uses & Restrictions:	Hydraulic Oil	
1.6	Distributor's Name:	Harbor Freight Tools USA, Inc.	
1.7	Distributor's Address:	26541 Agoura Road, Calabasas, CA 91302 USA	
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687)	
1.9	Business Phone / Fax:	+1 (805) 388-1000	

2. HAZARDS IDENTIFICATION

This product is classified as a HAZARDOUS SUBSTANCE but not as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia). DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. Classification: Asp. Tox. 1 Hazard Statements (H): H304 - May be fatal if swallowed and enters airways. Precautionary Statements (P): P280 - Wear protective gloves/eye protection. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331 – Do NOT induce vomiting. P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. P405 - Store locked up. P501 - Dispose of contents/ container to an approved waste disposal plant.



3. COMPOSITION & INGREDIENT INFORMATION

							EXPOSURE LIMITS IN AIR (mg/m³)								
					AC	GIH		NOHSC			OSHA				
					pp	m		ppm			ppm]		
							ES-	ES-	ES-				1		
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER		
DISTILLATES (PETROLEUM),	64741-88-4	NA	265-090-8	60-100	NA	5	5	NF	NF	5	NA	NA	OIL MIST		
SOLVENT REFINED HEAVY	Asp. Tox.1; H3	604													

4. FIRST AID MEASURES

		4. I INOT AID MEAGURES	
4.1	First Aid:	Ingestion: DO NOT INDUCE VOMITING. Contact ChemTrec a Center or local emergency telephone number for assattention. If vomiting occurs spontaneously, keep vides aspiration.	sistance and instructions. Seek immediate medical
		Eyes: If product gets in the eyes, flush eyes thoroughly with holding eyelid(s) open to ensure complete flushing. If use, consult a physician or emergency room immediate	the eyes or face become swollen during or following
		Skin: Remove contaminated clothing and wash affected are prompt medical attention. Do not wear contaminated of	lothing until after it has been properly cleaned.
		Inhalation: Remove victim to fresh air at once. If breathing is immediate medical attention. If breathing stops, perfor	
4.2	Effects of Exposure:	Ingestion: If product is swallowed, may cause nausea, vomiting a	nd/or diarrhea.
		Eyes: May cause transient mild-eye irritation with short-term	contact with liquid, spray or mist.
		Skin: This product can cause mild, transient skin irritation allergic skin reactions (e.g., rashes, welts, dermatitis) u	
		Inhalation: No significant adverse health effects are expected the Aspiration of liquid into the lungs can cause severe lunger.	·
4.3	Symptoms of Overexposure:	Eyes: Overexposure in eyes may cause redness, itching and	watering.
		Skin: Symptoms of skin overexposure may include redness can cause allergic skin reactions (e.g., rashes, welts, d	
4.4	Acute Health Effects:	Moderate irritation to eyes and skin near affected areas. Addit drowsiness, dizziness, headaches and nausea.	tionally, high concentrations of vapors can cause
4.5	Chronic Health Effects:	Contains a petroleum-based mineral oil. Prolonged or repeated skir characterized by drying, cracking, (dermatitis) or oil acne. Repeated bil mists at concentrations above applicable workplace exposure leveleffects.	or prolonged inhalation of petroleum-based mineral
4.6	Target Organs:	Eyes, Skin & Respiratory System.	

HARBOR FREIGHT TOOLS

Quality Tools at Ridiculously Low Prices

SAFETY DATA SHEET

Page 2 of 6 HFT-95979

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 4/30/2015

					<u> </u>						
		4. FIRST	AID MEA	SURES	- conf	t'd					
4.7	Medical Conditions Aggravated by Exposure:	Pre-existing dermatitis, other skin conditions, and disorders of the target organs (eyes, skin, and respiratory system). FLAMMABILITY						ENT	1 1 0 B		
		5. FIRE	FIGHTIN	G MEA	SURES)					
5.1	Fire & Explosion Hazards: Extinguishing Methods:	This material can burn but will not the flash point temperature that the heated vapor can ignite with exflash point. Carbon dioxide, can oxides of sulfur, phosphorus, zinconcentrations of hydrogen sulfice.	ot readily ignite can ignite whe plosive force. arbon monoxid inc and nitrog de can be rele	e. This mate en exposed Mists or sp de, smoke, en. Also, d ased.	rial will rele to a source rays may fumes, unl	ease vapors of ignition burn at ten burned hyd	In end nperatu rocarb	closed sures bel	spaces, low the d trace		0
5.3	Firefighting Procedures:	Keep containers cool until well and to protect personal. Avoid s boil over. Prevent runoff from supply, or any natural waterway positive pressure self-contained	Dry Chemical, Foam, Carbon Dioxide, & Water Fog. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Avoid spraying water directly into storage containers because of danger of boil over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.								
		6. ACCIDEN	ITAI REI	FASE	MEASI	IRES					
	Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves) Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For large spills (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with iner material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water.							rial with nce with ater and with inert iners for clothing			
		7. HANDLING	& STOR	AGE IN	FORM	ATION					
7.1	Work & Hygiene Practices:	Use normal hygiene practices. this product and before eating, d	Avoid breathing	ng vapors.			act. V	Vash ha	ands the	oroughly aff	er using
7.2	Storage & Handling:	Use and store in a cool, dry, w possible sources of ignition. Do Recommended maximum shelf li	vell-ventilated not store in ur	area. Kee marked co				t, open	flames	, sparks, a	nd other
7.3	Special Precautions:	Empty containers may contain pempty containers without comme			,	cut, heat o	or weld	l empty	contair	ners. Do n	ot reuse
		8. EXPOSURE CON	TROLS &	PFRS	ONAL F	PROTF	CTIC	N			
3.1	Exposure Limits:		ACGIH		NOHSC			OSHA		OTHER	
	ppm (mg/m³)	CHEMICAL NAME(S) DISTILLATES (PETROLEUM), SOLVENT REFINED HEAVY DADAGEINIC	NA 5	ES-TWA 5	ES-STEL NF	ES-PEAK NF	PEL 5	STEL NA	NA NA	OIL MIST	
3.2	Ventilation & Engineering Controls:	PARAFFINIC The use of mechanical dilution ventilation is recommended to maintain airborne concentrations below the recommended occupational exposure limits, whenever this material is used in a confined space, is heated above normal temperature (up to 38 °C) or is agitated.									
3.3	Respiratory Protection:	Vaporization or misting is not expected at ambient temperatures. Therefore, the need for respiratory protection is not anticipated under normal use conditions and with adequate ventilation. If elevated airborne concentrations above applicable workplace exposure levels are anticipated, a NIOSH-approved organic vapor respirator equipped with a dust/mist pre-filter should be used. Protection factors vary depending upon the type of respirator used. Respirators should be used in accordance with OSHA requirements (29 CFR 1910.134).									
8.4	Eye Protection:										



Page 3 of 6 HFT-95979

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0

SDS Revision Date: 4/30/2015

	1	EXPOSURE CONTROLS & PERSONAL PROTECTION – cont'd
8.5	Hand Protection:	Use gloves constructed of chemical resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected.
8.6	Body Protection:	Avoid prolonged and/or repeated skin contact. Use clean and impervious protective clothing (e.g., neoprene or Tyvek®) if splashing or spraying conditions are present. Protective clothing should include long-sleeves, apron, boots and additional facial protection. Remove oil contaminated clothing. Launder oil contaminated clothing before reusing. Contaminated leather goods should be removed promptly and discarded.
		9. PHYSICAL & CHEMICAL PROPERTIES
9.1	Appearance:	Clear liquid
9.2	Odor:	Characteristic mild petroleum odor
9.3	Odor Threshold:	NA .
9.4	pH:	NA NA
9.5	Melting Point/Freezing Point:	NA NA
9.6	Initial Boiling Point/Boiling	NA NA
9.7	Range: Flashpoint:	
9.8	Upper/Lower Flammability	> 150 °C (> 302 °F)
	Limits:	LEL: 0.9%; UEL: 7.0%
9.9	Vapor Pressure:	NA NA
9.10	Vapor Density:	NA NA
9.11	Relative Density:	0.8337 g/cm3 @ 15 °C (59 °F)
9.12	Solubility:	Insoluble
9.13	Partition Coefficient (log Pow):	NA NA
9.14	Autoignition Temperature:	NA NA
9.15	Decomposition Temperature:	NA NA
9.16	Viscosity:	15.21 @ 104 °F SUS
9.17	Other Information:	NA
		10. STABILITY & REACTIVITY
10.1	Stability:	
10.1	Hazardous Decomposition	Stable at normal temperatures.
10.2	Products:	Fumes, smoke, carbon monoxide, silicon oxides.
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Open flames, sparks, high heat, and close proximity to incompatible substances.
10.5	Incompatible Substances:	Strong oxidizing agents.
		11. TOXICOLOGICAL INFORMATION
11 1	Doutes of Entry	
11.1	Routes of Entry: Toxicity Data:	
11.2	Toxicity Data.	This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product and is presented below:
		Based on animal testing from similar materials & products, the acute toxicity of this product is expected to be: <u>Distillates</u> ,
		Petroleum, Solvent-Refined, Heavy Paraffinic – LD ₅₀ (oral, rat) > 5,000 mg/kg; LD ₅₀ (dermal, rabbit) > 2,000 mg/kg.
11.3	Acute Toxicity:	Mineral oil mists derived from highly refined oils are reported to have low acute and sub-acute toxicities in animals.
		Effects from single and short-term repeated exposures to high concentrations of mineral oil mists well above applicable
		workplace exposure levels include lung inflammatory reaction, lipoid granuloma formation and lipoid pneumonia. In acute
		and sub-acute studies involving exposures to lower concentrations of mineral oil mists at or near current work place
	0	exposure levels produced no significant toxicological effects.
11.4	Chronic Toxicity:	In long term studies (up to two years) no carcinogenic effects have been reported in any animal species tested.
11.5	Suspected Carcinogen:	Not listed by OSHA, NTP or ACGIH.
11.6	Reproductive Toxicity:	This product is not reported to produce reproductive toxicity in humans.
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.
	Teratogenicity:	This product is not reported to produce teratogenic effects in humans.
44 7	Reproductive Toxicity:	This product is not reported to produce reproductive effects in humans.
11.7	Irritancy of Product:	See section 4.3
11.8	Biological Exposure Indices:	NE
11.9	Physician Recommendations:	The viscosity range of the product(s) represented by this SDS is between 100 and 400 SUS at 100°F. Accordingly, upon ingestion there is a moderate risk of aspiration. Careful gastric lavage or emesis may be considered to evacuate large quantities of material. Subcutaneous or intramuscular injection requires prompt surgical debridement.



Page 4 of 6 **HFT-95979**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 4/30/2015 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: There are no specific data available for this product Effects on Plants & Animals: 12.2 There are no specific data available for this product 12.3 Effects on Aquatic Life: There are no specific data available for this product. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Dispose of in accordance with federal, state, provincial and local regulations. 13.2 Special Considerations: 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): **NOT REGULATED** IATA (AIR): 14.2 **NOT REGULATED** IMDG (OCN): 14.3 **NOT REGULATED** TDGR (Canadian GND): 14 4 **NOT REGULATED** ADR/RID (EU): 14.5 **NOT REGULATED** 14.6 SCT (MEXICO): **NOT REGULATED** 14.7 ADGR (AUS): NOT REGULATED 15. REGULATORY INFORMATION SARA Reporting 15.1 This product does not contain any substances subject to SARA Title III, section 313 reporting requirements. Requirements 15.2 SARA Threshold Planning There are no specific Threshold Planning Quantities for the components of this product. Quantity: TSCA Inventory Status: The components of this product are listed on the TSCA Inventory or are otherwise exempt. 15.3 15.4 CERCLA Reportable Quantity (RQ): 15.5 None of the ingredients are listed as Hazardous Air Pollutants (HAPs). None of the ingredients are listed as Toxic Other Federal Requirements: Pollutants under the Clean Water Act (CWA). None of the ingredients are listed as Priority Pollutants under the Clean Water Act (CWA). This product does not contain any Class 1 or Class 2 ozone depletors. 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS D2B (Other Toxic Effects) 15.7 State Regulatory Information: No ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). Other Requirements: The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC: Distillates (Petroleum), Hydrotreated Heavy Paraffinic: Harmful (Xn). Risk Phrases (R): 65 -

Harmful: may cause lung damage if swallowed. <u>Safety Phrases</u> (S): 53-45 – Avoid exposure – obtain special instructions before use. In case of accident or if you feel unwell seek medical advice

immediately (show the label where possible).



Page 5 of 6 **HFT-95979**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 4/30/2015 16. OTHER INFORMATION DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. Wash exposed skin areas thoroughly with 16.1 Other Information: soap and water after handling. Avoid eye contact. Wear protective gloves/eye protection/face protection. IF ON SKIN: Wash with soap and water. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. If skin irritation or a rash occurs - Get medical advice/attention. Store in a well-ventilated place. Keep cool. Use only as directed. KEEP OUT OF REACH OF CHILDREN. 16.2 Terms & Definitions: See last page of this Safety Data Sheet. 16.3 Disclaimer: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Harbor Freight Tools USA, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. Prepared for: 16.4 Harbor Freight Tools USA, Inc. 26541 Agoura Road **HARBOR FREIGHT TOOLS** Calabasas, CA 91302 USA Tel: +1 (805) 388-1000 http://www.harborfreight.com/ 16.5 Prepared by: ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600

Fax: +1 (310) 370-5700 http://www.shipmate.com

Page 6 of 6 **HFT-95979**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 4/30/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number					
EXPOSURE	EXPOSURE LIMITS IN AIR:					
ACGIH	American Conference on Governmental Industrial Hygienists					
С	Ceiling Limit					
ES	Exposure Standard (Australia)					
IDLH	Immediately Dangerous to Life and Health					
OSHA	U.S. Occupational Safety and Health Administration					
PEL	Permissible Exposure Limit					
STEL	Short-Term Exposure Limit					
TLV	Threshold Limit Value					
TWA	Time Weighted Average					

FIRST AID MEASURES:


CPR Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.

HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:













Full Face Respirator



Protective Clothing & Full Suit



Boots Sy



Full Face Respirator

Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit
mg/m3	milligrams per cubic meter
NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR	No Results
ppm	parts per million
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:							
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition						
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source						
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source						

HAZARD RATINGS:

0	Minimal Hazard			
1	Slight Hazard			
2	Moderate Hazard			
3	Severe Hazard			
4	Extreme Hazard			
ACD	Acidic			
ALK	Alkaline			
COR	Corrosive			
₩	Use No Water			
ох	Oxidizer			
TREFOIL	Radioactive			



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{lo}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC _o , LC _{lo} , & LC _o	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System				
DOT	U.S. Department of Transportation				
TC	TC Transport Canada				
EPA	U.S. Environmental Protection Agency				
DSL	Canadian Domestic Substance List				
NOHSC	National Occupational Health and Safety Commission (Australia)				
NDSL	Canadian Non-Domestic Substance List				
PSL	Canadian Priority Substances List				
TSCA	U.S. Toxic Substance Control Act				
EU	European Union (European Union Directive 67/548/EEC)				
WGK	Wassergefährdungsklassen (German Water Hazard Class)				
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System				

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

World Elie In Eliabodo III/CE IDENTI I Idinicio (Williamo) o Idinicio								
0	(3)	<u>(2)</u>	②	(T)	®		R	
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F	
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive	

EC (67/548/EEC) INFORMATION:

The state of the s		M	*			X	X
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\Diamond		*
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment