Skin:

Eyes: Skin:

4.3

4.4

4.5

Symptoms of Overexposure:

Acute Health Effects:

Chronic Health Effects:

Inhalation:

pulmonary effects

Page 1 of 6

HARB Quali	OR FREIGHT TOOLS by Tools at Ridiculously Low Prices		SAF	ETY [DAT	A S	SH	EE	T				HFT-96406
repa	ared to OSHA, ACC, ANSI	, NOHSC, WHMIS	, 2001/58 & 1272	/2008/EC Standa	ırds		SDS	Revisio	n: 1.0		SDS	Revision Da	ate: 5/13/2015
		1.	PRODU	CT & CON	<u>IPANY</u>	IDE	NTIF	FICA	TIOI	N			
1	Product Name:	2.25 TO	N SCOSS	SOR JACK	(
2	Chemical Name:	Lithium Grea	ase										
3	Synonyms:	P/N 96406											
ŀ	Trade Names:	Haul-Master											
	Product Uses & Restrictions	Lubricating (Grease										
	Distributor's Name:	Harbor Freig	ght Tools USA,	Inc.									
	Distributor's Address:	26541 Agou	ra Road, Cala	basas, CA 913	02 USA								
3	Emergency Phone:	CHEMTR	EC: +1 (703	3) 527-3887	/ +1 (80) 424	I-930	O (CC	N 67	6687)		
9	Business Phone / Fax:	+1 (805) 388	3-1000		•								
			2 H	AZARDS	IDENT	IFIC	ΔΤΙ)N					
	Hazard Identification:	This produc		as a HAZARD					ac DA	NGED	OUS (20002	
	Trazara rasminoation.			on criteria of N								30003	
				L IF SWALLO						,	٠٠٠		_
			n: Asp. Tox. 1;										
		Hazard Stat	ements (H): H3	304 – May be f	atal if swa	llowed	and er	nters a	irways.	H350) – Ma	y cause	
			ry Statements	(P): P280 – V	Vear prote	ctive q	loves/e	eve pr	otectio	n. P3	01+P3	10 – IF	
				ly call a POIS									
		P405 - Stor	re locked up.	P501 – Dispos	se of conte	ents/ co	ontaine	er to a	n appr	oved v	waste o	disposal	
		plant.											
		3. C	OMPOSI	ΓΙΟΝ & IN	GRED	IENT	INF	ORI	MAT	ON			
										SURE LI		AIR (mg/m ³)
						AC			NOHSC			OSHA	
						pp	m		ppm		Г	ppm	
ЕМ	ICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL IDL	.H OTHER
STI	LLATES (PETROLEUM),	64742-65-0	PY8038501	265-169-7	60-100	NA	NA	NF	NF	NF	100	NA NA	4
	ENT-DEWAXED HEAVY FFINIC *	Asp. Tox. 1,	Carc. 1B; H304,	H350									
	DUAL OILS (PETROLEUM	•		265-096-0	10-30	NA	NA	NF	NF	NF	NA	NA N	Δ
	ENT DEASPHALTED *	"	Carc. 1B; H304,		10-30	1471	1471					101 10	
		NA	NA NA	NA NA	5-10	NA	NA	NF	NF	NF	NA	NA N	A
OF	PRIETARY ADDITIVES		•						- I				•
on	tains less than 3% DMSO												
			4.	FIRST A	ID ME	ASU I	RES	,					
1	First Aid:	Ingestion:	DO NOT IN	DUCE VOMITI	NG. Cont	act Ch	emTre	c at +	1 (703	527-	3887 c	or the nea	rest Poison Cor
									•	•			immediate med
					•								reduce the risl
			aspiration.	-	-	,					`	•	
		Eyes:		•	•								at least 15 minu
			• • • • • • • • • • • • • • • • • • • •	` '					eyes	or face	becor	ne swolle	n during or follow
		OL:		a physician or e				-					
		Skin:											tation persists, s
		Inheleties		cal attention. D					-				
		<u>Inhalation</u> :					_					ppiementa	al oxygen and s
!	Effects of Exposure:	Ingestion:		edical attention							auon.		
	Zcolo oi Exposure.	Ingestion:	•	swallowed, may				-			:		
		F1/00:											
		Eyes:	,	ansient mild-ey								•	product can cal

This product can cause mild, transient skin irritation with short-term exposure. This product can cause

No significant adverse health effects are expected to occur upon short-term exposure to this product.

Symptoms of skin overexposure may include redness, itching, and irritation of affected areas The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.

allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.

Contains a petroleum-based mineral oil. Prolonged or repeated skin contact can cause mild irritation and inflammation characterized by drying, cracking, (dermatitis) or oil acne. Repeated or prolonged inhalation of petroleum-based mineral oil mists at concentrations above applicable workplace exposure levels can cause respiratory irritation or other

Aspiration of liquid into the lungs can cause severe lung damage or death.

Overexposure in eyes may cause redness, itching and watering.

Moderate irritation to eyes and skin near affected areas.

HARBOR FREIGHT TOOLS

Quality Tools at Ridiculously Low Prices

SAFETY DATA SHEET

Page 2 of 6 **HFT-96406**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 5/13/2015 4. FIRST AID MEASURES - cont'd 4.6 Target Organs: Eyes, Skin, Respiratory System 47 Medical Conditions Pre-existing dermatitis, other skin conditions, and disorders of the **HEALTH** 1 Aggravated by Exposure: target organs (eyes, skin, and respiratory system). **FLAMMABILITY** 1 PHYSICAL HAZARDS 0 PROTECTIVE EQUIPMENT В **EYES** SKIN 5. FIREFIGHTING MEASURES This material can burn but will not readily ignite. This material will release vapors when heated above Fire & Explosion Hazards: the flash point temperature that can ignite when exposed to a source of ignition. In enclosed spaces, heated vapor can ignite with explosive force. Mists or sprays may burn at temperatures below the flash point. Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and trace oxides of sulfur, phosphorus and nitrogen. Also, depending upon the conditions of use, low concentrations of hydrogen sulfide can be released. Extinguishing Methods: Dry chemical, foam, carbon dioxide, and water fog. Firefighting Procedures: 5.3 Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Avoid spraying water directly into storage containers because of danger of boil over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Spills Equipment. For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Use normal hygiene practices. Avoid direct skin contact. Wash hands thoroughly after using this product and before eating, drinking, or smoking. 72 Storage & Handling: Use and store in a cool, dry, well-ventilated area. Keep away from excessive heat, open flames, sparks, and other possible sources of ignition. Do not store in unmarked containers or storage devices. Recommended maximum shelf life: 36 months. 7.3 Special Precautions: Empty containers may contain product residue. Do not pressurize, cut, heat or weld empty containers. Do not reuse empty containers without commercial cleaning or reconditioning 8. EXPOSURE CONTROLS & PERSONAL PROTECTION Exposure Limits: **ACGIH** NOHSC OSHA OTHER ppm (mg/m³) TLV ES-TWA **ES-STEL** ES-PEAK CHEMICAL NAME(S) STEL PEL STEL IDLH DISTILLATES (PETROLEUM), NA NF NF NF 100 NA NA NA SOLVENT-DEWAXED HEAVY PARAFFINIC 8.2 Ventilation & Engineering The use of mechanical dilution ventilation is recommended to maintain airborne concentrations below the recommended Controls: occupational exposure limits, whenever this material is used in a confined space, is heated above normal temperatures (up to 38 °C) or is agitated. 8.3 Respiratory Protection: Vaporization or misting is not expected at ambient temperatures. Therefore, the need for respiratory protection is not anticipated under normal use conditions and with adequate ventilation. If elevated airborne concentrations above applicable workplace exposure levels are anticipated, a NIOSHapproved organic vapor respirator equipped with a dust/mist pre-filter should be used. Protection factors vary depending upon the type of respirator used. Respirators should be used in accordance with OSHA requirements (29 CFR 1910.134).



SAFETY DATA SHEET

Page 3 of 6 HFT-96406

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 5/13/2015 8. EXPOSURE CONTROLS & PERSONAL PROTECTION – cont'd 8 4 Eye Protection: Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants. Have suitable eve wash water available. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). 8.5 Hand Protection Use gloves constructed of chemical-resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, or the EU member states. 8.6 Body Protection: Avoid prolonged and/or repeated skin contact. Use clean and impervious protective clothing (e.g., neoprene or Tyvek®). Protective clothing should include long-sleeves, apron, boots and additional facial protection. If necessary, refer to appropriate standards of Canada, the EU member states, or U.S. OSHA 9. PHYSICAL & CHEMICAL PROPERTIES Appearance: Yellow - Brown Grease 9.2 Odor: Mild petroleum odor 9.3 Odor Threshold: NA 9.4 pH: NA Melting Point/Freezing Point: 9.5 NA Initial Boiling Point/Boiling 9.6 NA Range: 97 Flashpoint: NA 9.8 Upper/Lower Flammability NA 9.9 Vapor Pressure: NA 9 10 Vapor Density: NA 9.11 Relative Density: NA 9.12 Solubility: Insoluble 9.13 Partition Coefficient (log Pow): NA 9.14 Autoignition Temperature: NA 9.15 Decomposition Temperature: NA 9.16 Viscosity NA 9.17 Other Information: NA 10. STABILITY & REACTIVITY 10.1 Stability: Stable at normal temperatures 10.2 Hazardous Decomposition Fumes, smoke, carbon monoxide, silicon oxides. Products: 10.3 Hazardous Polymerization: Will not occur. 10.4 Conditions to Avoid: Open flames, sparks, high heat, and close proximity to incompatible substances 10.5 Incompatible Substances: Strong oxidizing agents 11. TOXICOLOGICAL INFORMATION Inhalation: NO Routes of Entry Absorption: YES Ingestion: 11.1 YES 11.2 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product and is presented below: Based on animal testing from similar materials & products, the acute toxicity of this product is expected to be: Mineral Oils – LD₅₀ (oral, rat) > 5,000 mg/kg. 11.3 Acute Toxicity Mineral oil mists derived from highly refined oils are reported to have low acute and sub-acute toxicities in animals. Effects from single and short-term repeated exposures to high concentrations of mineral oil mists well above applicable workplace exposure levels include lung inflammatory reaction, lipoid granuloma formation and lipoid pneumonia. In acute and sub-acute studies involving exposures to lower concentrations of mineral oil mists at or near current work place exposure levels produced no significant toxicological effects. Chronic Toxicity: Prolonged or repeated skin contact can cause mild irritation and inflammation characterized by drying, cracking, (dermatitis) or oil acne. 11.5 Suspected Carcinogen: 116 Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans. Mutagenicity: This product is not reported to produce mutagenic effects in humans. Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to produce teratogenic effects in humans. Reproductive Toxicity:

This product is not reported to produce reproductive effects in humans.

HARBOR FREIGHT TOOLS

Quality Tests at Ridiculously Low Prices

SAFETY DATA SHEET

Page 4 of 6 **HFT-96406**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 5/13/2015 11. TOXICOLOGICAL INFORMATION - cont'd 11.7 Irritancy of Product: See section 4.3 11.8 Biological Exposure Indices: NA 11.9 Physician Recommendations: The viscosity range of the product(s) represented by this SDS is between 100 and 400 SUS at 100°F. Accordingly, upon ingestion there is a moderate risk of aspiration. Careful gastric lavage or emesis may be considered to evacuate large quantities of material. Subcutaneous or intramuscular injection requires prompt surgical debridement. 12. ECOLOGICAL INFORMATION Environmental Stability 12.1 There are no specific data available for this product. Effects on Plants & Animals: There are no specific data available for this product 122 12.3 Effects on Aquatic Life There are no specific data available for this product. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Dispose of in accordance with federal, state, provincial & local regulations. 13.2 Special Considerations: 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): 14.1 **NOT REGULATED** 14.2 IATA (AIR): **NOT REGULATED** IMDG (OCN): 14.3 **NOT REGULATED** TDGR (Canadian GND): 14 4 **NOT REGULATED** ADR/RID (EU): 14.5 **NOT REGULATED** 14.6 SCT (MEXICO): **NOT REGULATED** 14.7 ADGR (AUS): **NOT REGULATED** 15. REGULATORY INFORMATION SARA Reporting 15.1 This product does not contain any substances subject to SARA Title III, section 313 reporting requirements. Requirements 15.2 SARA Threshold Planning There are no specific Threshold Planning Quantities for the components of this product. Quantity 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory or are otherwise exempt. 15.4 CERCLA Reportable Quantity (RQ) None of the ingredients are listed as Hazardous Air Pollutants (HAPs). None of the ingredients are listed as Toxic 15.5 Other Federal Requirements: Pollutants under the Clean Water Act (CWA). None of the ingredients are listed as Priority Pollutants under the Clean Water Act (CWA). This product does not contain any Class 1 or Class 2 ozone depletors. 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS D2B (Other Toxic Effects) 15.7 State Regulatory Information: None of the ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). 15.8 Other Requirements: The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC: Harmful (Xn). Risk Phrases (R): 65 - Harmful: may cause lung damage if swallowed. Safety Phrases (S): 1/2-53-45-46 - Keep locked up and out of reach of children. Avoid exposure - obtain special instructions before use. In case of accident or if you feel unwell seek medical advice immediately (show the label where possible). If swallowed, seek medical advice immediately and

show this container label.

HARBOR FREIGHT TOOLS

Guality Tools at Hidiculously Low Prices

SAFETY DATA SHEET

Page 5 of 6 **HFT-96406**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 5/13/2015 16. OTHER INFORMATION DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. Wear protective gloves/eye protection/face 16.1 Other Information: protection. IF ON SKIN: Wash with soap and water. If skin irritation or a rash occurs - Get medical advice/attention. Store in a well-ventilated place. Keep cool. Use only as directed. KEEP LOCKED UP AND OUT OF REACH OF CHILDREN. 16.2 Terms & Definitions: See last page of this Safety Data Sheet. 16.3 Disclaimer: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Harbor Freight Tools USA, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. 16.4 Prepared for: Harbor Freight Tools USA, Inc. 26541 Agoura Road **HARBOR FREIGHT TOOLS** Calabasas, CA 91302 USA **Quality Tools at Ridiculously Low Prices** Tel: +1 (805) 388-1000 http://www.harborfreight.com 16.5 Prepared by: ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700

http://www.shipmate.com

SAFETY DATA SHEET

Page 6 of 6 **HFT-96406**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 5/13/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number							
EXPOSURE	EXPOSURE LIMITS IN AIR:							
ACGIH American Conference on Governmental Industrial Hygienists								
C Ceiling Limit								
ES	Exposure Standard (Australia)							
IDLH	Immediately Dangerous to Life and Health							
OSHA	U.S. Occupational Safety and Health Administration							
PEL	Permissible Exposure Limit							
STEL	Short-Term Exposure Limit							
TLV	Threshold Limit Value							
TWA	Time Weighted Average							

FIRST AID MEASURES:

CPR Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.

HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard				
1	Slight Hazard				
2	Moderate Hazard				
3	Severe Hazard				
4	Extreme Hazard				



PERSONAL PROTECTION RATINGS:

	JOHAL	NO I LO	IION IX	1111400.
Α				
В				
С				
D				
Е				
F				





Splash Goggle









Protective Clothing & Full Suit

Dust Respirator





or Half- Full Face Dirator Respirator

Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit		
mg/m3	milligrams per cubic meter		
NA	Not Available		
ND Not Determined			
NE Not Established			
NF	Not Found		
NR	No Results		
ppm parts per million			
SCBA	Self-Contained Breathing Apparatus		

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILI	FLAMMABILITY LIMITS IN AIR:							
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition							
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source							
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source							

HAZARD RATINGS:

TO LES TO					
0	Minimal Hazard				
1	Slight Hazard				
2	Moderate Hazard				
3	Severe Hazard				
4	Extreme Hazard				
ACD	Acidic				
ALK	Alkaline				
COR	Corrosive				
₩	Use No Water				
ОХ	Oxidizer				
TREFOIL	Radioactive				



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s					
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal					
ppm	Concentration expressed in parts of material per million parts					
TD _{io}	Lowest dose to cause a symptom					
TCLo	Lowest concentration to cause a symptom					
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects					
TC, TC _o , LC _{lo} , & LC _o						
IARC	International Agency for Research on Cancer					
NTP	National Toxicology Program					
RTECS	Registry of Toxic Effects of Chemical Substances					
BCF	Bioconcentration Factor					
TL _m	Median threshold limit					
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution					

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NOHSC	National Occupational Health and Safety Commission (Australia)
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

	WORKE ENGLINE WEDGE MAN ELECTRICAL (WINNES) CTCTEME											
0	(3)	(②	(T)	®		R					
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F					
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive					

EC (67/548/EEC) INFORMATION:

		M	*			X	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

0.5	ke.			\Diamond			\Diamond		*
GH	S01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Expl	osive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment