

Page 1 of 6 **HFT-96676**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 7/25/2015

	1. PRODUCT & COMPANY IDENTIFICATION				
1.1	Product Name:	9 IN MAGNETIC TORPEDO LEVEL			
1.2	Chemical Name:	Low Boiling Point Naphtha			
1.3	Synonyms:	P/N 96676			
1.4	Trade Names:	Pittsburgh			
1.5	Product Uses & Restrictions:	Sight-Glass			
1.6	Distributor's Name:	Harbor Freight Tools USA, Inc.			
1.7	Distributor's Address:	26541 Agoura Road, Calabasas, CA 91302 USA			
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687)			
1.9	Business Phone / Fax:	+1 (805) 388-1000			

2. HAZARDS IDENTIFICATION

2.1 Hazard Identification: This product is classified as a hazardous substance and as dangerous goods according to the classification criteria of NOHSC: 1008 (2004) and ADG Code (Australia).

DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES SERIOUS EYE IRRITATION.

Classification: Flam. Liq. 1; Asp. Tox. 1; Skin Irrit. 2; STOT SE 3; Aq. Chronic 2.

<u>Hazard Statements</u> (H): H224 – Extremely flammable liquid and vapor. H304 – May be fatal if swallowed and enters airways. H319 – Causes serious eye irritation.

Precautionary Statements (P): P201 - Obtain special instruction before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat/sparks/open flame/hot surfaces - No Smoking. P233 - Keep container tightly closed. P243 Take precautionary measures against static discharge. P261 – Avoid breathing fume/mist/vapors/spray. P264 - Wash exposed skin areas thoroughly with soap and water after handling. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 -Avoid release to the environment. P280 - Wear protective gloves/eye protection/face protection. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331 - Do NOT induce vomiting. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water (or shower). P305+P351+P338 - IF IN EYES -Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention. P370+P378 – In case of fire: use CO₂, Halon (if permitted), dry chemical, or foam for extinction. P391 - Collect spillage. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).



3. COMPOSITION & INGREDIENT INFORMATION

								EXPO	SURE LI	MITS IN	AIR (mg	g/m³)		
					AC	GIH		NOHSC			OSHA			
					pp	m		ppm			ppm			
							ES-	ES-	ES-					
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	•	THER
LOW BOILING BOINT NABUTUA	8006-61-9	LX3300000	232-349-1	60-100	100	NA	NF	790	NF	200	NA	2000	MIST	
LOW BOILING POINT NAPHTHA	Flam. Liq. 1; As	sp. Tox. 1; Skin Ir	rit. 2; STOT SE	3; Aq. Chro	nic 2; I	1224, H	304, H	315, H3	36, H4	11		·		

4. FIRST AID MEASURES

			4. FIRST AID MEASURES
4.1	First Aid:	Ingestion:	If ingested, do not induce vomiting. Contact the nearest Poison Control Center or local emergency
		_	number. Provide an estimate of the time at which the material was ingested and the amount of the
			substance that was swallowed.
		Eyes:	Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm
			water for at least 15 minutes. If irritation occurs, contact a physician.
		Skin:	If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough
			washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a
			physician immediately.
		Inhalation:	Remove victim to fresh air at once.



Special Precautions:

7.3

Page 2 of 6 HARBOR FREIGHT TOOLS SAFETY DATA SHEET HFT-96676 Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 7/25/2015 4. FIRST AID MEASURES - cont'd If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system 42 Effects of Exposure: Ingestion: The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or Eyes: transient eye inflammation, ulceration. The vapor is discomforting to the eye. Splashes may cause severe eye irritation, possible corneal burns and eye damage. Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to skin, especially after prolonged contact. The product can cause allergic skin reactions Skin: (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory Inhalation: system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of concentrated vapors can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, nausea). Odor may give some warning of exposure, but odor fatigue may occur. 4.3 Symptoms of Overexposure: Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. 4.4 Acute Health Effects: Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. 4.5 Chronic Health Effects: The material may accentuate any pre-existing dermatitis condition. 4.6 Target Organs: Eyes, Skin, Respiratory System, Central Nervous System, Liver, Kidneys Pre-existing dermatitis, other skin conditions, and disorders of the 4.7 Medical Conditions **HEALTH** 2 Aggravated by Exposure: target organs (eyes, skin, and respiratory system). 3 **FLAMMABILITY PHYSICAL HAZARDS** 0 PROTECTIVE EQUIPMENT X **EYES** SKIN LUNGS 5. FIREFIGHTING MEASURES DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR! Keep away from heat/ sparks/ Fire & Explosion Hazards open flame/ hot surfaces - No Smoking. Keep container tightly closed. Take precautionary measures against static discharge. 5.2 Extinguishing Methods: CO₂, Halon (if permitted), Dry Chemical, Foam, as authorized. 5.3 Firefighting Procedures: This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product. HazChem Code: 3[Y]E. Hazard Identification Number: 33 6. ACCIDENTAL RELEASE MEASURES Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Spills Equipment. For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product. Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container 7.2 Storage & Handling: closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Storage temperature: 32-120 °F (0-49 °C). Take precautionary measures against static discharge. Store away from incompatible materials (see Section 10).

Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may

contain residual amounts of this product; therefore, empty containers should be handled with care.



Page 3 of 6 **HFT-96676**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 7/25/2015

3.1	Exposure Limits:	8. EXPOSURE CO	ACGIH	<u> </u>	NOHSC			OSHA		OTHER
	ppm (mg/m ³)	CHEMICAL NAME(S)		EL ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	- III-IX
		LOW BOILING POINT		IA NF	790	NF	200	NA	2000	MIST
		NAPHTHA								
.2	Ventilation & Engineering Controls:		hen working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans), to k sposure below the airborne exposure limits. Ensure that an eyewash station, sink or washbasin is available in cas sposure to eyes.							
3.3	Respiratory Protection:	No special respiratory prote	ection is req	uired under t	pical circ	umstances	of use	or han	dling. If	:
		necessary, use only respira								
		§1910.134, or applicable U			the appr	opriate sta	ndards	of Car	nada, its	
3.4	Eye Protection:	provinces, EU member state Wear protective eyewear (e	-,		aida abiala	d) at all tim		n hone	llina thia	
	Lyo i rotodioni	product. Always use protective	0,	•		,			0	
		special hazard; soft lenses								
		protection tested and appro-								
		EN 166(EU).								
3.5	Hand Protection:	If anticipated that prolonged								
		latex or rubber gloves for					U.S.	OSHA	29 CFR	
3.6	Body Protection:	§1910.138, the appropriate s					a and l	nandline	1 \//^	
		appropriate protective cloth								
		needed. If necessary, refer								
		OSHA.								
		9. PHYSIC	AL & CI	HEMICAL	. PROI	PERTIE	S			
.1	Appearance:	Transparent liquid (may be y	ellow-green)						
.2	Odor:	Penetrating hydrocarbon odd	or							
.3	Odor Threshold:	NA								
1.4	pH:	NA								
.5	Melting Point/Freezing Point:	NA								
9.6	Initial Boiling Point/Boiling Range:	> 60 °C (> 140 °F)								
9.7	Flashpoint:	< 0 °C (< 32 °F)								
9.8	Upper/Lower Flammability	LEL: 0.7% / UEL 7.0%								
9.9	Limits: Vapor Pressure:									
9.10	Vapor Density:	NA NA								
9.11	Relative Density:	NA								
9.12	Solubility:	Insoluble in water								
9.13	Partition Coefficient (log Pow):	NA								
9.14	Autoignition Temperature:	NA								
9.15	Decomposition Temperature:	NA								
9.16	Viscosity:	NA								
9.17	Other Information:	NA								
					•	•			-	
		10. S	STABILI	TY & REA	ACTIVI	ITY				
10.1	Stability:	Relatively stable under ambi	ent conditior	ns when store	d properly.	=				
10.2	Hazardous Decomposition	If exposed to extremely high			of therma	decompos	sition m	ay inclu	ude irrita	ting vapors and tox
	Products:	gases (e.g., oxides of carbor	n & nitrogen)							
10.3	Hazardous Polymerization:	Will not occur. Exposure or contact to extre	ma tampara	turas insama	atible obon	micala otror	a liabt	00115000	anarka	flama
10.4	Conditions to Avoid: Incompatible Substances:	Strong oxidizers, peroxides			alible cher	flicais, stroi	ig light	sources	s, sparks	, name.
0.5	meompatible oubstances.	Strong oxidizers, peroxides t	or strong acr	us.						
		11. TOX	וכטו סמ	SICAL IN	FORM	ΔΤΙΩΝ				
1.1	Routes of Entry:	Inhalation: YES			bsorption:				Ingest	on: YES
11.2	Toxicity Data:	This product has NOT been					rvicolor	ny data		
4	. Oxiony Data.	available for some of the co						jy uala,	iouila in	scientino illerature,
		Low Boiling Point Naphtha:	•	•		STREET DEIDW	•			
11.3	Acute Toxicity:	Moderate irritation to eyes				Additionally	hiah	concent	rations	of vapors can caus
		drowsiness, dizziness, head								
1.4	Chronic Toxicity:	The material may accentuate	e any pre-ex	isting dermati	is condition	on.				
1.5	Suspected Carcinogen:	Low Boiling Point Naphtha:								•



Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SAFETY DATA SHEET

SDS Revision: 1.1

Page 4 of 6 **HFT-96676**

SDS Revision Date: 7/25/2015

11. TOXICOLOGICAL INFORMATION - cont'd 11.6 Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans. Mutagenicity This product is not reported to produce mutagenic effects in humans Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. 11.7 Irritancy of Product: The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure 11.8 Biological Exposure Indices: NE Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION 12.1 **Environmental Stability** There are no specific data available for this product. 12.2 Effects on Plants & Animals There are no specific data available for this product. 12.3 Effects on Aquatic Life There are no specific data available for this product. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Dispose of in accordance with federal, state, provincial and local regulations Special Considerations: 13.2 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 14.1 49 CFR (GND): UN1993, FLAMMABLE LIQUIDS, N.O.S. (NAPHTHA), 3, II (LTD QTY, IP VOL ≤ 1.0 L); or CONSUMER COMMODITY, ORM-D - until 01/01/2021 14.2 IATA (AIR)*: ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 0.5 L); or Ap/A UN1993, FLAMMABLE LIQUIDS, N.O.S. (NAPHTHA), 3, II (LTD QTY, IP VOL ≤ 0.5 L) 14.3 IMDG (OCN): UN1993, FLAMMABLE LIQUIDS, N.O.S. (NAPHTHA), 3, II (LTD QTY, IP VOL ≤ 1.0 L) 14 4 TDGR (Canadian GND): UN1993, FLAMMABLE LIQUIDS, N.O.S. (NAPHTHA), 3, II (LTD QTY, IP VOL ≤ 1.0 L); or "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (IP VOL ≤ 1.0 L) 14.5 ADR/RID (EU): UN1993, FLAMMABLE LIQUIDS, N.O.S. (NAPHTHA), 3, II (LTD QTY, IP VOL ≤ 1.0 L) 14.6 SCT (MEXICO): UN1993, LIQUIDOS, INFLAMABLES, N.E.P. (NAFTA), 3, II (CANT. LTDA., IP VOL ≤ 1.0 L) ADGR (AUS): UN1993, FLAMMABLE LIQUIDS, N.O.S. (NAPHTHA), 3, II (LTD QTY, IP VOL ≤ 1.0 L) 15. REGULATORY INFORMATION SARA Reporting This product does not contain any substances subject to SARA Title III, Section 313 reporting requirements. 15.1 SARA Threshold Planning 15.2 There are no specific Threshold Planning Quantities for the components of this product. Quantity: 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory or are otherwise exempt. 15.4 **CERCLA Reportable Quantity** NA (RQ): None of the ingredients are listed as Hazardous Air Pollutants (HAPs). None of the ingredients are listed as Toxic 15.5 Other Federal Requirements Pollutants under the Clean Water Act (CWA). None of the ingredients are listed as Priority Pollutants under the Clean Water Act (CWA). This product does not contain any Class 1 or Class 2 ozone depletors. Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the Safety Data Sheet contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS B2, D2B (Flammable Liquid, Other Toxic Effects).



Page 5 of 6 **HFT-96676**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 7/25/2015

		15. REGULATORY INFO	RMATION – cont'd
15.7	State Regulatory Information:	List (FL), Massachusetts Hazardous Substances Right-to-Know List (PA), and Washington Permiss No other ingredients in this product, present in a criteria lists: California Proposition 65 (CA65), List (FL), Massachusetts Hazardous Substances Substances List (MN), New Jersey Right-to-Know Right-to-Know List (PA), Washington Permissible) is found on the following state criteria lists: Florida Toxic Substances List (MA), Minnesota Hazardous Substances List (MN), Pennsylvania sible Exposures List (WA). concentration of 1.0% or greater, are listed on any of the following state Delaware Air Quality Management List (DE), Florida Toxic Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous w List (NJ), New York Hazardous Substances List (NY), Pennsylvania Exposures List (WA), Wisconsin Hazardous Substances List (WI).
15.8	Other Requirements:	65 – Highly flammable. Irritating to eyes, skin a damage if swallowed. <u>Safety Phrases</u> (S): (2-)S container in a well-ventilated place. Keep away	larmful (F+, Xn). Risk Phrases (R): R11-36/37/38-and respiratory system. Harmful: may cause lung 0-16-26-46 – Keep out of reach of children. Keep from sources of ignition – No smoking. In case of of water and seek medical advice. If swallowed,
		16. OTHER INFO	DEMATION
16.1	Other Information:	DANGER! HIGHLY FLAMMABLE LIQUID A AIRWAYS. CAUSES SERIOUS EYE IRRITATION Obtain special instruction before use. Do not have away from heat/sparks/open flame/hot surfaces measures against static discharge. Avoid breath soap and water after handling. Contaminated protective gloves/eye protection/face protection. NOT induce vomiting. IF ON SKIN (or hair): The shower). IF IN EYES – Rinse continuously with a do – continue rinsing. If eye irritation persists permitted), dry chemical, or foam for extinction. release to the environment. Collect spillage. KEE WARNING! This product contains a substance(s) reproductive harm.	IND VAPOR. MAY BE FATAL IF SWALLOWED AND ENTERS ON. TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS. Indle until all safety precautions have been read and understood. Keep — No Smoking. Keep container tightly closed. Take precautionary ing fume/mist/vapors/spray. Wash exposed skin areas thoroughly with work clothing should not be allowed out of the workplace. Wear IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do like off immediately all contaminated clothing. Rinse skin with water (or water for several minutes. Remove contact lenses if present and easy to so Get medical advice/attention. In case of fire: use CO ₂ , Halon (if Store in a well-ventilated place. Keep cool. Store locked up. Avoid EPLOCKED UP AND OUT OF REACH OF CHILDREN.
16.3	Terms & Definitions: Disclaimer:	government regulations must be reviewed for ap Tools USA, Inc.'s knowledge, the information accuracy, suitability or completeness is not guard provided. The information contained herein relation to the materials, all component properties must be consult the latest edition.	SHA's Hazard Communication Standard, 29 CFR §1910.1200. Other oplicability to this product. To the best of ShipMate's & Harbor Freight contained herein is reliable and accurate as of this date; however, anteed and no warranties of any type, either expressed or implied, are ites only to the specific product(s). If this product(s) is combined with the considered. Data may be changed from time to time. Be sure to
16.4	Prepared for: Prepared by:	Harbor Freight Tools USA, Inc. 26541 Agoura Road Calabasas, CA 91302 USA Tel: +1 (805) 388-1000 http://www.harborfreight.com ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600	HARBOR FREIGHT TOOLS Quality Tools at Ridiculously Low Prices
		Fax: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com	

Page 6 of 6 HFT-96676

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 7/25/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
С	Ceiling Limit
ES	Exposure Standard (Australia)
IDLH	Immediately Dangerous to Life and Health
OSHA	U.S. Occupational Safety and Health Administration
PEL Permissible Exposure Limit	
STEL	Short-Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

FIRST AID MEASURES:


CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.


HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:















Splash Goggles







Dust & Vapor Half-Mask Respirator

Full Face

Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit
mg/m3	milligrams per cubic meter
NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR	No Results
ppm	parts per million
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILI	TY LIMITS IN AIR:
	Minimum temperature required to initiate combustion in air with no other
Temperature	source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will
	explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will
	explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
₩	Use No Water
ОХ	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{Io}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC _o , LC _{io} , & LC _o	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System			
DOT	U.S. Department of Transportation			
TC Transport Canada				
EPA U.S. Environmental Protection Agency				
DSL Canadian Domestic Substance List				
NOHSC National Occupational Health and Safety Commission (Australia)				
NDSL	Canadian Non-Domestic Substance List			
PSL	Canadian Priority Substances List			
TSCA	U.S. Toxic Substance Control Act			
EU	European Union (European Union Directive 67/548/EEC)			
WGK	Wassergefährdungsklassen (German Water Hazard Class)			
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System			

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

	*	(\odot	(18)		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

		M	*		®	×	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

		®	\Diamond			\limits	***	
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environ- ment