

Page 1 of 6 **HFT-97275**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 7/29/2015

1.1	Product Name:	18 OZ ARCTIC FREEZE® REFRIGERANT
1.2	Chemical Name:	1,1,1,2-Tetrafluoroethane
1.3	Synonyms:	P/N 97275
1.4	Trade Names:	Arctic Freeze®
1.5	Product Uses & Restrictions:	Refrigerant
1.6	Distributor's Name:	Harbor Freight Tools USA, Inc.
1.7	Distributor's Address:	26541 Agoura Road, Calabasas, CA 91302 USA
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687)
1.9	Business Phone / Fax:	+1 (805) 388-1000

2. HAZARDS IDENTIFICATION

2.1 Hazard Identification: This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1008(2004) and ADG Code (Australia). KEEP OUT OF REACH OF CHILDREN.

WARNING. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

Classification: Liquefied Gas.

Hazard Statements (H): H280 – Contains gas under pressure; may explode if heated. Precautionary Statements (P): P280 – Wear protective gloves and eye protection. P302 + P352 - IF ON SKIN: Wash with soap and water. P333 + P313 - If skin irritation or a rash occurs – Get medical advice/attention. P305+P351+P338 – IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice/attention. P304 - IF INHALED: Move to fresh air. If breathing has stopped, give artificial respiration and call physician immediately. P410 + P412 - Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122 °F. P410+P403 – Protect from sunlight. Store in a well-ventilated place. P501 – Dispose of contents/container through licensed treatment, storage or disposal facility.



3. COMPOSITION & INGREDIENT INFORMATION

							_		_				
						EXPOSURE LIMITS IN AIR (mg/m³)							
					AC	GIH		NOHSC	;		OSHA		
					pp	om		ppm			ppm		
							ES-	ES-	ES-				
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER
1 1 1 2 TETRAFI LIODOTLIANE	811-97-2	KI8842500	212-377-0	60-100	NA	NA	4240	NF	NF	NA	NA	NA	1000 TWA
1,1,1,2-TETRAFLUOROTHANE	Liq. Gas; H280)											
POLYALKYLENE GLYCOL	NA	NA	NA	5-15	NA	NA	NF	NF	NF	NA	NA	NA	
MONOBUTYL ETHER													
ADDITIVE DACKAGE	NA	NA	NA	1-10	NA	NA	NF	NF	NF	NA	NA	NA	
ADDITIVE PACKAGE													
LEAK SEALER	NA	NA	NA	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA	
LEAN SEALER													

4 FIRST AID MEASURES

		4. FIRST AID MEASURES
First Aid:	Ingestion:	If ingested, do not induce vomiting. Contact the nearest Poison Control Center or local emergency
		number. Provide an estimate of the time at which the material was ingested and the amount of the
		substance that was swallowed.
	Eyes:	Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm
		water for at least 15 minutes. If irritation occurs, contact a physician.
	Skin:	If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough
		washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a
		physician immediately.
	Inhalation:	Remove victim to fresh air at once. If breathing is difficult, provide supplemental oxygen. If breathing has
		stopped, provide artificial respiration. Seek immediate medical attention. Provide supportive treatment,
		keeping victim warm and quiet.
	First Aid:	Eyes:



Page 2 of 6

HFT-97275 Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 7/29/2015 4. FIRST AID MEASURES - cont'd 42 Effects of Exposure: Ingestion: If product is swallowed, may cause nausea, vomiting and/or diarrhea. "Frostbite-like" effects may occur if the liquid or escaping vapors contact the eyes. Mists may cause Eves: irritation. Frostbite-like" effects may occur if the liquid or escaping vapors contact the skin. Mists may cause Skin: irritation. Inhalation: Gross overexposure may cause central nervous system depression, dizziness, confusion, incoordination, drowsiness, irregular heartbeat accompanied by a strange feeling in the chest, "heart thumping," apprehension, light-headedness, weakness, fainting, loss of consciousness, and death. Symptoms of Overexposure: Inhalation may cause dizziness, confusion, incoordination, drowsiness, irregular heartbeat accompanied by a strange feeling in the chest, "heart thumping", apprehension, light-headedness, weakness, fainting, loss of consciousness, and Acute Health Effects: "Frostbite-like" effects may occur if the liquid or escaping vapors contact the eyes. Mists may cause irritation. Chronic Health Effects: "Frostbite-like" effects may occur if the liquid or escaping vapors contact the skin. Mists may cause irritation. Target Organs: Eyes, Skin, Respiratory System Medical Conditions Pre-existing dermatitis, other skin conditions, and disorders of the **HEALTH** 1 Aggravated by Exposure: target organs (eyes and skin). Pre-existing cardiovascular or central **FLAMMABILITY** 0 nervous system diseases. PHYSICAL HAZARDS 1 PROTECTIVE EQUIPMENT В EYES SKIN 5. FIREFIGHTING MEASURES Fire & Explosion Hazards: This product is non-flammable. Cylinders may rupture under fire conditions. This material will become combustible when mixed with air under pressure and exposed to strong ignition sources. Decomposition may occur. Contact of welding or soldering torch flames with high concentrations of refrigerant can result in visible changes in the size and color of the torch flame. The flame effect will only occur in concentrations of product well above the recommended exposure limit, therefore stop all work and ventilate the area before proceeding. Use forced ventilation to disperse refrigerant vapors from the work area before using any open flames. Extinguishing Methods: Water, Foam, CO₂, Dry Chemical. Use media appropriate for surrounding materials. Firefighting Procedures As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressuredemand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Spills Equipment (PPE). Secure spill area, remove or minimize all sources of ignition, and maximize ventilation. Stop spill or leak at source if safely possible. Deny entry to all unprotected individuals. Individuals involved in the cleanup must

4.3 44 4.5 4.6 47 5.2 5.3 6.1 wear appropriate personal protective equipment. Recover free liquid or cover with inert absorbent material and place into appropriate container(s) for disposal. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers or any natural waterway or drinking supply. Contact appropriate local and/or provincial authorities for assistance and/or reporting requirements. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION Use normal hygiene practices. Avoid direct skin contact. Wash hands thoroughly after using this product and before 7.1 Work & Hygiene Practices: eating, drinking, or smoking. 7.2 Storage & Handling: Use and store in a cool, dry, well-ventilated area. Keep away from excessive heat, open flames, sparks, and other possible sources of ignition. Do not store near or with any incompatible materials listed in Section 10. Do not store in unmarked or open containers. Protect cylinders from physical damage. Do not store in subsurface areas. Special Precautions: 7.3 Readily available emergency fire, first aid, and spill response equipment and/or measures are highly recommended.



Page 3 of 6 **HFT-97275**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 7/29/2015

3.2	Exposure Limits: opm (mg/m³)	CHEMICAL NAME(S)	ACGIH		NOHSC			OSHA		OTHER
.2		CUEMICAL NAME(C)	1							
,			TLV STEI	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	
,	/ III II O.E	1,1,1,2-TETRAFLUOROETHANE	NA NA	4240	NF	NF	NA	NA	NA	1000 TWA
	Ventilation & Engineering	Normal ventilation for standard m	anufacturing	procedures	is gene	rally ade	quate.	Local	exhaust	should be used wh
.3	Controls:	large amounts are released. Mech								
3		monitors may be necessary to dete		concentrat	ions in w	ork areas	s prior t	o use of	f torches	or other open flame
.3		or if employees are entering enclose								1
	Respiratory Protection:	No special respiratory protection								
		necessary, use only respiratory p §1910.134, or applicable U.S. s								
		provinces, EU member states, or A		nis, or the	арргор	mate Sta	iiiuaius	Oi Cai	iaua, ita	·
3.4	Eye Protection:	Wear protective eyewear (e.g., s		with side	-shield)	at all tim	nes whe	en hand	llina this	;
		product. Always use protective ey								
		shield if splashing or spraying is	anticipated.	Contact lei	nses pos	se a spe	cial haz	ard; so	ft lenses	
		may absorb and concentrate irritar								
		eye protection tested and approve	d under appr	opriate gov	ernment	standar	ds such	as NIO	SH (US)
.5	Hand Protection:	or EN 166(EU).								
.5	nand Protection.	Use gloves constructed of chemic frequent or prolonged contact is e								
		the appropriate standards of Cana				0.3. 03	ΠA 29 (2LK 81	910.130	,
i.6 I	Body Protection:	No special body protection is re	·			nces of	use ar	nd hand	ilina I	f
	,	necessary, refer to appropriate sta								'
		, , ,		,			,			
		9. PHYSICAL	& CHEM	ICAL P	ROPE	ERTIE	S			
.1	Appearance:	Pressurized clear liquid								
	Odor:	Slight ethereal odor								
	Odor Threshold:	NA								
	oH:	4.00-5.00								
	Melting Point/Freezing Point:	NA								
	nitial Boiling Point/Boiling									
!	Range:	NA								
	Flashpoint:	204 °C (399 °F) (liquid portion of p	roduct)							
	Upper/Lower Flammability Limits:	LEL: 11,000 ppm/UEL: 94,000 pp	m (liquid port	on of produ	ıct)					
9.9	Vapor Pressure:	NA								
).10	Vapor Density:	NA								
.11 I	Relative Density:	NA								
.12	Solubility:	Insoluble								
.13 I	Partition Coefficient (log Pow):	NA								
.14	Autoignition Temperature:	> 400 °C (752 °F)								
.15 I	Decomposition Temperature:	NA								
.16	Viscosity:	NA								
).17	Other Information:	NA								
		10. STA	BILITY 8	REAC	TIVIT	Υ				
0.1	Stability:	This product is stable.								
0.2	Hazardous Decomposition	Warning! Hazardous decomposi	tion products	are haza	rdous.	Thermal	decom	position	can vi	eld hydrofluoric aci
	Products:	possibly carbonyl fluoride. These								,
0.3	Hazardous Polymerization:	Will not occur.								
0.4	Conditions to Avoid:	Open flames, sparks, high heat, ar	nd close prox	mity to inco	ompatible	e substar	nces.			
0.5	Incompatible Substances:	Alkalis, and alkaline earth material	S	•	•					
		11. TOXICO	LOGICA	L INFO	RMA	TION			-	
1.1	Routes of Entry:	Inhalation: YES		Absorp					Ingest	ion: YES
	Toxicity Data:	The product has not been tested	for specific to				availal	ole in so		1.20
	•	that this material is a slight irritant,			. ,a	. otaaloo	, availai	30		
1.3	Acute Toxicity:	See Section 4.4								
	Chronic Toxicity:	See Section 4.5								
	Suspected Carcinogen:	NA								



Page 4 of 6

HFT-97275 Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 7/29/2015 11. TOXICOLOGICAL INFORMATION - cont'd 11.6 Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans. Mutagenicity: Tests have shown that this material does not cause genetic damage in bacterial or mammalian cell cultures, or in animals. Embryotoxicity: Animal data shows slight fetotoxicity but only at exposure levels producing other toxic effects in the adult animal Teratogenicity: This product is not reported to produce teratogenic effects in humans. Reproductive Toxicity: In a 2-year inhalation study, HFC-134A, at a concentration of 50,000 ppm, produced an increase in late-occurring benign testicular tumors, testicular hyperplasia and testicular weight in mice. The no-effect-level for this study was 10,000ppm. However, no change in reproductive performance was reported. Irritancy of Product: 117 Slight 11.8 Biological Exposure Indices: NE Physician Recommendations: Treat symptomatically. Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should only be used with special caution in situations of emergency life support. 12. ECOLOGICAL INFORMATION 12.1 **Environmental Stability** There are no specific data available for this product. Effects on Plants & Animals: EC₅₀ (Daphnia magna, 48h): 980 mg/L; LC₅₀ (Rainbow trout, 96h): 450 mg/L 12.2 12.3 Effects on Aquatic Life: There are no specific data available for this product. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Dispose of in accordance with federal, state, provincial and local regulations. 13.2 Special Considerations: 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR. IATA/ICAO. IMDG and the CTDGR.

	<u>, ' </u>	e required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.	
14.1	49 CFR (GND):	CONSUMER COMMODITY, ORM-D, DOT-SP 10232 (IP VOL ≤ 1.0 L) - until 12/31/2020 UN3159, 1,1,1,2-TETRAFLUOROETHANE, 2.2 (LTD QTY, IP VOL ≤ 1.0 L)	\(\)
14.2	IATA (AIR):	UN3159, 1,1,1,2-TETRAFLUOROETHANE, 2.2 (LTD QTY, IP VOL ≤ 820 mL)	\$ \$
14.3	IMDG (OCN):	UN3159, 1,1,1,2-TETRAFLUOROETHANE, 2.2 (LTD QTY, IP VOL ≤ 1.0 L)	\
14.4	TDGR (Canadian GND):	UN3159, 1,1,1,2-TETRAFLUOROETHANE, 2.2 (LTD QTY, IP VOL ≤ 1.0 L); or MARK PACKAGE "LIMITED QUANTITY/QUANTITÉ LIMITÉE" or "LTD QTY/QUANT LTÉE" (IP VOL ≤ 1.0 L)	\
14.5	ADR/RID (EU):	UN3159, 1,1,1,2-TETRAFLUOROETHANE, 2.2 (LTD QTY, IP VOL ≤ 1.0 L)	\
14.6	SCT (MEXICO):	UN3159, 1,1,1,2-TETRAFLUOROETHANE, 2.2 (LTD QTY, IP VOL ≤ 1.0 L)	\Diamond
14.7	ADGR (AUS):	UN3159, 1,1,1,2-TETRAFLUOROETHANE, 2.2 (LTD QTY, IP VOL ≤ 1.0 L)	\
15.1	SARA Reporting Requirements:	15. REGULATORY INFORMATION This product does not contain any substances subject to SARA Title III, Section 313 reporting requiren	nents.
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.	
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory or are otherwise exempt.	
15.4	CERCLA Reportable Quantity (RQ):	NA	
15.5	Other Federal Requirements:	None of the ingredients are listed as Hazardous Air Pollutants (HAPs). None of the ingredients Pollutants under the Clean Water Act (CWA). None of the ingredients are listed as Priority Pollutan Water Act (CWA). This product does not contain any Class 1 or Class 2 ozone depletors.	
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS A (Compressed Gas)	0



Page 5 of 6 **HFT-97275**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 7/29/2015

		15. REGULATORY INFO	RMATION – cont'd				
15.7	State Regulatory Information:	Know list; Massachusetts Right to Know List of C No other ingredients in this product, present in a c criteria lists: California Proposition 65 (CA65), L List (FL), Massachusetts Hazardous Substances Substances List (MN), New Jersey Right-to-Know	g state criteria lists: California Right-to-Know List; Minnesota Right-to-hemicals; New Jersey Right to Know List 8:59 Appendix A. concentration of 1.0% or greater, are listed on any of the following state Delaware Air Quality Management List (DE), Florida Toxic Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous W List (NJ), New York Hazardous Substances List (NY), Pennsylvania Exposures List (WA), Wisconsin Hazardous Substances List (WI).				
15.8	Other Requirements:	The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC: Irritant (Xi). Risk Phrases (R): 36 – Irritating to eyes. Safety Phrases (S): 2-25-26 – Keep out of reach of children. Avid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.					
		16. OTHER INFO	RMATION				
16.1	Other Information:	WARNING. CONTAINS GAS UNDER PRESSU protection. IF ON SKIN – Wash with soap and v IF IN EYES - Rinse continuously with water for continue rinsing. If eye irritation persists: Get m has stopped, give artificial respiration and cal temperatures exceeding 50 °C/122 °F. Protect fr OF CHILDREN. USE AND STORE IN WELL VEI	JRE; MAY EXPLODE IF HEATED. Wear protective gloves and eye water. If skin irritation or a rash occurs – Get medical advice/attention. several minutes. Remove contact lenses if present and easy to do – edical advice/attention. IF INHALED: Move to fresh air. If breathing II physician immediately. Protect from sunlight. Do no expose to om sunlight. Store in a well-ventilated place. KEEP OUT OF REACH NTILATED AREAS.				
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.					
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to O government regulations must be reviewed for ap Tools USA, Inc.'s knowledge, the information of accuracy, suitability or completeness is not guara provided. The information contained herein relations of the control	SHA's Hazard Communication Standard, 29 CFR §1910.1200. Other plicability to this product. To the best of ShipMate's & Harbor Freight contained herein is reliable and accurate as of this date; however, anteed and no warranties of any type, either expressed or implied, are tes only to the specific product(s). If this product(s) is combined with be considered. Data may be changed from time to time. Be sure to				
16.4	Prepared for:	Harbor Freight Tools USA, Inc. 26541 Agoura Road Calabasas, CA 91302 USA Tel: +1 (805) 388-1000 http://www.harborfreight.com	HARBOR FREIGHT TOOLS Quality Tools at Ridiculously Low Prices				
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com					



Page 6 of 6 **HFT-97275**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 7/29/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	CAS NO. Chemical Abstract Service Number			
EXPOSURE LIMITS IN AIR:				
ACGIH	American Conference on Governmental Industrial Hygienists			
С	Ceiling Limit			
ES	Exposure Standard (Australia)			
IDLH	Immediately Dangerous to Life and Health			
OSHA	U.S. Occupational Safety and Health Administration			
PEL	Permissible Exposure Limit			
STEL	Short-Term Exposure Limit			
TLV	Threshold Limit Value			
TWΔ	Time Weighted Average			

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.


HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:

Α			
В			
С			
D		型	
E			
F			



























OTHER STANDARD ABBREVIATIONS:

ML	Maximum Limit
mg/m3	milligrams per cubic meter
NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR	No Results
ppm	parts per million
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:				
Autoignition	Minimum temperature required to initiate combustion in air with no other			
Temperature	source of ignition			
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will			
	explode or ignite in the presence of an ignition source			
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will			
	explode or ignite in the presence of an ignition source			

HAZARD RATINGS:

Minimal Hazard					
1	Slight Hazard				
2	Moderate Hazard				
3	Severe Hazard				
4	Extreme Hazard				
ACD	Acidic				
ALK	Alkaline				
COR	Corrosive				
W	Use No Water				
ОХ	Oxidizer				
TREFOIL	Radioactive				



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
	S
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{Io}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{io} , LD _{io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC _o , LC _{lo} , & LC _o	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NOHSC	National Occupational Health and Safety Commission (Australia)
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	(3)	((4)	\odot	®		(R)
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

F.J.		Z.	¥		Ø X	×	×
О	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\Diamond		1
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment